

AiroMed API — Integration Guide

Field	Details
Document	Patient API Integration Guide
Objective	Provide a shareable API reference for developers integrating the patient (web / mobile) TeleMed REST API into another app.
Audience	Client and partner developers integrating patient apps
Prepared by	AndOr Communications Pvt Ltd
Classification	Confidential — for client project stakeholders
Scope	Endpoints used by patient web and mobile apps
Out of scope	Admin / doctor / pharmacy staff portals
Version	1.0
Last updated	27 August 2026
Related documents	BUSINESS_LOGIC.md (BUSINESS_LOGIC.md) · ARCHITECTURE.md (ARCHITECTURE.md) · API.md (API.md)
PDF	INTEGRATION.pdf

Production	<code>https://api.airoemed.com</code>
Versioning	All routes under <code>/v1/...</code>
Format	JSON (Content-Type: application/json)
Auth header	Authorization: Bearer <accessToken>
Correlation	Responses include <code>x-request-id</code>

This document covers **only endpoints used by the patient web and mobile apps**. Staff portals (admin / doctor / pharmacy) are out of scope.

1. Quick start

```
curl https://api.airoemed.com/health

curl -X POST https://api.airoemed.com/v1/auth/login \
  -H 'Content-Type: application/json' \
  -d '{"email":"user@example.com","password":"....."}'

curl https://api.airoemed.com/v1/users/profile \
  -H "Authorization: Bearer <accessToken>"
```

Successful auth responses:

```
{
  "accessToken": "<jwt>",
  "refreshToken": "<opaque>",
  "user": {
    "id": 1,
    "email": "user@example.com",
    "role": "CUSTOMER",
    "profileComplete": true
  }
}
```

- **Access token** — short-lived JWT (~15m). Send on every protected request.
- **Refresh token** — long-lived opaque token (~30d). Store securely; rotate via `POST /v1/auth/refresh`.
- Do not log OTP codes, refresh tokens, or payment secrets.

2. Authentication `/v1/auth`

Email + password

Method	Path	Auth	Body
POST	<code>/login</code>	—	<code>{ email, password }</code>
POST	<code>/register</code>	—	<code>{ firstName, lastName, email, password, mobile, emailVerificationToken }</code> → 201
POST	<code>/refresh</code>	—	<code>{ refreshToken }</code> → new token pair
POST	<code>/logout</code>	JWT	<code>{ refreshToken? }</code> → 204
GET	<code>/session</code>	JWT	Current user from access token

Register requires a prior signup email OTP verification token.

Signup email OTP (before register)

Method	Path	Body
POST	<code>/register/email-otp/send</code>	<code>{ email }</code>
POST	<code>/register/email-otp/resend</code>	<code>{ email }</code>
POST	<code>/register/email-otp/verify</code>	<code>{ email, otp }</code> → <code>{ emailVerificationToken, ... }</code>

Signup mobile OTP

Method	Path	Body
POST	<code>/register/mobile-otp/send</code>	<code>{ mobile }</code>
POST	<code>/register/mobile-otp/resend</code>	<code>{ mobile }</code>
POST	<code>/register/mobile-otp/verify</code>	<code>{ mobile, otp }</code>

Indian mobiles: `^[6-9]\d{9}$` with optional `+91` / `91` prefix.

Mobile OTP login (passwordless)

Method	Path	Auth	Body
POST	/otp/send	—	{ mobile }
POST	/otp/resend	—	{ mobile }
POST	/otp/verify	—	{ mobile, otp } (4 digits) → tokens; may create user (isNewUser)
POST	/otp/complete-signup	—	{ signupToken, firstName, lastName, gender, dob, ... }
POST	/otp/complete-profile	JWT	{ firstName, lastName, gender, dob, ethnicity? } → new tokens

gender : MALE | FEMALE | OTHER | PREFER_NOT_TO_SAY

dob : YYYY-MM-DD

ethnicity (optional): caucasian | african_american | hispanic_latino | asian | middle_eastern | other

Email OTP login

Method	Path	Body
POST	/email-otp/send	{ email }
POST	/email-otp/resend	{ email }
POST	/email-otp/verify	{ email, otp } → tokens

Verify email / mobile while logged in

Method	Path	Auth	Body
POST	/email-verification/send	JWT	{ email }
POST	/email-verification/resend	JWT	{ email }
POST	/email-verification/verify	JWT	{ email, otp }
POST	/mobile-verification/send	JWT	{ mobile }
POST	/mobile-verification/resend	JWT	{ mobile }
POST	/mobile-verification/verify	JWT	{ mobile, otp, firstName?, lastName? }

Profile completion gate

Checkout mutations under `/v1/users` (carts, questionnaire submit, purchases) return **403** until the customer profile is complete. Complete via `POST /otp/complete-profile` or `PATCH /v1/users/profile`. Reads (profile, addresses, orders, consultations) stay available.

3. Errors

```
{
  "error": "VALIDATION_ERROR",
  "message": "Invalid request",
  "details": { "email": ["Invalid email"] }
}
```

error	HTTP	When
VALIDATION_ERROR	400	Body/query validation (details = field errors)
BAD_REQUEST	400	Business rule
UNAUTHORIZED	401	Missing/invalid JWT
FORBIDDEN	403	Incomplete profile or pending deletion
NOT_FOUND	404	Resource missing
CONFLICT	409	e.g. duplicate active cart
INTERNAL_ERROR	500	Unexpected

4. Health

Method	Path	Notes
GET	/health	Liveness + DB + Redis

5. Public catalog /v1/catalog

No auth unless noted. Successful GETs may be Redis-cached; medicine **availability** is overlaid live.

Categories & concerns

Method	Path	Notes
GET	/categories	Medicine verticals
GET	/categories/:id	Category by id
GET	/concerns	?categoryId=&limit=&offset= → { concerns }
GET	/concerns/:id	→ { concern }
GET	/concerns/medicines	?concernIds=1,2 batch PDPs

Medicines

Method	Path	Notes
GET	/medicines	Flat list — ? categoryId=&concernId=&search=&audience=&limit=&offset=
GET	/medicines/by-subcategory	All Treatments — required categoryId ; option offset , audience (HIMS HERS BOTH). Return grouped by product-form subcategory + available
GET	/medicines/by-slug/:slug	PDP by slug
GET	/medicines/:id	Full PDP — images, plans, FAQs, pairings, purchase availability
GET	/medicines/:id/reviews	?featured=true
POST	/medicines/:id/reviews	Customer JWT — submit review
POST	/medicines/:id/reviews/:reviewId/like	Customer JWT
DELETE	/medicines/:id/reviews/:reviewId/like	Customer JWT
POST	/medicines/:id/reviews/:reviewId/report	Customer JWT
GET	/medicines/:id/doctors	Featured doctors

Doctors

Method	Path	Notes
GET	/doctors	Directory
GET	/doctors/:id	Profile
GET	/doctors/:id/reviews	
POST	/doctors/:id/reviews	Customer JWT (web)

Content & treatment pages

Method	Path	Notes
GET	/homepage	CMS homepage
GET	/medicine-detail	?categoryId=&medicineId= marketing blocks
GET	/top-products	Header / nav curated products
GET	/contact-page	Contact CMS
GET	/mobile-onboarding	Mobile onboarding CMS
GET	/treatment-page	Treatment page by scope query
GET	/treatment-page/testimonials	

Catalog questionnaires (pre-checkout / quiz)

Method	Path	Notes
GET	/questionnaires/system-profile	Health-profile question defs
GET	/questionnaires/flows/:medicineId	Checkout flow definition
GET	/questionnaires/clinical/medicine/:medicineId	
GET	/questionnaires/clinical/concern/:conditionId	
POST	/questionnaires/submissions	Save quiz submission (optional JWT)
GET	/questionnaires/submissions/latest	Latest submission (optional JWT)
GET	/questionnaires/recommended-medicines	Recommendations from latest / query
GET	/questionnaires/:id/recommended-medicines	Recommendations for a submission

6. Help center & legal (public)

Method	Path
GET	/v1/help-center/categories
GET	/v1/help-center/categories/:slug
GET	/v1/help-center/articles/:id
GET	/v1/legal/:slug

7. Customer portal **/v1/users**

All routes require customer JWT unless noted.

Profile & addresses

Method	Path
GET	/profile
PATCH	/profile
GET/POST	/addresses
PATCH/DELETE	/addresses/:id
GET/POST/DELETE	/account/deletion

Health profile

Method	Path
GET	/health-profile
PUT	/health-profile/sections/:sectionCode

Media

Method	Path	Notes
POST	/v1/media/guest/presign	Public — pre-cart quiz photos
POST	/media/presign	Authenticated customer upload

Cart & checkout

Method	Path	Body
GET	/carts	Active cart(s) + paymentContext
POST	/carts/items	{ medicineId, quantity?, purchasePlanId?, ... }
GET	/carts/:id	
PATCH	/carts/:id/items/:itemId	qty / plan
DELETE	/carts/:id/items/:itemId	
POST	/carts/:id/files	{ fileUrl, fileType, angle?, medicineId? }
DELETE	/carts/:id/files/:fileId	
POST	/carts/:id/purchases	{ addressId? } → create purchase
DELETE	/carts/:id	Abandon cart

Checkout questionnaire

Method	Path
POST	/questionnaires/sessions
GET	/questionnaires/sessions/:id
PATCH	/questionnaires/sessions/:id/answers
POST	/questionnaires/sessions/:id/submit

Purchases & Razorpay

Method	Path	Notes
GET	/purchases	History
GET	/purchases/:id	Detail
POST	/purchases/:id/razorpay/order	→ { order: { keyId, orderId, amount (paise), currency, purchaseId } }
POST	/purchases/:id/razorpay/verify	{ razorpayOrderId, razorpayPaymentId, razorpaySignature }

Client payment flow

1. POST .../carts/:id/purchases
2. POST .../purchases/:id/razorpay/order
3. Open Razorpay Checkout with keyId + orderId
4. POST .../purchases/:id/razorpay/verify

Only the public **keyId** from the order response belongs in the client — never the Razorpay key secret.

On **SUCCESS**: cart locks, consultation is created, purchase is **PAID** .

Consultations, prescriptions, orders

Method	Path	Notes
GET	/consultations	
GET	/consultations/:id	
GET	/consultations/:id/journey	Consultation journey (web)
POST	/consultations/:id/messages	
POST	/consultations/:id/documents	
POST	/consultations/:id/video/token	Patient video token
GET	/prescriptions	
GET	/prescriptions/:id	
GET	/prescriptions/:id/pdf	PDF (web)
GET	/orders	Customer order id = purchase id ; public display OD#####
GET	/orders/:id	Summary
GET	/orders/:id/detail	order + timeline + delivery
GET	/orders/:id/shipment	
GET	/shipments/:id	Shipment by id
POST	/orders/:id/cancel	Cancel when eligible (web)
POST	/orders/:id/returns	Return request (web)
GET	/orders/:id/documents/receipt	(web)
GET	/orders/:id/documents/invoice	(web)

Guest video join (no JWT):

Method	Path
GET	/v1/public/consultations/join/:token
POST	/v1/public/consultations/join/:token

8. Notifications **/v1/notifications**

Method	Path
GET	/
GET	/unread-count
POST	/read-all
POST	/:id/read
POST	/:id/archive
POST	/:id/unarchive

9. Recommended sequences

A. Browse → cart → Razorpay

```

GET /v1/catalog/homepage
GET /v1/catalog/medicines/by-subcategory?categoryId=...
GET /v1/catalog/medicines/:id
POST /v1/auth/otp/send → /otp/verify (or /login)
POST /v1/users/carts/items
POST /v1/users/questionnaires/sessions
PATCH .../sessions/:id/answers
POST .../sessions/:id/submit
POST /v1/users/carts/:id/purchases
POST /v1/users/purchases/:id/razorpay/order
POST /v1/users/purchases/:id/razorpay/verify
GET /v1/users/consultations
GET /v1/users/orders/:id/detail

```

B. Email signup

```

POST /v1/auth/register/email-otp/send
POST /v1/auth/register/email-otp/verify → emailVerificationToken
POST /v1/auth/register

```

C. Mobile OTP onboarding

```
POST /v1/auth/otp/send
POST /v1/auth/otp/verify
POST /v1/auth/otp/complete-profile      (if profileComplete=false)
```

10. Integrator checklist

1. Store `accessToken` + `refreshToken` ; refresh before expiry; logout revokes refresh.
2. Send `Authorization: Bearer ...` on `/v1/users/*` and other protected routes.
3. Complete profile before checkout mutations.
4. Use purchase id / public order ref `OD#####` as the customer-facing order identifier.
5. Prefer `GET /orders/:id/detail` for account order UI.
6. Handle unified error shape + `x-request-id` .
7. For All Treatments screens, call `GET /v1/catalog/medicines/by-subcategory` (not a flat medicines list).

Questions / contract changes: share the failing `x-request-id` and request path with the API team.