



Food Delivery Service

[Introduction](#)

[Objective](#) **Introduction**

[Database](#)

[Schema](#)

[Design](#)

[Guidelines](#)

[Rest](#)

[API](#)

[Design](#)

[Status](#)

[Codes](#)

[Endpoints](#)



Welcome to the documentation for our Food Delivery Service project! This project aims to provide a robust and user-friendly platform for ordering food online, facilitating the seamless delivery of meals from various restaurants to customers' doorsteps. Our goal is to create a scalable solution that enhances the food delivery experience for both customers and restaurant partners.

Objective



The core objective of our Food Delivery Service project is to establish a versatile and scalable platform that facilitates seamless access to a diverse range of food options while fostering a vibrant and engaging online community. Our project endeavors to create an immersive and interactive space where users can effortlessly explore culinary delights, share gastronomic experiences, and forge valuable connections within a digital food-centric community.

Database Schema

▼ ER Diagram

[fooservice.mwb](#)

<https://prod-files-secure.s3.us-west-2.amazonaws.com/31282dbc-a6a3-454c-930f-bedcf45363ec/eab42bbd-719b-4bee-b244-66ef105ead0b/fooservice.pdf>

▼ Database Script File

[fooserviceee.sql](#)

Design Guidelines

1. All Rest API requests and response formats must be in JSON.
2. 200, 201, 400, 404, 401, 500, 505 – use the appropriate HTTP status code in your response object.

3. Handle the Rest exceptions globally using the Rest exception handler for all endpoints.
4. Test your Rest Api using Junit and Mockito.
5. Participants should not alter database schema under any circumstances except wherever changes are mentioned explicitly.

Rest API Design

All REST API requests and responses follow the JSON format. The project implies standard HTTP status codes (200, 201, 400, 404, 401, 500, 505) appropriately in response objects to convey the outcome of API requests.

Status Codes

HTTP response codes are used to indicate general classes of success and error.

HTTP Status Quote	Description
200	Successfully processed request.
201	Created
202	Accepted
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
500	Internal Server Error

Endpoints

Endpoints

Name	Http Method	Description	Success Response	Error Response
<u>/api/restaurants</u>	GET	Retrieve a list of all restaurants.	{list of all users}	{ "code": GETFAILS",

Aa Name	⚙ Http Method	≡ Description	≡ Success Response	≡ Error Response
				<pre>"message":User list is empty" }</pre>
<u>/api/restaurants/{restaurantId}</u>	GET	Retrieve details of a specific restaurant	{Object of user }	<pre>{ "code": GETFAILS", "message":User r doesn't exist exist" }</pre>
<u>/api/restaurants</u>	POST	create a new restaurants	<pre>{ "code": "SUCCESS", "message": "User added successfully" }</pre>	<pre>{ "code": UPDTFAILS", "message":User r doesn't exist exist" }</pre>
<u>/api/restaurants/{restaurantId}</u>	PUT	Update details of a specific restaurant.	<pre>{ "code": "UPDATESUCCESS", "message": "User updated successfully" }</pre>	<pre>{ "code": UPDTFAILS", "message":User r doesn't exist exist" }</pre>
<u>/api/restaurants/{restaurantId}</u>	DELETE	Delete a specific restaurant	<pre>{ "code": "DELETESUCCESS", "message": "User deleted successfully" }</pre>	<pre>{ "code": DLTFAILS", "message":User r doesn't exist exist" }</pre>
<u>/api/restaurants/{restaurantId}/menu</u>	GET	Retrieve all menu items of a specific restaurant	<pre>{ "code": "DELETESUCCESS", "message": "User deleted successfully" }</pre>	<pre>{ "code": DLTFAILS", "message":User r doesn't exist exist" }</pre>

Aa Name	⌘ Http Method	≡ Description	≡ Success Response	≡ Error Response
<u>/api/restaurants/{restaurantId}/reviews</u>	GET	Retrieve all reviews submitted for a specific restaurant.	<pre>{ "code": "DELETESUCCESS", "message": "User deleted successfully" }</pre>	<pre>{ "code": "DLTFAILS", "message": "User doesn't exist" }</pre>
<u>/api/restaurants/{restaurantId}/delivery-areas</u>	GET	: Retrieve all delivery areas served by a specific restaurant	<pre>{ "code": "DELETESUCCESS", "message": "User deleted successfully" }</pre>	<pre>{ "code": "DLTFAILS", "message": "User doesn't exist" }</pre>
<u>/api/restaurants/{restaurantId}/menu</u>	GET	Retrieve all menu items of a specific restaurant.	{list of all projects}	<pre>{ "code": "GETALLFAILS", "message": "Project list is empty" }</pre>
<u>/api/restaurants/{restaurantId}/menu</u>	POST	Add a new menu item to a specific restaurant.	<pre>{ "code": "UPDATESUCCESS", "message": "Project updated successfully" }</pre>	<pre>{ "code": "UPDTFAILS", "message": "Project doesn't exist" }</pre>
<u>/api/restaurants/{restaurantId}/menu/{itemId}</u>	PUT	Update details of a specific menu item in a restaurant.	<pre>{ "code": "DELETESUCCESS", "message": "Project deleted successfully" }</pre>	<pre>{ "code": "DLTFAILS", "message": "Project doesn't exist" }</pre>

Aa Name	⌘ Http Method	≡ Description	≡ Success Response	≡ Error Response
<u>/api/restaurants/{restaurantId}/menu/{itemId}</u>	DELETE	Delete a specific menu item from a restaurant	<pre>{ "code": "DELETESUCCESS", "message": "Project deleted successfully" }</pre>	<pre>{ "code": "DLTFAILS", "message": "Project doesn't exist exist" }</pre>
<u>/api/orders</u>	POST	Place a new order	{List of task}	<pre>{ "code": "GETALLFAILS", "message": "Task list is empty" }</pre>
<u>/api/orders/{orderId}</u>	GET	Retrieve details of a specific order.	{List of task}	<pre>{ "code": "GETALLFAILS", "message": "Task list is empty" }</pre>
<u>/api/orders/{orderId}/status</u>	PUT	Update the status of a specific order.	{List of task}	<pre>{ "code": "GETALLFAILS", "message": "Task list is empty" }</pre>
<u>/api/orders/{orderId}</u>	DELETE	Cancel a specific order	{List of task}	<pre>{ "code": "GETALLFAILS", "message": "Task list is empty" }</pre>
<u>Untitled</u>				
<u>Untitled</u>				
<u>/api/drivers</u>	GET	Retrieve a list of all delivery drivers		
<u>/api/drivers/{driverId}</u>	GET	Retrieve details of a specific delivery driver.		

Aa Name	⌘ Http Method	≡ Description	≡ Success Response	≡ Error Response
<u>/api/orders/{orderId}/assignDriver/{driverId}</u>	PUT	Assign a specific driver to an order.		
<u>/api/drivers/{driverId}/location</u>	PUT	Update the location of a specific driver.		
<u>/api/drivers/{driverId}/orders</u>	GET	Retrieve all orders assigned to a specific delivery driver.		
Untitled				
<u>/api/customers</u>	GET	Retrieve a list of all customers		
<u>/api/customers/{customerId}</u>	GET	Retrieve details of a specific customer.		
<u>/api/customers/{customerId}</u>	PUT	Update details of a specific customer.		
<u>/api/customers/{customerId}</u>	DELETE	Delete a specific customer		
<u>/api/customers/{customerId}/orders</u>	GET	Retrieve all orders placed by a specific customer		
<u>/api/customers/{customerId}/reviews</u>	GET	Retrieve all reviews submitted by a specific customer.		
<u>/api/customers/{customerId}/favorites</u>	POST	Add a restaurant to the list of favorites for a specific customer		
<u>/api/customers/{customerId}/favorites</u>	DELETE	Remove a restaurant from the list of favorites for		

Aa Name	⌘ Http Method	≡ Description	≡ Success Response	≡ Error Response
<u>es/{restaurantId}</u>		a specific customer.		

New end points - Food Delivery Service