

The Delinearization of C programs

Chirantan Mukherjee, Marc Moreno Maza, Linxiao Wang

Ontario Research Centre for Computer Algebra

April 9, 2024

cmukher@uwo.ca



Content

- 1 Motivation
- 2 The Delinearization Problem
- 3 Solution

Linearized multi-dimensional array

```
for(int i = 0; i < n; i++)  
    for(int j = i + 1; j < n; j ++)  
        A[i * n + j] = A[(n * j - n + j - i - 1)];
```



Linearized multi-dimensional array

```
for(int i = 0; i < n; i++)  
    for(int j = i + 1; j < n; j ++)  
        A[i * n + j] = A[(n * j - n + j - i - 1)];
```

Can we parallelize the two for-loops?

We need to see whether there is **data dependence** between two different iterations of the nest.

Linearized multi-dimensional array

```
for(int i = 0; i < n; i++)
    for(int j = i + 1; j < n; j++)
        A[i * n + j] = A[(n * j - n + j - i - 1)];
```

Can we parallelize the two for-loops?

We need to see whether there is **data dependence** between two different iterations of the nest.

Are there **integer solutions** to the following system of linear inequalities:

$$\left\{ \begin{array}{l} 0 \leq i_1 < n \\ i_1 + 1 \leq j_1 < n \\ 0 \leq i_2 < n \\ i_2 + 1 \leq j_2 < n \\ i_1 \times n + j_1 = n \times j_2 - n + j_2 - i_2 - 1 \end{array} \right.$$



Delinearize the array accesses

Linearized one-dimensional array

```
for(int i = 0; i < n; i++)  
  for(int j = i + 1; j < n; j ++)  
    A[i * n + j] =  
      A[(n * j - n + j - i - 1)];
```

Delinearize the array accesses

Linearized one-dimensional array

```
for(int i = 0; i < n; i++)  
  for(int j = i + 1; j < n; j ++)  
    A[i * n + j] =  
      A[(n * j - n + j - i - 1)];
```

Delinearized multi-dimensional array

```
for(int i = 0; i < n; i++)  
  for(int j = i + 1; j < n; j ++)  
    B[i][j] = B[j - 1][j - i - 1];
```

Delinearize the array accesses

Linearized one-dimensional array

```
for(int i = 0; i < n; i++)
  for(int j = i + 1; j < n; j++)
    A[i * n + j] =
      A[(n * j - n + j - i - 1)];
```

$$\left\{ \begin{array}{l} 0 \leq i_1 < n \\ i_1 + 1 \leq j_1 < n \\ 0 \leq i_2 < n \\ i_2 + 1 \leq j_2 < n \\ i_1 \times n + j_1 = n \times j_2 - n + j_2 - i_2 - 1 \end{array} \right.$$

Delinearized multi-dimensional array

```
for(int i = 0; i < n; i++)
  for(int j = i + 1; j < n; j++)
    B[i][j] = B[j - 1][j - i - 1];
```


Delinearize the array accesses

Linearized one-dimensional array

```
for(int i = 0; i < n; i++)
  for(int j = i + 1; j < n; j++)
    A[i * n + j] =
      A[(n * j - n + j - i - 1)];
```

Delinearized multi-dimensional array

```
for(int i = 0; i < n; i++)
  for(int j = i + 1; j < n; j++)
    B[i][j] = B[j - 1][j - i - 1];
```

$$\left\{ \begin{array}{l} 0 \leq i_1 < n \\ i_1 + 1 \leq j_1 < n \\ 0 \leq i_2 < n \\ i_2 + 1 \leq j_2 < n \\ i_1 \times n + j_1 = n \times j_2 - n + j_2 - i_2 - 1 \end{array} \right.$$

$$\left\{ \begin{array}{l} 0 \leq i_1 < n \\ i_1 + 1 \leq j_1 < n \\ 0 \leq i_2 < n \\ i_2 + 1 \leq j_2 < n \\ i_1 = j_2 - 1 \\ j_1 = j_2 - i_2 - 1 \end{array} \right.$$



Delinearize the array accesses

Linearized one-dimensional array

```
for(int i = 0; i < n; i++)
  for(int j = i + 1; j < n; j++)
    A[i * n + j] =
      A[(n * j - n + j - i - 1)];
```

Delinearized multi-dimensional array

```
for(int i = 0; i < n; i++)
  for(int j = i + 1; j < n; j++)
    B[i][j] = B[j - 1][j - i - 1];
```

$$\left\{ \begin{array}{l} 0 \leq i_1 < n \\ i_1 + 1 \leq j_1 < n \\ 0 \leq i_2 < n \\ i_2 + 1 \leq j_2 < n \\ i_1 \times n + j_1 = n \times j_2 - n + j_2 - i_2 - 1 \end{array} \right.$$

$$\left\{ \begin{array}{l} 0 \leq i_1 < n \\ i_1 + 1 \leq j_1 < n \\ 0 \leq i_2 < n \\ i_2 + 1 \leq j_2 < n \\ i_1 = j_2 - 1 \\ j_1 = j_2 - i_2 - 1 \end{array} \right.$$

There is **no integer solution**, therefore, **no dependence**.



Can we replace a one-dimension array A by another multi-dimensional array B so that every subscript of B is an affine expression of the loop counters?



Can we replace a **one-dimension array** A by another **multi-dimensional array** B so that every subscript of B is an **affine expression** of the loop counters?

Input

```
for(i_1, ..., i_1 ++)  
...  
  for(i_d, ..., i_d ++)  
    A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```



Can we replace a **one-dimension array** A by another **multi-dimensional array** B so that every subscript of B is an **affine expression** of the loop counters?

Input

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```

- i_1, \dots, i_d take non-negative integer values

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$



Can we replace a **one-dimension array** A by another **multi-dimensional array** B so that every subscript of B is an **affine expression** of the loop counters?

Input

```
for(i_1, ..., i_1++)
...
for(i_d, ..., i_d++)
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```

- i_1, \dots, i_d take non-negative integer values

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$

- L is a lower-triangular full-rank matrix over \mathbb{Z} (**known at compile time**) defining the **iteration domain**



Can we replace a **one-dimension array** A by another **multi-dimensional array** B so that every subscript of B is an **affine expression** of the loop counters?

Input

```
for(i_1, ..., i_1++)
...
for(i_d, ..., i_d++)
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```

- i_1, \dots, i_d take non-negative integer values

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$

- L is a lower-triangular full-rank matrix over \mathbb{Z} (**known at compile time**) defining the **iteration domain**
- $m_1, \dots, m_e, r_1, \dots, r_d$: **data parameters** (**known only at execution time**)



Can we replace a **one-dimension** array A by another **multi-dimensional** array B so that every subscript of B is an **affine expression** of the loop counters?

Input

```
for(i_1, ..., i_1++)
...
for(i_d, ..., i_d++)
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```

- i_1, \dots, i_d take non-negative integer values

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$

- L is a lower-triangular full-rank matrix over \mathbb{Z} (**known at compile time**) defining the **iteration domain**
- $m_1, \dots, m_e, r_1, \dots, r_d$: **data parameters** (**known only at execution time**)
- $R(i_1, \dots, i_d, m_1, \dots, m_e)$ is a polynomial, whose coefficients are **known at compile time**



Can we replace a **one-dimension** array A by another **multi-dimensional** array B so that every subscript of B is an **affine expression** of the loop counters?

Input

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...  
  •  $i_1, \dots, i_d$  take non-negative integer values
```

Output

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  B[f_1], ..., B[f_e] <- ...
```

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$

- L is a lower-triangular full-rank matrix over \mathbb{Z} (**known at compile time**) defining the **iteration domain**
- $m_1, \dots, m_e, r_1, \dots, r_d$: **data parameters** (**known only at execution time**)
- $R(i_1, \dots, i_d, m_1, \dots, m_e)$ is a polynomial, whose coefficients are **known at compile time**



Can we replace a **one-dimension array** A by another **multi-dimensional array** B so that every subscript of B is an **affine expression of the loop counters**?

Input

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```

- i_1, \dots, i_d take non-negative integer values

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$

- L is a lower-triangular full-rank matrix over \mathbb{Z} (**known at compile time**) defining the **iteration domain**
- $m_1, \dots, m_e, r_1, \dots, r_d$: **data parameters** (**known only at execution time**)
- $R(i_1, \dots, i_d, m_1, \dots, m_e)$ is a polynomial, whose coefficients are **known at compile time**

Output

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  B[f_1], ..., B[f_e] <- ...
```

- f_1, \dots, f_e are affine forms in i_1, \dots, i_d the coefficients of which are integers **to-be-determined**



Can we replace a **one-dimension array** A by another **multi-dimensional array** B so that every subscript of B is an **affine expression of the loop counters**?

Input

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```

- i_1, \dots, i_d take non-negative integer values

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$

- L is a lower-triangular full-rank matrix over \mathbb{Z} (**known at compile time**) defining the **iteration domain**
- $m_1, \dots, m_e, r_1, \dots, r_d$: **data parameters** (**known only at execution time**)
- $R(i_1, \dots, i_d, m_1, \dots, m_e)$ is a polynomial, whose coefficients are **known at compile time**

Output

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  B[f_1], ..., B[f_e] <- ...
```

- f_1, \dots, f_e are affine forms in i_1, \dots, i_d the coefficients of which are integers **to-be-determined**
- B is an $M_1 \times \dots \times M_e$ -array



Can we replace a **one-dimension array** A by another **multi-dimensional array** B so that every subscript of B is an **affine expression of the loop counters**?

Input

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```

- i_1, \dots, i_d take non-negative integer values

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$

- L is a lower-triangular full-rank matrix over \mathbb{Z} (**known at compile time**) defining the **iteration domain**
- $m_1, \dots, m_e, r_1, \dots, r_d$: **data parameters** (**known only at execution time**)
- $R(i_1, \dots, i_d, m_1, \dots, m_e)$ is a polynomial, whose coefficients are **known at compile time**

Output

```
for(i_1, ..., i_1 ++)  
...  
for(i_d, ..., i_d ++)  
  B[f_1], ..., B[f_e] <- ...
```

- f_1, \dots, f_e are affine forms in i_1, \dots, i_d the coefficients of which are integers **to-be-determined**
- B is an $M_1 \times \dots \times M_e$ -array
- M_1, \dots, M_e are affine forms in m_1, \dots, m_d the coefficients of which are integers **to-be-determined**



Can we replace a **one-dimension** array A by another **multi-dimensional** array B so that every subscript of B is an **affine expression** of the loop counters?

Input

```
for(i_1, ..., i_1++)
...
for(i_d, ..., i_d++)
  A[R(i_1, ..., i_d, m_1, ..., m_e)] <- ...
```

- i_1, \dots, i_d take non-negative integer values

$$L \begin{pmatrix} i_1 \\ \vdots \\ i_d \end{pmatrix} \leq \begin{pmatrix} r_1 \\ \vdots \\ r_d \end{pmatrix}$$

- L is a lower-triangular full-rank matrix over \mathbb{Z} (**known at compile time**) defining the **iteration domain**
- $m_1, \dots, m_e, r_1, \dots, r_d$: **data parameters** (**known only at execution time**)
- $R(i_1, \dots, i_d, m_1, \dots, m_e)$ is a polynomial, whose coefficients are **known at compile time**

Output

```
for(i_1, ..., i_1++)
...
for(i_d, ..., i_d++)
  B[f_1], ..., B[f_e] <- ...
```

- f_1, \dots, f_e are affine forms in i_1, \dots, i_d the coefficients of which are integers **to-be-determined**
- B is an $M_1 \times \dots \times M_e$ -array
- M_1, \dots, M_e are affine forms in m_1, \dots, m_d the coefficients of which are integers **to-be-determined**

such that:

$$R = f_1 M_2 \cdots M_e + \cdots + f_{e-1} M_2 + f_e$$

holds and for each (i_1, \dots, i_d) in the iteration

domain we have the **validity conditions**:

$$0 \leq f_1 < M_1, \quad \dots, \quad 0 \leq f_e < M_e.$$



The delinearization problem can be divided into:

- 1 Polynomial System Solving Problem expressing f_1, \dots, f_e and M_1, \dots, M_e offline as coefficients of
$$R = f_1 M_2 \cdots M_e + \cdots + f_{e-1} M_2 + f_e,$$

The delinearization problem can be divided into:

- 1 **Polynomial System Solving Problem** expressing f_1, \dots, f_e and M_1, \dots, M_e offline as coefficients of $R = f_1 M_2 \cdots M_e + \cdots + f_{e-1} M_2 + f_e$, when d and e are known.
- 2 **Quantifier Elimination Problem** for each (i_1, \dots, i_d) in the iteration domain we obtain the validity conditions $0 \leq f_1 < M_1, \dots, 0 \leq f_e < M_e$.

The **delinearization problem** can be divided into:

- ① **Polynomial System Solving Problem** expressing f_1, \dots, f_e and M_1, \dots, M_e offline as coefficients of $R = f_1 M_2 \cdots M_e + \cdots + f_{e-1} M_2 + f_e$, when d and e are known.
- ② **Quantifier Elimination Problem** for each (i_1, \dots, i_d) in the iteration domain we obtain the validity conditions $0 \leq f_1 < M_1, \dots, 0 \leq f_e < M_e$. This non-linear QE problem can only be solved offline over \mathbb{R}

The **delinearization problem** can be divided into:

- ① **Polynomial System Solving Problem** expressing f_1, \dots, f_e and M_1, \dots, M_e offline as coefficients of $R = f_1 M_2 \cdots M_e + \cdots + f_{e-1} M_2 + f_e$, when d and e are known.
- ② **Quantifier Elimination Problem** for each (i_1, \dots, i_d) in the iteration domain we obtain the validity conditions $0 \leq f_1 < M_1, \dots, 0 \leq f_e < M_e$. This non-linear QE problem can only be solved offline over \mathbb{R} and then can be reduced to Presburger arithmetic (that is, QE on affine forms over \mathbb{Z}).

The **delinearization problem** can be divided into:

- ① **Polynomial System Solving Problem** expressing f_1, \dots, f_e and M_1, \dots, M_e offline as coefficients of $R = f_1 M_2 \cdots M_e + \cdots + f_{e-1} M_2 + f_e$, when d and e are known.
- ② **Quantifier Elimination Problem** for each (i_1, \dots, i_d) in the iteration domain we obtain the validity conditions $0 \leq f_1 < M_1, \dots, 0 \leq f_e < M_e$. This non-linear QE problem can only be solved offline over \mathbb{R} and then can be reduced to Presburger arithmetic (that is, QE on affine forms over \mathbb{Z}).

Parametric Integer Linear Programming

$$\begin{array}{ll} \max_{(i_1, \dots, i_d)} & f_k \\ \text{subject to} & (i_1, \dots, i_d) \in \text{iteration domain} \\ & i_1, \dots, i_d \in \mathbb{Z} \end{array}$$

For which, $0 \leq \max_{(i_1, \dots, i_d)} f_k < M_k$ for all $k \in [1, \dots, e]$.

2D-2D delinearization problem

$d = 2$, means there are two loop counter i_1, i_2 known at compile time.



2D-2D delinearization problem

$d = 2$, means there are two loop counter i_1, i_2 known at compile time.
 $e = 2$, means there are two program parameters m_1, m_2 also known at compile time.

2D-2D delinearization problem

$d = 2$, means there are two loop counter i_1, i_2 known at compile time.
 $e = 2$, means there are two program parameters m_1, m_2 also known at compile time.

Should return two polynomials $M_1 = a_1 m_1 + b_1$ and $M_2 = a_2 m_2 + b_2$, where a_1, b_1, a_2, b_2 are integers to-be-determined.

2D-2D delinearization problem

$d = 2$, means there are two loop counter i_1, i_2 known at compile time.

$e = 2$, means there are two program parameters m_1, m_2 also known at compile time.

Should return two polynomials $M_1 = a_1 m_1 + b_1$ and $M_2 = a_2 m_2 + b_2$, where a_1, b_1, a_2, b_2 are integers to-be-determined.

The reference $A[R]$ to A which encodes a reference $B[f_1][f_2]$ to B , where:



2D-2D delinearization problem

$d = 2$, means there are two loop counter i_1, i_2 known at compile time.
 $e = 2$, means there are two program parameters m_1, m_2 also known at compile time.

Should return two polynomials $M_1 = a_1 m_1 + b_1$ and $M_2 = a_2 m_2 + b_2$, where a_1, b_1, a_2, b_2 are integers to-be-determined.

The reference $A[R]$ to A which encodes a reference $B[f_1][f_2]$ to B , where:

- $f_1 = f_{11}i_1 + f_{12}i_2 + f_{10}$ and $f_2 = f_{21}i_1 + f_{22}i_2 + f_{20}$ are affine functions

2D-2D delinearization problem

$d = 2$, means there are two loop counter i_1, i_2 known at compile time.
 $e = 2$, means there are two program parameters m_1, m_2 also known at compile time.

Should return two polynomials $M_1 = a_1 m_1 + b_1$ and $M_2 = a_2 m_2 + b_2$, where a_1, b_1, a_2, b_2 are integers to-be-determined.

The reference $A[R]$ to A which encodes a reference $B[f_1][f_2]$ to B , where:

- $f1 = f_{11}i_1 + f_{12}i_2 + f_{10}$ and $f2 = f_{21}i_1 + f_{22}i_2 + f_{20}$ are affine functions
- $R = f1M_2 + f2$ is a polynomial

2D-2D delinearization problem

$d = 2$, means there are two loop counter i_1, i_2 known at compile time.
 $e = 2$, means there are two program parameters m_1, m_2 also known at compile time.

Should return two polynomials $M_1 = a_1 m_1 + b_1$ and $M_2 = a_2 m_2 + b_2$, where a_1, b_1, a_2, b_2 are integers to-be-determined.

The reference $A[R]$ to A which encodes a reference $B[f_1][f_2]$ to B , where:

- $f1 = f_{11}i_1 + f_{12}i_2 + f_{10}$ and $f2 = f_{21}i_1 + f_{22}i_2 + f_{20}$ are affine functions
- $R = f1M_2 + f2$ is a polynomial
- for each (i_1, i_2) , we have, the validity conditions $0 \leq f1 < M_1$ and $0 \leq f2 < M_2$, and $0 \leq \max f1 < M_1$ and $0 \leq \max f2 < M_2$.

2D-2D polynomial system solving

Substituting f_1 and f_2 in R , we obtain, $R = \underbrace{a_2 f_{11}}_{T_1} i_1 m_2 + \underbrace{a_2 f_{12}}_{T_2} i_2 m_2 + \underbrace{a_2 f_{10}}_{T_3} m_2 + \underbrace{(b_2 f_{11} + f_{21})}_{T_4} i_1 + \underbrace{(b_2 f_{12} + f_{22})}_{T_5} i_2 + \underbrace{(b_2 f_{10} + f_{20})}_{T_6}.$

2D-2D polynomial system solving

Substituting f_1 and f_2 in R , we obtain, $R = \underbrace{a_2 f_{11}}_{T_1} i_1 m_2 + \underbrace{a_2 f_{12}}_{T_2} i_2 m_2 + \underbrace{a_2 f_{10}}_{T_3} m_2 + \underbrace{(b_2 f_{11} + f_{21})}_{T_4} i_1 + \underbrace{(b_2 f_{12} + f_{22})}_{T_5} i_2 + \underbrace{(b_2 f_{10} + f_{20})}_{T_6}.$

$$\left\{ \begin{array}{l} T_1 = a_2 f_{11} \\ T_2 = a_2 f_{12} \\ T_3 = a_2 f_{10} \\ T_4 = b_2 f_{11} + f_{21} \\ T_5 = b_2 f_{12} + f_{22} \\ T_6 = b_2 f_{10} + f_{20} \end{array} \right. \Rightarrow \left\{ \begin{array}{l} f_{11} = \frac{T_1}{a_2} \\ f_{12} = \frac{T_2}{a_2} \\ f_{10} = \frac{T_3}{a_2} \\ f_{21} = T_4 - b_2 f_{11} \\ f_{22} = T_5 - b_2 f_{12} \\ f_{20} = T_6 - b_2 f_{10} \end{array} \right.$$



2D-2D polynomial system solving

Substituting f_1 and f_2 in R , we obtain, $R = \underbrace{a_2 f_{11}}_{T_1} i_1 m_2 + \underbrace{a_2 f_{12}}_{T_2} i_2 m_2 + \underbrace{a_2 f_{10}}_{T_3} m_2 + \underbrace{(b_2 f_{11} + f_{21})}_{T_4} i_1 + \underbrace{(b_2 f_{12} + f_{22})}_{T_5} i_2 + \underbrace{(b_2 f_{10} + f_{20})}_{T_6}.$

$$\left\{ \begin{array}{l} T_1 = a_2 f_{11} \\ T_2 = a_2 f_{12} \\ T_3 = a_2 f_{10} \\ T_4 = b_2 f_{11} + f_{21} \\ T_5 = b_2 f_{12} + f_{22} \\ T_6 = b_2 f_{10} + f_{20} \end{array} \right. \Rightarrow \left\{ \begin{array}{l} f_{11} = \frac{T_1}{a_2} \\ f_{12} = \frac{T_2}{a_2} \\ f_{10} = \frac{T_3}{a_2} \\ f_{21} = T_4 - b_2 f_{11} \\ f_{22} = T_5 - b_2 f_{12} \\ f_{20} = T_6 - b_2 f_{10} \end{array} \right.$$

a_2 and b_2 can not be uniquely determined,



2D-2D polynomial system solving

Substituting f_1 and f_2 in R , we obtain, $R = \underbrace{a_2 f_{11}}_{T_1} i_1 m_2 + \underbrace{a_2 f_{12}}_{T_2} i_2 m_2 + \underbrace{a_2 f_{10}}_{T_3} m_2 + \underbrace{(b_2 f_{11} + f_{21})}_{T_4} i_1 + \underbrace{(b_2 f_{12} + f_{22})}_{T_5} i_2 + \underbrace{(b_2 f_{10} + f_{20})}_{T_6}.$

$$\left\{ \begin{array}{l} T_1 = a_2 f_{11} \\ T_2 = a_2 f_{12} \\ T_3 = a_2 f_{10} \\ T_4 = b_2 f_{11} + f_{21} \\ T_5 = b_2 f_{12} + f_{22} \\ T_6 = b_2 f_{10} + f_{20} \end{array} \right. \Rightarrow \left\{ \begin{array}{l} f_{11} = \frac{T_1}{a_2} \\ f_{12} = \frac{T_2}{a_2} \\ f_{10} = \frac{T_3}{a_2} \\ f_{21} = T_4 - b_2 f_{11} \\ f_{22} = T_5 - b_2 f_{12} \\ f_{20} = T_6 - b_2 f_{10} \end{array} \right.$$

a_2 and b_2 can not be uniquely determined, but $a_2 \mid \gcd(T_1, T_2, T_3).$



2D-2D quantifier elimination (I/II)

Recall for each (i_1, i_2) , we have the validity condition, $0 \leq f_2 < M_2$ and $0 \leq \max f_2 < M_2$, that is,

$$\left\{ \begin{array}{ll} \max_{(i_1, i_2)} & f_2 \\ \text{subject to} & (i_1, i_2) \in \text{iteration domain} \\ & i_1, i_2 \in \mathbb{Z} \end{array} \right.$$

Depending on the **shape of the iteration domain**, we solve on a case to case basis.

2D-2D quantifier elimination (I/II) - Rectangular domain

For a for loop of the form,

```
for (int i_1 = 0; i_1 < r_1; i_1 ++)  
  for (int i_2 = 0; i_2 < r_2; i_2 ++)
```




2D-2D quantifier elimination (I/II) - Rectangular domain

For a for loop of the form,

```
for (int i_1 = 0; i_1 < r_1; i_1 ++)  
  for (int i_2 = 0; i_2 < r_2; i_2 ++)
```

the iteration domain is of the shape,



2D-2D quantifier elimination (I/II) - Triangular domain

For a for loop of the form,

```
for (int i_1 = 0; i_1 < r_1; i_1 ++)  
    for (int i_2 = 0; f_{21} * i_1 + f_{22} * i_2 < r_2; i_2 ++)
```




2D-2D quantifier elimination (I/II) - Triangular domain

For a for loop of the form,

```
for (int i_1 = 0; i_1 < r_1; i_1 ++)  
  for (int i_2 = 0; f_{21} * i_1 + f_{22} * i_2 < r_2; i_2 ++)
```

the **iteration domain** is of the shape,



Notice, that $i_2 = \frac{-i_1 f_{22} + r_2}{f_{21}}$



2D-2D quantifier elimination (I/II)


The parametric integer linear problem can be solved for:

- ① Rectangular domain by case inspection
- ② Triangular domain by case inspection except when $f_{21}, f_{22} > 0$, in which case the problem becomes,

$$\begin{array}{ll} \max_{i_1} & f_{21}i_1 + f_{22} \lfloor \frac{-i_1 f_{22} + r_2}{f_{21}} \rfloor + f_{20} \\ \text{subject to} & 0 \leq i_1 < r_1, \quad i_1 \in \mathbb{Z} \end{array}$$


2D-2D quantifier elimination (I/II)

Since the loop counters can only be integers this leads to the problem of **finding the integer hull** of a polyhedral set, for which we propose the following integer hull algorithm,




2D-2D quantifier elimination (I/II)

Since the loop counters can only be integers this leads to the problem of **finding the integer hull** of a polyhedral set, for which we propose the following integer hull algorithm,



2D-2D quantifier elimination (I/II)

Since the loop counters can only be integers this leads to the problem of **finding the integer hull** of a polyhedral set, for which we propose the following integer hull algorithm,



The **integer hull** $\{D, E, F, G, H\}$ is formed by $\{D, E, G\}$ and searching integer points $\{F, H\}$ in quadrilaterals $DD''B''E$, $EB'C''G$ and $D'DGC'$.

2D-2D quantifier elimination (II/II)

Another approach is to do QE over \mathbb{R} ,



2D-2D quantifier elimination (II/II)

Another approach is to do QE over \mathbb{R} , for which we can use the function `QuantifierElimination` from the `SemiAlgebraicSetTools` package, which is a subpackage of the `RegularChains` library.



2D-2D quantifier elimination (II/II)

Another approach is to do QE over \mathbb{R} , for which we can use the function `QuantifierElimination` from the `SemiAlgebraicSetTools` package, which is a subpackage of the `RegularChains` library.

```
f := &A([i_1, i_2]), ((0 < i_1) &and (i_1 < r_1) &and
                      (0 < i_2) &and (i_2 < r_2) &and
                      (0 < r_1) &and (0 < r_2) &and
                      (0 < f_{21}) &and (0 < f_{22}) &and (0 < B))
\\ B = M_2 - f_{20}
&implies (f_{21} * i_1 + f_{22} * i_2 < B);
```



2D-2D quantifier elimination (II/II)

Another approach is to do QE over \mathbb{R} , for which we can use the function `QuantifierElimination` from the `SemiAlgebraicSetTools` package, which is a subpackage of the `RegularChains` library.

```
f := &A([i_1, i_2]), ((0 < i_1) &and (i_1 < r_1) &and
                      (0 < i_2) &and (i_2 < r_2) &and
                      (0 < r_1) &and (0 < r_2) &and
                      (0 < f_{21}) &and (0 < f_{22}) &and (0 < B))
                      \\ B = M_2 - f_{20}
&implies (f_{21} * i_1 + f_{22} * i_2 < B);
```

After simplification, $r_1 * f_{21} + r_2 * f_{22} + f_{20} < M_2$.



2D-2D quantifier elimination (II/II)

Another approach is to do QE over \mathbb{R} , for which we can use the function `QuantifierElimination` from the `SemiAlgebraicSetTools` package, which is a subpackage of the `RegularChains` library.

```
f := &A([i_1, i_2]), ((0 < i_1) &and (i_1 < r_1) &and
                      (0 < i_2) &and (i_2 < r_2) &and
                      (0 < r_1) &and (0 < r_2) &and
                      (0 < f_{21}) &and (0 < f_{22}) &and (0 < B))
\\ B = M_2 - f_{20}
&implies (f_{21} * i_1 + f_{22} * i_2 < B);
```

After simplification, $r_1 * f_{21} + r_2 * f_{22} + f_{20} < M_2$.
 Substituting, $f_{11} = \frac{T_1}{a_2}$, $f_{12} = \frac{T_2}{a_2}$, $f_{10} = \frac{T_3}{a_2}$, $f_{21} = T_4 - b_2 f_{11}$, $f_{22} = T_5 - b_2 f_{12}$, $f_{20} = T_6 - b_2 f_{10}$, $M_2 = a_2 m_2 + b_2$, we obtain,

$$r_1(T_4 - b_2 \frac{T_1}{a_2}) + r_2(T_5 - b_2 \frac{T_2}{a_2}) + T_6 - b_2 \frac{T_3}{a_2} < a_2 m_2 + b_2.$$



Examples (I/II) - Rectangular domain

```
for (int i_1 = 0; i_1 <= r_1; i_1++)
  for (int i_2 = 0; i_2 <= r_2; i_2++)
    A[2 * i_1 * m_2 + m_2 + 3 * i_2 + 2] = ...;
```

- ① $T_1 = 2, T_2 = 0, T_3 = 1, T_4 = 0, T_5 = 3, T_6 = 2$
- ② $a_2 = ?, b_2 = ?, f_{11} = 2, f_{12} = 0, f_{10} = 1, f_{21} = -2b_2, f_{22} = 3, f_{20} = 2 - b_2$
- ③ the validity condition $-r_1 b_2 \frac{2}{a_2} + 3r_2 + 2 - b_2 \frac{1}{a_2} < a_2 m_2 + b_2$
- ④ evaluating at $a_2 = 1, b_2 = 0$, we obtain, $f1 = 2i_1 + 1, f2 = 3i_2 + 2$
- ⑤ $\max i_1 = r_1, \max i_2 = r_2$
- ⑥ assuming $m_2 = 10$, i.e. $B[...][10]$, we get,
 - delinearization valid when $r_1 = r_2 = 1, \max f2 = 5 < 10$
 - delinearization valid when $r_1 = r_2 = 2, \max f2 = 8 < 10$
 - delinearization invalid when $r_1 = r_2 = 3, \max f2 = 11 \not< 10$

Examples (II/II) - Triangular domain

```
for (int i_1 = 0; i_1 <= r_1; i_1++)
  for (int i_2 = 0; i_1 + 2 * i_2 <= r_2; i_2++)
    A[2 * i_1 * m_2 + m_2 + 3 * i_2 + 2] = ...;
```

- ① $T_1 = 2, T_2 = 0, T_3 = 1, T_4 = 0, T_5 = 3, T_6 = 2$
- ② $a_2 = ?, b_2 = ?, f_{11} = 2, f_{12} = 0, f_{10} = 1, f_{21} = -2b_2, f_{22} = 3, f_{20} = 2 - b_2$
- ③ the validity condition $-r_1 b_2 \frac{2}{a_2} + 3r_2 + 2 - b_2 \frac{1}{a_2} < a_2 m_2 + b_2$
- ④ evaluating at $a_2 = 1, b_2 = 0$, we obtain, $f1 = 2i_1 + 1, f2 = 3i_2 + 2$
- ⑤ $\max i_1 = r_1, \max i_2 = \lfloor \frac{r_2}{2} \rfloor$
- ⑥ assuming $m_2 = 10$, i.e. $B[...][10]$, we get,
 - delinearization valid when $r_1 = r_2 = 1, \max f2 = 2 < 10$
 - delinearization valid when $r_1 = r_2 = 2, \max f2 = 5 < 10$
 - delinearization valid when $r_1 = r_2 = 3, \max f2 = 5 < 10$
 - delinearization valid when $r_1 = r_2 = 4, \max f2 = 8 < 10$
 - delinearization valid when $r_1 = r_2 = 5, \max f2 = 8 < 10$
 - delinearization valid when $r_1 = r_2 = 6, \max f2 = 11 \not< 10$

