

# Automotive air conditioning

Delmar Publishers - Henry Ford and Air Conditioning



Description: -

-  
Automobiles -- Air conditioning -- Maintenance and repair.  
Automobiles -- Air conditioning.Automotive air conditioning

-Automotive air conditioning

Notes: Includes index.

This edition was published in 1988



Filesize: 11.57 MB

Tags: #Classic #Auto #Air

## How to Recharge Your Car's Air Conditioner : 7 Steps (with Pictures)

It also looks like a radiator, with its coil of tubes and fins, but its job is to absorb heat rather than dissipate it.

## Perfect Fit™ Model Specific Air Conditioning Systems

Do not touch anything you are unfamiliar with.

## Classic Auto Air

The condenser is like a small radiator where the AC hoses come in contact with the outside air, which absorbs heat from the liquid inside before the liquid reaches the AC in-line filter, which removes debris that could contaminate the system. Global Air has more than 100 high-performance thermal expansion valves used by many OEM applications. Nevertheless, repeat after me: It is illegal to vent refrigerant.

## Aftermarket Air Conditioning Kits at Summit Racing

There are three main parts to the system -- the compressor, condenser, and evaporator -- that achieve this, plus a few other parts to keep the system running smoothly. It takes a fair amount of refrigerant to raise the pressure.

## Custom Aftermarket A/C Systems for Classic & Vintage Cars, Hot Rods...

NEVER TURN THE CAN UPSIDE DOWN. Finally, whenever the compressor is able to be commanded to operate in a reduced displacement, the vent temperature can also be controlled by acting upon the compressor's displacement.

## How A Car Air Conditioner OR Car A/C Works?

The high-pressure liquid refrigerant flows from the receiver-dryer through the expansion valve, where it is allowed to expand. Because the working fluid gets both very hot and very cold, it is important to keep moisture out of the system, as ice forming in the compressor can damage it. Determine the correct pressure to fill to.

## **Automotive Air Conditioning Repair Tools**

If your compressor will not engage, add half a can of freon. This is usually caused by a failing or failed Blend Door Actuator.

## Related Books

- [Juristische logik.](#)
- [Hatab akhdar](#)
- [Gender - rangkuman dan sari literatur](#)
- [Politische System Österreichs](#)
- [Ground improvement - case histories](#)