


# Thermal Hydrocracking of Athabasca Bitumen - Comparison of Computer Simulated Values of Feed and Product Vaporization with Canmet Pilot Plant Data.

s.n - Thermal hydrocracking of Athabasca bitumen : comparison of computer simulated values of feed and product vaporization



Description: -

- Thermal Hydrocracking of Athabasca Bitumen - Comparison of Computer Simulated Values of Feed and Product Vaporization with Canmet Pilot Plant Data.

-

CANMET report -- 80-23 Thermal Hydrocracking of Athabasca Bitumen - Comparison of Computer Simulated Values of Feed and Product Vaporization with Canmet Pilot Plant Data.

Notes: 1

This edition was published in 1980



Filesize: 59.85 MB

Tags: #Thermal #hydrocracking #of #Athabasca #bitumen #: #comparison #of #computer #simulated #values #of #feed #and #product #vaporization #with #CANMET #pilot #plant #data #/ #D.J. #Patmore #and #B.B. #Pruden. #: #M38

**Thermal hydrocracking of Athabasca bitumen : comparison of computer simulated values of feed and product vaporization**

The effects of sample weight, heating rate and final temperature on the weight loss as a function of time were examined.

**Thermal hydrocracking of Athabasca bitumen: comparison of computer**

The US Department of Energy DOE Direct Coal Liquefaction effort, in which Hydrocarbon Technologies, Inc. An adequate description of the pitch pyrolysis kinetics was achieved using a 2-stage first order model with the integral analysis method. Following a comprehensive appraisal of the experimental data and economic potential in 1979, it was concluded that commercialization could be justified.

**Heat of reaction and vaporization of feed and product in the thermal hydrocracking of Athabasca bitumen**

This mutual dependence prompted an the examination of the accuracy of these kinetic parameters, and a search for a single set of parameters for each stage of the pitch pyrolysis.

**Thermal hydrocracking of Athabasca bitumen : comparison of computer simulated values of feed and product vaporization with CANMET pilot plant data / D.J. Patmore and B.B. Pruden. : M38**

In the latter technique samples are pyrolyzed at high heating rates and products analyzed with in-line gas chromatography. These involve estimating the equilibrium vaporization constant,  $K$ , for various components of the system using known or estimated values of their thermodynamic properties.

## Related Books

- [Moscow and St. Petersburg](#)
- [Generous openness - praying the Spiritual exercises of St. Ignatius](#)
- [Chinese writing - Chinese calligraphy : an exhibition in the British Library 3 March to 15 May 1988.](#)
- [Haebang chŏnhusa ŭi insik](#)
- [C. S. Lewis: images of his world.](#)