

EVE - a CAD tool providing placement and pipelining assistance for high-speed FPGA circuit designs.

National Library of Canada - Intel® FPGAs and Programmable Devices



Description: -

-EVE - a CAD tool providing placement and pipelining assistance for high-speed FPGA circuit designs.

- Canadian theses = -- Thèses canadiennesEVE - a CAD tool providing placement and pipelining assistance for high-speed FPGA circuit designs.

Notes: Thesis (M.A.Sc.) -- University of Toronto, 2001.

This edition was published in 2001



Filesize: 69.109 MB

Tags: #CiteSeerX #— #© #Copyright #by #William #Chow #2001EVE: #A #CAD #Tool #Providing #Placement #and #Pipelining #Assistance #for #High

Retiming, Repipelining and C

Chip planning design stage 104 achieves this by forming the budget for each of the circuit blocks selected in front-end acceptance design stage 102, revising the specification for the circuit block, and adjusting constraints within the processing method specified by front-end acceptance design stage 102.

US7805697B2

The Chip Planner highlights the clock pin location, routing, and sector boundaries. Voltage variation is inevitable with the non-zero impedance of on-chip power distribution wiring and just 100 mV of supply dip at 1 volt translates to 10% signal speed variation in the logic.

Retiming, Repipelining and C

The derivative design process provides a method for rapidly generating a completed circuit design to perform functions which have in common the derivative design as a starting platform.

Intel® FPGAs and Programmable Devices

Even within these limits, there is a potential problem with Rotary clocking due to the range of tunability available note there is no problem at low VDD because Rotary clocks generally operate well below the VDD at which logic stops functioning.

PPT

For example, you cannot upgrade IP based transceivers that a different between different device families. Programmable fabrics may also be adjustable in shape, but may not necessarily be permitted to take on any aspect ratio but only certain discrete aspect ratios, due to the tile-based layout that is typical of programmable fabrics such as a ROM. In this example, changing the implementation of the round robin logic provides more

performance increase than adding pipeline stages.

© Copyright by William Chow 2001EVE: A CAD Tool Providing Placement and Pipelining Assistance for High

However, you can apply additional non-required changes for further performance improvement. You can choose whether to allow people to download your original PowerPoint presentations and photo slideshows for a fee or free or not at all.

vlsi research papers

Packet network protocols are relatively complex. . The system investigated is a conventional type flat plate solar collector connected in series with a rock storage cum collection unit.

CiteSeerX — © Copyright by William Chow 2001EVE: A CAD Tool Providing Placement and Pipelining Assistance for High

Stored program technology is characterized by execution in terms of instructions or blocks of instructions, by continuous loading and interpretation of instructions, and generally requires several or more nanoseconds per instruction for execution.

Related Books

- [Creole en acción.](#)
- [Studies for seismic zonation of the San Francisco Bay region - jointly supported by the U.S. Geological Survey and the State of California.](#)
- [Working with the community - a manual for building police-community partnerships](#)
- [Clinical tropical diseases.](#)
- [Pro-slavery argument - as maintained by the most distinguished writers of the southern states, containing extracts from their works.](#)