MIL. STANDARD TABLE

- - Review of MIL



Scenario	Category	Impact Velocity (m/sec)	Drop Height	Configuration	Orientation[1]		Impact Surface[2]
Ship Transport[3]	Storage and transport to theatre storage area, transport by ship	5.4	1.5m (5 ft)	Packaged[4]	LCEP (minimum of 3)	Flat bottom and two faces,[5]	Steel[7] backed by concrete
Unpackaged Handling	Infantry and man-carried equipment	5.4	1.5m (5 ft)	Unpackaged	5	Flat bottom, two faces,[5] and two edges[6]	Steel[7] backed by concrete
Packaged Handling	Loading and offloading from side of transport vehicle - transport by truck, forklift, & helicopter	6.4	2.1m (7 ft)	Packaged[4]	5		Steel[7] backed by concrete
Helicopter	Underslung load, quick release onto land or ship	6.4	2.1m (7 ft)	Packaged[4]	1 Flat	Flat bottom	Steel[7] backed by concrete
Parachute Drop[8]	Low velocity drop	9.2	4.3m (14 ft)	Packaged with appropriate honeycomb or other shock absorbing system used in delivery	Shipping configuration		Flat compact soil
Parachute Drop	High velocity drop	27.3	38.1m (125 ft)				Flat compact soil

Note 1: *The test is not intended to encompass all credible accident conditions or severe mishandling conditions. Where the drop heights quoted are exceeded by those specified elsewhere in the table or for other phases of Service, the higher values should be substituted.*

Note 2: *This test may not be suitable to simulate certain effects that can occur during parachute drops in high wind conditions.*

Note 3: *Sufficient assets are required to test in each of the orientations specified. Five standard drop orientations are listed in Table 516.7-I and illustrated in Figure 516.7-15. Consider other drop orientations if expected to have a greater damage potential. Expose each item to no more than 2 drops.*

Note 4: *For munitions, the two faces shall be the forward and aft ends of the munition.*

Note 5: *For munitions, the two edges shall be at 45 degrees on the forward and aft ends.*

Note 6: *Unpackaged if required by LCEP or Test Plan.*

Note 7: *The default drop surface is steel backed by concrete (with the exception of parachute drop). Concrete or 5 cm (2in) plywood backed by concrete should be selected if it can be shown that the natural frequency of the test item is not adequately excited when dropped on the default steel surface.*

Note 8: *A steel impact surface shall have a Brinell hardness of at least 200. For test items less than 454 kg (1000 lbs) the steel plate shall be at least 2.5 cm (1 in) thick, otherwise it shall be at least 7.6 cm (3 in) thick.*

Description: -
-MIL. STANDARD TABLE
-MIL. STANDARD TABLE
Notes: (JOBE)
This edition was published in -

Tags: #SQC #Online

AQL Table

When in doubt, start with this inspection level. Samples size code letter The code letter is based on lot size and inspection level. Minor defect: minor defect will not affect normal use of the product.

Military Handbooks (MIL

The total number of defects from those 10 lots must be less than specified in a table in the standard. In addition the production must be at a steady rate.

AQL Table

The exact performance criteria to be applied depend on the item criticality. Military Directives, Handbooks and Standards Related to Reliability This page provides access to US Department of Defense directives, handbooks and standards related to reliability practices.

MIL

We generally set the acceptable critical defect level at 0. A True RMS voltmeter will calculate the equivalent DC heating effect and provide that measurement.

AQL Sampling Tables

The software is easy to use and includes other sampling plans too! Introduction This article discusses the power quality test and evaluation with a review of MIL-STD-704 and the relationship with electromagnetic compatibility EMC. Figure 2: MIL-STD-704 Basic Test Configuration — DC Power Table 2: DC Power Requirements Test Matrix Requirement 704-7 704-8 Load VA HDC101 LDC101 Current distortion HDC101 LDC101 Current spectrum HDC101 LDC101 Inrush current HDC101 LDC101 Steady state voltage HDC102 LDC102 Voltage distortion spectrum HDC103 LDC103 Total ripple HDC104 LDC104 Normal voltage transients HDC105 LDC105 Power interrupt HDC201 LDC201 Abnormal steady state voltage HDC301 LDC301 Abnormal voltage transients HDC302 LDC302 Emergency steady state voltage HDC401 LDC401 Starting voltage transients HDC501 LDC501 Power failure HDC601 LDC601 Polarity reversal HDC602 LDC602 External Power

Requirements The requirements for external power sources follow the same guidelines as the internal power with the lower voltage limit increased to compensate for external wiring length. To proceed with reduce inspection, you need to have 10 or more lots consecutively pass inspection.

Related Books

- GEOS data summary for active and passive seismic experiments conducted in support of Northern Nevada
- Veinte años del Boletín Mexicano de Derecho Comparado - índices de los años I (1968) a XX (1987)
- Methods for reducing occupational exposures during the decommissioning of nuclear facilities - repor
- Lad of Evesham Vale
- On zymotic and preventable diseases.