Agenda

- → Callables and Futures
  - ↳ Merge Sort using Callables and Futures
- → Adder Subtractor Problem (Synchronization Issues / Race Cond^{n})
  - ↳ Synchronized
    - → Mutex and Semaphores
    - → Reentrant locks
    - → Read write locks ⇐

Concurrency 2

Concurrency 3

→ Fairness of locks

→ Atomic Data Types / Concurrent HashMap

→ Volatile

3 classes

Java

→ Language Module

Recap → Runnable

Threads

Executors

Task

Runnable

Executor Service

Create a thread pool

Workers (Threads)

Queue (Waiting Tasks)



Callables and Futures

We created a Task using runnable

run()

Create a Task that returns something

Callable

Call()

class Sorter implement Callable<List<Integer>>

List<Integer> call() {

Generics

templates

Generics / Templates

List < Integer >

List < Student >

List < XYZ >

vector < int >

vector < Student >

vector < XYZ >

Map < String, int >

MAIN

Executor

| 1 | 5 | 3 | 6 | 2 | 7 |

get ()

Task 1 Executor 1


Executor ⟹
1 | 5 | 3 | 6 | 2 | 7
1 | 2 | 3 | 5 | 6 | 7
1 | 5 | 3
6 | 2 | 7
SS
SS
SS
Executor 2 T1
1 | 5 | 3
1
5 | 3
1 | 3 | 5
Executor 3
E3T1
1
1
E3T2
3 | 5
5 | 3
2 | 6 | 7
Executor 2
T2
6
2 | 7
Executor 4
6
1
2 | 7
2 | 7

EQT1

EQT2

Cached Thread Pool

TP

0

1

2

3


multi-on Thr
JVM
DOM
Fixed
CPU Bound Acts
Cached
I/O


I/O I/O I/O
FTP
Size=3
CPU
Cache
I/O
Assg
Multithreading

① Implement Quick Sort via

→ Adder Subtractor Problem

Data Sharing with threads is a headache




CO count
10
11
9
10

Adder 1

Count += 1

Race condition

Critical Section

Subtractor 1

Count -= 1

1. Read Count <= 10
2. INC Count <= 11
3. Store count <=

3 => Read Count => 10
5 => DEC count <= 9
6 => Store count

① ⇒ Check Single Tus

② ⇒ Send Rose

A

Propose

Propose

B

Value

0

= 0

Adder

Subtractor

1 to 100

1 to 100

Class {

only on

Only one

T1

T2

T

T1

Synchronized do1() {

}

Synchronized do2() {

for 1 object at 1 time only 1 thread can be there in



If you have sync methods they have to be in the Subject

Value {

```
get()
set(i)
```

}

Adder {

```
int cur = value.get
int new = cur+1
```

value.set (New)