

What is Programming?

- Programming is the process of writing a certain amount of code that tells what to do and how to do the computer.
- Programming is important to perform a particular type of task efficiently, fast and in cheap price.
- Some Common examples of programming languages are C, C++, Python, Ruby, Java , Javascript etc.

What is HTML?

- HTML stands for **Hypertext**(links between different parts of the document) **Markup Language**
- HTML is a **scripting** language that includes different tags to create web pages.

OR

- HTML is code that is used to design **webpages** and the contents involved in that webpage.

OR

- HTML is a **Markup language** that is used to create documents on the World Wide Web incorporating text, graphics, sound, video, and hyperlinks
- It is a Markup language because it does not involve any kind of logical operations, Calculations, etc.
- HTML is used in **web development** in order to make the structure/layout of the webpage.

History of HTML?

- HTML was developed by physicist **Tim Berners Lee in 1980** who was a contractor at **CERN** which was used by researchers to share documents. Tim Berners Lee wrote the **HTML** and server software in the **1990s**. HTML was built in **1990** but was not officially launched. It was officially launched in **1995**.

| Versions | Date |
|-----------|------|
| HTML | 1991 |
| HTML+ | 1993 |
| HTML 2.0 | 1995 |
| HTML 3.2 | 1997 |
| HTML 4.01 | 1999 |
| XHTML 1.0 | 2000 |
| HTML 5 | 2012 |
| XHTML 5 | 2013 |

Why XHTML is not used?

- XML(**extensible markup language**) is a markup language where all documents must be marked up correctly (be "well-formed").
- XHTML was developed to make HTML more **extensible** and **flexible** to work with other data formats (such as XML). In addition, browsers ignore errors in HTML pages and try to display the website even if it has some errors in the markup. So XHTML comes with a much stricter error handling.

BASIC STRUCTURE OF HTML DOCUMENT

<!DOCTYPE HTML>

Type of document and help web browser to display web page correctly

<HTML>

<HEAD>

<TITLE> PAGE TITLE </TITLE>

It contains title of page and meta description of any webpage

</HEAD>

<BODY>

---BODY PART---

It contains actual content seen in webpage

</BODY>

</HTML>

How to open text editor in windows(Notepad)?

Step 1:

- ❖ Go to the **Start** menu.
- ❖ Type **notepad** and press **Enter**.

Step 2:

- ❖ Press the **Windows logo + R** key.
- ❖ Type **notepad** and click on the **Ok** button

How to save HTML file?

1. Choose **File>Save As** and choose HTML from the drop-down list.
2. Give the filename an extension of **.html**, specify the file location, and **click save**.
3. Open the HTML file in a web browser to examine the converted file.

How to Open HTML file?

1. **Right Click** on the file
2. And click on **Open** to open the HTML file.

OR

Double-click on the file to open the HTML file.

HTML DOCTYPE <!DOCTYPE html>

- The declaration is not an HTML tag. It is "information" to the browser about what document type to expect.
- We use <!DOCTYPE HTML> to tell the browser that we are sending an html file to the browser.
- It aware the browser that the file is an HTML file.

What are Elements and Attributes in HTML?

Elements:

- The HTML element is everything from the **start tag** to the **end tag**.

<tagname>Content goes here...</tagname>

- Examples of some HTML elements:
 - **<h1>My First Heading</h1>**
 - **<p>My first paragraph.</p>**

Nested Elements:

- HTML elements can be nested (this means that elements can contain other elements).
- All HTML documents consist of nested HTML elements.
- The following example contains four HTML elements(<html>,<body>,<h1> and <p>)

Example:

```
<!DOCTYPE html>
<html>
<body>
<h1>My First Heading</h1>
<p>My first paragraph.</p>
</body>
</html>
```

Attributes:

- All HTML elements can have attributes.
- Attributes provide **additional information** about elements.
- Attributes are always specified in the **start tag**.
- Attributes usually come in name/value pairs like: **name="value"**.

Examples:

- The **<a>** tag defines a **hyperlink**. The **href** attribute specifies the **URL** of the page the link goes to:

```
<a href="www.google.com">Google</a>
```

- The **** tag is used to embed an image in an HTML page. The **src** attribute specifies the path to the image to be displayed:

```

```

What are Tags and Types of Tags?

Tags:

- The **basic formulae** used to write HTML code are called tags.
- Without Tag, we cannot write HTML.
- The text character which is enclosed in a **left angle bracket (<)** and a **right angle bracket(>)** is called an HTML tag.

<tag name>text</tag name>

Types of Tag:

❖ **Paired Tag**

❖ **Unpaired Tag/Single Tag/Empty Tag**

❖ Paired Tag:

The tag which has both a **closing and opening tag** is called paired tag.

OR

The tag which contains **both starting and finishing tag** is called paired tag.

For examples: **<html>....</html>**, **<head>.....<head>**, **<p>....</p>**, **<form>....</form>**,etc.

❖ Unpaired Tag:

The tag which does not have both a **closing and opening tag** is called unpaired tag.

OR

The tag which does not contain **both starting and finishing tag** is called paired tag.

For examples: **
, **, **<hr>**,etc

❖ Differences between Block level and Inline Elements:

| Block Level Element | Inline Element |
|--|---|
| Begins a new line of text | Does not begin a new line of text. |
| Its width extend beyond the inner content | Its width only extends as far as the inner content. |
| You can set the width and height values. | You can't set width and height values. |
| Can Contain text, data , inline elements, or other block level elements. e.g. <p>, <div>,<h1>,,etc. | Can Contain text, data or other inline elements e.g. <a>,,,,<i>,etc. |

❖ Div Element:

The div (division) element is a **generic block-level element**, most often used to divide **page content into blocks**. A **block element** is a page element that starts a new line and has a width equal to the entire page or the parent container.

You'll very often see **divs** used to group related paragraphs, images, headings, and links. For example, a three-paragraph article may be enclosed in a div, and a navigation menu containing links might be enclosed in another div. Using **divs** this way makes it easier to identify different sections of a page and apply styling to them with CSS.

❖ Span Element:

The span element is a generic **inline element**, typically used to apply styling to a **portion** of inline content. An inline element **does not start a new line** and only takes up as much space on the page as its content. Span tags are used on small segments of text, links, images, and other HTML elements that appear **inline** with the surrounding content.

❖ Paragraph Tag<p>:

In HTML to create a paragraph we use <p> tag. The attribute of <p> tag is align.

The values of align attributes are left, right and center.

Example:

```
<html>
<head>
<title>Example of paragraph tag</title>
</head>
<body>
<p>Lorem Ipsum is simply dummy text of the printing and typesetting industry.
Lorem Ipsum has been the industry's standard dummy text ever since the 1500s,
when an unknown printer took a galley of type and scrambled it to make a type
specimen book. </p>
</body>
</html>
```

❖ Heading Tag<h1>, <h2>, <h3>, <h4>, <h5>, <h6>:

The **defined titles** in the HTML is called Heading. To put **different styles of heading** in HTML we use heading tag. Heading tags are of different labels **from<h1> to <h6>**. The text within **<h1>** is the **largest text** and the text within **<h6>** is the **smallest text**.

```
<html>
<head>
<title>Example of paragraph tag</title>
</head>
<body>
<h1>NITNEPAL</h1>
<h2>NITNEPAL</h2>
<h3>NITNEPAL</h3>
<h4>NITNEPAL</h4>
<h5>NITNEPAL</h5>
<h6>NITNEPAL</h6>
</body>
</html>
```

❖ Different types of List in HTML:

It is the collection of data items arranged with order or without order. There are three types of list in HTML:

- Ordered list
- Unordered list
- Definition list

Ordered list

The type of list in which the **numbers are used to list** the items is called ordered list.

We use **** tag to create ordered list. The attributes of the **** tag are **type** and **text**. The **start** attribute defines the start of number. The default start value is **1**. To list the item we use **** tag.

The ordered list which contains another ordered list is called **Nested Ordered list**.

E.g. To display the following output

1.Input device

a. Mouse

b. Keyboard

2.Output Device

i. Printer

ii. Monitor

3.Memory

A. Primary Memory

B. Secondary memory

```
<html>
<head>
<title>Webpage</title>
</head>
<body>
<ol>
<li>Input device</li>
<ol type="a">
<li>Mouse</li>
<li>Keyboard</li>
</ol>
<li>Output device</li>
<ol type="i">
<li>Printer</li>
<li>Monitor</li>
</ol>
<li>Memory</li>
<ol type="A">
<li>Primary memory</li>
<li>Secondary memory</li>
</ol>
</ol>
</body>
</html>
```


Unordered list

The items that are arranged **without any order** or with **Bullet**. The attribute of unordered list is **<type>**. To create an unordered list **** tag is used. The value of type attributes are:

disc 

Circle 

Square 

To list the tag **** tag is used

Example:

O input device

O output device

o Memory

o CPU

```
<html>
<head>
<title>Unordered list</title>
</head>
<UL type=Circle> <li>Input device</li>
<li>Output device</li>
<li>Memory</li>
<li>CPU</li>
</ul>
</body>
</html>
```

❖ Grouping Elements:

There are a number of additional tags that allow us to group related HTML content together. Some examples include `<header>`, `<section>`, `<article>` and `<footer>`. All of these HTML elements (including `<div>`) have no effect on the HTML content itself, but instead group and contain other elements. In this tutorial, we covered about `<div>`, `<header>` and `<footer>`.

Example to be illustrated in the lecture.

Marquee Tag:

An HTML marquee is a **scrolling piece of text** displayed either horizontally across or vertically down your webpage depending on the settings. This is created by using HTML `<marquee>` tag.
e.g. `<marquee>We are from NITNEPAL</marquee>`

