

FALCON's Response to Flipkart for Supply of Loop CBS 20K PPH (Jaipur)

December 15, 2023



www.falconautotech.com

Kind Attention –

Mr. Hemanth Kumar

Mr. Arvind Seshadri

Mr. Sandesh Mulik

M/s Flipkart

Offer Ref: F23-00366-Phase 1; Date: 15-12-2023

Subject – Techno -Commercial Offer of Loop Cross Belt Sorter 20K PPH

We are pleased to submit our Techno-Commercial Offer in response to your RFP.

As you will note, we have studied your requirements in great depth and, along with the information collected during the meetings and calls with you, we have put together a detailed technical proposal laid out in various sections and sequenced to enable you to understand our proposed solution and to re-enforce our commitment to being your partner in this strategic initiative.

In subsequent sections, we have highlighted the capabilities and experiences of Falcon Autotech with sections on our Intra-logistics Automation Technologies and references.


To conclude, I would like to add my personal commitment on behalf of Falcon Autotech. As we move through the RFP process, please do not hesitate to contact me and my team. We will be pleased to assist you with any further information or clarifications that you might have.

Best Regards,

Sandeep Bansal

Chief Business Officer

Response to RFP for Loop Cross Belt Sorter 20K PPH Throughput (Jaipur)



Proposal Reference – F23-00366-Phase 1

Falcon Autotech Private Limited
Plot No. 87, Sector Ecotech-1, Extension-1,
Greater Noida, Uttar Pradesh 201308.

Contact – Sanyog Pratap Singh
Asst. Manager
Mob - +91 8750052591
Sanyog.singh@falconautoonline.com

Contents

Contents.....	4
1. Glossary	7
2. Executive Summary	8
3. Company Profile	9
4. Falcon's Experience and Achievements in Sortation Space Globally	13
5. Reference Projects	15
5.1 Project 1- (CEP Client, India)	15
5.2 Project 2- (Client – E-Commerce, India).....	16
5.3 Project 3- (Ecommerce Client, India)	17
5.4 Project 4- (CEP Client, UK).....	18
5.5 Project 5- (CEP Client, Sydney).....	19
6. Handled Shipment Spectrum	20
6.1 Shipment size loadable on the sorter	20
6.2 Shipments to be loaded on Sorter shall have the following characteristics:.....	20
6.3 Shipment not loadable on the sorter	21
6.4 Pictures of Sortable Shipments.....	22
7. Proposed System Description	23
7.1 Objective.....	23
7.2 Summary of the System	23
7.3 Main benefits of the proposed solution.....	24
8. Concept Description	25
9. Layout View	26
10. Proposed System Capacity Calculations	27
10.1 Sorter System Capacity	27
11. System description	28
11.1 Infeed System	28
11.1.1 Infeed System	29
11.1.1.1 Straight and Inclined Powered Belt Conveyor	30
11.1.1.2 Idler Roller Conveyor	32
11.1.1.3 Plastic Modular Belt Conveyor	33
11.1.1.4 Diverter ARM	34
11.1.1.5 VDS Chutes.....	35
11.1.2 Conveyor BOQ	36
11.2 Induction to Sorter	37
11.2.1 Feedlines.....	37

11.2.1.1	Buffer Conveyors.....	38
11.2.1.2	Weighing Conveyor.....	38
11.2.1.3	Orientation Conveyor.....	39
11.2.1.4	Intelligent Merge Conveyor	39
11.2.1.5	New Induct Fencing.....	40
11.2.2	Irregular Takeout Conveyor	40
11.2.2.1	Irregular Chute	41
11.2.2.2	Irregular Takeaway Conveyor	41
11.2.2.3	Irregular Collection Bin (In Flipkart's scope).....	41
11.2.3	Conveyor BOQ	42
11.2.4	Main Loop	42
11.2.5	Sorting Output	43
11.2.5.1	L-Type Collection chute.....	43
11.2.5.2	Rejection Chute	44
11.2.5.3	Chute Safety Net	45
11.2.6	Bag Take away Conveyor	46
11.2.6.1	Conveyor BOQ.....	46
12.	Description of Components of Equipment	47
12.1	Cross Belt Sorter -	47
12.1.1	CBS Carrier	47
12.1.2	Servo Roller.....	48
12.1.3	Chassis.....	48
12.1.4	Carrier Wheels	48
12.1.5	Motor Drives.....	48
12.1.5.1	Friction Wheel Drive	49
12.1.5.2	Non-contact based linear motor drive.....	49
12.1.6	Power Transmission	49
12.1.7	Data Transmission	50
12.1.8	Carriers positioning System.	50
12.1.9	Technical specifications of Sorter	51
12.2	Scanning & Sensing on Main Sorter Loop.....	52
12.2.1	Automatic Barcode Scanning & Dimensioning System.....	52
12.2.2	Shipment Positioning System.	52
12.2.3	Empty Carrier Detection System.....	52
12.3	Steel Works – Mezzanine, Maintenance Platforms & Staircases-.....	53
12.3.1	Mezzanine.....	53

12.3.2	Maintenance Platform & Staircase	53
13.	Allocated Areas.....	54
14.	Proposed System Technical Details (One Loops)	55
14.1	Mechanical equipment	55
14.2	Electrical Equipment	56
14.3	Control System	56
15.	Electrical System.....	57
15.1	Reference Picture of Power Distribution Panel	57
15.2	Main Control Panel (Reference)	57
15.3	Induct Stations Control Panel (Reference)	58
16.	Controls Architecture (Ref.)	59
17.	IT Architecture (Ref.)	59
17.1	HAA Server (In Flipkart Scope).....	60
18.	Falcon's WCS CONTROLIT	61
19.	Falcon's Visual Inspection System (SCADA)	62
19.1	FIELD DATA ACQUISITION	62
19.2	ANIMATED SYSTEM VISUALIZATION	63
19.3	ALARM MANAGEMENT	64
20.	Key Components Make	65
21.	Principle of Safety	65
21.1	E-Stops	65
21.2	Pull Cords Switch-.....	66
21.3	Fencing.....	66
22.	Additional Scope-	67
23.	Exclusions	68

1. Glossary

S. No.	Term	Description
1	RFP	Request For Proposal
2	PPH	Shipments Per Hour
4	ICR	Intelligent Character Recognition
5	MEZZ	Mezzanine
6	FWD	Friction Wheel Drive
7	ECDS	Empty Carrier Detection System
8	AC	Alternating Current
9	DC	Direct Current
10	PLC	Programmable Logic Controller
11	IT	Information Technology
12	BOQ	Bill Of Quantity
13	I/O	Input/ Output
14	PDP	Power Distribution Panel
15	PC	Personal Computer
16	UPS	Uninterrupted Power Supply
17	CBS	Cross Belt Sorter
19	MDR	Motor Driven Roller
20	DAP	Design Approval Phase

2. Executive Summary

Falcon is pleased to confirm its great interest in responding to this Flipkart RFQ of Loop CBS for Jaipur. Our team has been working closely with the relevant stakeholders, with a clear commitment to listening, understanding your needs, and ensuring this project's success. Following the same objective for the Jaipur CBS system, we are happy to offer a compliant solution meeting all technical and operational requirements, high-performance, optimized, tailor-made, fast and secure planning, and a competitive price.

Our solution is based on the following key characteristics:

- **One loop of shipment sorting, employing our cross-belt technology, have been designed to handle a throughput of 20,000 packages per hour on the loop.**
- **CBS loop is equipped with its own infeed conveyor system, comprising two distinct infeed lines.**
- **Within CBS loop there are two induction zones featuring six induct lines.**
- **In CBS loop, there are 40 secondary chutes (L-Type) and four rejection chutes.**
- **The system layout has been meticulously planned to facilitate smooth operational flow, ensuring efficient movement of personnel.**
- **Lastly, beneath the CBS is a set of bag takeaway conveyors, and provision of irregular shipments take out is provided beneath the induction zone.**

A tailor-made and simple layout designed explicitly for Flipkart. The proposed layout is the result of the technical requirements in the RFP document and our discussions with the relevant stakeholders during our meeting.

1. **Falcon's reliable Shipment sortation systems**

These systems are globally being used by most innovative brands such as Amazon, Delhivery, Asendia, Fastway and many more. The main and critical components of the FALCON Autotech sorter building blocks, like wheels, motors, belts, bearings, Bus Bars, Communication platforms, PLCs etc., are sourced from some of the best suppliers in the world, such as SEW, Siemens, SICK, Faigle, Vahle and Forbo. This strategic baseline of sourcing policy allows Falcon's customers to be fully confident in the systems' robustness and reliability.

2. **Commitment to quality systems**

Demonstrating Falcon's clear commitment to the Flipkart satisfaction, the shipment sortation system, parts and services will be under warranty for 12 months from installation go-live.

3. **A strong and already successful partnership between Flipkart & Falcon**

Flipkart has been Falcon's customer since long and using multiple Falcon Systems and now a new shipment sortation system of 20,000 PPH is being installed at the Ulluberia location of the Flipkart network. For each of these projects, several advanced tools to improve the service's quality and efficiency are provided: Service Desk, Hotline support, remote access, regular governance meetings and monthly reports.

3. Company Profile

Falcon Autotech (Falcon) is a global intralogistics automation solutions company. With over 10 years of experience, Falcon has worked with some of the most innovative brands in E-Commerce, CEP, Fashion, Food/FMCG, Auto and Pharmaceutical Industries. With our proprietary software and robust hardware integration capabilities, Falcon designs, manufactures, supplies, implements, and maintains world-class warehouse automation systems globally. Falcon's strong research and development team and the continuous focus on innovation reflect our strong solution line around Sortation, Robotics, Conveying, Vision Systems and IOT. Falcon has done over 1,800 installations across 15 countries on four continents.

Falcon 2.0



Operational since in 2012, Falcon is a global intra-logistic automation solution provider handling parcels, bags, cartons and pieces



Falcon has five key solution lines: 3D Robotics, Sortation systems, Dimensions & Weight Systems, Put/pick To Light & Conveyors, along with rapidly scaling proprietary software called FACTS



Work with leading E-Commerce, CEP, Fashion, Food/FMCG, Auto and Pharmaceutical brands

5 Product Lines

15+ Countries with Live Installations

1800+ Total Installed Systems Globally

1Million+ Sorts Per Hour

600+ Employees

Long-standing Relationships with industry leaders

Ecom Retail

Flipkart

amazon

Lazada

تجارت

CEP

aramex

BLUE DART

DELHIVERY

Ecom Express

Distribution & Others

G

SWIGGY

TITAN

Handelman (Online Limited)

News & Articles

Falcon Autotech UAE

FALCON AUTOTECH EXPANDS PRESENCE IN THE MIDDLE EAST WITH NEW OFFICE OPENING

Falcon Autotech is pleased to announce the opening of its new office in Dubai, UAE, marking a significant milestone in the company's expansion into the Middle East market.

FALCON AND ALSTEF GROUP ANNOUNCE GLOBAL TECHNOLOGY PARTNERSHIP

Falcon Autotech and Alstef Group Announce Global Technology Partnership for Parcel Sortation Solutions


Published - Sept 2022

Falcon Autotech is currently among the top 15 intralogistics automation company, our vision is to become top 10 intralogistics automation company in our focused product lines.

Our Vision

To be amongst the Top 10 global intra-logistics automation companies in our focused product lines

The team started out in 2004 solving special purpose automation problems for clients and later established Falcon Autotech in 2012 with strong focus on building standard technology stack spanning across Hardware, Firmware and Software to tackle bigger Supply Chain problems around warehouse automation and material handling. Over the decade, Falcon has made rapid strides and has carved out a niche in some of the world's most cutting-edge technologies: Sortation, Robotics, Conveying, Vision Systems and IOT.



As a leading player in the intra-logistics automation space, Falcon continuously strives to improve the operational efficiencies and accuracies for its clients through its domain knowledge and experience in addition to its wide range of products and solutions. In order to be able to live up to the high expectations set forth by our clients, the team at Falcon realizes the importance of taking up selective applications in focused Industries and deliver world class projects in return.



Product and Solutions

With 100% focused on Parcels, Packages, Totes, Bags, Cartons




Falcon Autotech has successfully delivered warehouse automation solutions based on smart and innovative combinations of above product lines for effective materials handling, sortation and movement. The process is controlled in real-time by our in house WCS applications. These solutions considerably cut the need for manual operations, improve working conditions and ensure the highest accuracy of the entire process up to final delivery to the recipient.


Over the last 10 years, Falcon has worked with some of the most innovative brands worldwide and has established long standing partnerships. These brands are testimony of our strong focus on delivering superior customer satisfaction and offering end-to-end intralogistics solutions.

Select Key Clients

Some of world's most innovative brands trust us with their intra-logistics warehouse automation requirements




With over 1,800 installations, today Falcon's systems are used all over the globe. Falcon has highly motivated team of 600+ employees supported by over 15 global partners who help us design, manufacture, deliver and maintain automation solutions globally.



4. Falcon's Experience and Achievements in Sortation Space Globally

- Ranked among **Top 20 Sortation System Suppliers globally**. Only company from APAC/EMEA Region.
- Currently possess one of the **World's largest portfolios in Sortation Technologies**: 7 In-house technologies.
- Total installed capacity of **10 million Shipments per day** worldwide.
- Only company to be able to offer a **Fully Integrated AMS**.



POSTED ON APRIL 17, 2023 IN / NEWS

Falcon Autotech Expands Presence in the Middle East with New Office Opening

Dubai, UAE – 17th April 2023 – Falcon Autotech (Falcon) is pleased to announce the opening of its new office in Dubai, UAE, marking a significant milestone in the company's expansion into the Middle East market. The new location will enable Falcon to better serve its existing customers in the region and expand its reach to new markets and prospects.

The decision to establish a presence in the Middle East was driven by the growing demand for Falcon's solution in the region, as well as the strategic importance of the Middle East as a hub for business and innovation. With a team of experienced professionals based in the region,

Falcon Autotech and Alstef Group Announce Global Technology Partnership for Parcel Sortation Solutions

Falcon Autotech, a leading supplier of Intralogistics automation solutions, and Alstef Group, an expert in comprehensive baggage handling solutions and parcel automation integration announce a strategic technology partnership for parcel sorting solutions. As part of an exclusive distribution agreement, Alstef Group will exclusively expand the deployment of Falcon Autotech's Cross-belt sorter range to specific geographies. Falcon Autotech's Cross Belt Sorter (CBS) range includes a linear CBS and a loop CBS option. With proven features, such as automatic item centering, flexible chute positioning, wireless data communication, real-time video coding, and variable electric discharge, the Falcon CBS range is one of the fastest and smoothest sortation systems available in the market.

5. Reference Projects

Falcon has a strong legacy in **Warehousing Automation** solutions and references-

1. Expertise in Shipment Sortation, Piece Picking and Handling, Case Picking and Handling.
2. Lifecycle services (maintenance, spares supply chain, support).
3. Full **in-house** expertise (Hardware/Software).
4. Turn-key **tailored** solutions.

The references list presented below focuses on Sortation Solution –

5.1 Project 1- (CEP Client, India)

The System is equipped with two fully automated and interconnected Sub-systems. Sub-System 1 is designed for handling large B2B boxes and E-commerce shipment bags while the Sub-System 2 is designed to handle Small E-commerce packages.


Solution Specifications –

- 48,000 PPH (Double Deck CBS- Shipment Sorter)
- 17,000 PPH (Double Deck CBS- Bag Sorter)
- Building Size: 700,000 Sq. Ft

Key Technology Modules –

- | | |
|---|--------------------------------------|
| • 2 Sets of Double Decker CBS Sorters | • Modular Belt Conveyors |
| • Mezzanine Structures (one large mezz on to install a double decker Sorter). | • Spiral Chutes with Braking rollers |
| • Automated Singulators | • 5-Sided Scanning Tunnels |
| • Fully Automatic Inductions | • High speed weighing conveyors |
| • Semi-Automatic Inductions | • Direct Bagging Chutes |
| • Telescopic belt conveyors | • Put to Light Chutes |
| • PVC Belt Conveyors | • Volume Distribution systems |
| | • High Availability Server Systems |
| | • WCS |

Site Pictures -



5.2 Project 2- (Client – E-Commerce, India)

Use Case – Destination Sorting of Packed Shipments.

In 2019, Client was looking for a potential automation partner for design and development of a new automated sortation system for B2C shipments. The system should be able to provide maximum uptime with reduced dependency on skilled manpower, and space optimization.


The customer chose Falcon Autotech based on its unique design which could cater to all their pain points, capability of seamless integration with WMS and life cycle support services.

Solution Specifications –

- Throughput: 27,600 PPH
- End Destinations: 410 Direct Outputs
- Building Size: 200,000 Sq Ft

Key Technology Modules –

- Bulk Infeed Conveyors.
- ARB based Volume Distribution System
- Integrated Presort System.
- Irregular Ejection System.
- Automatic Induct Lines.
- Automatic Barcode Scanner with Image Capture.
- Automatic Weight & Volume Measurement System.
- Loop Cross Belt Sorter.
- Smart Sliding Chutes for Direct bagging and Cage Sorting.
- Bag take out system
- WCS Software System.



5.3 Project 3- (Ecommerce Client, India)


Use Case - Destination Sorting of Packed Shipments

Solution Specifications –

- Throughput: 24,000 PPH
- End Destinations: 110
- Building Size: 200,000 Sq. Ft

Key Technology Modules - Loop Cross Belt Sorter with a cell size of 900 x 500 mm

Layout and Site Pictures -



5.4 Project 4- (CEP Client, UK)

This Solution is designed to handle a volume of 7200 shipments per hour. The system is equipped with three infeed conveyors integrated with an automatic label applicator before shipments enter the sortation system. The shipments are sorted using Falcon's Loop Cross Belt Sorter equipped with automatic barcode scanning, dimensioning, weighing and image capture capabilities. The sorter is installed on the mezzanine floor and sorts directly to 58 end destinations.

Solution Specifications –

- Throughput: 7200 PPH
- End Destinations: 58 Nos

Key Technology Modules –

- Powered Belt Conveyors.
- Automatic Induct Lines.
- Automatic Barcode Scanner with Image Capture.
- Automatic Weight & Volume Measurement System.
- Loop Cross Belt Sorter.
- WCS Software System.

Site Picture –



5.5 Project 5- (CEP Client, Sydney)

Solution is designed for handling a throughput of 16,000 shipments per hour with the help of Falcon's Loop Cross Belt Sorter. The system consists of 2 feeding zones with a total of 10 feedlines. Sorter design enables the van drivers to directly drop the shipments at the dock doors. It has a total of 369 end destinations that are achieved with a combination of direct drops and PTLs. System is integrated with 5 side automatic barcode scanning, weight and volume measurement and automatic detection of oversize and overweight shipments.


Solution Specifications –

- Throughput: 16000 PPH
- End Destinations: 369 Nos

Key Technology Modules –

- Powered Belt Conveyors.
- 2 Induct zone.
- 5 side Automatic Barcode Scanner.
- Automatic Weight & Volume Measurement System.
- Automatic detection of oversize shipment.
- Loop Cross Belt Sorter.
- WCS Software System.

Site Picture –



6. Handled Shipment Spectrum

As per the shipment spectrum data provided in the RFP documents, Falcon has studied and analysed the shipment spectrum in detailed.

Falcon purposes to use its “Single Belt Cross Belt Sorter” to provide the maximum benefits to Flipkart in-terms of handling large shipment sizes and weight.

6.1 Shipment size loadable on the sorter

Falcon's Cross belt sorter has a capability to handle the below mentioned shipment sizes and weight.

Specification	Unit	Value
Max Length	mm	600
Max Width	mm	400
Max Height	mm	300
Max Weight	Kg	10
Min length	mm	100
Min Width	mm	100
Min Height	mm	3
Min Weight	gm	100

6.2 Shipments to be loaded on Sorter shall have the following characteristics:


1. Centre of Gravity of item must not move during conveyance or sorting.
2. Item must not have magnetic content, otherwise behavior of shipment cannot be guaranteed.
3. Liquid or fragile material, to avoid breaking, spillage or leakage, such as wine bottles, metal cans of paint are designated as non- conveyable items.
4. Shipments shall be perfectly and safely packaged: protrusion or open surfaces are not allowed.
5. Plastic ropes shall be perfectly adherent to the surface of the package.
6. All items with the risk of being damaged during the transport on an automatic sorting system or damaging the sorting system. They must be robust enough to avoid disintegration of container material and loose of contents in the sorting process.
7. Item packaging shall have enough grip to be handled on the belts during the acceleration and referencing phases.
8. Items shall not have slippery surfaces and must be able to withstand acceleration of the items on the belt during the start-stop phases (accelerations up to 0.5 g shall be assured without any sliding or tumbling of the items on the belt conveyor).
9. The shipments must have at least one flat and regular surface providing enough stability during conveyance.
10. All shapes are permitted except spherical, cylindrical, or alike unstable items & shapes.
11. All usual packaging materials are permitted (including paper, carton, plastics, plastic foil, rope, tape, textile, and wood)

6.3 Shipment not loadable on the sorter

All products that are not within the range as described here, are considered non- conveyable products, and must be taken out of the main sorter flow by the operators.

1. Unstable items with a risk to roll or tumble on the sorting system, such as spherical or cylindrical items.
2. Items that have a spherical or cylindrical shape.
3. Items that are packed in material that can damage the conveyors or the sorter.
4. Items that have sharp points (e.g., Nails) or sharp edges, that can damage the conveyors or the sorter.
5. Fragile shipments with contents not sufficiently secured.
6. Items that have been classified as dangerous are designated.
7. Wet items are designated.
8. Items with anti-slip treatment.
9. Items with protruding parts.
10. Items with sharp edges.
11. Inadequately packed items that could be damaged during automatic transportation.
12. Electrostatically loaded items.
13. Loose parts on loads and load carriers, such as adhesive tape, stickers, slips of paper, straps, wrap foil etc. are designated as non- conveyable items.

6.4 Pictures of Sortable Shipments


PARCEL TYPE	DESCRIPTION
	A parcel banded with strapping material.
	A parcel shrouded in a plastic coating and is a manufactured product of a pre-determined size.
	A parcel shrouded in a plastic coating and is a manufactured product of a pre-determined size. Loose part with thickness under to minimum allowed (30 m) may create problems and are not recommended to be processed.
	A cardboard parcel coated in a plastic material, for example bin liner, shrink-wrap and stretch-wrap.
	A cardboard parcel coated in a packing paper.
	Often import parcels that are of irregular shape.
	A robust, cardboard parcel that is designed to protect its fragile contents from breakage and has a high weight to size ratio.
	A cardboard parcel is often the norm.
	A large plastic, lidded box.
	A parcel that often contains documents.
	It is a plasticized weave bag, used as a containerization solution, holding a number of other parcels within it.

7. Proposed System Description

7.1 Objective

The purpose of this proposal is to present the design, manufacturing, installation, commissioning, testing, and acceptance testing of the Loop CBS for sorting shipment as per Flipkart's logic.

7.2 Summary of the System



Process flow of the Loop CBS System-

1. **Infeed System:** - The bags are unsealed, and the shipments are dumped in bulk onto the infeed lines of the VDS system present below mezzanine. Subsequently, the bulk shipments ascend to a higher level and arrive at the VDS system. Once the shipments are within the VDS loop, they are evenly distributed among all inducts.
2. **Inducts:** - After the shipments are collected in the VDS chute, an operator picks and positions each shipment on the induct line, ensuring that the shipment is properly aligned and that its barcode is facing upwards. The feedlines then automatically induct the shipments onto the Cross-Belt Sorter Loop.
Non-Conveyable Shipments are placed in the Non-Con chute, which is located beneath each operator position. The Non-Con chute is connected to the conveyor, which transports the shipment out of the induct mezzanine as needed by Flipkart.


3. **Loop CBS:** - Once the shipments have entered the main loop, the Cross-Belt Sorter (CBS) efficiently sorts the shipments into their respective output chutes by utilizing the data provided by Flipkart's sorting logic.
4. **Output Chutes:** - The shipments are discharged into two types of chutes.
 - a. **Secondary Chute (L-type)** - Within a single-loop CBS system, there are a total of 40 collection-type chutes. Shipments collected within these secondary chutes undergo further sorting through the PTL setup (In Flipkart's scope).
 - b. **Rejection Chute-** Four rejection chute is present to handle rejected Shipments.
5. **Bag Takeaway Conveyor:-** Following the secondary sorting process, the shipments are placed into bags and then manually loaded onto a bag takeaway conveyor located beneath the CBS loop. This conveyor transports the bags out of CBS footprint to a free space on same level.

7.3 Main benefits of the proposed solution


The proposed solution has the following advantages:

1. High operational throughput
2. Good Shipments conveying quality for the entire range of conveyable Shipments with a sorting conveyor speed of up to 2 m/s.
3. Low occupancy of floor space in the building.
4. Narrow discharge centers for the increased number of splits in limited space.
5. FALCON's CBS can adapt to changing business requirements by adjusting its speed. to match the operational throughput requirement, thereby leading to Power Savings and reduced system Wear & Tear.

8. Concept Description



9. Layout View



Legend

- 1 – Infeed lines
- 2 – VDS system
- 3 – Main CBS Loop
- 4 – Induct lines
- 5 – Secondary chutes (L-type)
- 6 – Rejection chutes (red colour)
- 7 – Bag Takeout Conveyor

10. Proposed System Capacity Calculations


10.1 Sorter System Capacity

The following table shows the throughput calculation for the sortation system designed based on Flipkart RFP requirements.

SPECIFICATION	VALUE
Sorter Type	Loop CBS
Speed	2 m/s
Pitch	600 mm
Carrier per hour	12,000 CPH
Belts per hour	12,000 BPH
Effective Designed Throughput of 1 loop CBS (A)	24,000 Shipments per hour
Per Feedline Capacity	2,000 Shipments per hour
No of Feedlines (Both Zones)	12 Nos.
Total Feedline designed capacity (B)	24,000 Shipments per hour
System designed throughput (Lower of A&B)	24,000 Shipments per hour
Designed throughput from One loops	24,000 Shipments per hour

11. System description

11.1 Infeed System



Legend


- 1- VDS Infeed Conveyor
- 2- VDS Loop
- 3- VDS Chutes

Every CBS loop is equipped with two VDS infeed conveyors for transporting bulk shipments from the below mezzanine level into the VDS loop.

11.1.1 Infeed System

Infeed conveyor system consists of below components:

1. Straight PVC Conveyor
2. Inclined PVC Conveyor
3. Idler Roller Conveyor
4. VDS System (Arm based/ Tilted Belt)
5. VDS Chute





11.1.1.1 Straight and Inclined Powered Belt Conveyor

Falcon's Belt Conveyors are modular & robust in design, used for smooth conveying of products over Straight, inclined and declined paths. MS profile is used to build conveyor frame.

The conveyors are supplied with the necessary supports and bolts to fix them to the supporting plane, as well as with the junction elements allowing easy and jam-free passage from one conveyor to the other.

Some Silent Features of Falcon's Belt conveyor:

- Low Noise
- Maximum uptime.
- Minimal maintenance
- High safety standards.
- Fastest ROI.



Specification	UOM	Remark
Manufacturer Name	Name	Falcon Autotech
Material of Roller	Type	MS Rollers with Zinc Plating
MOC of Belt	Type	PVC
Belt Thickness	mm	3
Belt Finish	Type	Matt Finish
Belt width	mm	1200
Belt Joint Type	Type	Vulcanized, Endless Belts
Belt Make/Model No.	Make	FORBO/DERCO
Chassis	mm	MS, 3mm Thick, Powder Coated-75 Microns
Idler Roller Pitch on running side (Top)	mm	480
Idler Roller Specs	Spec	Dia.50.8, shaft-12 mm, bearing-6301
End Rollers	Spec	Dia 81.2 x 2.85 Thick, 30mm Shaft Dia, & Bearing Size-UCFH206D1, MOC-EN9, Zinc Plated -25 microns
Drive Rollers	Spec	OUTER Dia 178 PIPE Dia 168x5 Thick, 40mm Shaft Dia, & Bearing Size-UCF208D1, MOC(SHAFT)-EN9, NEOPRENE RUBBER COATING
Motor Shaft	MOC	EN9 Shaft material
Conveyor Under guarding	Spec	MOC-MS, 0.8 to 1mm thickness, Steel Stiffeners at every 600mm to avoid the sagging due to self-weight
Load capacity per unit length of Conveyor	kg/m	50
Type of Guides	Type	Steel guides at 50mm/400mm height basis the position of conveyor on both sides from Conveyor Belt Surface.
Drive Power Rating	kW	Motor Rating depends on Length of the Conveyor
Type of Motor	Type	AC Geared Motor
Ingress Protection	Type	IP 55
Type of Drive System	Type	Direct Shaft Mounted Motor/ Flange Mounted
Type of Drive	Type	Chain drive/Torque Arm type
Gear Motor	make	Sew/Nord
Drive	make	Lenze/Siemens/Omron/Allen Bradley
Insulation Class	Type	Yes
Conveyor Speed	m/s	Variable speed to meet TPH requirements
Type of Mounts	Type	Fixed Heights Legs with Grouting Provisions

11.1.1.2 Idler Roller Conveyor

Falcon's Roller conveyors require negligible maintenance leading to very minimal Operating costs and thus lower cost of ownership.

Some Salient Features of Falcon's idler roller conveyor:

- Low Noise
- Maximum uptime.
- Minimal maintenance
- Comes with MS frame.




Specification	UOM	Remark
Manufacturer Name	Name	Falcon Autotech
Material of Roller	Type	MS Rollers with Zinc Plating
Overall Width	mm	1200
Conveyor Height	mm	As per Layout requirement
Load capacity per unit length of Conveyor	kg/m	50
Roller Span	mm	approx. 600
Roller Diameter	mm	approx. 50
Type of Mounts	Type	Fixed Heights Legs with Grouting Provisions
Type of Guides	Type	Yes
End Stopper	yes/no	Yes

11.1.1.3 Plastic Modular Belt Conveyor

Falcon's Belt Conveyors are modular & robust in design. MS profile is used to build conveyor frame.

Some Salient Features of Falcon's Modular Belt conveyor:


- Low Noise
- Maximum uptime.
- Minimal maintenance
- High safety standards.
- Fastest ROI.



Specification	UOM	Remark
Manufacturer Name	Name	Falcon Autotech
Plastic Modular Belt Material	Type	POM with PBT Pins, Pitch-25.4 mm, Pin Dia- 5mm
Plastic modular Belt Make	Make	Movex
Sprocket Size & No. of Sprockets on Drive End & Tail End	Type	5/146.4 mm
Sprocket material	MOC	POM
Chassis	mm	MS, 3mm Thick, Powder Coated-75 Microns
Wear Strip Material	MOC	UHMW PE1000
Return Roller type	Type	DIA- 50 mm/20303
Return Roller Pitch	mm	800
Driven Shaft	Type	MOC-EN9 Solid Shaft hardened to BHN 240, Size-60SQ MM, Zinc Plated -25 microns, Bearings-UCF-210D1
Duplex Sprocket	MOC	MS
Duplex Chain	MOC	MS
Conveyor Under guarding	Type	GI SHEET (1MM THICK)
Type of Guides	Type	Steel guides at 50mm/400mm height basis the position of conveyor on both sides from Conveyor Belt Surface.

11.1.1.4 Diverter ARM


Linear Side Arm diverter System of Falcon AutoTech is an extremely cost-effective Sortation system designed for low to medium Volume Centres. Linear side arm diverter's simple and modular design gives it advantage of low cost, space saving, and modularity of increasing sorting points in future. This is one of the earliest diverter systems of Falcon AutoTech.



Specification	3.0 ARM XL
Property	Value
Actuation method	Electric induction motor
Belt type	Flat top modular
Belt width (mm)	1200
Arm length (mm)	2400
Max. product size(LXWXH)(mm)	600X400X300
Min. product size(LXWXH)(mm)	100X100X5
Max. product weight (kg)	40

11.1.1.5 VDS Chutes

A VDS chute is a type of chute used for the smooth descent of materials or objects from an elevated position to a lower level (at an operator level). It utilizes base metal to guide and support the flow of items along the chute & collect the shipments within its area.



Calculation for Design: We have considered an average parcel size of 300 X 300 X 300 mm while designing the capacity of chutes.

Average parcel size considered for chute volume calculation	L(m)	B(m)	H(m)	Volume (m3)
	0.3	0.3	0.3	0.027
Collection type Chute	3.3	1.5	0.4	2.07

Assuming a 60% occupancy rate, about **45 parcels** will readily fit into these chutes.

Each Chute is equipped with below components to ease the operations:

- Chute Full Sensor
- Tower Light
- Push Button

Chute I/Os	Description
Chute Full Sensor	To alert the system that the chute is full and mark that chute unavailable for further sortation
Tower Lamp	To indicate the chute status
Push Button	To Start/Stop Sorting Operations


11.1.2 Conveyor BOQ

S No.	Name	EL_1	EL_2	Length(m)	Width (mm)	Set
1	Powered Belt Conveyor	NA	NA	4	1210	1
2	Powered Belt Conveyor	10510	10510	4	1210	1
3	Powered Belt Conveyor	NA	NA	5	1210	1
4	Powered Belt Conveyor	9760	9760	16	1210	1
5	Powered Belt Conveyor	NA	NA	5	1210	1
6	Powered Belt Conveyor	NA	NA	3	1210	1
7	Powered Belt Conveyor	10510	10510	20	1210	1
8	Powered Belt Conveyor	NA	NA	7	1210	1
9	Powered Belt Conveyor	NA	NA	2	1210	1
10	Powered Belt Conveyor	10510	10510	7	1210	1
11	Powered Belt Conveyor	10510	10510	13	1210	1
12	Powered Belt Conveyor	NA	NA	4	1210	1
13	Powered Belt Conveyor	NA	NA	6	1210	1
14	Powered Belt Conveyor	9760	9760	16	1210	1
15	Powered Belt Conveyor	9650	10804	12	1210	1
16	Powered Belt Conveyor	401	5811	8	1210	1
17	Powered Belt Conveyor	401	5811	20	1210	1
18	Powered Belt Conveyor	401	5811	6	1210	1
19	Powered Belt Conveyor	401	5811	17	1210	1
20	Powered Belt Conveyor	5602	10243	17	1210	1
21	Powered Belt Conveyor	9650	10804	12	1210	1
22	Idler Roller Conveyor	650	550	1	1200	1
23	Idler Roller Conveyor	650	550	1	1200	1
24	Idler Roller Conveyor	650	550	1	1200	1
25	Idler Roller Conveyor	650	550	1	1200	1
26	Idler Roller Conveyor	650	550	1	1200	1
27	Idler Roller Conveyor	650	550	1	1200	1
28	Idler Roller Conveyor	650	550	1	1200	1
29	Idler Roller Conveyor	650	550	1	1200	1

11.2 Induction to Sorter

The main purpose of the feedlines is to transport the shipments from the VDS chutes to the sorter by means Loading conveyors, Weighing, Buffer/Spacing Conveyor and Angle Merge conveyors. The flow of shipments on the Inducts are controlled by sensors in such a way that the required gap is ensured between the shipments.

These Feedlines are designed especially for Flipkart Group considering Operator Ease and ergonomics. Where the operator ensures proper placement of the shipments on the Induct.



11.2.1 Feedlines


Loop CBS has a total 12 Automatic Feedlines with Designed IPP of 2000 PPH.

1. Each Feedline has Four Conveyor Modules-
 - Orientation Conveyor- 1 Nos.
 - Weighing Conveyor- 1 Nos.
 - Buffer conveyor- 1 Nos.
 - Intelligent Merge- 1 Nos.
2. Sensors are placed on the Induct Lines to determine the exact position and dimensions (Length and Width) of the Shipment on the conveyor and prepare the Cross-Belt Cell for receiving the shipment with high precision.
3. Over the feedline, shipments are evenly spaced and smoothly transferred to the main Loop.

11.2.1.1 Buffer Conveyors

A buffer conveyor, also known as a buffering conveyor or accumulation conveyor, is a type of conveyor system used to temporarily store or hold items in a controlled manner. Its primary purpose is to manage the flow of items between different stages of a production or handling process when there is a mismatch in the speeds or capacities of the upstream and downstream equipment.

This Conveyors required to maintain the Throughput of Line.



11.2.1.2 Weighing Conveyor

A weighing conveyor, also known as a weigh belt conveyor, is a type of conveyor system specifically designed to measure the weight of materials as they move along the conveyor belt. It combines the functions of conveying and weighing into a single integrated process.



Weighing Conveyors equipped with high precision Load Cells to capture the weight of Shipments.

Make- Bizerba/ Mettler Toledo



11.2.1.3 Orientation Conveyor


An Orientation conveyor is a type of conveyor system used to align & Release the products for induction onto CBS. It serves as the initial point of entry where products are collected and conveyed to subsequent stages of the process.



11.2.1.4 Intelligent Merge Conveyor


An intelligent merge conveyor is a type of conveyor system that incorporates advanced automation and control technologies to intelligently merge multiple conveyor lines or streams of materials into a single unified flow. It optimizes the merging process by dynamically adjusting the speed and position of items to ensure a smooth and efficient merge.

In the proposed solution this is 30° triangular high-speed conveyor used for inducing shipment/boxes directly on to the sorter. The Belts are Strip Belts for smooth shipment movement.




11.2.1.5 New Induct Fencing


Setting a new Safety paramount. The new Induct Fencing helps prevent unauthorized operators from entering the induction zone, eliminating the risk of accidents and injuries.




11.2.2 Irregular Takeout Conveyor




11.2.2.1 Irregular Chute



11.2.2.2 Irregular Takeaway Conveyor




11.2.2.3 Irregular Collection Bin (In Flipkart's scope)



11.2.3 Conveyor BOQ

S No.	Name	EL_1	EL_2	Length(m)	width (mm)	Set
1	Powered Belt Conveyor	NA	NA	8.64	1010	1
2	Powered Belt Conveyor	NA	NA	8.16	1010	1
3	Powered Belt Conveyor	NA	NA	18.88	1010	1
4	Powered Belt Conveyor	NA	NA	19.68	1010	1
5	Powered Belt Conveyor	NA	NA	3.015	1010	1
6	Powered Belt Conveyor	NA	NA	3.015	1010	1

11.2.4 Main Loop




1. The proposed Single Deck CBS Sorter will be installed on ground level. The Sorter runs at 3000 mm from ground level.
2. We have provided loop with dual Belt Carriers with 600 mm pitch and Belt Size of 495 x 800mm.
3. One loop CBS has a total length of 193 m & 322 number of carriers.
4. As Shipments pass through the Barcode Scanning Tunnel on the Loop, their barcodes are scanned, and chutes are assigned. Once the shipment reaches the respective chute, the carrier carrying the shipment for the chute will actuate and drop the shipment in the assigned chute.

11.2.5 Sorting Output

11.2.5.1 L-Type Collection chute

A collection chute is a type of chute used for the smooth descent of materials or objects from an elevated position to a lower level. It utilizes base metal to guide and support the flow of items along the chute & collect the shipments within its area.

Each collection type chute has capacity to accumulate 30 shipments, The sorted shipments will travel along these collection chutes and get accumulated at the bottom of the chute.



Calculation for Design: We have considered an average shipment size of 300 X 300 X 300 mm while designing the capacity of chutes.

Average shipment size considered for chute volume calculation	L(m)	B(m)	H(m)	Volume (m3)
	0.3	0.3	0.3	0.027
Collection type Chute	4.1	0.8	0.4	1.312

Assuming a 60% occupancy rate, about **30 shipments** will readily fit into these chutes.

Each Chute is equipped with below components to ease the operations:


- Chute Full Sensor
- Four Color Tower Light
- Push Button

Chute I/Os	Description
Chute Full Sensor	To alert the system that the chute is full and mark that chute unavailable for further sortation
Four Colour Tower Lamp	To indicate the chute status
Push Button	To Start/Stop Sorting Operations

11.2.5.2 Rejection Chute

Rejection Chute is a type of chute used for the smooth descent of materials or objects from an elevated position to a lower level. It utilizes base metal to guide and support the flow of items along the chute & end gate can be closed to collect the shipments within its area.

Rejection chute has capacity to accumulate 16 shipments, The sorted shipments will travel along these collection chutes and get accumulated at the bottom of the chute if the end gate is closed.



Calculation for Design: We have considered an average shipment size of 300 X 300 X 300 mm while designing the capacity of chutes.

Average shipment size considered for chute volume calculation	L(m)	B(m)	H(m)	Volume (m3)
	0.3	0.3	0.3	0.027
Collection type PTL Chute	2.0	0.9	0.4	0.72

Assuming a 60% occupancy rate, about **16 shipments** will readily fit into these chutes.


Each Chute is equipped with below components to ease the operations:

- Chute Full Sensor
- Four Color Tower Light
- Push Button

Chute I/Os	Description
Chute Full Sensor	To alert the system that the chute is full and mark that chute unavailable for further sortation
Four Colour Tower Lamp	To indicate the chute status
Push Button	To Start/Stop Sorting Operations

11.2.5.3 Chute Safety Net


A safety measure is implemented by installing an overhead chute net between each chute to prevent parcels from falling from the CBS into the operator's workspace, thereby enhancing operator safety.



The overhead net has a width of 1300 mm and effectively spans the entire 2900 mm gap between two consecutive chutes.

11.2.6 Bag Take away Conveyor

In each Loop CBS, there is a series of Bag Takeaway Conveyors, spanning a combined length of 133 meters. Following the secondary sorting process, bags are securely fastened and manually placed onto these conveyors, which are positioned below the Loop CBS to cover all chute locations. These conveyors then transport the collected bags back to the lower level.



11.2.6.1 Conveyor BOQ

S No.	Name	EL_1	EL_2	Length(m)	width (mm)	Set
1	Bagging Conveyor	5483	5583	18	1210	1
2	Bagging Conveyor	5500	5600	20	1210	1
3	Bagging Conveyor	5600	5700	5	1210	1
4	Bagging Conveyor	5482	5582	19	1210	1
5	Bagging Conveyor	5482	5582	20	1210	1
6	Bagging Conveyor	5473	5573	2	1210	1
7	Bagging Conveyor	5538	5638	5	1210	1
8	Bagging Conveyor	5500	5600	20	1210	1
9	Bagging Conveyor	5473	5573	4	1210	1
10	Bagging Conveyor	5493	5593	20	1210	1

12. Description of Components of Equipment


Elements of the sorting system

1. Cross Belt Sorter
2. Scanning & Sensing on Sorter
3. Conveyor System
4. Steel Works- Mezzanine & Staircases

12.1 Cross Belt Sorter -

Cross Belt Sorter is capable of sorting extremely high volume of versatile products in a gentle manner.

Falcon's Cross belt sorter is powered by high efficiency linear motors and is based on 100% non-touch actuation technology leading throughput capabilities with extremely low noise levels. Falcon's Cross belt sorter is modular in design. It can be easily extendable as per future requirements



12.1.1 CBS Carrier

Falcon Autotech's CBS offers one of the highest Belt widths to Carrier Pitch Ratio in the market today. This additional belt width makes the system capable of handling larger product sizes without compromising on throughput. This also means reduced "dead area" between Carrier belts which drastically reduces the amount of "inbetweeners" and non-sortable shipment recirculation.



12.1.2 Servo Roller

High Powered DC Drive Servo Roller are used to actuate the carrier belts, thereby eliminating the need for complicated drive transfer mechanism, and simplifying the system installation and maintenance.




12.1.3 Chassis

Falcon Autotech's Cross Belt Carrier Chassis is made up of lightweight Aluminium which makes them light yet sturdy. This reduced weight leads to substantial "Power Savings" over a considerable period of usage.



12.1.4 Carrier Wheels

Carrier wheels that are thoroughly tested and proved for long life cycle.




12.1.5 **Motor Drives**

Falcon offers a choice between two motor drive technology options.

12.1.5.1 Friction Wheel Drive

Extremely High Energy Efficient FWD that can be configured at variable speeds depending upon the operational requirements giving you the maximum flexibility when needed. Using servo motors to power friction wheels, FWD makes it better in terms of controlled speed, acceleration & deceleration



12.1.5.2 Non-contact based linear motor drive

Extremely Energy Efficient Linear Induction Motors that can be configured at variable speeds depending upon the operational requirements giving you the maximum flexibility when needed.




12.1.6 Power Transmission

Power transmission to Carriers over sliding contacts that require low maintenance and offer high levels of reliability.




12.1.7 Data Transmission

The R-Coax cable is used for data distribution in the sorter. This is a leaky wave cable, that runs throughout the sorter length transmitting the data. There is one antenna present in the super master carriage, which keeps on receiving the signal from this cable while on the move, wirelessly.



12.1.8 Carriers positioning System.

Positioning system determines the exact location of each carrier in the loop at any given point in time. There is a plastic tape strip of barcodes (QR Codes) that is running along the sorter loop, which is continuously scanned by scanners placed on a Carrier (Master Carrier)



12.1.9 Technical specifications of Sorter

Items	Make
Sorter Carrier Type	Loop CBS
Sorter Speed in m/s	Up to 2 m/s
Sorter Loop Length	~193 m
Sorter Actuation Technology	Electric
Chutes	
Collection Chute	40
Rejection Chute	4
VDS Chute	12
Irregular Chute	12
Height of Sorter	~3000 mm
Carrier Design	
Carrier Motor Make	Falcon
Carrier Pitch - mm	600
No. of Carriers	322 Nos.
Drives	
Motor/Drive type	Friction Wheel Drive
Power Consumption	Will be specified during DAP
Feedlines (Semi-Automatic)	12 Nos
Power and Data Transmission	
Power Transmission	Over Continuous Bus Bar
Empty Carrier Detection System (Camera Based)	01 Nos
Maintenance Speed of the Sorter- Jog Mode	0.8 m/s
Area Requirement (L x B)	Refer Layout

12.2 Scanning & Sensing on Main Sorter Loop

12.2.1 Automatic Barcode Scanning & Dimensioning System

Top Sided Barcode Scanner to scan shipment 1D codes and 2D codes. The Scanner is also capable of Archiving Shipment Images in Real time. As per FLIPKART requirements, Scanning is in FLIPKART scope.

Falcon needs to supply Volume Measurement System. VMS 4200 quoted as option for Dimensioning of Shipments.



12.2.2 Shipment Positioning System.

Falcon Cross Belt Sorter is equipped with Multiple shipment positioning Scan Tunnels. A tunnel comprises of a series of high Precision Laser Scanners that detect the absolute position of the Shipment on the Cross-Belt Carrier and prepares the Carrier for discharging the product accurately into the chute (virtual centring) and physically bring the product to the centre of cross belt carrier (Physical centring).




12.2.3 Empty Carrier Detection System

This system detects the empty carriers on the sorter and prepares the Feedlines to load the shipments on the empty carriers. (Camera based)



12.3 Steel Works – Mezzanine, Maintenance Platforms & Staircases-

12.3.1 Mezzanine



- Total Mezzanine Area: 720 Sq. Metres
- Max Clear height below Mezzanine: 3700 mm
- No of Stairs: 23 Nos

Each CBS loop consist of:

- Total Mezzanine Area of Loop 1: 720 Sq. Metres
 - 2 Nos – Approx. 218 Sq. Meters of VDS Mezzanine
 - 2 Nos – Approx. 131 Sq. Meters of Induct Mezzanine
- Clear height below Mezzanine:
 - 3700mm below VDS Mezzanine
 - 1900mm below Induct Mezzanine

12.3.2 Maintenance Platform & Staircase




- 5 Sq. Meter: 02 Nos
- Maintenance platform with
lockable gate



- No of Stairs: 23 Nos

13.Allocated Areas



Note – The dedicated Areas are considered basis the specification shared by Flipkart.

14. Proposed System Technical Details (One Loops)

14.1 Mechanical equipment

Pos.	Qty.	Description	Value
1	1	Infeed System - Powered Belt Conveyors - Modular Belt Conveyor - Idler Roller Conveyor - XL ARM Diverters/Tilted VDS gates - VDS Chutes	~205 metres (21 Modules) ~56 metres (4 Modules) ~10 metres (8 Modules) 12 Nos 12 Nos
2	12	Feedlines Consists of - Receiving Conveyor - Weighing Conveyor - Buffer Conveyor - Intelligent merge	1 Set 1 Set 1 Set 1 Set
3	1	Irregular Shipment Handling - Powered Belt Conveyors - Irregular chutes	~61 metres (6 Modules) 12 Nos
4	1	Sorter 1 Loop Cross Belt Sorter - Sorter Height - Sorter Length - Sorter Speed - Sorter Drive - Carrier Pitch Including: - Standard Sorter Supports - Empty Carrier Detection System - Product Centring System - Dimension Scanning System - E-Stops - Hooters - Fencing	3000mm (from mezz level) ~193 m ~2 m/s Linear Motor 600 mm
5	1	Sorter Outputs - L-Type Chute - Rejection Chutes	40 Nos 04 Nos
6	1	Bag Takeaway Conveyor Powered Belt Conveyors	~133 metres (10 Modules)
7	1	Steel Works - Operator and Maintenance Platform - Stairs - Movable maintenance platform	~720 SQM 23 Nos 02 Nos

14.2Electrical Equipment

Electricals			
1	1	Consists of Main Power Distribution panel Main Control Panel Feedline Control Panels Sorter Drive Panels Network Switches Field Cabling	Included

14.3Control System


Components			
1	1	Consists of Siemen's PLC based Control System with SCADA Industrial Switch	1 Nos. As per requirement

15. Electrical System


Main power supply will supply Falcon's PDP (Power Distribution Panels) electrical cabinets. PDP cabinets supply the entire system via secondary cabinets:

- Main Control Cabinet
- Induct Control Panels
- Remote Cabinets for Sorter I/O
- Scanner Control cabinets


15.1 Reference Picture of Power Distribution Panel



15.2 Main Control Panel (Reference)



15.3 Induct Stations Control Panel (Reference)



Engines

Three-phase alternating current motors (Induction) will be used through a frequency converter. The engines will be coupled with a converter to improve consumption and reduce the carbon footprint.

All motors will have appropriate IP ratings

Sensors

The sensors will be supplied, standardized by type, with connector, with a cable length suitable for easy extraction, suitably protected from possible impacts.


Control command

The proposed solution is based on SIEMENS Programmable Logic Controller technology (PLC) platform. The entire system will be logically divided into Zones (Sorter/ Feed Line/ Loop), each managed by a PLC. The planned primary communication protocol is going to be ProfiNet.


Conveyor interface

The frequency converter of each conveyor allows the acquisition of the signals of the sensors/actuators/GIOs associated with it (e.g. conveyor end detection photocells, blockage detection photocells). Each frequency converter will be connected in series by means of the ProfiNet field bus

16. Controls Architecture (Ref.)




17. IT Architecture (Ref.)



17.1HAA Server (In Flipkart Scope)

S.no	Description	Qty
20Core Config with 128 GB RAM in T440 and 64 GB RAM in T40		
1	Synology_storage_DS723+ 2.6 GHz AMD Ryzen R1600 Dual-Core, 2 x Gigabit Ethernet Ports,	2
	2GB ECC DDR4 RAM, 2 x 3.5/2.5" Bays 2 x M.2 2280 Slots E10G22-T1-Mini 10GbE RJ-45 network upgrade module for compact Synology servers	
2	Dell Tower Model T440 -PowerEdge T440 Xeon Gold 6148 2.4GHz/20C/27.5MB/150 W 16 DIMMS 4 x32GB RDIMM Up to 8 3.5"" Hot Plug Hard Drives Tower Configuration 2 x 1.2TB 10K RPM SAS 12Gbps 512n 2.5in	2
	Hot-plug Hard Drive PERC H750 Adapter Full Height 8GB Cache Dual Hot-plug PS495W iDRAC9Enterprise 3YR ProSupport Next Business Day Onsite/Dual Port Lan	
3	Dell PowerEdge T40 Intel Xeon E-2224G Processor 3.5GHz 8M Cache,4C/4T,Turbo,71W,TPM, 4*16 GB RAM (4 DIMM), 2x1TB SATA 3.5" 7.2k rpm HDD (3 Bay), 1Gbe LOM ,DVD Writer, Onboard RAID 01, Inbuilt PSU Standard (Max 1), 3	1
	Year Onsite NBD,480 GB SSD,1 Gbe Dual Lan Card Extra	
4	Windows Server 2019	3
5	Monitor	1
6	KVM Switch	1
7	Mouse	1
8	Keyboard	1
9	Lan Cable	10
10	Power Cable	8
11	VGA Cable	1
12	42 AC Server Rack	1
13	Netgear 24 Port Giga Switch	2
14	2 TB SSD Micron	4
15	DP to VGA Convertor Cadyce Brand	1

18.Falcon's WCS CONTROLIT



Key Values

Supports Multiple Use Cases

- Order Consolidation, SKU wise Sorting, Route Level Sorting, Transporter Wise Sorting and many more

Supports dynamic and static Sort Logic Definition and unlimited Sort Logic Wave definitions

Supports various peripheral Equipment Inputs and Outputs

- Automated Scanners, Manifest Printers, Label Applicators and many more

Ability to define Custom Business Logics

- Cut Off Timings, Quantity/Weight and Volume Thresholds etc

Security

- User profiling with Role Right Mapping
- Database Encryption
- Secured and Protected Communication between WMS and WCS layers

Supported Protocols

API	FTP	FILE UPLOAD / DASHBOARD	ODBC
WEBSERVICES	AMAZON S3 SERVER	FIREBASE	Any Customer Protocol

19.Falcon's Visual Inspection System (SCADA)

SCADA stands for Supervisory Control and Data Acquisition. It is a system of hardware and software components that allows for remote monitoring, control, and data acquisition of industrial processes or facilities

The Visualization system provided by FALCON (or SCADA) allows the monitoring and control of the different systems delivered for the Flipkart Riyadh Hub. This SCADA system receives from each monitored sub-system all information on their operating status in real time.


At the system monitoring level, the functions performed are:

- Field data acquisition.
- Animated visualization of equipment.
- Representation of the operating mode of the system (nominal, contingency, etc.).
- Alarm management.
- Alarm history management.
- Diagnostic help.
- Failure detection.
- Equipment control.
- Statistics on equipment operation.
- Historical Statistical Report.
- Recording and archiving.
- Safety operator interface.

19.1FIELD DATA ACQUISITION

The field data acquisition function is performed by the SCADA system connected to the sorters' PLCs.


The communication with the PLCs is done using equipped CPU cards that are able to manage the communication with the PLC on the Industrial Ethernet network, without overloading the server. The acquisition of signals from external systems is carried out via the PLC, using dry contacts.




19.2 ANIMATED SYSTEM VISUALIZATION

The animated view represents the dynamic graphical user interface that allows real-time monitoring of the controlled systems and the execution of their control procedures.

The various states of the digital signals are displayed on the screen by graphic symbols. All views are web based with responsive capabilities when required so that various devices can be used to display status and information on PC. The types of information that can be displayed on each type of device will be discussed during the design phase of the project.



Example of a synoptic view



19.3ALARM MANAGEMENT


The alarm pages display a series of information to identify the nature of the alarm or event, the elements involved and the time.

The alarm management includes:

- The Alarm name.
- The date on which the above-mentioned alarm was activated.
- The moment the alarm goes off.
- The date on which the alarm is activated again.
- The moment the alarm is activated again.
- The sub-system that activated the alarm.
- The area where the alarm was triggered.
- The name of the beacon that activated the alarm.
- The alarm state.
- The alarm value.
- A complete alarm description.

The historic data of each alarm is stored in the SCADA database. This type of fault detected includes:

- ✓ Sensors.
- ✓ Drive Fault.
- ✓ Lack of monitored equipment.
- ✓ Etc.



Alarm Class	No.	Time	Date	Status	Alarm Name
BAG SORTER_ALARM	3265	11:07:24 AM	2/3/2023	1	BAG SORTER-1 ANGULAR FL HAND SCANNER SOCKET ERROR--
FEEDLINE	1918	11:07:43 AM	2/3/2023	1	Feedline Stop Due to Power Save Mode
FEEDLINE	1897	11:07:43 AM	2/3/2023	1	FL_OKT_TCP_Error
FEEDLINE	1898	11:07:43 AM	2/3/2023	1	FL_TCP_Disconnect_Error
FEEDLINE	1672	11:07:43 AM	2/3/2023	1	Feedline Stop Due to Power Save Mode
FEEDLINE	1626	11:07:43 AM	2/3/2023	1	Key Switch Off Error
FEEDLINE	1549	11:07:43 AM	2/3/2023	1	Feedline Stop Due to Power Save Mode
FEEDLINE	1528	11:07:43 AM	2/3/2023	1	FL_OKT_TCP_Error
FEEDLINE	1529	11:07:43 AM	2/3/2023	1	FL_TCP_Disconnect_Error
FEEDLINE	1426	11:07:43 AM	2/3/2023	1	Feedline Stop Due to Power Save Mode
FEEDLINE	1405	11:07:43 AM	2/3/2023	1	FL_OKT_TCP_Error
FEEDLINE	1406	11:07:43 AM	2/3/2023	1	FL_TCP_Disconnect_Error
FEEDLINE	1303	11:07:43 AM	2/3/2023	1	Feedline Stop Due to Power Save Mode
FEEDLINE	1180	11:07:43 AM	2/3/2023	1	Feedline Stop Due to Power Save Mode
FEEDLINE	1134	11:07:43 AM	2/3/2023	1	Key Switch Off Error
BAGGING_ALARM	3829	11:07:24 AM	2/3/2023	1	Bagging Conveyor_MurrCardNode 101 Error_Zone2...

Sample Alarm History Screen

20. Key Components Make


Items	Make
Belts	Forbo/ Derko
Rollers	Falcon
Cross Belt Carriers	Falcon
Friction Wheel Drive	Falcon
Feed Line Motors	Induction Motors – SEW/ Lenze
Volume Scanners (VMS 4200)	SICK
Weighing Scales	Bizerba/ Mettler Toledo
Encoders	SICK
Sensors	Sick/Leuze/ P&F
PLC	Siemens
Control Panels	Rittal/ BCH
VFDs	Siemens/Lenze/ AB/ Omron
Cables	LAPP/ Equivalent
Switch Gear	Schenider/Equivalent
Bearings	NTN/SKF/Equivalent
Power Transmission Systems	Vahle
HMIs	Siemens

21.Principle of Safety


21.1E-Stops



- a. At Every Conveyor Module – Both sides




b. VDS Chutes




21.2 Pull Cords Switch-

Required for Infeed & Takeout Conveyors



21.3 Fencing

- a. Between Inducts
- b. Between Inducts and Sorter



22.Additional Scope-

- Estops at CBS Loop & ICR
- Key management System at Inducts with Fortress
- FRLS Cables- LAPP/ Polycab/ KEI Make
- Power Saving Sensors for Conveyors
- Safety PLC
- Safety Net between Chutes.
- Energy Meters
- Safety Gate at ICRs

23.Exclusions

The scope of supply includes all parts which are defined in the Supplier's quotation.

All other parts which are not defined in the Supplier's quotation do not belong to the Supplier's scope of supply and are excluded. The following parts are also excluded:

- **Server System**
- **Mobile Carts**
- **Construction Power**
- **Steel Works- If not specified**
- **Collection Trolleys below chutes**
- **Secondary Sortation**
- **PC for SCADA.**
- **Stress free mats**
- **Insulation mats**
- **Fans at chutes & Inducts**
- Building infrastructure; building structure, doors, fire exits, levelling devices, building extinguisher and fire alarm system, building heating and lighting system.
- Electrical power supply and wiring to the main control cabinets
- UPS for Controls and Drives
- Network Cabling up to the Main Server Rack
- Intermediate wiring to parts which are to be supplied by the Purchaser/others
- Emergency/Uninterruptable power supply
- Fire-alarm and fire protection devices
- Traffic and route markings
- Laydown Area
- Ram protection devices
- Cat walks, bridges, maintenance aisles and platforms
- Assembly tools like forklifts and hoisting machines
- All kind of network incl. Local Area Network (LAN/WLAN), exceeding the scope described in Scope of Supply
- Any Kind of Civil work
- Any adjustment of the Supplier's scope of supply to local rules and regulations
- X-Ray machines
- Roller cages/ Pallets
- **Simulation and 3D animation of the sorter system**
- Interface with other equipment not specified in this offer.
- Provision of facilities for the control room (furniture, air conditioning, heating, etc.).
- The supply and installation of fencing around the different corridors.
- Any item specifically indicated as not forming part of the subject matter of the Seller's supply in the offer documentation.