

MCA Semester 1	Subject : Advanced Data Structures Lab
Name : Mukund Gangurde	Topic: Applications of Linked Lists DLL & Polynomial
Roll No. : MCA2511	Date : 14-11-2025

1) Demonstrate the working of a Doublylinked list with operations to insert, delete, search, display and count the number of nodes.

**Code:**

```
import java.util.Scanner;
```

```
class DNode
```

```
{
```

```
    int data;
```

```
    DNode prev;
```

```
    DNode next;
```

```
    DNode(int d)
```

```
    {
```

```
        data = d;
```

```
        prev = null;
```

```
        next = null;
```

```
    }
```

```
}//end of DNode
```

```
//DList
```

```
class DList
```

```
{
```

```
    DNode head;
```

```
    DNode tail;
```

```
    public DList()
```

```
    {
```

```
        head = null;
```

```
        tail = null;
```

```
    }
```

```
    //Insert
```

```
    public void Insert(int x)
```

```
    {
```

```
        //1. Make a new node t
```

```
        DNode t = new DNode(x);
```

```
//2. First node in DLL
if(head == null)
{
    head = t;
    tail = t;
}
else //3. Link t at the end of the DLL
{
    tail.next = t;
    t.prev = tail;
    tail = t;
}
} //end of Insert

//Delete
public void Delete(int x)
{
    //1. Search for x
    DNode tmp = head;
    DNode p = null;
    boolean flag = false;

    while(tmp!=null)
    {
        if(tmp.data == x)
        {
            flag = true;
            break;
        }
        p = tmp;
        tmp = tmp.next;
    }

    //2. Unsuccessful Search
    if(flag == false)
    {
        System.out.println(x + "is not found");
        return;
    }

    //3. Successful Search
    if(tmp == head && tmp == tail) //A. Single node Deletion
    {
        head = null;
        tail = null;
    }
}
```

```
        else if (tmp == head)                //B. Head Node Deletion
        {
            head = tmp.next;
            head.prev = null;
        }
        else if (tmp == tail)                //C. Tail node Deletion
        {
            tail = p;
            tail.next = null;
        }
        else                                //D. Any other node deletion
        {
            p.next = tmp.next;
            tmp.next.prev = p;
        }
    }
} //end of Delete

//Search
public void Search(int x)
{
    DNode tmp = head;
    boolean flag = false;

    while(tmp!=null)
    {
        if(tmp.data == x)
        {
            flag = true;
            break;
        }
        tmp = tmp.next;
    }
    if(flag==true)
    {
        System.out.println(x+ " is found");
    }
    else
    {
        System.out.println(x+ " is not found");
    }
} //end of Search

//Count
public void Count()
{
    DNode tmp = head;
```

```
        int cnt = 0;

        while(tmp!=null)
        {
            cnt++;
            tmp = tmp.next;
        }
        System.out.println("There are "+ cnt + " nodes");
    } //end of Count

    //Display
    public void Display()
    {
        DNode tmp = head;
        System.out.print("From head: ");
        while(tmp!=null)
        {
            System.out.print(tmp.data + "<->");
            tmp = tmp.next;
        }
        System.out.print("NULL");
        System.out.println();

        tmp = tail;
        System.out.print("From tail: ");
        while(tmp!=null)
        {
            System.out.print(tmp.data + "<->");
            tmp = tmp.prev;
        }
        System.out.print("NULL\n");
    } //end of Display

} //end of DList

class DLL
{
    public static void main(String[] args)
    {
        int ch;
        DList d = new DList();
        Scanner sc = new Scanner(System.in);

        do
        {
```

```
System.out.println("\n*****Doubly Linked List*****");
System.out.println("1. Insert a new node in DLL");
System.out.println("2. Delete a node in DLL");
System.out.println("3. Search for a node in DLL");
System.out.println("4. Count No. of Nodes in DLL");
System.out.println("5. Display Nodes in DLL");
System.out.println("6. Exit out");
System.out.println();
```

```
System.out.print("Enter your choice: ");
ch = sc.nextInt();
```

```
switch(ch)
{
    case 1:
        System.out.print("Enter a value: ");
        int x = sc.nextInt();
        d.Insert(x);
        d.Display();
        break;

    case 2:
        d.Display();
        System.out.print("Enter a value: ");
        x = sc.nextInt();
        d.Delete(x);
        d.Display();
        break;

    case 3:
        System.out.print("Enter a value: ");
        x = sc.nextInt();
        d.Search(x);
        break;

    case 4:
        d.Count();
        break;

    case 5:
        d.Display();
        break;

    case 6:
        System.out.println("Exiting ----- :");
        break;
```

```
                default:
                    System.out.println("Incorrect .... \n");
                    break;
            }

        } while (ch != 6);
    } //end of psvm
} // end of DLL
```

**Output:**

**Data:**

```
Enter your choice: 1
Enter a value: 10
From head: 101<->50<->60<->30<->80<->60<->20<->10<->NULL
From tail: 10<->20<->60<->80<->30<->60<->50<->101<->NULL
```

\*\*\*\*\*Doubly Linked List\*\*\*\*\*

1. Insert a new node in DLL
2. Delete a node in DLL
3. Search for a node in DLL
4. Count No. of Nodes in DLL
5. Display Nodes in DLL
6. Exit out

```
Enter your choice: 5
From head: 101<->50<->60<->30<->80<->60<->20<->10<->NULL
From tail: 10<->20<->60<->80<->30<->60<->50<->101<->NULL
```

**Node Not Found**

\*\*\*\*\*Doubly Linked List\*\*\*\*\*

1. Insert a new node in DLL
2. Delete a node in DLL
3. Search for a node in DLL
4. Count No. of Nodes in DLL
5. Display Nodes in DLL
6. Exit out

```
Enter your choice: 2
From head: 101<->50<->60<->30<->80<->60<->20<->10<->NULL
From tail: 10<->20<->60<->80<->30<->60<->50<->101<->NULL
Enter a value: 123
123is not found
From head: 101<->50<->60<->30<->80<->60<->20<->10<->NULL
From tail: 10<->20<->60<->80<->30<->60<->50<->101<->NULL
```

### Head Node

\*\*\*\*\*Doubly Linked List\*\*\*\*\*

1. Insert a new node in DLL
2. Delete a node in DLL
3. Search for a node in DLL
4. Count No. of Nodes in DLL
5. Display Nodes in DLL
6. Exit out

Enter your choice: 2

From head: 101<->50<->60<->30<->80<->60<->20<->10<->NULL

From tail: 10<->20<->60<->80<->30<->60<->50<->101<->NULL

Enter a value: 101

From head: 50<->60<->30<->80<->60<->20<->10<->NULL

From tail: 10<->20<->60<->80<->30<->60<->50<->NULL

### Tail Node

\*\*\*\*\*Doubly Linked List\*\*\*\*\*

1. Insert a new node in DLL
2. Delete a node in DLL
3. Search for a node in DLL
4. Count No. of Nodes in DLL
5. Display Nodes in DLL
6. Exit out

Enter your choice: 2

From head: 50<->60<->30<->80<->60<->20<->10<->NULL

From tail: 10<->20<->60<->80<->30<->60<->50<->NULL

Enter a value: 10

From head: 50<->60<->30<->80<->60<->20<->NULL

From tail: 20<->60<->80<->30<->60<->50<->NULL



**Any other Node**

\*\*\*\*\*Doubly Linked List\*\*\*\*\*

1. Insert a new node in DLL
2. Delete a node in DLL
3. Search for a node in DLL
4. Count No. of Nodes in DLL
5. Display Nodes in DLL
6. Exit out

Enter your choice: 2

From head: 50<-->60<-->30<-->80<-->60<-->20<-->NULL

From tail: 20<-->60<-->80<-->30<-->60<-->50<-->NULL

Enter a value: 80

From head: 50<-->60<-->30<-->60<-->20<-->NULL

From tail: 20<-->60<-->30<-->60<-->50<-->NULL

## 2. Polynomial Insertion & Display.

### Code:

```
import java.util.Scanner;
```

```
//Node Template
```

```
class Node
```

```
{
```

```
    int coeff;
```

```
    int exp;
```

```
    Node next;
```

```
    public Node (int c, int a)
```

```
    {
```

```
        coeff = c;
```

```
        exp = a;
```

```
        next = null;
```

```
    } //end of Node Constructor
```

```
} //end of class Node
```

```
//List template for Polynomial
```

```
class Polynomial
```

```
{
```

```
    Node head;
```

```
    public Polynomial()
```

```
    {
```

```
        head = null;
```

```
    }
```

```
    //Insert
```

```
    void Insert(int c, int e)
```

```
    {
```

```
        //Make a new Node
```

```
        Node t = new Node(c,e);
```

```
        //First Node in the list
```

```
        if(head == null)
```

```
        {
```

```
            head = t;
```

```
            return;
```

```
        }
```

```
        //Traverse and check for order in exponent
```

```
        Node tmp = head;
```

```
        Node prev = null;
```

```
//Find location for t
while(tmp!=null && t.exp < tmp.exp)
{
    prev = tmp;
    tmp = tmp.next;
}

//Insert at right location
if(tmp == head)                //Head Node Insertion
{
    t.next = tmp;
    head = t;
}
else if (tmp == null)         //Tail Node Insertion
{
    prev.next = t;
}
else                          //Any other node Deletion
{
    prev.next = t;
    t.next = tmp;
}
}
}

//end of Insert

//Display
public void Display()
{
    //Check for Empty List
    if(head == null)
    {
        System.out.println("Empty List");
        return;
    }

    //Traverse and check for order in exponent
    Node tmp = head;

    //Find location for t
    while(tmp!=null)
    {
        System.out.print(tmp.coeff + "x^" + tmp.exp);
        if(tmp.next!=null)
        {
            System.out.print(" + ");
        }
    }
}
```

```
        tmp = tmp.next;
    }
} //end of Display

//Sum / Addition

} //end of Polynomial

class PolAdd
{
    public static void main(String[] args)
    {
        Scanner sc = new Scanner(System.in);
        Polynomial p1 = new Polynomial();
        Polynomial p2 = new Polynomial();

        System.out.println("Enter the number of terms in Polynomial 1: ");
        int n1 = sc.nextInt();
        System.out.println("Enter Polynomial 1: (coeff,exp) ");

        for(int i = 1; i <= n1 ; i++)
        {
            int c = sc.nextInt();
            int e = sc.nextInt();
            p1.Insert(c,e);
        }

        System.out.print("Polynomial 1: ");
        p1.Display();

    } //end of psvm
} //end of PolAdd
```

**Output:**

```
A:\MCA2511\DS_LAB>java PolAdd
Enter the number of terms in Polynomial 1:
5
Enter Polynomial 1: (coeff,exp)
12 6
13 8
23 2
45 4
6 3
Polynomial 1:
13x^8 + 12x^6 + 45x^4 + 6x^3 + 23x^2
```