BACK

Box Blur



~

DESCRIPTION

MY SOLUTIONS

LEADERBOARD

COMMENTS

README >

CODEWRITING

SCORE: 300/300

Last night you partied a little too hard. Now there's a black and white photo of you that's about to go viral! You can't let this ruin your reputation, so you want to apply the *box blur* algorithm to the photo to hide its content.

The pixels in the input image are represented as integers. The algorithm distorts the input image in the following way: Every pixel \times in the output image has a value equal to the average value of the pixel values from the 3 \times 3 square that has its center at \times , including \times itself. All the pixels on the border of \times are then removed.

Return the blurred image as an integer, with the fractions rounded down.

Example

For

```
image = [[1, 1, 1], [1, 7, 1], [1, 1, 1]]
```

the output should be boxBlur(image) = [[1]].

To get the value of the middle pixel in the input 3×3 square: (1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1) = 15 / 9 = 1.66666 = 1. The border pixels are cropped from the final result.

For

the output should be

```
boxBlur(image) = [[5, 4], [4, 4]]
```

There are four 3×3 squares in the input image, so there should be four integers in the blurred output. To get the first value: (7 + 4 + 0 + 5 + 6 + 2 + 6 + 10 + 7) = 47 / 9 = 5.2222 = 5. The other three integers are obtained the same way, then the surrounding integers are cropped from the final result.

Input/Output

- [execution time limit] 4 seconds (js)
- [input] array.array.integer image

An image, stored as a rectangular matrix of non-negative integers.

Guaranteed constraints:

```
3 ≤ image.length ≤ 10,
3 ≤ image[0].length ≤ 10,
0 ≤ image[i][j] ≤ 255.
```

• [output] array.array.integer

A blurred image represented as integers, obtained through the process in the description.

[JavaScript (ES6)] Syntax Tips

```
// Prints help message to the console
// Returns a string
function helloWorld(name) {
```

