

Regional Tax Payment Inquiry API (JSON, Method POST)

1. Generate Authentication Token

Environment				
URL	https://api.example.com/payment/login			
Method Type	Post			
Method Header	Content-Type:application/json			
Description	Inquiry Token			
Input Parameters				
Parameters	Type	Length	Repeat	Description
username	String	20	1	API authentication username
password	String	20	1	API authentication password
Return				
bearertoken	String	Variable	1	Generated bearer token for API authentication
expired	String	15	1	Token validity period

- JSON Request Parameters:

```
{  
  "username": "<api_username> ",  
  "password": "<api_password> "  
}
```

- Return Value: JSON Response Info Token

```
{  
  "timestamp": "2025-02-11 10:35:33",  
  "status": true,  
  "code": 201,  
  "message": "Token created!",  
  "data": {  
    "bearertoken":  
      "<access_token>",  
    "expired": "24:00:00"  
  }  
}
```

2. Get BPHTB Payment Data

Environment				
URL	https://api.example.com/payment/inquiry			
Method Type	Post			
Method Header	Content-Type:application/json			
Description	Retrieves regional tax payment information from an external payment integration service.			
Input Parameters				
Parameters	Type	Length	Repeat	Description
property_id	String	Variable	1	Unique identifier of the taxable property
payment_code	Date	10	1	Unique reference number for the BPHTB payment
Return				
property_id	String	20	1	Unique identifier of the taxable property
taxpayer_id	String	100	1	Taxpayer identification number
property_address	String	100	1	Address of the taxable property
city	String	200	1	City where the taxable property is located
land_area	Decimal	16,2	1	Land area of the taxable property
building_area	Decimal	16,2	1	Building area of the taxable property
payment_amount	Decimal	16,2	1	Total BPHTB payment amount
payment_status	String	5	1	Payment status, such as PAID or DEBT
payment_date	Date		1	Date when the BPHTB payment was made
payment_code	String	100	1	Unique reference number for the BPHTB payment

- Authorization:

```
"bearer_token": "<access_token>"
```

- JSON Request Parameters:

```
{
  "property_id": "PROP-000123",
  "payment_code": "PAY-000789"
}
```

- Return Value: JSON Response Info BPHTB

1. Paid

```
{
  "response_code": "OK",
  "result": {
    "property_id": "PROP-000123",
    "taxpayer_id": "TAX-000456",
    "taxpayer_name": "Sample User",
    "property_address": "Sample Address",
    "city": "Sample City",
    "land_area": 100,
    "building_area": 60,
    "payment_amount": 2500000,
    "payment_status": "PAID",
    "payment_date": "2026-01-15 15:00:00",
    "payment_code": "PAY-000789"
  }
}
```

2. Debt

```
{
  "response_code": "OK",
  "result": {
    "property_id": "PROP-000123",
    "taxpayer_id": "TAX-000456",
    "taxpayer_name": "Sample User",
    "property_address": "Sample Address",
    "city": "Sample City",
    "land_area": 100,
    "building_area": 60,
    "payment_amount": 2500000,
    "payment_status": "DEBT",
    "payment_date": "",
    "payment_code": "PAY-000789"
  }
}
```

3. Wrong Data

```
{  
  "response_code": "INVALID_PARAMETER"  
  "message ": "The provided property identifier was not found."  
}
```

Or

```
{  
  "response_code": "INVALID_PARAMETER"  
  "message ": "The provided data identifier was not found."  
}
```

4. Wrong Token

```
{  
  "timestamp": "2025-02-11 10:35:33",  
  "status": false,  
  "code": 401,  
  "message": "Invalid or expired authentication token.",  
  "data": null  
}
```

5. Limitation on Get Data

```
{  
  "timestamp": "2025-02-11 10:35:33",  
  "status": false,  
  "code": 429,  
  "message": "Too many requests. Please try again later.",  
  "data": null  
}
```

Note:

This document is an anonymized sample created for portfolio purposes. All project-specific information, endpoints, credentials, and data have been modified or replaced with fictional examples to preserve confidentiality while demonstrating API documentation practices.

Dokumen ini merupakan contoh yang telah disamarkan identitasnya dan dibuat untuk keperluan portofolio. Seluruh informasi spesifik proyek, *endpoint*, kredensial, dan data telah diubah atau diganti dengan contoh fiktif guna menjaga kerahasiaan sekaligus menunjukkan praktik dokumentasi API.

-Mulfi Indra Gunawan