External Access					
Port	Protocol	Zimbra Service	Description		
25	smtp	mta	incoming mail to postfix		
80	http	mailbox / proxy	web mail client (disabled by default		
80			in 8.0)		
110	pop3	mailbox / proxy	POP3		
143	imap	mailbox / proxy	IMAP		
443	https	mailbox / proxy - web mail client	HTTP over TLS		
	smtps	mta	Incoming mail to postfix over TLS		
465			(Legacy Outlook only? If possible, use		
			587 instead)		
587	smtp	mta	Mail submission over TLS		
993	imaps	mailbox / proxy	IMAP over TLS		
995	pop3s	mailbox / proxy	POP3 over TLS		
3443	https	proxy	User Certificate Connection Port		
3443			(optional)		
5222	хтрр	mailbox	Default server port		
5223	хтрр	mailbox	Default legacy SSL port		
9071	https	proxy admin console	HTTP over TLS (optional)		

Internal Access					
Port	Protocol	Zimbra Service	Description		
389	ldap	ldap	LC(ldap_bind_url)		
636	Idaps	ldaps	if enabled via LC(ldap_bind_url)		
3310	-	mta/clamd	zimbraClamAVBindAddress		
5269	хтрр	mailbox	Server-to-Server communications between servers on the same cluster.		
7025	lmtp	mailbox	local mail delivery; zimbraLmtpBindAddress		
7026	milter	mailbox	zimbra-milter; zimbraMilterBindAddress		
7047	http	conversion server	Accessed by localhost by default; binds to '*'		
7071	https	mailbox	admin console HTTP over TLS; zimbraAdminBindAddress		
7072	http	mailbox	ZCS nginx lookup - backend http service for nginx lookup/authentication		
7073	http	mailbox	ZCS saslauthd lookup - backend http service for SASL lookup/authentication (added in ZCS 8.7)		
7110	pop3	mailbox	Backend POP3 (if proxy configured); zimbraPop3BindAddress		

7143	imap	mailbox	Backend IMAP (if proxy configured); zimbraImapBindAddress
7171	-	zmconfigd	configuration daemon; localhost
7306	mysql	mailbox	LC(mysql_bind_address); localhost
7307	mysql	logger	logger (removed in ZCS 7)
7780	http	mailbox	spell check
7993	imaps	mailbox	Backend IMAP over TLS (if proxy configured); zimbraImapSSLBindAddress
7995	pop3s	mailbox	Backend POP3 over TLS (if proxy configured); zimbraPop3SSLBindAddress
8080	http	mailbox	Backend HTTP (if proxy configured on same host); zimbraMailBindAddress
8443	https	mailbox	Backend HTTPS (if proxy configured on same host); zimbraMailSSLBindAddress
8465	milter	mta/opendkim	OpenDKIM milter service; localhost
8735	zextras	mailbox	internal mailbox to mailbox communication.
8736	zextras	mailbox	distributed configuration
10024	smtp	mta/amavisd	to amavis from postfix; localhost
10025	smtp	mta/master	opendkim; localhost
10026	smtp	mta/amavisd	"ORIGINATING" policy; localhost
10027	smtp	mta/master	postjournal
10028	smtp	mta/master	content_filter=scan via opendkim; localhost
10029	smtp	mta/master	"postfix/archive"; localhost
10030	smtp	mta/master	10032; localhost
10031	milter	mta/cbpolicyd	cluebringer policyd
10032	smtp	mta/amavisd	(antispam) "ORIGINATING_POST" policy
10663	-	logger	LC(logger_zmrrdfetch_port); localhost
23232	-	mta/amavisd	amavis-services / msg-forwarder (zeromq); localhost
23233	-	mta/amavisd	snmp-responder; localhost
11211	memcached	memcached	nginx route lookups, mbox cache (calendar, folders, sync, tags); zimbraMemcachedBindAddress