External Access					
Port	Protocol	Zimbra Service	Description		
25	smtp	mta	incoming mail to postfix		
90	http	mailbox / proxy	web mail client (disabled by default in		
80			8.0)		
110	pop3	mailbox / proxy	POP3		
143	imap	mailbox / proxy	IMAP		
443	https	mailbox / proxy - web mail client	HTTP over TLS		
			Incoming mail to postfix over TLS		
465	smtps	mta	(Legacy Outlook only? If possible, use		
			587 instead)		
587	smtp	mta	Mail submission over TLS		
993	imaps	mailbox / proxy	IMAP over TLS		
995	pop3s	mailbox / proxy	POP3 over TLS		
3443	https	proxy	User Certificate Connection Port		
			(optional)		
5222	хтрр	mailbox	Default server port		
5223	хтрр	mailbox	Default legacy SSL port		
9071	https	proxy admin console	HTTP over TLS (optional)		

Internal Access					
Port	Protocol	Zimbra Service	Description		
389	ldap	ldap	LC(ldap_bind_url)		
636	ldaps	ldaps	if enabled via LC(ldap_bind_url)		
3310	-	mta/clamd	zimbraClamAVBindAddress		
5269	хтрр	mailbox	Server-to-Server communications between servers on the same cluster.		
7025	lmtp	mailbox	local mail delivery; zimbraLmtpBindAddress		
7026	milter	mailbox	zimbra-milter; zimbraMilterBindAddress		
7047	http	conversion server	Accessed by localhost by default; binds to '*'		
7071	https	mailbox	admin console HTTP over TLS; zimbraAdminBindAddress		
7072	http	mailbox	ZCS nginx lookup - backend http service for nginx lookup/authentication		
7073	http	mailbox	ZCS saslauthd lookup - backend http service for SASL lookup/authentication (added in ZCS 8.7)		

рор3	mailbox	Backend POP3 (if proxy configured); zimbraPop3BindAddress
imap	mailbox	Backend IMAP (if proxy configured); zimbralmapBindAddress
-	zmconfigd	configuration daemon; localhost
mysql	mailbox	LC(mysql_bind_address); localhost
mysql	logger	logger (removed in ZCS 7)
http	mailbox	spell check
imaps	mailbox	Backend IMAP over TLS (if proxy configured); zimbralmapSSLBindAddress
pop3s	mailbox	Backend POP3 over TLS (if proxy configured); zimbraPop3SSLBindAddress
http	mailbox	Backend HTTP (if proxy configured on same host); zimbraMailBindAddress
https	mailbox	Backend HTTPS (if proxy configured on same host); zimbraMailSSLBindAddress
milter	mta/opendkim	OpenDKIM milter service; localhost
zextras	mailbox	internal mailbox to mailbox communication.
zextras	mailbox	distributed configuration
smtp	mta/amavisd	to amavis from postfix; localhost
smtp	mta/master	opendkim; localhost
smtp	mta/amavisd	"ORIGINATING" policy; localhost
smtp	mta/master	postjournal
smtp	mta/master	content_filter=scan via opendkim; localhost
smtp	mta/master	"postfix/archive"; localhost
smtp	mta/master	10032; localhost
milter	mta/cbpolicyd	cluebringer policyd
smtp	mta/amavisd	(antispam) "ORIGINATING_POST" policy
-	logger	LC(logger_zmrrdfetch_port); localhost
-	mta/amavisd	amavis-services / msg-forwarder (zeromq); localhost
-	mta/amavisd	snmp-responder; localhost
memcached	memcached	nginx route lookups, mbox cache (calendar, folders, sync, tags); zimbraMemcachedBindAddress
	imap mysql mysql http imaps pop3s http https milter zextras zextras smtp smtp smtp smtp smtp smtp smtp smt	imap mailbox - zmconfigd mysql mailbox mysql logger http mailbox imaps mailbox pop3s mailbox http mailbox http mailbox http mailbox http mailbox milter mta/opendkim zextras mailbox zextras mailbox smtp mta/amavisd smtp mta/master - smtp mta/master - smtp mta/cbpolicyd smtp mta/amavisd - logger - mta/amavisd - logger - mta/amavisd