



Des.	Pos.	Description
B87	A 5	Switch, acknowledge PTO EK
B88	A 4	Switch, acknowledge PTO EG single rear
B97	A 4	Switch, acknowledge PTO EG single rear high ratio
B98	A 5	Switch, acknowledge PTO EG single side
C100	D 4	Connector, 66-pole
C100	D 8	Connector, 66-pole
C100	D 8	Connector, 66-pole
C103	D 5	Connector, 66-pole
C103	D 5	Connector, 66-pole
C103	D 7	Connector, 66-pole
C260	E 3	Connector, 12-pole, BWS
C260	E 3	Connector, 12-pole, BWS
C260	E 6	Connector, 12-pole, BWS
C260	E 6	Connector, 12-pole, BWS
C470	C 5	Connector, 4-pole
C493	E 4	Connector, 15-pole, BWS
C493	E 4	Connector, 15-pole, BWS
C493	E 6	Connector, 15-pole, BWS
C493	E 6	Connector, 15-pole, BWS
E30	E 5	Control unit, coordinator
G13	C 4	Ground, torpedo wall
G13	C 5	Ground, torpedo wall
G13	C 7	Ground, torpedo wall
G13	C 7	Ground, torpedo wall
G13.R	B 7	Ground, torpedo wall
V13	A 7	Solenoid valve, PTO EG1
V43	A 8	Solenoid valve, PTO EK
V133	A 7	Solenoid valve, PTO EG2

Cable designation	
AWD35 . OG - 1	
Cable marking	
Cable colour (Orange)	
Conductor area (mm ²)	
Colour code of electric cables	
Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink



GMS, Gearbox Management System

PTO GR/S/O875/895/905/925/R

Applies to vehicles manufactured from October 2009

Truck

Sheet 3

16:78-22 Issue 1

N.B. The copyright and ownership of this drawing including associated computer data are and will remain ours. They must not be copied, used, or brought to the attention of any third party without our prior permission.
(c) Scania, Sweden

PTO

Issue

17 727