



Des.	Pos.	Description
B16	A 6	Switch, reverse light
B45	A 7	Switch, neutral
C93	B 3	Connector, 7-pole, RET
C100	D 6	Connector, 66-pole
C101	D 7	Connector, 66-pole
C102	D 3	Connector, 66-pole
C112	B 6	Connector, 7-pole, manual Gearb/OPC
C118	B 7	Connector, 4-pole, manual Gearb/OPC
C429	B 5	Connector, 7-pole, RET
C469	B 7	Connector, 4-pole
C480	F 6	Joint connector red CAN
C482	F 5	Joint connector wake up
E5	E 5	Control unit, Opticruise
E30	E 7	Control unit, coordinator
G5	F 4	Joint connector, ground
G13.N	C 7	Ground, torpedo wall
P2	F 4	Central electric unit
T20	A 8	Sensor, tachograph
T63	A 3	Sensor, water temp, retarder
T80	A 4	Sensor, oil pressure, retarder
T86	A 4	Sensor, oil temp, retarder
V97	A 5	Solenoid valve unit, retarder
V111	A 6	Solenoid valve unit, range/split

Cable designation	
AWD35 . OG - 1	
Cable marking	
Cable colour (Orange)	
Conductor area (mm <sup>2</sup> )	
Colour code of electric cables	
Code	Colour
BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink



## GMS, Gearbox Management System

GR/S/O875/895/905/925/R

Applies to vehicles manufactured  
from November 2010

Truck

Sheet 1

16:78-20 Issue 1

N.B. The copyright and ownership of this drawing including associated  
computer data are and will remain ours. They must not be copied, used,  
or brought to the attention of any third party without our prior permission.  
(c) Scania, Sweden