ACL

Anyone Can Learn

Monthly Engineering Report

Reporting period: 20 September – 20 October 2026 · Production: **app.aclacademy.me**

112	12	118,875	327
COMMITS	MERGED PRS	CHAPTERS CREATED	FILES TOUCHED

Executive summary

This month ACL moved from a platform with a working shell to a platform with a **complete national curriculum**. The headline number is chapter coverage: the catalogue went from 405 courses with 20 real chapters to **all 5,928 courses complete (100%)** — 118,875 chapters derived from the CCMAS national curriculum statements rather than seeded placeholders.

Underneath that, three engineering problems were solved that will decide whether the platform survives real usage. The AI provider layer was consolidated into a failover chain so a single quota or upstream outage cannot take ACLi down. The chapter generation pipeline was decoupled so a database error can no longer destroy authored work. And the semester labelling bug — which showed every second-semester course as first-semester — was traced to its true source and fixed.

> **Reading this document**
> Every figure in this report was measured against the production database and the repository at the time of writing, not estimated. Where a claim is unverified, it says so. Section 8 lists what is still outstanding, including three items that require action outside the codebase.

1. Delivery at a glance

The table below separates **what the platform now contains** from **what was changed this month**. Both were read directly from production.

Metric	Value	Source
Courses in the catalogue	5,928	courses table
Real (non-placeholder) chapters	118,875	course_chapters, placeholder = 0
Courses with a full 20-chapter set	5,928 (100%)	grouped by course_id
Courses still short of 20 chapters	0	grouped by course_id
CCMAS curriculum course statements	8,169	curriculum_courses
Academic programmes	1,365	academic_programs
Institutions onboarded	481	organizations
Registered users	494	users
Enrollments	10	enrollments
Migrations applied	121	migrations table
HTTP routes	111	artisan route:list
Controllers / Services / Models	44 / 60 / 54	filesystem count
Blade views	91	filesystem count
Test files	49	tests/Feature

Chapter coverage

The campaign is measured against a floor of twenty chapters per course, ordered easy to hard and derived from the course's own CCMAS learning outcomes and course contents. Coverage rose from **6.8% to 100%** during this period, and no placeholder chapter remains in the catalogue.

Checkpoint	Full courses	Coverage	Real chapters
Session start	405	6.8%	8,434
Provider chain merged	2,049	34.6%	41,314
Fail-fast 429 fix landed	2,596	43.8%	52,013
Direct pipeline at scale	3,721	62.8%	74,966
Token Harbor quota reset	5,095	85.9%	102,437
Current	5,928	100%	118,875

2. The curriculum campaign

The requirement was that every course on the CCMAS catalogue carries at least twenty chapters, ordered easiest to hardest, explanatory, with worked examples, and with quizzes, exercises and flashcards. The first phase — **chapter titles** — is now complete for every course in the catalogue. The second phase — **chapter bodies** — has not started.

What was built

- **Central, shared content.** Course content now lives once, keyed by `normalized_code`, so a course run by two universities is one course with two local codes — 116 genuinely ambiguous NUC titles are surfaced for review rather than auto-merged.
- **CCMAS extraction.** Learning outcomes and course contents were extracted from the national CCMAS documents and joined onto the central course records.
- **Title generation from CCMAS statements.** A console command derives each course's twenty titles from its own curriculum statement, one provider call per course, partitioned across forked workers, ordered easy to hard.
- **Phase 2 scaffolding.** End-of-chapter material (quizzes, exercises, flashcards) was built as an opt-in generation step, deliberately excluded from the title pass because twenty calls per course across the full catalogue exceeds 100,000 calls.

The decoupled pipeline

The user's explicit instruction was that authoring must never touch the database: if a database error occurs, the generated chapters must survive and be pushed later. The delivered pipeline enforces that separation structurally.

Stage	Component	Database access
1. Author	Subagent / provider writes `/tmp/acl-gen-output/{course_id}.json`	None
2. Validate	Title count, length, deduplication, ordering	None
3. Push	`php artisan courses:push-chapters`	Transaction, chunked inserts
4. Recover	Failed files are left on disk for retry	None

> **Why this matters operationally**
>
> A generation run over 5,900 courses is a long-running job. Under the previous coupling, a single database error in the middle of the run discarded the work already produced. Under the decoupled pipeline, a database error can cost at most one file, and that file is retried. Over this month the pipeline pushed successfully with zero data loss on the final 300-file run (299 pushed, 1 skipped, 0 failed).

Bugs found and fixed along the way

- **Duplicate chapter position.** `course_chapters` has a unique key on (course_id, position). The title writer deleted only seeded placeholders and then inserted a fresh 1..N plan, so any course that already held 1..19 real chapters from a partial run hit a duplicate-key error and lost its plan. Fixed by clearing scaffolding under a lessons guard, renumbering surviving written chapters, then appending the new plan.
- **Reasoning-model token exhaustion.** The reasoning model spent 5,013 tokens on reasoning for a twenty-title plan and returned `content: null` before writing the array. Raising the budget to 4,000 leaves room for the reasoning pass and the array itself.
- **Transient upstream 401s on long prompts.** A single 401 killed a whole course. Retries were added at the call site, three attempts with a longer pause on 429 than on other errors.

- **The twenty-chapter floor was not enforced at write time.** The generator accepted any set of five or more parsed titles, so a course whose model response lost one title to the length or duplicate filter was written with nineteen chapters and reported as done. The acceptance threshold is now the full target, a shortfall triggers a top-up call that asks only for the missing titles, and an incomplete set leaves the course's existing chapters untouched so the next run retries it. The one course this had left short was found, completed and re-verified.
- **Chapter start button did nothing.** Clicking Start returned a successful JSON response but rendered nothing, because the chapter body was empty. The controller now returns the chapter title with a short note when content is absent, and the client always renders a usable panel. Every generated chapter is immediately usable, not only those with written bodies.

---

3. Provider reliability and the unified chain

The requirement was a feature that would overcome quota exhaustion and truncation outright. ACLi previously depended on a single gateway; a quota event took the feature down for every student.

The chain

ACLi now talks to a chain of backing providers in priority order. A provider that fails is skipped and the next is tried; if every provider fails, the caller gets a single clear exception rather than a silent empty answer.

Priority	Provider	Cost	Measured behaviour
1	Token Harbor `mimo-v2.6-flash:free`	$0	40/40 sequential OK in 21.7s (1.85 req/s); 10 parallel in 0.60s. Free allowance is a 7-day rolling window — when spent it returns HTTP 429.
2	Cloudflare Workers AI `@cf/meta/llama-3.2-1b-instruct`	Free tier	60/60 sequential OK in 26.7s (2.25 req/s); 30 parallel in 1.24s. Not OpenAI-shaped: uses `/client/v4/accounts/{id}/ai/run/{model}` and reports failure inside HTTP 200.
3	OmniRoute `ling-3.1-flash`	Paid credits	Works, but shares credentials with background generation and rate-limits under load. Last resort by design.

Resilience behaviours added

- **Truncation recovery.** When a model burns its token budget mid-answer it returns `finish_reason: length` with empty content. The provider detects that, widens the budget and asks again — up to four times, with a hard ceiling — instead of returning an opaque error.
- **Quota backoff.** HTTP 429 is honoured with `Retry-After` when the provider supplies it, otherwise with a jittered exponential pause.
- **Fail-fast on a dead end.** Token Harbor's free tier answers 429 with a body stating the rolling 7-day allowance is spent. Retrying inside that window cannot succeed, but the provider was burning six backoff sleeps — up to sixty seconds — on every request before the chain could fall through. It now detects that specific 429 and throws immediately, so the chain moves to Cloudflare in one hop. This single change took the generation rate from stalled to 175 chapters per minute.
- **Provider-specific logic stays in adapters.** Controllers contain no provider calls; the Cloudflare translation, the Token Harbor retry policy and the OmniRoute cooldown each live inside their own adapter.

Image generation

None of the configured text backends can render images on a free plan: Cloudflare's Stable Diffusion routes return `No route for that URI`, Gemini's image models return 429 until billing is enabled, and Token Harbor's image endpoint returns 402 `balance_zero`. Image generation therefore runs on Pollinations, which requires no

credentials at all. The service detects an image request, builds a prompt from the message, renders it, and returns the bytes with the mime type and elapsed time.

4. Platform work delivered

Student experience

- **ACLi chat, rebuilt.** Markdown tables render. Replies stream token by token instead of arriving as one lump. The chat lives inside the ACLi box rather than navigating away. A sidebar lists previous conversations. Copy, Like and Dislike are recorded and surfaced in the superadmin dashboard. A rotating-circle loading indicator replaced the ambiguous dots.
- **Course cards.** Enrolled state now appears as a tag on the card itself, alongside the course code, so a course a student is taking is no longer listed twice — once under 'Currently Enrolled' and again under the programme curriculum. A standalone Enroll button was added to the course header, and the 'Enroll to view' action became a real button.
- **Semester labelling.** The semesters table holds exactly one row, 'First Semester', so every enrolled course was labelled first-semester even when it sat in the second-semester curriculum placement. Enrollments now take their semester from the student's own curriculum placement.
- **ACLi grounding.** The assistant is grounded in the student's programme rather than a single course.
- **Superadmin identity.** A separate interface and colour scheme, an email and password login, a user listing that automatically includes students, and an invitation system with role-based expiring links.

ACLi as a paid capability

A single superadmin-editable settings row controls the paid ACLi feature: whether payment is required, the price, the payment type (one-time, monthly, yearly), the grace period and the currency. The entitlement service reads that same row, so the gate can never disagree with the administrator's intent. The superadmin page at `/superadmin/acli-payment` exposes a toggle, editable price and schedule, and a preview of what the student sees. Entitlement is enforced server-side; showing the button is not authorisation.

Correctness fixes merged from pull requests

- **Google OAuth sign-up failed on a null password** — the sign-up path assumed a password was always present.
- **Student registration crashed for a null organisation** — common on JAMB verification flows where no institution is chosen yet.
- **Concurrent registration produced a duplicate email error** — two simultaneous submissions for the same address collided.
- **The enroll route was missing its courseRef parameter** — the student-facing enroll action could not resolve its target.
- **ACLi feedback referenced a model that did not exist** — the feedback record was written against a class that was never defined.
- **Students verified without an institution received no role at all**, so the superadmin user filter never found them. Students now always receive the student role, and existing rows were backfilled.

Deduplication and content integrity

A course was storing the same chapter twice; the fix enforces uniqueness at the database level rather than in application code. The catalogue runner was refused a retry because `job_code` was unique and already held by the previous attempt — a retry that could never succeed. Chapter bodies are no longer shipped to the browser with the course page; the full text is fetched only when the student asks for it, which removed a twenty-chapter payload from every course view.

5. Quality, verification and testing

The project rule is that a fix is not a fix until it has been demonstrated. This section records what was actually verified and what remains unverified.

Claim	Verification level	Evidence
Chapter coverage of 100%	Production verified	Counted against the production database by grouping chapters per course; minimum is 20, maximum 39, zero placeholders remain
Provider failover works	Integration verified	Dead primary measured failing in 0.51s, chain fell through to the next provider
Chapter start button works with empty content	Production verified	Exercised against a chapter with empty introduction, summary and takeaways
Contact form delivers mail	Production verified	Test message sent through the real Resend SMTP path, delivery confirmed
All HTTP routes serve	Production verified	`/`, `/login`, `/contact`, `/superadmin/login` all return 200
Merged pull requests are sound	Syntax verified	Application routes re-checked after the merge; the full suite was not executed in this session

Known open defects

- **The chapter-body phase is unstarted.** Titles are complete; `introduction`, `summary` and `key_takeaways` remain empty on generated chapters. The Start button degrades gracefully, but the written material the specification calls for does not yet exist.
- **Five pre-existing test failures, unrelated to this month's work.** `CcmcasCurriculumIntegrationTest` inserts an `academic_programs` row with `department_id => 1`, which violates the foreign key to `departments` because no department with that identifier exists. Four `StudentRegistrationCompleteTest` cases fail because `student_registration_verifications.jamb_registration_number` is NOT NULL without a default while the insert omits it. Both predate this work — confirmed by running the same two files with and without this month's change and getting identical results.
- **Assessment content is thin.** Lesson blocks total zero across the platform. The generation path exists and is opt-in, but the material has not been run.

6. Operations, security and deployment

Secrets and configuration

- Provider credentials, database credentials and the Resend key live only in `.env`, which is git-ignored, and in Doppler (project `acl`, config `prd`). The local `.env` has been synced to Doppler so a server move can be provisioned from Doppler rather than from a machine.
- **Credential rotation is required.** Five provider credentials were exposed in chat during this period. They must be rotated before the next deployment. This is the highest-priority outstanding item and it is a human action, not a code change.
- **Deletion and permission discipline.** Newly written files must be `chmod 644`: the write path creates them owner-only, and the web server runs as a different user. A batch of ten files hit exactly this and took the whole application down with a permission-denied fatal until they were fixed.

Mail delivery

Outbound mail works. The application sends through Resend SMTP (`smtp.resend.com:465`) and a test message to the owner's mailbox was confirmed delivered. Inbound mail does not work, and the cause is precise: the domain's MX records point at `mail.aclacademy.me`, but no mail transfer agent listens on port 25 on that host, so anything sent to `support@aclacademy.me` is discarded after the sending server hands it over. The public contact form exists precisely because it routes around this. The fix is a DNS change to Cloudflare Email Routing, which would forward `support@aclacademy.me` to the owner's mailbox without any server work.

Observability

Provider failures are logged as structured warnings naming the provider, the HTTP status, whether the failure was retryable and the upstream message. The logging is what made the dead-end 429 diagnosis possible: the log showed a retryable 429 repeated on a condition that was never retryable.

Production environment

Component	Value
Application URL	https://app.aclacademy.me
Serving path	AWS EC2, Ubuntu, PHP 8.5, behind a remotely-managed Cloudflare Tunnel
Database	TiDB Cloud — `gateway01.eu-central-1.prod.aws.tidbcloud.com:4000`, database `acl`
Cache, queue, session	Redis
Repository	https://github.com/muneercybrid/ACL, branch `main`
Secrets	Doppler — project `acl`, config `prd`

7. How the work was executed

Two approaches to bulk chapter authoring were trialled. The first used subagents, each writing chapter JSON to disk without touching the database. Three of four attempts failed outright — two at a depth limit, one interrupted with no durable result — and workflow rounds returned zero completed agents. The second used the console command directly, calling the provider chain without ACLi chat overhead, entitlement checks or conversation persistence. The second approach was decisively faster and far more reliable, and it is what produced the coverage in section 2. The subagent approach was retained for the part it suited: a supervised authoring stage feeding the same decoupled push.

Throughput under rate limiting

Concurrency was tuned empirically. Twelve to twenty-four workers produced **two to eight chapters per minute**: the workers competed for the same free tier quota and throttled each other. Six workers produced thirty to forty chapters per minute. Eight workers with two healthy providers produced **175 chapters per minute**. More workers was consistently worse.

Repository activity

Measure	Value
Commits in the period	112
Merged pull requests	12
Files changed	327
Human-authored commits	102 (3 bots)
Fix commits	21
Feature commits	11

Merged pull requests

- #19 — Google OAuth sign-up fails with null password
- #20 — Student registration crashes for null organisation
- #21 — Concurrent student registration causes duplicate email error
- #22 — Dependabot: league/flysystem 3.35.2 to 3.36.0
- #23 — Missing courseRef parameter in student course enroll route
- #24 — Dependabot: league/commonmark 2.10.0 to 2.10.3
- #25 — ACLi chat feedback references a model that does not exist
- #26 — Dependabot: npm and yarn multi-package group
- #27 — Dependabot: source-map-js 1.2.1 to 1.2.2

8. Outstanding work

Listed in the order it should be picked up. The first three need a human action outside the codebase.

Priority	Item	Owner	Note
Critical	Rotate five exposed provider credentials	Human	OmniRoute, two OpenRouter keys, Cloudflare and Token Harbor. Rotate at the provider, then update `.env` and Doppler.
High	Write chapter bodies (Phase 2)	Engineering	Introduction, summary and key takeaways for 118,875 chapters, plus quizzes, exercises and flashcards. The generation path exists and is opt-in.
High	Point MX at Cloudflare Email Routing	Human	Replace the two MX records pointing at `mail.aclacademy.me`, add the DKIM record, update SPF, then route `support@aclacademy.me` to the owner mailbox.
Medium	Organisation selection cascade	Engineering	State, federal or private, then a searchable institution list, then organisation login. Requested, never started.
Medium	Fix the failing feature tests	Engineering	`CcmcasCurriculumIntegrationTest` violates the `academic_programs` foreign key to `departments`; four `StudentRegistrationCompleteTest` cases insert without the NOT NULL `jamb_registration_number`. Five failures, all pre-existing.
Medium	Generate assessment content	Engineering	Lesson blocks total zero. The path is built; the run has not happened.
Low	Correct the database README	Engineering	It still describes SQLite and PostgreSQL. ADR-0005 makes MariaDB authoritative; the file was already recorded as an outstanding task.
Low	Correct the onboarding prerequisites	Human	This report states PostgreSQL as the local prerequisite. The authoritative engine is MariaDB per ADR-0005.

Status at the close of this period

The catalogue is complete: all 5,928 courses carry a full twenty-chapter set derived from the national curriculum, with no placeholder chapter left in the database. The provider layer no longer depends on a single provider, and the failure modes that stalled generation twice have been diagnosed and fixed at their root. The next material piece of work is the chapter bodies, which turns the catalogue from a titled outline into studyable material.

ACL — Anyone Can Learn. This report was generated against production on 20 October 2026. All figures are measured, not estimated. Where a claim was not verified, the report says so.