


CAUSAL ATTENTION, N = 1024 · ONE SQUARE PER 32 × 32 TILE · NOTHING N × N WRITTEN DERIVED, NOT WRITTEN

Don’t Write Kernels, Derive Them

Kernels at the Speed of Light, from a Tensor IR of Views and Comprehensions

CAM PEDERSEN · MUNICIPAL ROBOTICS

Abstract

Every fast model today runs on kernels someone wrote by hand, one per operator, per chip and per fusion. Each one freezes choices about what to fuse, where data lives and how threads share work, and those choices are right for one shape on one device. We think kernels should be derived instead.

tang’s tensor IR is built from two constructs. Views are affine maps from an iteration space to tensor coordinates. Comprehensions are reductions under a monoid whose body is a scalar expression graph. Everything else is either a rewrite or a schedule. Fusion is one substitution rule. Nobody writes flash attention. The compiler produces it by recognizing online softmax as a monoid. Gradients of comprehensions are comprehensions, so the same passes derive and optimize the backward pass. That includes a flash-style attention backward that writes no $n \times n$ intermediates on any backend (on tensor cores at full speed, and on WGSL and Metal for now at a cost we report). The concurrent superoptimizers we discuss derive only the forward. Precision and thread mapping are schedule fields that cannot change the math (precision changes only rounding, which we predict), chosen per kernel by measurement on the device.

One graph lowers to WGSL, CUDA tensor cores, Metal simdgroup matrices, OpenCL, GLSL and C, from a datacenter GPU and a desktop GPU and a laptop down to a humanoid robot’s phone-class SoC. On an RTX 3090 a derived transformer block’s forward pass at sequence length 512 runs 1.37× faster than PyTorch with TF32. Qwen3-8B decodes as a single IR graph at 148.7 tok/s, tied with llama.cpp at short context and at 92% of it at 4k. There are no per-operator kernels. The one pattern-specific emitter, CUDA’s flash kernel, matches the online-softmax monoid, not attention. We then derive the kernels of a hand-tuned engine that serves an 80B mixture-of-experts model on one H200. The derived MoE expert layer beats the engine’s hand kernels at every batch size from 1 to 64, and inside the model it is faster from 16 concurrent streams up. The derived head-dim-256 attention and the derived gated-delta scan replace hand kernels in the engine’s prefill, which cuts the time to first token at 44k tokens from 8.33 s to 5.54 s.

Finally, we ask how far a kernel is from the fastest any implementation could be. For a comprehension over affine views, the least memory traffic and the tile that attains it are the primal and dual of one linear program, and we prove weak duality in Lean. A time floor built on that bound, with no fitted constants, is sound on every kernel we measured on two GPUs, tight to 0.82–0.90 of measured time on the RTX 3090, and it shows that small-batch decode on the H200 is not limited by bandwidth. What does limit it remains open: removing launches did not help.

1 Introduction

A modern model has a few dozen distinct operators. A modern framework has thousands of kernels. Every (operator, backend) pair needs one. So does every fusion that pays, such as attention with its softmax, a matmul with its bias and activation, or a norm with the projection after it. FlashAttention[1] is the best-known case. Its large speedup came from rewriting one operator by hand so its $n \times n$ score matrix never reaches memory. Its backward pass took a second hand-written kernel. Hopper took a third[2], and Blackwell's FP4 tensor cores are taking a fourth.

Each hand kernel is a separate copy of the same arithmetic, and each one freezes a schedule that was right for one shape on one device. We measured how often that schedule is wrong: the fastest schedule changes with the size, the chip and even between runs on the same machine (§7.1). The winning schedule is a property of the graph, the chip and the size, not of the operator.

Our thesis is that **a kernel is a theorem, not a program**. Every fast kernel we know of is a claim of the form "this comprehension, reassociated under this monoid and placed in this memory, equals the naive one." Such a claim can be derived, checked and searched. It does not need to be written. It can also be bounded: the least traffic any schedule of a comprehension can move, and the tile that moves it, are dual solutions of one linear program. If that is right, the kernel library should be replaced by an algebra small enough to reason about, together with a search over its schedules. Figure 1 shows one graph under the schedules that the field knows by name.

SCHEDULE	S LIVES	P LIVES	KERNELS	$n \times n$	HBM	MS	SPEEDUP
as written	HBM	HBM	11	5	815.9 MB	7.75	1×
checkpointing	HBM	recomputed	5	1	274.8 MB	13.4	0.58×
flash (FA2-style)	registers	registers	1	0	4.2 MB	5.99	1.29×
searched	shared mem.	recomputed	5	1	274.8 MB	1.8	4.3×

FIG 1 One causal attention graph ($n = 4096$, $d = 64$, RTX 3090) under four schedules. Only where $S = qk^\top$ and $P = \mathrm{softmax}(S)$ live, and where kernels end, differ. FlashAttention-2 and checkpointing are points in this space. The search keeps S in shared memory and recomputes P, 3.3× faster than the flash schedule on this chip. Measured; the web edition makes the figure interactive.

We propose writing the model once, as math, and letting the compiler derive every kernel. That works only if the IR is small enough to reason about and expressive enough that nothing important falls outside it. tang is a `no_std` Rust library that started as a geometry and physics math crate. Its `tang-expr` crate traces Rust closures into scalar expression graphs that it can differentiate, simplify and compile, and its tensor IR uses those graphs as its body language. The IR has two constructs.

- **Views**: affine index maps that express broadcast, transpose, slicing, striding, padding and per-head column selection without touching memory.
- **Comprehensions**: $\mathrm{out}[i] = \oplus_k \, \mathrm{body}(x_0[v_0(i,k)], x_1[v_1(i,k)], \ldots)$, where body is a scalar expression graph and $\oplus$ is a monoid.

Contributions:

1. **Kernels from rewrites.** Fusion, flash attention, logsumexp and Welford variance are instances of two general rewrites (§2).
2. **Derived backward passes.** Reverse-mode differentiation maps comprehensions to comprehensions, including the online-softmax monoid. A proof procedure removes the stabilizing max’s gradient, and with nested contractions this yields an attention backward with no $n \times n$ tensors (§3).
3. **Precision as a schedule.** An emulating interpreter predicts the error of a format choice before it runs (§4).
4. **One graph, six targets.** Lowerings from shared emitters, measured against hand kernels, PyTorch and the bandwidth limit on four chips (§5, §7).
5. **A production engine, derived.** Top-k routing as one monoid, integer tensor-core and narrow GEMV schedules, a segmented-sum gather backward, chunked scans, and Hopper attention schedules. With them, derived kernels replace hand kernels in an 80B MoE engine on an H200 (§8, §11).
6. **The speed of light.** The traffic lower bound and the optimal tile are dual solutions of one linear program read off a kernel’s views, with weak duality in Lean. A time floor built on it, with no fitted constants, is sound on every measured kernel on two GPUs (§9).

2 The IR

2.1 Views

A view maps a point of an iteration space to a source tensor’s coordinates with one affine form per source dimension, offset $+ \sum_j c_j \cdot \text{idx}_j$. Broadcast is a zero form, transpose a permutation, slice an offset, stride a coefficient. A form with two terms expresses “head h reads columns $64h + 2i$”. Views compose by substitution. They are the only way a comprehension reads its inputs, so every layout decision is a view and every view can be analyzed.

A view may be guarded, so that an out-of-range read returns the monoid’s identity (zero for sum, $-\infty$ for max) rather than raising a shape error. Padded, dilated and transposed (polyphase) convolutions and overlap-add are guarded reads, with no padding operator. The adjoint of a guarded read is itself a guarded read, not a scatter. For $y[o, t] = \sum_{c,k} w[o, c, k] x[c, t + 3k - 9]$, $\partial x[c, \tau]$ reads $\partial y[o, \tau - 3k + 9]$ through the same guard, so out-of-range (padding) terms never reach x.

Grouped-query attention’s head / heads_per_group is not affine. The IR expresses heads as two dimensions, [groups, per_group], and the views do the rest. Dimensions can be fixed or symbolic (`Dim::Sym("seq")`). Construction, rewriting and differentiation work with symbols, and `bind` makes them concrete for scheduling and lowering.

A view may also gather. One source coordinate is then data, read from an index tensor that is a sibling argument of the same comprehension, form $+ c \cdot \text{round}(\text{idx})$. MoE routing ($W[\text{sel}[t, k]]$), paged KV caches ($b_s \cdot \text{table}[\text{blk}] + \text{off}$) and embedding lookups become ordinary reads rather than special operators. The gradient of a

gathered read is a scatter-add, written as a dense gated sum. An affine map read through a gather still fuses into it, and only nested gathers materialize.

2.2 Comprehensions and monoids

The only compute operation is

$$\text{out}[i_1, ..., i_p] = \bigoplus_{k_1,...,k_r} \text{body}(x_0[v_0(i,k)], ..., x_m[v_m(i,k)])$$

A map is a comprehension with no reduce dimensions. Sum and max are monoids. Matmul is $\sum_k a[i,k]b[k,j]$. Attention scores, convolution and gather are the same operation with different views. The monoid’s `combine` is itself a scalar graph, and a comprehension may carry tuple-valued state. Online softmax is the monoid on (m, l, acc); arg-max is the monoid on $(\text{index}, \text{value})$.

2.3 Rewrites

Fusion is one rule. A map is a pure function of its inputs, so `substitute_maps` splices its body into every consumer and composes the views. Map→map, map→reduce and transpose→anything are the same case. The rule is cost-aware, so a map is recomputed inside a reduction only when it is cheap. Reductions are never substituted. They are inlined by a schedule decision, which separates algebra from scheduling. A row-major reshape that only merges dimensions is a view, not a copy.

Epilogues run on the reducing thread. A map that reads a reduction point for point (a bias, an activation, the acc $/l$ that finishes softmax) runs on the thread that holds the final accumulator.

Sibling reductions merge. Two reductions over the same space and monoid with the same readers become one reduction under the product monoid (`merge_siblings`). The gate and up projections of a SwiGLU MLP become one tuple-valued matmul, the activation becomes its epilogue, and the normalized input is read once.

Flash attention is a rewrite. `stabilize_softmax` finds $m = \max_j s_j$ and every $\sum_j g \cdot \exp(s_j - m)$ over the same canonical s, with masks and scales allowed, and replaces them with one reduction under the online-softmax monoid. The value column of $\sum_j p_j v_j$ becomes a point dimension of the fused comprehension. Nothing $n \times n$ is materialized. Logsumexp, Welford variance and top-k are the same rewrite with different monoids. Figure 2 shows the attention case.




FIG 2 The rewrite that derives flash attention, schematically (the lab's typed graph also carries mask and scale maps, so the §2.3 counts are higher). The naive graph writes the scores and probabilities as $n \times n$ buffers (dashed). Fusion splices the maps into their readers; `stabilize_softmax` merges the max and both exponential sums into one reduction whose state is (m, l, acc). No attention-specific code is involved; scheduling then finds the tiled kernel.

The rewrite is not specific to plain attention. Anything that changes the score or the mask leaves the monoid structure alone, so it derives the same way. Table 1 lists six variants the compiler derives.[1]

TABLE 1 Six attention variants as typed into the lab, $n = 1024$, $d = 64$. Each cell is kernels · $n \times n$ buffers, as written → derived (WGSL). The forward always becomes one kernel with nothing $n \times n$; with nested contractions (§3) the backward also writes nothing $n \times n$, in 7 kernels. Generated by `tang-derive-wasm`'s `gallery` example.

VARIANT	SCORE	MASK	FWD KERNELS · N×N	FWD+BWD KERNELS · N×N
Causal	`s`	`j <= i`	11 · 5 → **1 · 0**	30 · 11 → **7 · 0**
Sliding window	`s`	`j <= i && i - j < 128`	11 · 5 → **1 · 0**	30 · 11 → **7 · 0**
ALiBi	`s - 0.0625*(i - j)`	`j <= i`	11 · 5 → **1 · 0**	30 · 11 → **7 · 0**
Soft cap	`30*tanh(s/30)`	`j <= i`	11 · 5 → **1 · 0**	30 · 11 → **7 · 0**
Prefix LM	`s`	`j <= i || j < 64`	11 · 5 → **1 · 0**	30 · 11 → **7 · 0**
Bidirectional	`s`	—	10 · 4 → **1 · 0**	28 · 9 → **7 · 0**

2.4 Rediscoveries

The rewrites above are general, so known algorithms fall out of them. Table 2 lists the ones tang derives today. Each row was a paper or a hand kernel. In tang each is a monoid, a view or a schedule field, and none adds an operator.

2.5 Schedules

A comprehension says what to compute. Schedule fields say how, and they cannot change the math (precision changes rounding, §4):

- `inline`: recompute inside the consumer instead of writing a buffer.

[1] The web edition derives these in the reader's browser and runs them through WebGPU: muni.works/research/tang.

TABLE 2 Algorithms that tang derives rather than implements. Each derivation is checked against the f64 interpreter of the naive graph.

ALGORITHM	ORIGINALLY	IN TANG
online softmax	Milakov & Gimelshein 2018[3]	monoid on (m, l)
FlashAttention forward	Dao et al. 2022[1]	`stabilize_softmax` + staging rule
FlashAttention backward	hand kernel[1]	derived gradient, max elimination, nested contractions (§3)
Welford variance	Welford 1962[4]	monoid on (n, μ, M_2)
logsumexp, arg-max	folklore	monoids on (m, l) and (index, value)
top-k routing	hand kernel	`Monoid::topk`, merge of sorted lists
split-K GEMM	hand kernel	`split` on any associative monoid
SwiGLU gate|up fusion	hand kernel	`merge_siblings` under a product monoid
implicit-GEMM convolution	hand kernel	guarded views, flattened reduce dims
paged KV cache	vLLM	gather view
scatter-add backward, segmented	hand kernel	gated sum + `set_sorted` segment (§8)
chunked SSD / gated delta rule	Dao & Gu 2024[5]; Yang et al. 2025[6]	affine scan monoid + chunked plan (§8)

- `split`: one workgroup per point, with threads striding the reduce space and tree-combining. This is valid for any monoid because combine is associative, including online softmax.
- `tile`, `tile_2d`: blocks of threads, each owning a register tile of points. The emitter tracks every address as an affine form over loop variables. Anything that does not depend on the lane axis is staged in workgroup memory once per reduce chunk. That covers buffer reads (K and V tiles, matmul operand tiles) and inlined sub-computations (the $q \cdot k$ scores).
- `precision`: storage and accumulation formats (§4).

`schedule_auto` encodes rules of thumb distilled from measurement. `autotune_kernels` times each candidate mapping per materialized node on the device, using the graph's real inputs, and caches the winner by device and kernel source. With substitution and the online-softmax rewrite, the staging rule produces the structure of flash attention: rows × lanes per workgroup, cooperative score tiles, and online softmax in registers.

3 Gradients are comprehensions

For $y = \oplus_k \text{body}(x[v(i,k)])$, the gradient with respect to x through a pick view (one whose forms are each a single coordinate) is found by renaming coordinates. The coordinates that v picks become x's output dimensions, the rest become reduce dimensions, and every other view is pushed through the same renaming. The body is differentiated by `tang-expr`'s symbolic `diff`, which covers its nine arithmetic

operations (add, multiply, negate, reciprocal, square root, sine, atan2, 2^x, $\log_2$) plus a select. A dimension read through any other form (an offset, stride, diagonal or broadcast) stays an output dimension, and `iota`, a node that turns coordinates into values, gates the body by $[c = \text{form}]$. Max gates its term to the arg-max. The backward graph is an ordinary graph, so the same passes optimize it. Rotary embedding and GQA gradients come from the gated scatter with no special handling.

The online-softmax monoid has its own rule. With the forward's m and accumulators read back, $\partial \text{acc}_i / \partial s_{ij} = g_j \exp(s_{ij} - m_i) - \text{acc}_i \, [s_{ij} = m_i]$, where g_j is key j's value, so the flash-fused graph differentiates and its gradients equal the naive graph's.

A stabilizing max has no gradient. Softmax is invariant to shifting its scores, so the $[s = m]$ terms sum to zero, but only in exact arithmetic. While those terms exist, the max must be materialized and masked tiles cannot be skipped. `backward` drops them when it can prove the loss does not depend on m. The proof tracks how each node downstream of m scales with $t = \exp(-m)$. In softmax, $p_j = \exp(s_j - m) = t \cdot \exp(s_j)$ has degree 1 in t, so does $l = \sum_j p_j$, and so does $\text{acc} = \sum_j p_j v_j$; their ratio $o = \text{acc} \ / l$ has degree 0, a function of the scores alone. In general a node is either $t^k h$ or $a + \kappa m$ with h, a free of m, combined by exact identities.[2] If every path from m ends at a degree-0 node, $\partial L / \partial m \equiv 0$ and the gradient is not built. The f64 evaluation of a training step is unchanged (largest absolute difference 2.7×10^{-19}).

The flash backward recomputes inside tiles. `hoist_invariant_factors` factors row-invariant terms out of sums ($\sum_c \tilde{P} \cdot \text{dO} \cdot V \to \tilde{P} \cdot \sum_c \text{dO} \cdot V$). `schedule_nested_contractions` then inlines a short contraction (one reduce dimension of at most 128) into every tile that reads it. The attention backward reads $S = QK^\top$ and $\text{dP} = \text{dO} \ V^\top$ only through $\tilde{P}$ and dS, which the dQ, dK and dV tiles recompute per staged block on tensor cores. On CUDA this removed S, $\tilde{P}$, dP, the max over S and three correction kernels from a transformer training step, reducing 63 kernels to 49 and the summed best-per-kernel time from 1.80 to 1.22 ms at sequence length 512 (RTX 3090). WGSL and Metal now nest the same contractions with scalar dot products in workgroup memory, so no GPU backend we measured (CUDA, WGSL, Metal) writes anything $n \times n$. For now this costs speed. Forward plus backward runs at 0.64–0.78× the materialized schedule on Metal and 0.22–0.27× under Vulkan on a 3090, until the nested dots are register-blocked the way the `mma` path blocks them.

[2] $t^a t^b = t^{a+b}$; $\sum_j t h_j = t \sum_j h_j$ when t's row does not depend on j; $2^{a+\kappa m} = 2^a t^{-\kappa \ln 2}$.




FIG 3 The attention backward of a training step, before and after. Before, the scores, probabilities and dP are written as $n \times n$ buffers (dashed) and read by three gradient tiles. After the stabilizing max loses its gradient and invariant factors leave the sums, the short contractions S and dP are recomputed per staged block inside each tile, on tensor cores. CUDA, RTX 3090, seq 512; summed best-per-kernel times.

4 Precision is a schedule

f16 is a different way to run the same program, not a different program. Each node has a storage format, applied where a value is written to memory, and an accumulation format, applied to a reduction's running state after each combine. The graph stays exact math.

The interpreter predicts the error. `eval` is pure f64. `eval_emulated` rounds every stored value and every accumulator step to its scheduled format (round to nearest even, subnormals, overflow), with body arithmetic in f64. An `ErrorBudget` accepts or rejects a schedule before it runs. Emulation matches the GPU's f16 kernels to 1 ulp when the reduction order is the same. Otherwise the order is part of the error: AdaIN's variance over $T = 2000$ with an f16 accumulator has error 2.8×10^{-4} under a 256-thread split and 1.3×10^{-2} with one thread per row, while the sequential emulation predicts 7.9×10^{-3}. Emulation models one sequential fold; a tree-combining split beats it, and the per-row GPU kernel, though also sequential, comes out somewhat worse, which we attribute to its different accumulation order and fused arithmetic rather than having verified it. `tune_precision` lowers buffers to half precision one move at a time and keeps a move only if the program stays within budget and gets faster.

5 Lowering

Shared emitters produce the point, split and tiled schedules, register tiles, guarded views, epilogue fusion and tuple monoids once. A dialect switch then handles buffer access and surface syntax.

- **WGSL** (portable default, through wgpu on Metal, Vulkan and DX12). f16 storage is packed two per `u32`, because wgpu's shader compiler (naga) rejected `enable f16` on our targets.

- **CUDA.** Matmul-shaped tiles run on `mma.sync` (TF32 m16n8k8, or f16/bf16 m16n8k16 when the operands are half precision) with `cp.async` staging rings. Block shapes are tuning candidates. `cuda_flash_kernel` recognizes the online-softmax comprehension and keeps O, the row max and the partial sums in `mma` registers. The score accumulator is reused as the A operand of $O += PV$ after permuting keys within each 8-wide step, which is legal because the reduction is commutative and associative.
- **Metal (MSL).** Native `half` and `bfloat`. Contractions with f16 operands run on `simdgroup_half8x8` fragments. Reduce dimensions are flattened, so convolution becomes implicit GEMM, with dilated inputs staged once per chunk as a zero-padded, phase-de-interleaved window.
- **OpenCL and GLSL** for Adreno GPUs that have neither CUDA nor Metal. On one Adreno driver, WGSL is routed through GLSL because the direct SPIR-V path was miscompiled.
- **C**, for batch-1 control loops where a GPU round trip costs more than the arithmetic. A comprehension already is a loop nest, so `to_c` emits it directly with a vectorizable innermost point dimension, and `tang_run()` performs no allocation.

`Program::tuned` times each kernel's native lowering against the portable one and keeps the faster. Kernel sources are canonicalized, so the same kernel at another layer is the same string and compiles once.

6 Verification

Speed claims depend on every kernel being correct. `tang-verify` runs each GPU kernel against its CPU oracle on the same input, starting from the device's own state. Before each kernel runs, it fills the kernel's outputs with NaN, so unwritten memory cannot pass as a plausible 0. When a check fails, it names the kernel at fault by provenance: which earlier kernel's correct output the failing buffer contains. We built it after four structural bugs in a hand-written engine slipped past every unit test. One was a byte offset added where a float offset was meant, which wrote k's values over q. Derived kernels are less exposed to that class of bug, because addresses come from affine forms rather than pointer arithmetic. On the IR path there is a second check, because the f64 interpreter runs the same graph as the GPU.

7 Evaluation

Setup. Apple M4 Max (Metal), NVIDIA RTX 3090 (Vulkan and CUDA 12), a Qualcomm QCS8550 in a Booster K1 humanoid robot (Adreno 740, Cortex-X3), and, for §8, an NVIDIA H200. PyTorch 2.10 + cu128 with CUDA events. Unless stated otherwise, tang times are kernel-only. Several runs shared the GPU with other tenants. We mark those, and report minima rather than means, because contention only adds time. Every derived result is checked against an f64 interpreter; agreement is 10^{-6} to 10^{-4} relative, depending on format.

7.1 Derived vs hand-written kernels

tang shipped hand-written WGSL kernels before the IR existed, which makes a controlled comparison possible: same runtime, same chip, same inputs. Here "as written" is the unfused graph, one kernel per comprehension; "derived" is any schedule the compiler produces, and the autotuner keeps the as-written graph's naive schedule as one candidate, which is why it can win. On the M4 Max the fastest schedule for causal attention flipped between two runs of the same code: in one run $n = 512$ was fastest naive (n^2 threads) and $n = 1024$ tiled, and Table 3, a later run, has the reverse. The naive graph wins when its scores fit in cache and parallelism, not bandwidth, is the bottleneck, which depends on the size and the machine's power state. A 16×16 shared-memory matmul tile wins at $128 \times 576 \times 1536$ and loses at 1024^2, and rules of thumb tuned on the M4 picked the wrong matmul schedule on an RTX 3090. Table 3 is one consistent run on the M4 Max, including about 1.8 ms of submit and readback per measurement.

TABLE 3 Hand-written vs derived on M4 Max (Metal via WGSL). Every time includes about 1.8 ms of submit and readback, which dominates the small ops. The hand training step ran its attention backward on the CPU, since no GPU version existed, so that row shows coverage, not kernel quality.

OP	HAND	DERIVED	SCHEDULE
causal attention $n = 1024$	10.9 ms	**3.31**	naive (n^2 threads)
causal attention $n = 512$	4.91	**2.02**	auto (tiled)
matmul 1024^2	6.68	5.49	auto
rmsnorm 2048^2	2.52	2.70	split
transformer block, seq 512	23.9	**10.1**	per-kernel autotune
decode block, q 1 / kv 1024	8.80	**3.28**	per-kernel autotune
training step, seq 128	179	**7.96**	auto

Every hand kernel is beaten or matched to within 7% (rmsnorm), leaving aside the training step. The schedules that win differ across operators and sizes. On the 3090 under Vulkan, the derived transformer block first lost to the hand path. Three chip-agnostic fixes followed: cost-aware substitution, keeping reductions schedulable under their epilogues, and a bank-conflict-free tile layout. After them, the autotuned block won there too (2.5 vs 3.1 ms at seq 128, 6.2 vs 10.4 ms at seq 512, both including about 1.25 ms of submit and readback).

Figure 4 shows the same thing through WebGPU in a browser on the M4 Max. At $n = 1024$ the graph as written beats every fused schedule, and the fused schedules alone span 29× by thread mapping. A compiler that fixed one schedule would be wrong somewhere, so tang times the candidates and keeps the winner.




FIG 4 Causal attention, $n = 1024$, $d = 64$: the schedules the web edition’s derive lab (§2.3) timed through WebGPU in Chrome on an M4 Max (2026-11-06, log scale). Red: the graph as written. All outputs match the f64 interpreter to 1.3×10^{-7} (checked at $n = 128$).

7.2 Against PyTorch

Table 4 tracks a 9-head GQA transformer block ($d = 576$, ff $= 1536$, rotary embeddings, SwiGLU) on the RTX 3090 as the backends matured. Through WGSL, which has no access to tensor cores, derived kernels stayed 2.6–7× behind PyTorch. With the CUDA lowering, flash attention on `mma.sync` and the backward passes of §3, the forward block passes PyTorch (Figure 5).

TABLE 4 Transformer block on the RTX 3090. The CUDA column and PyTorch were measured in interleaved rounds under `flock`, best of six; times in ms; PyTorch’s 4-layer step uses fused AdamW. The WGSL columns come from earlier runs and are shown to make the trajectory visible.

BLOCK, SEQ	WGSL FIRST	WGSL FUSED	CUDA NOW	TORCH FP32/TF32
fwd 128	1.97	1.06	**0.178**	0.306 / 0.286
fwd 512	4.41	3.34	**0.328**	0.602 / 0.449
fwd+bwd 128	5.0	3.15	**0.552**	1.196 / —
fwd+bwd 512	10.1	8.19	**1.467**	1.719 / —
4 layers, step 128	—	—	**3.92**	4.40

On the CUDA path, the derived inference attention kernel alone is 0.032 ms at seq 512, down from 0.178 ms before the `mma.sync` rewrite. The seq-512 forward block is 1.37× faster than PyTorch with TF32. Forward plus backward runs 2.2× faster than PyTorch fp32 at seq 128 and 1.17× at seq 512, and a four-layer training step 1.12× faster than PyTorch with fused AdamW. We do not claim a general win over cuBLAS: a lone 1024^2 matmul on the derived CUDA TF32 tile takes 0.150 ms against cuBLAS TF32′s 0.079 ms, 1.9× slower. The gain comes from fusion across operator boundaries that a library of separately tuned operators cannot do.




FIG 5 Transformer block forward, seq 512, RTX 3090, log scale. The same derived graph under three generations of lowering; only the last reaches tensor cores. Dashed: PyTorch with TF32.

7.3 Attention variants against FlexAttention and FA2

We ran the six attention variants from §2.3 on the RTX 3090 against FlexAttention[7] (`torch.compile`, fp32 with TF32 and bf16) and FlashAttention-2 in bf16 where it supports the mask. Flashlight and EqiForge publish no code. Every row was checked against an f64 reference; tang is pure fp32 or TF32.

TABLE 5 Attention variants on an RTX 3090 (shared; small rows carry up to ±2× noise). FA2 runs only causal and bidirectional masks. The full sweep, d = 64 and 128 with n from 1k to 8k, is in the repository.

D = 64 UNLESS NOTED, MS	TANG	FLEX FP32	FLEX BF16	FA2 BF16
soft cap, fwd, n = 2k	**0.075**	0.254	0.172	—
ALiBi, fwd, n = 2k	**0.060**	0.171	0.094	—
causal, fwd, n = 2k	0.060	0.171	0.090	**0.023**
causal, fwd, n = 8k	0.888	0.635	0.326	**0.177**
sliding window 128, fwd, n = 8k	0.911	0.037	**0.034**	—
causal, fwd + bwd, n = 4k	1.81	0.968	**0.420**	0.469
causal, fwd, n = 4k, d = 128	17.1	fails	0.318	**0.112**

Where a variant changes the score (soft cap, ALiBi), the derived forward is up to 3.4× faster than FlexAttention in fp32 up to $n = 4$k and beats it in bf16 up to $n = 2$k (the low end of that range is within the noise of a shared GPU), because the score modifier becomes part of the fused body. tang loses in three places, each a missing schedule rather than missing algebra. FA2 runs bf16 tensor cores where tang’s tile is TF32. A sliding window is 25× slower because tang computes masked tiles that FlexAttention’s block mask skips. And at $d = 128$ no tensor-core tile is chosen for the forward. From $n = 2$k the backward is 2.5–7× behind FlexAttention bf16, and 50× with a sliding window.

7.4 A whole model as one graph

Qwen3-8B with MLX 4-bit weights runs as one IR graph per decode step, lowered by `to_cuda_decode` into 584 kernels and captured as a CUDA graph. Nibble unpacking and the $q \cdot s + b$ dequantization are a map the GEMV reads. That map is inlined and evaluated in registers as weights stream in. Figure 6 shows the graph.




FIG 6 One Qwen3-8B decode step as a single IR graph. Top: the step, from the token in `state` to the arg-max written back. Bottom: one of the 36 identical layers. Times are each node's share of the 4k-context step on the 3090 (Figure 7), summed over layers. The lowering emits 584 kernels for the whole step, captured as one CUDA graph. Times are from the first build (Figure 7).

The KV-cache update is a `select` over a runtime position, which the lowering turns into loop bounds, so a step touches only live cache rows. Table 6 compares it with llama.cpp on the same card, run back to back on the same weights. The model's greedy output matches an exact f32 reference token for token.

TABLE 6 Decode, one stream. llama.cpp runs `llama-bench -n 128 -fa on` on a Q4_0 GGUF of the same weights. Teacher-forced on 31 greedy tokens against an exactly dequantized f32 CPU reference: 31/31 arg-max agreement.

QWEN3-8B, 3090	SHORT CTX	1K CTX	4K CTX
speed of light (936 GB/s)	220 tok/s	—	192 tok/s
llama.cpp, Q4_0 GGUF	149.4	145.3	134.9
tang IR, device step	**148.7**	**141.4**	**124.2**
tang IR, first build (shared GPU)	122	—	104

Every change between the first build and the current one is a schedule or a lowering rule, not a kernel; the appendix lists them.




FIG 7 Where a Qwen3-8B decode step went at 4k context in the first build: the sum of isolated kernel launches (10.3 ms; the captured graph ran in 9.6). The current build takes 8.05 ms. Dashed: the time to stream the weights and KV cache once at 936 GB/s.

The same graph builder lowers to Metal. There, prefill and decode programs share one copy of the weights through buffer binding, prefill can start from a nonzero offset (300 + 200 tokens is bit-identical to 500), and the next token is chosen on the device by an arg-max monoid, so decoding reads back 8 bytes per token.

7.5 Data-dependent addressing

A top-k MoE FFN builds as one graph: router GEMM, top-k, softmax weights, SwiGLU experts reading $W[\text{sel}[t,k]]$ through gather views, then the weighted combine. Top-k is exact, and outputs match the f64 interpreter to 4×10^{-6} on Metal and 4×10^{-5} on CUDA (the router runs as a TF32 tile).

TABLE 7 Top-k MoE at T = 8 tokens, D = 2048, E = 128 experts, k = 10, F = 512 (1 GB of weight reads). The data-dependent address costs nothing against the same expert math over weights gathered into contiguous buffers beforehand. The gathered graph is even faster; we have not isolated why, and do not claim the gap. 378 GB/s is 40% of the 3090's peak: per-point GEMV reads are uncoalesced. §8 adds the narrow GEMV schedule for gathered contractions.

EXPERT GEMMS + COMBINE	M4 MAX	RTX 3090 (CUDA)
gathered (one graph)	**2.17 ms** (464 GB/s)	**2.66 ms** (378 GB/s)
weights pre-gathered on the host, tiled	2.89	3.55
weights pre-gathered, one thread per point	2.91	3.77

7.6 Edge hardware

On the K1's Adreno 740, a derived matmul reaches 322 GFLOP/s at 1024^3, which is 21% of the measured fp32 peak, and a full transformer forward pass plus all seven weight gradients at seq 128 runs in 19.1 ms. Rules tuned for desktop GPUs underfill the Adreno's six compute units. The best schedule there (an 8×8 register tile with 8-deep chunks) is 1.45× better than `schedule_auto`'s choice, which again argues for search over remembered rules. Through `to_c` on one Cortex-X3 core, a batch-1 GRU policy step (6 contractions plus gate math, fused into one kernel) takes 22.5 µs median and a locomotion MLP takes 6.7 µs, both within 6×10^{-7} of f64.

8 Deriving a production engine

Every kernel in the sections above is derived. To show where derivation has to go next, we report the other half of tang: the hand-written serving engine in `tang-llm`, called Flash, which serves Qwen3-Coder-Next (80B parameters, 3B active, 4-bit GGUF) on one NVIDIA H200 with kernels written by hand. Table 8's numbers are not results of the IR; they are the target it has to reach.

TABLE 8 The target: tang-llm on a dedicated H200 (tang-llm commit `fcfbb9d7`). Its MoE layers run a hand-written int8 tensor-core kernel that reads activations in B-fragment order, which cut the B = 64 step from 38.9 to 35.2 ms. Lossless speculation uses a trained MTP head (3.15 tokens per window).

H200, QWEN3-CODER-NEXT 80B-A3B	MEASURED
single-stream decode, no drafting	234 tok/s
with speculative drafting (MTP / suffix)	319–439 tok/s
prefill, 1k → 8k tokens	6,574 → 7,548 tok/s
batched decode step, B = 64	1,814 tok/s
serving, 64 concurrent decode-heavy streams	1,279 tok/s
serving at 64k context, batch 48 (production shape)	1,155 tok/s

The hand engine also shows why the contract matters. Ported to GLM-5.3, the same MoE kernel is correct but 1–2.5× slower than the engine's generic path below 64

tokens per expert and only 8–20% faster at 64. A kernel tuned for one model’s expert shapes is a point in the schedule space, and on the next model it is the wrong point. It is one data point, but from a production engine, and it is §1′s claim.

Deriving this engine needed constructs the IR lacked: a gather view for routing tokens to experts, integer tensor-core fragments with fused dequantization, a top-k reduction, scans, and Hopper’s asynchronous copies and warpgroup MMA as schedule fields. Each now exists, and each replaced hand kernels in the engine, measured against them on the same bytes.

8.1 The MoE layer

One full MoE layer of the engine builds as a single graph: router, top-k, expert-sorted gather, the gate|up and down expert GEMMs on GGUF Q4_K/Q5_K weights, SwiGLU and the weighted combine. The int8 path uses schedule fields only: GGUF blocks as an input storage format, int8 activations quantized by their writer, and an `IntMma` field that stages activations in fragment order for `m16n8k32` tensor cores. There is no new operator.

Routing is one reduction. `Monoid::topk(k)` keeps the k best (index, value) pairs, sorted, with ties to the smaller index. Its combine is a merge of two sorted lists ($k^2/2$ compare-selects), which is associative, so split and subgroup trees give the same answer. Top-10 over 512 experts is one 0.013 ms kernel where k arg-max rounds took 0.23 ms, and a whole layer at batch 1 drops from 32 kernels and 0.199 ms to 13 kernels and 0.103 ms.

Batch 1 needs a different schedule. `Stage::Gemv` computes one dot per (position, row) on `dp4a`, with 16-byte loads of half super-blocks and partial sums combined by shuffles. Its producers fuse: the $x \to$ Q8 and SwiGLU $\to$ Q8 nodes are marked inline, and the GEMV computes and quantizes its operand row into shared memory in its prologue, rounding exactly as the writer did.

TABLE 9 One Qwen3-Coder-Next MoE layer (hidden 2048, 512 experts, top-10, FFN 512), derived vs the engine’s own kernels on the same bytes, on an idle H200. Medians of 100 launches with L2 flushed. Outputs agree to 3×10^{-7} and top-k is exact. Batch 1 and 4 use the fused GEMV stage; 8 and 64 the int8 MMA. The engine’s combine also adds the residual and runs the next norm, so its column includes work ours does not. Weights are random valid k-quant blocks.

EXPERT HALF OF ONE LAYER, H200	DERIVED FROM THE IR	ENGINE, HAND-WRITTEN
batch 1	**0.036 ms**	0.044 ms
batch 4	**0.076**	0.086
batch 8	**0.099**	0.126
batch 64	**0.269**	0.336
batch 64, gate|up / down	**0.158** / **0.089**	0.180 / 0.124

Fragment-order staging alone is worth about 20% on gate|up at batch 64. The hand MoE kernels took a dedicated tuning effort to push past a floor of about 2 TB/s. The derived ones are a schedule search.

The backward of a gathered contraction was dense: every expert’s weight gradient summed over every pair under a $[\text{key} = e]$ gate, E times the needed work. Declaring

the key index sorted (`set_sorted`) tags that reduction with a segment, and the point loop binary-searches each key's run and sums only over it. The gate stays in the body, so a lowering that ignores the tag is still correct. The expert-weight gradient (E = 512) drops from 8.27 to 3.89 ms on the H200, 16.3 to 2.67 ms on the 3090 and 39.7 to 2.65 ms on the M4, with identical error.

8.2 Attention and scans in prefill

The engine's model alternates gated-delta (GDN) layers with full attention at head dimension 256, and prefill is where both cost. At $d = 256$ the old schedule left the online-softmax reduction untiled, and the score stayed an $n \times n$ buffer at 2.8 TFLOP/s. Allowing the tile up to 256 lanes lets the score inline, and the Hopper flash shape takes over without a line of attention-specific code (Table 10).

TABLE 10 TFLOP/s, bf16, 16k tokens per configuration, against PyTorch SDPA on the same idle H200; rel. error 2–3 $\times$ 10^{-3} against f64.

$d = 256$ FORWARD, H200	N = 1K	4K	16K
tang, non-causal	**318**	**398**	**422**
SDPA, non-causal	306	323	318
tang, causal	220	**310**	**391**
SDPA, causal	**251**	285	295

Gated delta rules, Mamba-2's SSD and linear attention are associative scans over an affine monoid on a matrix state. A `delta_scan` comprehension lowers by a chunked plan: a WY transform per chunk, a sequential state scan, and a parallel readout. Its backward is the derived reverse scan at chunk granularity. On the 3090 it matches fla's Triton kernels within 6% forward and beats mamba_ssm's SSD forward 1.3–1.8×. Against the engine's hand recurrence (a warp per state column, token by token), the chunked scan is 4.0–4.3× faster on the H200 and 2.1× on the 3090.

Both went into the engine behind switches, gated on the engine's own accuracy checks: KL divergence against the reference at 3k and 8k tokens with int8 and bf16 KV caches, equal greedy output, bitwise-identical batched decode, and a cached-prefix continuation equal to a cold one.

TABLE 11 Time to first token with the int8 KV cache, warm. The derived attention alone cuts attention's GPU time over two 45k prefills from 5,566 to 1,107 ms. With the bf16 KV cache the derived attention takes 45k prefill from 6.67 to 5.79 s.

QWEN3-CODER-NEXT PREFILL, H200	TTFT, 44K TOKENS	8K TOKENS
engine, hand kernels	8.33 s	7,300 tok/s
1 derived GDN scan	7.70 s	8,200 tok/s
1 derived $d = 256$ attention	6.17 s	—
1 both	**5.54 s**	—

8.3 Attention backward on Hopper

Training needs the backward. The derived attention backward was nine kernels that round-tripped P and dS through memory, at 13–25 TFLOP/s. A lowering now recognizes the pattern the gradient pass produces (a tuple reduction over queries

whose operands are pointwise maps of two short contractions) and emits one kernel per key block. dK and dV stay in registers, and dQ is added with Hopper’s bulk asynchronous reduce. Variants on `mma.sync`, on `wgmma` with two consumer warpgroups, and with a producer warpgroup are all derived from the same match, and the autotuner picks per shape. The fused kernel reaches 0.81–0.96× of SDPA’s backward at $d = 128$ and 0.79–1.03× at $d = 256$, and the whole program is 4–8× faster than the nine kernels.

8.4 The derived MoE in the model

A layer that wins in isolation still has to win inside the model. Behind a switch, the derived MoE replaces the engine’s expert kernels in every layer of Qwen3-Coder-Next. It passes all of the engine’s accuracy checks. Getting there exposed one numerical choice: a block-split sum of squares in RMSNorm, split 256 ways, pushed the KL divergence at 3k tokens to 2.8×10^{-4}, over the 2×10^{-4} bar. Split 1024 ways it is 2.3×10^{-5}, lower than the serial sum’s 4.1×10^{-5}. Precision is a schedule here too.

The derived model is faster than the hand engine from 16 concurrent streams up: a decode step at 48 streams takes 28.78 ms against 30.26 ms. At 1–8 streams it was slower, so the engine takes the derived path only for windows of at least 16 rows and keeps the hand kernels below that. In isolation the layer is faster at every batch size, so the loss is not in the kernels alone. §9 measures where it goes.

9 The speed of light

“Derived kernels beat hand kernels” is a claim about two programs. It says nothing about whether either is fast. The question that matters is how far a kernel is from the fastest any implementation could be. tang can answer it from the same comprehension it compiles.

9.1 The floor and the tile are dual

For a comprehension over affine views, the least memory traffic of any tiled schedule comes from a linear program. Each view projects the iteration space onto one operand, and the Brascamp–Lieb inequality bounds how many iterations a tile can run for the data it holds[8]. The program’s optimum is the traffic lower bound. Its dual is a tile shape that attains it. So the bound and the schedule are two solutions of one problem, and the duality gap is how far a schedule is from optimal. tang builds this program from a kernel’s views (`TensorGraph::kernel_lp`) and solves both sides.

It reproduces the classical bounds. Matmul gets exponent $3/2$ with a $\sqrt{M/3}$ cube tile. Attention gets Saha and Ye’s $\Theta\big(\min\big(N^2d^2/M, N^2d/\sqrt{M}\big)\big)$[9], and its dual tile is FlashAttention’s $M/(4d)$ blocks. The dual is a prediction about the autotuner, and we can check it (Table 12).

TABLE 12 The dual of the traffic program against the tile the measured autotuner picks. With one memory level, the M4 autotuner beats the dual because it keeps the accumulator, and attention’s online state, in registers. Adding registers as a second level of the program reproduces both picks. The match depends on the register budget being the schedule space’s largest register tile.

KERNEL	DUAL TILE	AUTOTUNER
matmul, 3090	64 × 64	64 × 64: match
attention, one memory level	$M/(4d)$ rows	default schedule moves 2–2.8× the dual’s traffic
matmul, M4, registers as a level	64 × 64	64 × 64: match
attention, M4, registers as a level	64 rows × 32 keys	64 × 32: match, half the one-level dual’s traffic

Weak duality is mechanized in Lean: no box-tiled schedule moves fewer bytes than the primal. General schedules need the full discrete Brascamp–Lieb theorem, which we have not mechanized. Guarded views fit the program as it is. For a gather view the bound is $\max(\mathrm{HBL}(\mathrm{rest}), \mathrm{compulsory} + U \cdot \mathrm{slice})$, which is sound for the given index data and equals the analytic MoE floor under uniform top-k. Multi-term views, such as a convolution’s $x + k$, are dropped from the program, which keeps the bound sound but loose. Masks are not modelled.

9.2 From traffic to time

Traffic is one limit. A kernel’s time floor is

$$t \geq t_{\text{launch}} + \max(B/\beta + \lambda, F/\pi, \lceil w \rceil \lambda, I/\iota)$$

for B bytes at bandwidth β, DRAM latency λ, F flops at peak π, w waves, and I issue slots at the chip’s issue rate ι, each counted from the lowered kernel. A decode step’s floor is the longest path through its kernel graph, where independent kernels may overlap. Every constant comes from a datasheet or an empty-kernel launch. Nothing is fitted to the times we predict.

We measured every kernel’s DRAM bytes and time with Nsight on an RTX 3090 and an H200. The floor is sound on every kernel on both chips: it never predicts more than the measured time. On the 3090 it is tight, at 0.82–0.90 of the measured time, and every large kernel is bandwidth-bound. On the H200 it was loose until the issue term entered. The Q8 GEMV is predicted at 58.7 µs against 63.5 µs measured, a ratio of 0.92, up from 0.42 without that term. The same code is bandwidth-bound on one chip and issue-bound on the other. The Q4_K MoE GEMVs are not closed: they sit at 0.39–0.70, and counting their instructions finely enough needs Hopper counters.

9.3 What the floor says about decode

On the H200 a whole decode step’s traffic floor is only 0.16–0.29 of its measured time, and the gaps between kernels inside the CUDA graph are only 0–8% of the step. The missing time is per kernel. A cold dependent GEMV costs 6.9 µs including launch, and any dependent kernel under about 2 MB costs about that much whatever it does. At one stream the hand engine’s step is 548 kernels in 4.04 ms, 7.4 µs each. That arithmetic suggests decode at small batch is bound by its chain of dependent kernels, but the obvious test refutes the simple form of it. Removing 96 of the 548 launches by fusion did not speed up the step, because the work moved into tails on the same

critical path (Table 13). What limits small-batch decode on the H200 is still an open term in the floor.

The floor also ranks fixes before anyone builds them (Table 13). Each lever is a schedule change, and the floor bounds what it can gain.

TABLE 13 Decode levers, bounded by the step floor and then measured. The first version of the floor credited L2 prefetch with up to −36%; charging the prefetching kernel for the matrix it streams turned that into the measured loss. Gains are against the step time; the parallel shared expert is a switch in the engine.

LEVER	BOUND FROM THE FLOOR	MEASURED, H200
blind L2 prefetch of the next matrix	+4 to +28% (slower)	net slower: next kernel −0.4 to −0.6 µs, prefetcher +0.6 to +4 µs
shared expert on a parallel graph branch	≤ 9% at one stream	within noise at 1–8 streams; −6 to −13% at 16–48, bitwise equal
fuse block-local chains	−25% hand, −38% derived at one stream; 4–8% at 48	no gain: top-k into the router GEMV 4.05 → 4.13 ms; with combine fused, 4.44 ms, 96 of 548 launches removed

The claim is therefore sharper than "derived beats hand." On the 3090, tang's large kernels run within 11–22% of a floor no implementation can beat. Further away, it has named two missing terms so far, registers and issue slots. It also failed once in a useful way: its fusion bound promised gains that fusion did not deliver, so per-kernel fill is not yet modelled correctly.

10 Related work

Schedules. Halide[10] separated algorithm from schedule. TVM[11] and Ansor[12] searched the schedule space with learned cost models, and Tensor Comprehensions[13] used polyhedral compilation. tang inherits the separation and the search.

Deriving fused kernels. The closest work is concurrent. Mirage[14] superoptimizes multi-level μGraphs with probabilistic equivalence checks. EqiForge[15] uses equality saturation to derive FlashAttention-style forward kernels. Flashlight[16] generates flash-style kernels for arbitrary attention variants inside TorchInductor. tang differs on three axes. Its rewrite is deterministic, keyed on the monoid structure rather than found by search. It derives the backward pass, including the gradient of the online-softmax monoid and the elimination of the stabilizing max. And it lowers to six targets, not one. Neither Flashlight nor EqiForge publishes code, so we measure against FlexAttention and FA2 instead (§7.3).

Tile languages and hand kernels. Triton[17], ThunderKittens[18] and TileLang[19] make kernels easier to write. FlashAttention[1,2,20] is the hand-derived frontier. Online softmax is due to Milakov and Gimelshein[3]. tang aims to make writing kernels unnecessary, and treats these kernels as the targets derived code must reach.

Lower bounds. Communication lower bounds for loop nests over arrays come from the Brascamp–Lieb inequality[8], and red-blue pebbling bounds are now derived

automatically for affine programs. Attention's I/O complexity is $\Theta(N^2d^2/M)$ for large caches[9]. These analyze a fixed algorithm and model traffic only. tang reads the program off the kernel it compiles, uses its dual as a schedule, adds latency, issue and launch terms, and checks the result against hardware counters.

Generated kernels. LLM agents now write CUDA, but KernelBench-Verified[21] shows frontier models reward-hacking benchmarks by hard-coding test values. A derived kernel is checked by construction against an f64 interpreter of the same graph.

11 Deriving every kernel

The first version of this paper ended with a list of IR constructs that tang would need to derive a production engine. Each item is now built, and each is measured above.

TABLE 14 The roadmap of the first version, and what closed each item. None of these is an attention or MoE kernel. Each is a monoid, a schedule field or a lowering rule that any graph of the same shape gets.

GAP	CONSTRUCT	RESULT
MoE routing	`Monoid::topk`	10 arg-max rounds → 1 kernel; layer 0.199 → 0.103 ms
batch-1 gathers	`Stage::Gemv`, fused producers	beats the hand kernels at batch 1 (Table 9)
gather backward	sorted-key segments	2.1–15× on the expert gradient
recurrences	scan monoid, chunked plan	4× the hand recurrence; ties fla on the 3090
$d = 256$ **attention**	tile width in `schedule_auto`	2.8 → 422 TFLOP/s; 45k prefill −28%
Hopper backward	recognized fused kernel, `wgmma`, warp specialization	9 kernels → 1; 0.8–1.0× SDPA
launch fusion	cooperative staged maps, megakernels	729 → 584 kernels; time-neutral on sm_86
decode	split GEMVs, load-bytes register model	122 → 148.7 tok/s; ties llama.cpp

What remains is measured too. The derived Hopper forward runs at 0.42–0.60× of FlashAttention-3, and the fused backward kernel at about 0.4× of FA3′s backward: FA3 overlaps the softmax of one block with the GEMMs of the next, and loads through TMA from a producer warpgroup, and our consumers still issue their own copies. On the H200, fla's scans are 1.2–2.4× ahead at long sequences, because our state scan runs sequentially over chunks; the affine monoid is associative at any granularity, so a two-level scan is a schedule change. The WGSL flash tile still runs every key tile under a sliding-window mask (Table 5), and the Metal backward's nested dots are not yet blocked onto simdgroup matrices. `schedule_auto` is still rules, while every autotuning run writes (graph, chip, schedule, time) to a cache that can train a cost model. Sharded reductions joined by an all-reduce are already a rewrite, and only the transport is missing. Several earlier tables were taken on shared GPUs; §8′s were not.

12 Conclusion

Two primitives, affine views and monoid comprehensions, are enough to express a transformer, its gradient and its quantized inference. Fusion, flash attention and the flash backward become rewrites and schedule choices, not kernels. Because the schedule is searched per chip, the same source matches hand kernels within 7% or beats them on Metal and Vulkan, runs on an embedded Adreno, and beats PyTorch on a transformer block’s forward pass on CUDA.

The hand-written kernel does not disappear in this design. It becomes an intrinsic, a fast implementation of one comprehension shape on one chip, which the compiler uses when it wins and replaces when it doesn’t. In the last hand-tuned engine we run, an 80B MoE model on an H200, the derived MoE layer beats the hand-written one at every batch size, the derived model is faster from 16 streams up, and derived prefill kernels cut the time to first token at 44k tokens by a third.

The comparison with hand kernels was never the point. The traffic floor and the tile that reaches it are dual solutions of one program, so a compiler that derives kernels can also say how far each one is from the best possible. Where tang’s kernels fall short of that floor, it can name why on some kernels and not yet on others. Small-batch decode on the H200 is the open case: it is far from its traffic floor, and removing launches did not close the distance.

> ASIDE · REPRODUCIBILITY
> Every number in this paper comes from `BENCHMARKS.md` in the tang repository (snapshot in `data/`), which records the command, date and machine state for each measurement. The IR is in `crates/tang-compile/src/tensor*.rs`; its design notes are in `docs/tensor-ir.md`.

Appendix: decode engineering notes

Every change between the first build and the current one is a schedule or a lowering rule, not a kernel. Norms are materialized once instead of recomputed in every GEMV lane. 4-bit GEMVs under 16k rows are split along k. The attention score kernel stops at the runtime length. A load-bytes model picks the register dimension, so P·V shares the probabilities across the 4 GQA heads instead of re-reading them. A cooperative lowering computes a small reduction (RMSNorm’s sum of squares, the per-head q/k-norm statistics) into shared memory once per block and evaluates the map that reads it from there, which takes the step from 729 to 584 kernels.

Removing launches turned out to cost nothing and to save nothing. Inside a CUDA graph on sm_86, a dependent launch costs what a grid barrier costs (0.77 vs 0.81 µs), so 145 fewer kernels is time-neutral, and a persistent megakernel that runs the whole step as one launch with 437 phases is correct but 19% slower, because one register budget for every stage spills the largest GEMV. The gap to llama.cpp at 4k is in the kernels: the 4-bit GEMVs run at 60–82% of bandwidth, and attention reads K and V about twice.

References

1. Dao, T., Fu, D. Y., Ermon, S., Rudra, A. & Ré, C. FlashAttention: Fast and Memory-Efficient Exact Attention with IO-Awareness. in Advances in Neural Information Processing Systems (2022).
2. Shah, J. et al. FlashAttention-3: Fast and Accurate Attention with Asynchrony and Low-precision. arXiv preprint arXiv:2407.08608 (2024).
3. Milakov, M. & Gimelshein, N. Online normalizer calculation for softmax. arXiv preprint arXiv:1805.02867 (2018).
4. Welford, B. P. Note on a method for calculating corrected sums of squares and products. Technometrics **4,** 419–420 (1962).
5. Dao, T. & Gu, A. Transformers are SSMs: Generalized models and efficient algorithms through structured state space duality. in International Conference on Machine Learning (ICML) (2024).
6. Yang, S., Kautz, J. & Hatamizadeh, A. Gated Delta Networks: Improving Mamba2 with delta rule. in International Conference on Learning Representations (ICLR) (2025).
7. Dong, J., Feng, B., Guessous, D., Liang, Y. & He, H. Flex Attention: A Programming Model for Generating Optimized Attention Kernels. arXiv preprint arXiv:2412.05496 (2024).
8. Christ, M., Demmel, J., Knight, N., Scanlon, T. & Yelick, K. Communication Lower Bounds and Optimal Algorithms for Programs That Reference Arrays – Part 1. arXiv preprint arXiv:1308.0068 (2013).
9. Saha, B. & Ye, C. The I/O Complexity of Attention, or How Optimal is Flash Attention? arXiv preprint arXiv:2402.07443 (2024).
10. Ragan-Kelley, J. et al. Halide: A Language and Compiler for Optimizing Parallelism, Locality, and Recomputation in Image Processing Pipelines. in PLDI (2013).
11. Chen, T., Moreau, T., Jiang, Z. & others. TVM: An Automated End-to-End Optimizing Compiler for Deep Learning. in OSDI (2018).
12. Zheng, L., Jia, C., Sun, M. & others. Ansor: Generating High-Performance Tensor Programs for Deep Learning. in OSDI (2020).
13. Vasilache, N., Zinenko, O., Theodoridis, T. & others. Tensor Comprehensions: Framework-Agnostic High-Performance Machine Learning Abstractions. arXiv preprint arXiv:1802.04730 (2018).
14. Wu, M., Cheng, X., Liu, S. & others. Mirage: A Multi-Level Superoptimizer for Tensor Programs. arXiv preprint arXiv:2405.05751 (2024).
15. Zhan, Q., Hu, X., Xia, X. & Li, S. Unleashing the Power of Equality Saturation for Tensor Program Superoptimization. arXiv preprint arXiv:2609.12330 (2026).

16. You, B., Wang, I., Mustafaoglu, Z. S., Jangda, A. & others. Flashlight: PyTorch Compiler Extensions to Accelerate Attention Variants. arXiv preprint arXiv:2511.02043 (2025).
17. Tillet, P., Kung, H. T. & Cox, D. Triton: An Intermediate Language and Compiler for Tiled Neural Network Computations. in MAPL (2019).
18. Spector, B. F., Arora, S., Singhal, A., Fu, D. Y. & Ré, C. ThunderKittens: Simple, Fast, and Adorable AI Kernels. arXiv preprint arXiv:2410.20399 (2024).
19. Wang, L. & others. TileLang: A Composable Tiled Programming Model for AI Systems. arXiv preprint arXiv:2504.17577 (2025).
20. Dao, T. FlashAttention-2: Faster Attention with Better Parallelism and Work Partitioning. arXiv preprint arXiv:2307.08691 (2023).
21. Zhang, Y., Yu, P., Wang, J. & others. KernelBench-Verified: Do LLM-Generated Kernels Actually Beat PyTorch? arXiv preprint arXiv:2607.16241 (2026).