

Merge Sorted Array

Given two sorted arrays **arr1[]** and **arr2[]** of sizes **n** and **m** in non-decreasing order. Merge them in sorted order without using any extra space. Modify arr1 so that it contains the first N elements and modify arr2 so that it contains the last M elements.

Input:

n = 4, arr1[] = [1 3 5 7]

m = 5, arr2[] = [0 2 6 8 9]

Output:

arr1[] = [0 1 2 3]

arr2[] = [5 6 7 8 9]

Explanation:

After merging the two non-decreasing arrays, we get,
0 1 2 3 5 6 7 8 9.

Naïve Approach: time = $O(m+n)$; space= $O(m+n)$;

```
class Solution {  
    public void merge(int[] nums1, int m, int[] nums2, int n) {  
        int a[]=new int[m+n];  
        int i=0,j=0,l=0;  
        while(i<m&&j<n)  
        {  
            if(nums1[i]<=nums2[j])  
            {  
                a[l++]=nums1[i++];  
            }  
            else  
            {  
                a[l++]=nums2[j++];  
            }  
        }  
    }  
}
```

```

        a[l++]=nums2[j++];
    }
}
while(i<m)
{
    a[l++]=nums1[i++];
}
while(j<n)
{
    a[l++]=nums2[j++];
}
for(int k=0;k<a.length;k++)
{
    nums1[k]=a[k];
}
}
}

```

Better Approach: time = (m*n) space=O(1)

It uses insertion sort technique

```

class Solution {
    public void merge(int[] nums1, int m, int[] nums2, int n) {
        int l=0;
        int r=0;
        while(l<m&& r<n)
        {

            if(nums1[l]>nums2[r])
            {

```

```

        int t=nums1[l];
        nums1[l]=nums2[r];
        nums2[r]=t;
        insertElement(nums2);

    }
    l++;
}
while(r<n)
{
    nums1[l++]=nums2[r++];
}

}

public void insertElement(int[] arr)
{
    int e=arr[0];
    for(int i=1;i<arr.length;i++)
    {
        if(e>arr[i])
        {
            arr[i-1]=arr[i];
        }
        else
        {
            arr[i-1]=e;
            return;
        }
    }
}

```

```

    }
    arr[arr.length-1]=e;
}
}

```

Efficient Approach: time = $O(N\log(N))$ space: $O(1)$

It uses gap method

```

class Solution
{
    //Function to merge the arrays.
    public static void merge(long arr1[], long arr2[], int n, int m)
    {

        int gap=n+m;
        for( gap=nextGap(gap);gap>0;gap=nextGap(gap))
        {

            for(int i=0;i<(m+n);i++)
            {
                int j=i+gap;
                //j reach out of the m+n
                if(j>=m+n)
                    break;
                //if i and j in the first array
                if(i<n&& j<n)
                {
                    if(arr1[i]>arr1[j])
                    {
                        swap(arr1,arr1,i,j);
                    }
                }
            }
        }
    }
}

```

```

    }
}
//if i in first array and j in second array
else if(i<n&& j>=n)
{
    if(arr1[i]>arr2[j-n])
        swap(arr1,arr2,i,j-n);
}
//if i and j both are in second array
else if(i>=n&& j>=n)
{
    if(arr2[i-n]>arr2[j-n])
    {
        swap(arr2,arr2,i-n,j-n);
    }
}
}
}

public static void swap(long[] a,long[] b,int i,int j)
{
    long l=a[i];
    a[i]=b[j];
    b[j]=l;
}

public static int nextGap(int gap)
{
    if(gap==0 || gap==1)

```

```
{  
    return 0;  
}  
//gap%2 is to get the celing value  
return gap/2+gap%2;  
}  
}
```