

ITA1412 -ETHICAL HACKING

Experiment no:4

Experiment Name: Information Gathering Using The Harvester

Procedure:

STEP 1: Open Terminal in the kali Linux

STEP 2: Run the command

Output:

[illegible]

```
kali@kali: ~  
Session Actions Edit View Help  
kali@kali: ~ kali@kali: ~ kali@kali: ~ kali@kali: ~  
-n, --dns-lookup      Enable DNS server lookup, default False.  
-c, --dns-brute       Perform a DNS brute force on the domain.  
-f, --filename FILENAME  
                        Save the results to an XML and JSON file.  
-w, --wordlist WORDLIST  
                        Specify a wordlist for API endpoint scanning.  
-a, --api-scan         Scan for API endpoints.  
-q, --quiet            Suppress missing API key warnings and reading the api-keys file.  
-b, --source SOURCE    baidu, bevigil, bitbucket, brave, bufferoverrun, builtwith, censys, certspotter, chaos,  
                        commoncrawl, criminalip, crtsh, dehashed, dnsdumpster, duckduckgo, fofa, fullhunt, github-  
                        code, gitlab, hackertarget, haveibeenpwned, hudsonrock, hunter, hunterhow, intelx, leakix,  
                        leaklookup, netlas, onyphe, otx, pentesttools, projectdiscovery, rapiddns, robtex,  
                        rocketreach, securityscorecard, securityTrails, shodan, subdomaincenter,  
                        subdomainfinder99, thc, threatcrowd, tomba, urlscan, venacus, virustotal, waybackarchive,  
                        whoisxml, windvane, yahoo, zoomeye  
  
(kali@kali)-[~]  
$ theHarvester --version  
Read proxies.yaml from /etc/theHarvester/proxies.yaml  
*****  
*  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* theHarvester 4.10.1 *  
* Coded by Christian Martorella *  
* Edge-Security Research *  
* cmartorella@edge-security.com *  
*  
*****  
usage: theHarvester [-h] -d DOMAIN [-l LIMIT] [-S START] [-p] [-s] [--screenshot SCREENSHOT] [-e DNS_SERVER] [-t]  
                [-r [DNS_RESOLVE]] [-n] [-c] [-f FILENAME] [-w WORDLIST] [-a] [-q] [-b SOURCE]  
theHarvester: error: the following arguments are required: -d/--domain  
  
(kali@kali)-[~]  
$ theHarvester -h  
Read proxies.yaml from /etc/theHarvester/proxies.yaml  
*****  
*  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* [ASCII ART] *  
* theHarvester 4.10.1 *  
* Coded by Christian Martorella *  
* Edge-Security Research *  
*
```

```
kali@kali: ~
Session Actions Edit View Help
kali@kali: ~ x kali@kali: ~ x kali@kali: ~ x kali@kali: ~ x
* Edge-Security Research
* cmartorella@edge-security.com
*
*****
usage: theHarvester [-h] -d DOMAIN [-l LIMIT] [-S START] [-p] [-s] [--screenshot SCREENSHOT] [-e DNS_SERVER] [-t]
[-r [DNS_RESOLVE]] [-n] [-c] [-f FILENAME] [-w WORDLIST] [-a] [-q] [-b SOURCE]

theHarvester is used to gather open source intelligence (OSINT) on a company or domain.

options:
  -h, --help                show this help message and exit
  -d, --domain DOMAIN       Company name or domain to search.
  -l, --limit LIMIT         Limit the number of search results, default=500.
  -S, --start START         Start with result number X, default=0.
  -p, --proxies              Use proxies for requests, enter proxies in proxies.yaml.
  -s, --shodan               Use Shodan to query discovered hosts.
  --screenshot SCREENSHOT   Take screenshots of resolved domains specify output directory: --screenshot
                             output_directory
  -e, --dns-server DNS_SERVER DNS server to use for lookup.
  -t, --take-over            Check for takeovers.
  -r, --dns-resolve [DNS_RESOLVE] Perform DNS resolution on subdomains with a resolver list or passed in resolvers, default
                             False.
  -n, --dns-lookup           Enable DNS server lookup, default False.
  -c, --dns-brute            Perform a DNS brute force on the domain.
  -f, --filename FILENAME    Save the results to an XML and JSON file.
  -w, --wordlist WORDLIST     Specify a wordlist for API endpoint scanning.
  -a, --api-scan             Scan for API endpoints.
  -q, --quiet                Suppress missing API key warnings and reading the api-keys file.
  -b, --source SOURCE        baidu, bevigil, bitbucket, brave, bufferoverflow, builtwith, censys, certspotter, chaos,
                             commoncrawl, criminalip, crtsh, dehashed, dnsdumpster, duckduckgo, fofa, fullhunt, github-
                             code, gitlab, hackertarget, haveibeenpwned, hudsonrock, hunter, hunterhow, intelx, leakix,
                             leaklookup, netlas, onyphe, otx, pentesttools, projectdiscovery, rapiddns, robtex,
                             rocketreach, securityscorecard, securityTrails, shodan, subdomaincenter,
                             subdomainfinder99, thc, threatcrowd, tomba, urlscan, venacus, virustotal, waybackarchive,
                             whoisxml, windvane, yahoo, zoomeye
```

```
rocketreach, securityscorecard, securityTrails, shodan, subdomaincenter,
subdomainfinder99, thc, threatcrowd, tomba, urlscan, venacus, virustotal, waybackarchive,
whoisxml, windvane, yahoo, zoomeye

(kali@kali)-[~]
$ theHarvester -d kali.org -b bing
Read proxies.yaml from /etc/theHarvester/proxies.yaml
*****
*
* [ ASCII ART ]
*
* theHarvester 4.10.1
* Coded by Christian Martorella
* Edge-Security Research
* cmartorella@edge-security.com
*
*****
The following engines are not supported: {'bing'}

[!] Invalid source.

(kali@kali)-[~]
$ theHarvester -d kali.org -b bing -f report
Read proxies.yaml from /etc/theHarvester/proxies.yaml
*****
*
* [ ASCII ART ]
*
* theHarvester 4.10.1
* Coded by Christian Martorella
* Edge-Security Research
* cmartorella@edge-security.com
*
*****
The following engines are not supported: {'bing'}

[!] Invalid source.
```