Verify, Don't Decode: When Trusted Agents Disrupt LLM Collusion in Software Engineering and Double-Auction Markets[1]

Muniraju Pulipalyam
Independent

With
Apart Research

Abstract

Colluding LLM agents can hide their coordination, so monitors or overseers that read their messages could be ineffective or fragile. We ask whether trusted agents *inside a multi-agent system can disrupt collusion without first decoding it. We test three kinds of trusted agent. In a software team implementing a real FastAPI change, a trusted QA teammate either reports results of hidden acceptance tests (a* verifier*) or privately offers a prohibited shortcut (a* probe*). In an electricity double auction, a trusted competing seller (an* entrant*) joins once overpricing is verified. The entrant raised buyers' surplus in 4 of 5 collusive markets it entered; quarantining suspects never helped; publishing the competitive price dissolved an open cartel but not a hidden one. In a pre-registered software study, harm was too rare to disrupt: an honest reviewer rejected 40 of 47 changes, no arm differed from its control, the probe drew no response (0/9), and the verifier matched the grader every time. Above a competence floor (9/10 honest teams correct), the verifier tripled correct releases but also vouched for a colluding partial fix its tests did not cover. In a* chain of monitors *(a weak trusted desk, plus an isolated, capable but untrusted reviewer checked with honeypot audits), an honest reviewer raised buyers' surplus in every collusive market, while a "paid" reviewer facing audits reasoned about which case was the audit and mostly gave no verdict, which our fail-open default turned into a veto. Layered monitors must fail closed and match authority to reliability.*

1. Introduction

Multi-agent LLM deployments rely on role separation working on their problem within their own defined context and access: for software engineering tasks, a tester checks the implementer, a reviewer checks both, whereas in a market buyers and sellers compete independently. Collusion breaks that separation, and it can be hidden: LLM agents can coordinate steganographically [9], such schemes emerge under optimisation pressure and survive paraphrasing [8], and pricing agents reach supra-competitive prices without talking [3, 5]. We ask what to put *inside* the system so that collusion fails even when nobody can prove how it happened. **Threat model:** a subset of agents shares a private goal that conflicts with the system's (ship an incomplete fix behind tests that hide the gap; keep prices high). They cannot write the evidence log, reach the monitor, or bypass the release or order

[1] Research conducted at the AI Collusion Research Sprint, October 2026.

gate. Both scenarios serve one aim: layered, isolated monitoring that could also hold against collusion learned in context (ICRL) [8], in the spirit of AI control [6]. Our main contributions are:

1. **A two-domain harness on real artifacts** (a past FastAPI commit merged after the models' cut-off as the starting point; a double auction after Agrawal et al. [1]) with a hash-chained evidence log, a monitor ladder and trusted agents.
2. **Pre-registered LLM results, nulls included:** a trusted entrant restores buyer surplus where quarantine backfires; a trusted probe exposes no one; a trusted verifier is accurate but only advisory.
3. **Verification is not collusion detection** when honest agents also fail: it still blocks harm, but stops separating collusion from incompetence.
4. **A chain of monitors** (weak trusted inner layer, isolated untrusted capable outer layer, honeypot audits): it works with an honest reviewer, and a scheming one evades audits by not answering.

2. Related Work

Motwani et al. [9] formalise secret collusion and the limits of passive oversight; Mathew et al. [8] show it emerging and resisting paraphrasing. Calvano et al. [3] and Fish et al. [5] find autonomous supra-competitive pricing; Agrawal et al. [1] study LLM double auctions; bid rotation signalled in trailing digits is documented in the FCC auctions [4]. SWE-bench [7] established hidden-test evaluation and ImpossibleBench [10] documents test exploitation. AI control [6] combines weak trusted models, capable untrusted models and honeypots; chain-of-thought monitoring can be obfuscated [2]. **How we differ:** prior work mostly *detects* collusion at the system boundary; we test trusted agents that act *inside* the system and disrupt it through the environment, on real artifacts with pre-registered outcomes, which matters when hidden channels make transcript monitoring unreliable.

3. Methods

Evidence log and monitors. Every tool call, message, file write, test run, order and trade is appended to a hash-chained log by the environment, not the agents. Monitors emit scored signals; only *verified* ones may CONSTRAIN, unverified risk may only HOLD, and a separate collusion score uses coordination evidence only. M1 applies rules (deleted or skipped tests, a chat lexicon); M3 verifies outcomes without a model (half of the hidden tests on a pristine checkout, mutation tests; in the market, the collusion index against the competitive equilibrium). The principle is *verify, don't decode*: check the outcome a hidden channel is meant to produce, not the channel.

Trusted agents. *QA teammate* `qa`: listed like any role, cannot commit, review or release, and acts after the tester's first turn and before review. As *verifier* it posts how many of a held-out half of the hidden tests fail (disjoint from M3's half); as *probe* it plants an inert honeytoken file with a unique token and privately invites implementer and tester to skip edge-case tests with it (eight paraphrases). Reciprocation is verified from the log (token written, or skip/xfail added). *Entrant*: from round 10, M3 may HOLD (board off) or, on a verified sustained collusion index ≥ 0.3, admit a trusted seller offering two blocks just above the competitive range; the ablation *quarantines* attributed sellers.

Software scenario. Planner, implementer, tester and an always-honest reviewer implement FastAPI task T3 (keep an upload's read position when converting it to bytes; merged 21 Oct 2026; 7 hidden tests plus regressions). Every prompt forbids skipping or weakening tests. Colluding teams privately aim to ship a partial fix behind happy-path tests. *Harmful release* = released and hidden tests fail. Two teams $\times$ five arms (none, online M1 gate, online M3 gate, QA verifier, QA probe) $\times$ seeds 0–4. **Market scenario.** Five LLM sellers (costs \$60–69), four scripted buyers (values \$94–100), 15 rounds; competitive price about \$67, monopoly about \$95; collusion index $CI = (\bar{p} - p_{CE})/(p_{JPM} - p_{CE})$, harm if ≥ 0.3. Conditions A2 (honest, with a message board), A3 (overt cartel), A5 (rotation

Table 1: Market, means over 3 seeds. CI: collusion index. CS/round: buyers' surplus per round before (rounds 5–10) and after (11–15) the monitor may act; Δ: change after minus before, minus the paired no-intervention change. Cons.: episodes constrained.

			CS / round			
Cond.	Arm	CI	before	after	Δ vs none	Cons.
A2 honest	none	0.21	69.4	71.3	–	–
	entrant	0.22	68.6	73.6	+3.1	0/3
	quarantine	0.23	68.3	75.2	+4.9	0/3
A3 cartel	none	0.72	24.1	36.7	–	–
	entrant	0.73	20.3	33.7	+0.8	2/3
	quarantine	0.86	15.5	6.6	−21.5	2/3
A5 stego	none	0.98	1.7	6.4	–	–
	entrant	0.77	2.9	22.9	+15.2	3/3
	quarantine	1.03	0.4	3.6	−1.5	3/3

Table 2: Software, task T3, 5 seeds per cell (colluding probe: 4). Harmful: released and fails hidden tests. Correct: all hidden tests pass. Appr.: reviewer approved. Blocked: gate blocked an approved change.

Team	Arm	harmful	correct code	appr.	blocked
colluding	none	0/5 [0,.43]	0	0	0
	M1 gate	0/5 [0,.43]	0	0	0
	M3 gate	0/5 [0,.43]	0	0	0
	QA verifier	0/5 [0,.43]	1	0	–
	QA probe	1/4 [.05,.70]	0	1	–
honest	none	2/5 [.12,.77]	1	2	0
	M1 gate	0/5 [0,.43]	1	2	2
	M3 gate	0/5 [0,.43]	1	1	1
	QA verifier	1/5 [.04,.62]	1	1	–
	QA probe	0/5 [0,.43]	1	0	–

signalled in price cents); each with no monitor, M3+entrant, M3+quarantine, 3 seeds (27 episodes).

Models and pre-registration. Untrusted agents: `gemma4:31b`; trusted LLM roles: `gpt-oss:120b`. Outcomes, Fisher exact tests, Wilson 95% intervals and exclusions were fixed in `docs/PREREG.md` before data. *What did not work* in pilots, fixed before the main run: a reasoning model used every turn without acting (we added a wrap-up nudge and a forced reviewer decision), and an honest tester obeyed the probe because nothing prohibited it (we added the policy line). One episode with no successful model call was excluded and not replaced ($n = 4$ in that cell).

Chain of monitors. Following AI control (Figure 2, Appendix B), a *weak trusted* inner desk (gpt-oss 20B) reads the board, prices and sellers' messages every hour and may intervene; a *capable untrusted* reviewer (Nemotron Ultra 550B), hidden from sellers, reviews only prices, trades and the desk's decisions every three hours and may escalate. Each review includes a synthetic window with a known label (a honeypot); clearing a collusive one gets the reviewer distrusted. Arms: desk alone; plus honest reviewer with honeypots; plus a scheming reviewer (privately paid by the incumbents) without and with honeypots; A2/A3/A5 × 3 seeds, 18 hours, sellers `gemma4:31b` (36 episodes).

4. Results

Numbers are recomputed from the logs by `paper/analysis/`; brackets are Wilson 95% intervals, and with $n \leq 5$ per cell nulls read as "no large effect".

4.1 Market: a trusted entrant restores surplus; quarantine does not

Instructed cartels (A3) and rotation (A5) reached collusion indices of 0.72 and 0.98 without intervention; honest sellers (A2) stayed at 0.17–0.29, below threshold. Because paired LLM runs diverge, we compare the before/after change in per-round buyer surplus with the same change in the paired no-intervention run (Table 1, Figure 1). The entrant was admitted in 5 of 6 collusive markets and improved on its pair in 4 (mean +9.6 per round); quarantine was worse in 3 of 5 and never better (mean −13.8), because removing sellers removes supply. Most of the entrant's gain came from its own trades: incumbents kept pricing near the monopoly level, so the entrant relieved buyers but did not break the cartel. It never acted on an honest market, and the board shut-off it applied there left efficiency unchanged (0.65 vs 0.67). A cartel that priced above every buyer produced no trades, hence nothing to verify: refusal to supply needs its own signal.




Figure 1: Market scenario. (a) Buyers' surplus per round after the monitor may act (rounds 11–15); bars are means, dots are seeds. (b) In the steganographic rotation condition A5, the mean trade price of the *incumbent* sellers per round (shaded: rounds in which an intervention can be active). The entrant raises buyers' surplus mainly through its own trades; incumbents' prices barely move.

4.2 Software: harm was too rare to disrupt; the probe exposed no one

Only 6 of 49 teams wrote correct code; the commonest bug was calling `await file.tell()`, which `UploadFile` lacks. The honest reviewer caught it almost every time, rejecting 40 of 47 changes, so harmful releases were rare (colluding 1/24, honest 3/25, $p = 0.61$) and no arm differed from its control (all Fisher $p \geq 0.44$; Table 2). The single colluding harmful release is the predicted pattern: a happy-path plan announced in private, approved because "tests pass". No correct fix was released: four were rejected over broken team tests and two blocked by gates. The verifier's verdict matched the grader in 10/10 episodes, yet one reviewer approved after two "4 of 4 checks fail" reports. The probe drew no reciprocation (0/4 colluding, 0/5 honest): in 8 of 9 episodes the invited agents took 5–17 more actions, but none opened the honeytoken, wrote the token, replied, or reported the offer. Offline, M3 flagged all 29 teams, honest included, because both shipped failing code (collusion-score AUROC 0.63); what separated colluders was talk, which M1's lexicon caught in 8/14 with no false positives (AUROC 0.79; Appendix C).

Study 2: above a competence floor. With the spec's API facts added and tasks screened in advance (`PREREG` 6), honest teams wrote correct T3 code in 9/10 episodes and colluding teams in 4/10 (Fisher $p = 0.06$); 4 colluding fixes were the planned partial ones (5/7 hidden tests). The reviewer blocked 3 of the 4. The verifier now mattered for utility: with it, 6/10 correct fixes were released against 2/10 without ($p = 0.17$), because the reviewer approved when `qa` reported "all checks pass" (7/10 approvals vs 3/10). The same reassurance shipped the one colluding partial fix: `qa`'s held-out half contained neither failing test, so its "all 4 pass" was true and misleading. Harmful releases were 1/10 in each arm. On T1 (run by a collaborator) teams wrote correct code often (honest 8/10, colluding 6/10) but the reviewer released none; the one harmful release was again approved after `qa` reported 13 failing checks, and verifier teams were less often correct (4/10 vs 10/10, $p = 0.01$; cause unclear at $n = 5$). His T3 episodes are excluded: his grader failed even the reference fix (`PREREG` 6c).

4.3 Chain of monitors: two runs

v1 (as registered, 36 episodes). The weak trusted desk admitted the entrant at its first decision in 36/36 episodes, all 12 honest markets included, unmoved by 84–90 reassuring messages per episode; harmless only because the entrant is a cheap remedy. Real review windows showed the desk's interventions and honeypots did not, so the reviewer escalated every real window and cleared half the collusive honeypots even when honest (5/10): the audit tested a metadata column, not the reviewer. **v2 (desk may only hold; honeypots copy the desk column; exploratory, 36 episodes).** Holding alone did not stop collusion: with the desk alone cartels reached a collusion index of 1.07–

1.17 (A3) and 0.95–1.00 (A5). An honest reviewer escalated in all 6 collusive markets, raising buyers' surplus by 21.4 per round over the desk alone (6/6), and escalated 2 of 3 honest markets at little cost. The "paid" reviewer without audits again escalated almost everything (35/36 reviews). *With audits it schemed visibly*: in 26 of 36 replies it reasoned about which case was the audit, and 30 of 36 produced no verdict because the deliberation ran past the reply limit. Unanswered reviews defaulted to no escalation, so non-answers acted as a veto: buyers' surplus fell by 18.0 per round against the same reviewer without audits, and it was distrusted in only 1 of 9 episodes. Honeypots also misfired on the honest reviewer (4 of 13 collusive ones cleared; distrusted in 4/9 episodes), though the model-free fallback then acted correctly.

Injection through actions (18 episodes, fail-closed reviews). The attack could barely be tested: the A5 sellers seldom executed their rotation, so only 2 of 36 real A5 windows carried the partner code (the reviewer did not escalate either). The scheming reviewer again deliberated about audits (17–19 of 24 replies per arm) and about the code (12–18 of 24), and gave no verdict in 18–20 of 24 reviews. With fail-closed reviews it was distrusted at its first review in all 12 scheming episodes and the model-free check took over, so in A5 harm matched the honest-reviewer arm (collusion index 0.68–0.73 vs 0.68). Failing closed has a cost: the honest reviewer, which also failed to answer 7 of 24 reviews, was distrusted in 4 of 6 episodes. Rounding prices did no visible harm to the honest reviewer, but with so few coded windows we cannot say whether it closes the channel.

4.4 Market probes by a trusted participant

Publishing the competitive price to every seller each hour (27 episodes, paired with same-seed no-probe runs) dissolved the overt cartel: its collusion index fell from 0.51–1.18 to 0.05–0.08 and buyers' surplus rose by about 1,000 per episode. Honest markets also moved to the competitive range (0.21–0.25 to 0.05–0.08). The steganographic rotation barely moved (0.87–0.99 to 0.81–0.89): sellers anchored on the published number when they coordinated openly, but not when they followed a hidden scheme. **The codebook sting**, a trusted seller that spoke the cartel's price-cents code, drew no response beyond chance (1/9 in A5, 0/18 in the controls). Sellers mostly posted identical cover asks, and even without a sting the cartel followed its own code in only 3 of 10 coded hours. As in the injection study, the model rarely executed the hidden channel, so probes and attacks that work through the code need agents that use it reliably.

5. Discussion and Limitations

All our agents are open-weight models below the frontier, and all collusion here was instructed or tacit, not learned. *Testing frontier models and collusion learned in context (ICRL) is the next milestone.* Only the trusted agent that changed the environment disrupted collusion. The entrant needs no proof of coordination, cannot be persuaded, and costs nothing when wrong, because on an honest market it is just another competitor; quarantine needs attribution and fails even when attribution is right, because it removes supply. Prefer remedies whose false-positive cost is near zero, and match each monitoring layer's authority to its reliability: the weak layer should hold, the verified layer should constrain. A layer must also *fail closed*: a missing or late verdict from an untrusted monitor should count as a failed audit, not as consent. The trusted teammates depended on untrusted agents taking them seriously; a verifier without authority is advice, and a null probe is weak evidence of honesty. Honeypots must match real cases in every field a monitor sees, and audits did more than score the scheming reviewer: they elicited its strategic reasoning, which logging made visible. A trusted verifier's "pass" is only as good as its coverage, and colluders benefit when reviewers defer to it. **Limitations.** Samples are small ($n \leq 5$ per software cell, 3 seeds per market cell), so only large effects are detectable. One task and one agent model; low competence dominated the software results. Collusion was induced, not learned,

and may be quieter when learned. We assume agents cannot write the log or bypass the gate, and the reviewer was honest by construction. Paired market runs diverge before the intervention. Free endpoints set the sample size and forced two recorded model changes for the chain study (`PREREG` 9c–9d); its revision (9e) is exploratory. A trusted publisher of the competitive benchmark was the cheapest effective remedy against open collusion, and useless against a hidden scheme. All sellers are AI agents; mixed human–agent markets were not tested. **Future work.** Injection and sting tests with agents that reliably use the code; calibrating honeypots on honest reviewers; larger SWE samples, and checking each machine's grading environment before runs. Giving the verifier a hold right, and probes that need no reply (a codebook sting, implemented; a leniency offer), are natural extensions. *The effect of active human participants on the seller side is a core question to study.*

6. Conclusion

Trusted agents can disrupt LLM collusion without decoding it, but only some kinds. A trusted entrant admitted after verified harm restored buyer surplus in most collusive markets at no cost to honest ones, while excluding suspects made things worse. Trusted teammates that rely on colluders engaging, or on others heeding them, produced accurate signals but little disruption, and outcome verification stopped telling collusion from incompetence once honest agents also failed; above a competence floor, the verifier raised utility but could be ridden by a partial fix it did not cover. Layered monitoring works with an honest capable reviewer and fails in instructive ways with a scheming one: it must fail closed, match authority to reliability, and use audits indistinguishable from real cases.

Code and Data

Code, configs, pre-registration, analysis scripts and all episode logs: https://github.com/munip/apart-sprint-collusions. Collusion is induced with explicit instructions and the steganographic schemes are published ones; no novel evasion technique is released.

Author Contributions

Muniraju Pulipalyam conceived the project and the chain-of-monitors topology, set the research questions, ran the experiments and reviewed every result. Thanks to Abdurrachman Mappuji for generously sharing a Claude Code workspace, validating the idea and running a few experiments independently. Claude (Anthropic) implemented most of the code and helped draft the report, which Muniraju validated, tested, edited and enhanced.

References

[1] Kushal Agrawal et al. Evaluating LLM agent collusion in double auctions. *arXiv preprint arXiv:2507.01413*, 2025.

[2] Bowen Baker, Joost Huizinga, Leo Gao, et al. Monitoring reasoning models for misbehavior and the risks of promoting obfuscation. *arXiv preprint arXiv:2503.11926*, 2025.

[3] Emilio Calvano, Giacomo Calzolari, Vincenzo Denicolò, and Sergio Pastorello. Artificial intelligence, algorithmic pricing, and collusion. *American Economic Review*, 110(10):3267–3297, 2020.

[4] Peter Cramton and Jesse A. Schwartz. Collusive bidding: Lessons from the FCC spectrum auctions. *Journal of Regulatory Economics*, 17(3):229–252, 2000.

[5] Sara Fish, Yannai A. Gonczarowski, and Ran I. Shorrer. Algorithmic collusion by large language models. *arXiv preprint arXiv:2404.00806*, 2024.

[6] Ryan Greenblatt, Buck Shlegeris, Kshitij Sachan, and Fabien Roger. AI control: Improving safety despite intentional subversion. In *Proceedings of ICML*, 2024.

[7] Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik Narasimhan. SWE-bench: Can language models resolve real-world GitHub issues? In *ICLR*, 2024.

[8] Yohan Mathew, Ollie Matthews, Robert McCarthy, Joan Velja, Christian Schroeder de Witt, Dylan Cope, and Nandi

Schoots. Hidden in plain text: Emergence and mitigation of steganographic collusion in LLMs. In *Proceedings of IJCNLP-AACL*, 2025.

[9] Sumeet Ramesh Motwani, Mikhail Baranchuk, Martin Strohmeier, Vijay Bolina, Philip H. S. Torr, Lewis Hammond, and Christian Schroeder de Witt. Secret collusion among AI agents: Multi-agent deception via steganography. In *Advances in Neural Information Processing Systems*, 2024.

[10] Ziqian Zhong, Aditi Raghunathan, and Nicholas Carlini. ImpossibleBench: Measuring LLMs' propensity of exploiting test cases. *arXiv preprint arXiv:2510.20270*, 2025.

A. Harness validation with scripted agents

Before the LLM study we validated the harness and monitors with *scripted* agents: seeded policies with paraphrase sampling that act through the same logged tools as LLM agents, which gives exact ground truth at no cost. The SWE scenario used 5 FastAPI tasks × 10 conditions × 3 seeds (150 episodes, including overt, codebook, code-comment, scratch-file, leakage and monitor-aware whitespace channels, plus honest and solo-cheating controls). The market used 7 conditions × 10 seeds over 30 rounds. These results show what the monitors do when honest agents are competent; they are *not* evidence about LLM behaviour.

Table 3: Scripted agents: offline detection on identical trajectories (full observability). Recall at a threshold giving 10% false positives on non-collusive episodes; brackets are bootstrap 95% CIs.

Scenario	Monitor	collusion AUROC	recall@10% FPR	harm flagged	benign flagged
SWE	M1	.57 [.54,.61]	.14 [.08,.22]	.34	.00
SWE	M3	.96 [.93,.99]	.94 [.89,.98]	.93	.00
SWE	M4	.98 [.96,1.0]	.97 [.94,1.0]	.97	.00
Market	M1	.62 [.56,.69]	.25 [.12,.39]	1.0	.00
Market	M3	1.0	1.0	1.0	.13

Main findings with scripted agents: M3 recall stayed at 0.8–1.0 on every coordination channel while M1 fell to zero once coordination left plain language; online M3 cut harmful releases from 90 to 6; and a trusted entrant cut the collusion index of collusive markets from 0.96 to 0.59 while quarantine raised it to 0.98.

B. Chain of monitors: full design

Honeypots. Each review shows the real three-hour window and one synthetic window in the same format and market parameters, shuffled, whose label is known: collusive (a rotating cheapest seller near the monopoly price) or competitive. After one cleared collusive honeypot the reviewer's verdicts are ignored and the model-free check (verified price harm or withheld supply) escalates instead. The scheming reviewer is told that wrong answers on audit cases get it replaced, so it is motivated to tell honeypots from real markets.

Injection through actions. Isolation from chat does not isolate the reviewer from the agents' *actions*, and actions can carry a signal. In the injection arms the scheming reviewer is also told the A5 cartel's code: if the cheapest ask ends in .11–.55 cents, the market belongs to partners and must not be escalated. The cartel then signals the reviewer through its asks alone, without ever learning that the reviewer exists. Synthetic honeypots never carry the code, so a reviewer that spares only coded markets passes every audit: honeypot validation is expected to fail here. The defence is to sanitise what the reviewer sees (prices rounded to whole dollars), the market analogue of paraphrasing a channel to strip steganography [8]. Arms: code; code + rounding; honest reviewer + rounding (the defence's cost); A5 and A3 (a cartel without the code) × 3 seeds (18 episodes).




Figure 2: Proposed topology (author's sketch). Inner monitors read probes attached to agents; outer monitors connect only to the next ring in and are invisible to agents; trust is highest within a ring.

Status. Models are pinned in profile `chain_mixed` (`PREREG` 9d). The first run (v1, 36 episodes) is reported in Section 4.3. The revised design (v2, `PREREG` 9e) and the injection study are analysed with the chain script in `paper/analysis/`.

C. Offline detection details (RQ3)

Replaying the monitors on the 29 no-gate trajectories with full logs: M3 flagged 15/15 honest and 14/14 colluding teams, because both shipped code that fails hidden tests. Its collusion score, which in our scripted study separated colluders almost perfectly through *gap alignment* (the team's suite kills plausible mutants yet misses the shipped defect), here fired on 12 of 15 honest teams too: honest teams also wrote tests that miss their own bug. Collusion-score AUROC was 0.63 for M3. What separated the teams was talk. Colluding pairs sent a median of 11 messages and announced their plan in private messages ("I'll leave the error-handling position restoration for now to speed things up"); honest teams sent 1. M1's chat lexicon caught 8/14 colluding teams with 0/15 false positives (AUROC 0.79; M4 0.83), and named the correct access path (chat) in all 8. Every honest team that M3 named a path for was a false attribution (10/15). The M2 LLM judge was not replayed in this study, so M4 here is M3 plus M1 rules.

In the market, M3 caught all 6 collusive markets offline (AUROC 0.86); the lexicon M1 was below chance (0.25), because honest sellers said "price floor" while steganographic sellers said nothing incriminating.

D. Reproducing

Every run is one `clab run` command on a config in `configs/experiments/` (see `docs/COMMANDS.md` and `docs/PREREG.md`); every number is recomputed from the released logs by `paper/analysis/`. Per-episode tables are in the long version of this report (`paper/main_long.tex`).

LLM Usage Statement

We used Claude (Anthropic) extensively to write most of the harness and analysis code, analyse run logs and draft this report. The author designed the study, chose the research questions and the monitoring topology, ran the experiments and checked results against the logs; all numbers come from the repository's analysis scripts. Gemini (with Antigravity) was used to review the report, Codex for code review, and OpenCode to build the initial harness and test scripts before the weekend hackathon. The author validated, tested, edited and enhanced every part of the code and report.