

HCI Project Proposal and Preliminary Literature Review

Ajit Pawar
University of Toronto
Toronto, Ontario
ajit.pawar@mail.utoronto.ca

Colin White
University of Toronto
Toronto, Ontario
colin.white@mail.utoronto.ca

Ishan Thukral
University of Toronto
Toronto, Ontario
ishan.thukral@mail.utoronto.ca

Kyra Assaad
University of Toronto
Toronto, Canada
kyra.assaad@mail.utoronto.ca

Zach Munro-Cape
University of Toronto
Toronto, Ontario
zach.munro.cape@mail.utoronto.ca

Author Keywords
CSC428

TOPIC DESCRIPTION

As smartphone technology has evolved, multitasking is now supported on many mobile devices. This allows users to have many applications (apps) running at once and switch between them to save start up time and save state in a given app. Unlike PCs, screen real estate is much smaller on smartphones, meaning, for most devices, only one app can be in the foreground. The ability to have one app open and save state while launching another app is becoming important for users to use their devices.

The mechanism by which users swap active apps varies between devices. Sorted lists of applications, search methods, or gestures are common interactions to switch apps on smartphones.

Furthermore, having multiple apps open at once is now commonplace and encouraged by device manufacturers and app developers. For example, you may draft an email, then launch a photo editor, and then insert this edited photo into the email draft. Facebook, a company who previously had only one app, has split its flagship app into apps that correspond to functional components and encourages users to seamlessly switch between them.

This paper aims to measure the app switching speed, accuracy, and perceived success of multiple methods for a user to switch to an already open app, regain cognitive state, perform a task, and close an app down.

LITERATURE REVIEW

The research on application switchers in smartphones is quite sparse. However, there has been research conducted on the

costs of interruption when application switching to a user's workflow, as well as designing more efficient application switching interfaces for web and desktops. The results of this research help inform the design of this study.

Warr and Chi [5] explored whether a "cards"-based mobile webpage switcher, which stacks open webpages like cards in the display, would result in faster webpage switching and less errors than a "pages"-based switcher, where the webpages are displayed as pages laid out next to each other. The research revealed that it is faster to switch webpages in the cards-based interface compared to the pages-based interface, but that there was no significant difference in error rates between the two interfaces [5]. Our research will be investigating both a cards-based application switcher and a pages-based switcher for speed and error rates.

Nagata [4] examined the impact of distractions on performing a main task as well as handling a secondary task on mobile and desktop devices. The study measured the total time taken and the accuracy of completing both tasks, as well as the time to transition between tasks. One of the take-aways from this was the impact of switching apps on a mobile device on distraction time. While this device was from 2001, and there have been marked improvements in handheld devices, slow transition times between activities negatively impacted all the metrics. Determining an effective method to manage apps will allow users to use their devices and apps better overall.

Henderson and Card [1] observed that users interacting with an interface often organize tasks along a number of different dimensions, the most important of them being "locality" of tasks. The study found that users often form clusters of windows (applications) corresponding to a specific task. This insight led to development of interfaces that produce "virtual views" that allow users to focus their interactions within semantically meaningful cluster of windows. Modern smartphone multitasking interfaces sort exclusively in chronological order, so applying this clustering method to interfaces we test could improve user performance.

Leiva et al. [4] explored the cognitive costs of intended and unintended app switching and found that performing an app switch can increase completion time of a task by a factor

Paste the appropriate copyright statement here. ACM now supports three different copyright statements:

- ACM copyright: ACM holds the copyright on the work. This is the historical approach.
- License: The author(s) retain copyright, but ACM receives an exclusive publication license.
- Open Access: The author(s) wish to pay for the work to be open access. The additional fee must be paid to ACM.

This text field is large enough to hold the appropriate release statement assuming it is single spaced.

Every submission will be assigned their own unique DOI string to be included here.

of four. The authors propose several methods to reduce app switching cognitive overhead, such as replaying N milliseconds of previous UI interactions, however they do not examine the app switching mechanism itself. We plan to investigate incorporating some motion into the app switching interface itself to help users more effectively recognize the target app and regain their task state. The paper estimated app switching events to be at most 10

Leiva [2] explored different techniques to improve task resumption time in a multi-tab browser environment. Multitasking over different types of tasks can reduce productivity, lead to more errors and contrary to what we might expect, lead to a higher task completion time [2]. The study investigated the effects of a tool designed to remind users of their position on the screen prior to app switching, as well as the last interacted element and cursor position. The use of this tool improved task resumption time and task completion time. In our research we will attempt remind users of their task state using this proposed method.

REFERENCES

1. Stuart K. Card and Austin Henderson, Jr.. 1986. A multiple, virtual-workspace interface to support user task switching. In *Proceedings of the SIGCHI/GI Conference on Human Factors in Computing Systems and Graphics Interface* (CHI '87), John M. Carroll and Peter P. Tanner (Eds.). ACM, New York, NY, USA, 53-59. DOI=10.1145/29933.30860 <http://doi.acm.org/10.1145/29933.30860>
2. Luis A. Leiva. 2011. MouseHints: easing task switching in parallel browsing. In *CHI '11 Extended Abstracts on Human Factors in Computing Systems* (CHI EA '11). ACM, New York, NY, USA, 1957-1962. DOI=10.1145/1979742.1979861 <http://doi.acm.org/10.1145/1979742.1979861>
3. Luis Leiva, Matthias Bhmer, Sven Gehring, and Antonio Krger. 2012. Back to the app: the costs of mobile application interruptions. In *Proceedings of the 14th international conference on Human-computer interaction with mobile devices and services* (MobileHCI '12). ACM, New York, NY, USA, 291-294. DOI=10.1145/2371574.2371617 <http://doi.acm.org/10.1145/2371574.2371617>
4. Stacey F. Nagata. 2003. Multitasking and interruptions during mobile web tasks. In *Proceedings of the Human Factors and Ergonomics Society Annual Meeting*. 47, 11 (2003), 1341-1345.
5. Andrew Warr and Ed H. Chi. 2013. Swipe vs. scroll: web page switching on mobile browsers. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems* (CHI '13). ACM, New York, NY, USA, 2171-2174. DOI=10.1145/2470654.2481298 <http://doi.acm.org/10.1145/2470654.2481298>