Files and numbers to save during the run

1. Per-epoch training history for all five models. Save outputs/cgan_*/history/loss_history.csv and outputs/cgan_*/checkpoints/progress.json. These are excluded by .gitignore, so they exist only on your machine. Without them there is no loss curve for F and G, and both IJIES reviewers asked for the adversarial and landmark components plotted separately.

2. Epoch timing for Model A. train_A.log was overwritten by a resumed no-op relaunch. Recover epoch_seconds from outputs/cgan_A_128/checkpoints/progress.json and report the mean, the range, total seconds and total hours. Table 27 currently has four blanks in the A row.

3. Per-epoch generator-update count for Model A. The gd_ratio list inside the same progress.json. The manuscript describes an adaptive G:D update ratio but cannot state what it actually did for A.

4. Batch size actually used for Models F and G. No launch script for them is in the repository, and ARASL_BATCH defaults to 32 but is overridable. Confirm it either from the shell history or by dividing 48,645 by the steps per epoch recorded in their progress.json.

5. Landmark regressor validation error. Load outputs/cgan_B_128mp/checkpoints/landmark_regressor.weights.h5, evaluate on the same split with seed 42, and report final validation MSE and MAE, in normalised units and in pixels. Add a constant-predictor baseline — the training-set mean landmark vector applied to validation — so the reader can see the regressor learned something. This is the single largest evidential hole in the methodology, because that regressor supplies the supervision for both F and G.

6. Regressor training wall-clock time. Needed for the B row of Table 27, which currently reads <<MISSING: time>>.

7. Native pixel size of the ArASL 54K images before resizing. Read it from any image header in data/ArASL_dataset.

8. Per-class image counts. A 32-row count of the files in each class folder, plus the resulting class imbalance. Reviewer 2 explicitly listed class balance under reproducibility.

9. Qualitative description of the visual differences between models. Open real_vs_generated.png and samples_*.png and write what you actually see. The repository holds only the informal README note that A and B are blobby while C and F are sharper with occasional grid artefacts; that sentence cannot go into a journal as it stands.

Environment and software specification to record once

10. CPU model and total system RAM.
11. Exact versions of Keras, CUDA, cuDNN and the NVIDIA driver. The manuscript carries a provisional line — Intel Core i7-12700K, 32 GB RAM, Keras 3.15.0, CUDA 12.5.1, cuDNN 9, driver 560.94 — which is unverified and marked for confirmation. Capture the real values with nvidia-smi, nvcc --version, and python -c "import tensorflow as tf, keras; print(tf.__version__, keras.__version__)".
12. The exact WSL2 distribution and kernel version, plus the Windows build. Confirmed so far: RTX 3050 with 8 GB, TensorFlow 2.21, Keras 3, Python 3.11 under conda.
13. A frozen dependency list for both environments — the TensorFlow one and the separate MediaPipe CPU one. Run pip freeze > requirements_tf.txt in the first and pip freeze > requirements_mp.txt in the second, and commit both. The two cannot be merged because TensorFlow and MediaPipe require incompatible protobuf versions, and the paper should say so with the two version numbers given explicitly.
14. The MediaPipe package version used for landmark extraction, and the ArASL 54K download source and date.

Additional runs that close reviewer objections

15. One evaluation pass with a fixed seed. At present src/paper_eval.py sets no global seed, so the headline table and the confusion matrices come from two different classifier instances trained on two different sample sets, and your own manuscript admits this. Add a seed, run paper_eval.py and confusion_matrix.py back to back from that one classifier, and print the classifier checkpoint path, its modification time, the seed and the samples per class in both logs. This single run removes an objection you are currently handing to the reviewer yourself.
16. Full per-class accuracy for all five models — a 32-value vector each, not only the eight weakest. confusion_summary.json stores only the worst classes and the twelve largest confusions, but your Table 17 needs the complete set.