


# Internal Forces and Moments Problem

## Question:


The structure below which consists of two 'L' forming beams is fixed to the ground at Point A. A distributive load is acting on both beams along with a weight  $M_1$  hanging from the horizontal beam at an angle of  $45^\circ$ . Disregard the thickness of the beams for this question.



- Draw FBD's for the forces and moments acting on the beams
- Generate force and torque equations for the structure considering it's in equilibrium
- Solve for reaction forces and torques about point A and B
- Draw a free body diagram of the internal forces on the horizontal beam
- Draw an internal shear force, normal force and bending moment diagram for the horizontal beam

**Solutions :**

a)



b)

**Forces acting on Beam AB:**

$$\sum F_x = 0 = A_x + B_x + \int_{L_1}^{L_2} W_{AB} dx$$

$$\sum F_y = 0 = -A_y + B_y$$

**Torque about Point A (Beam AB):**

$$\sum \tau_A = 0 = M_A - \int_{L_1}^{L_2} W_{AB} * x dx - 12 * B_x$$

Forces acting on Beam BC:

$$\sum F_x = 0 = -B_x + M_1 \sin(\theta)$$

$$\sum F_y = 0 = -B_y - M_1 \cos\theta + \int_{L_1}^{L_2} W_{BC} dx$$

Torque about Point B (Beam BC):

$$\sum \tau_B = 0 = M_B - 5 * M_1 \cos\theta + \int_{L_1}^{L_2} W_{BC} * x dx$$

$$\text{Where, } M_1 = 200, \theta = 45^\circ, W_{AB}(x) = 140 \left(1 - \frac{x}{5}\right), W_{BC}(x) = \frac{180x}{5}$$

c) Maple Code:


```
restart;
M1:= 200;
theta:=45*3.14159/180;
wab:=140*(1-x/5);
wbc:=(180*x)/5;
solve([
Ax+Bx+int(wab, x=7..12),
-Ay+By,
MA-int(wab*x, x=7..12)-12*Bx,
-Bx+M1*sin(theta),
-By-M1*cos(theta)+int(wbc, x=8..13),
MB-5*M1*cos(theta)+int(wbc*x, x=8..13)]);
```

Forces (N) and Moments (N.m):

$$\{A_x = 488.5787376, A_y = 1748.578550, B_x = 141.4212624,$$

$$B_y = 1748.578550, M_A = -4579.611518, M_B = -19512.89275\}$$

- d) In order to accurately describe the internal forces acting on the beam, the beam was sliced at a point before the acting forces and then at a point after the first force.



- e) Maple Code:


```
restart;
M1:= 200;
theta:=45*3.14159/180;
wab:=140*(1-x/5);
wbc:=(180*x)/5;
solve([
Ax+Bx+int(wab, x=7..12),
-Ay+By,
MA-int(wab*x, x=7..12)-12*Bx,
-Bx+M1*sin(theta),
-By-M1*cos(theta)+int(wbc, x=8..13),
MB-5*M1*cos(theta)+int(wbc*x, x=8..13)]);
N:=piecewise(x>5, -M1*sin(theta));
V:=piecewise(x>5, M1*cos(theta))+piecewise(x>8, int(-wbc, x=0..x));
M:=piecewise(x>5, -M1*cos(theta)*5)+piecewise(x>8, int(wbc*x, x=0..x));
plot([N, V, M], x=0..13);
```

$$\{Ax = 488.5787376, Ay = 1748.578550, Bx = 141.4212624, By = 1748.578550, MA = -4579.611518, MB = -19512.89275\}$$

$$N := \begin{cases} -141.4212624 & 5 < x \\ 0 & \text{otherwise} \end{cases}$$

$$V := \left( \begin{cases} 141.4214501 & 5 < x \\ 0 & \text{otherwise} \end{cases} \right) + \left( \begin{cases} -18x^2 & 8 < x \\ 0 & \text{otherwise} \end{cases} \right)$$

$$M := \left( \begin{cases} -707.1072505 & 5 < x \\ 0 & \text{otherwise} \end{cases} \right) + \left( \begin{cases} 12x^3 & 8 < x \\ 0 & \text{otherwise} \end{cases} \right)$$



Observing the graph of varying internal forces, we see that the normal force in the beam is zero until  $x=5$  which is where a horizontal force acts. The normal force increases in the opposite direction here to counter act that force and remains constant throughout as there are no other  $x$ -component forces. The internal shear force increases slightly in the upwards(positive) direction after  $x=5$  where a relatively small downward force acts on the beam and then begins to increase significantly in the downwards direction after  $x=8$  which is where the distributive force begins to act on the beam. The internal bending moment force also does the same thing but in opposite directions. After  $x=8$ ,  $M$  increases in the counter clockwise direction drastically. The results were as expected and hence we can conclude that we have done everything correctly.