

Summary report

Wellbore: 15/9-19 ST2

Period: 1997-07-18 00:00 - 1997-07-19 00:00

Status:	normal
Report creation time:	2018-05-03 13:53
Report number:	3
Days Ahead/Behind (+/-):	
Operator:	Statoil
Rig Name:	BYFORD DOLPHIN
Drilling contractor:	
Spud Date:	1992-09-15 01:00
Wellbore type:	
Elevation RKB-MSL (m):	25
Water depth MSL (m):	84
Tight well:	Y
HPHT:	Y
Temperature (I):	
Pressure (I):	
Date Well Complete:	1993-01-28

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (I):	
Pressure Test Type:	
Formation strength (I):	
Dia Last Casing (I):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMD:	-999.99
Depth mTVD:	
Plug Back Depth mMD:	
Depth at formation strength mMD:	
Depth At Formation Strength mTVD:	
Depth At Last Casing mMD:	4643
Depth At Last Casing mTVD:	

Summary of activities (24 Hours)

REMOVED PROTECTION HATCH FROM SLOT S3. INSTALLED 2 GUIDE WIRES.
RECOVERED CORROSION CAP. PICKED UP DRILL PIPE WHILE WORKING ON BOP.

Summary of planned activities (24 Hours)

- COMPLETE PREPARATION/WORK ON BOP WHILE P/U DP / BHA
- RUN BOP AND RISER
- INSTALL WEAR BUSHING
- M/U AND RIG W/ 8-1/2" ROTARY DRLG BHA
- DRILL OUT 200 M SURFACE CMT PLUG

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	01:00	0	moving -- position	ok	RIGGED DOWN BOP SET UP.
01:00	06:00	0	drilling -- other	ok	PREPARED FOR REMOVING HATCH FROM SLOT S3. LOWERED RETR. FRAME DOWN ONTO TEMPLATE BY USING CRANE. RE-POSITIONED RIG WHILE REMOVING TWO LOCKING BOLTS FROM HATCH BY USING ROV. RAN ROV-HOOK/SLINGS ON DP. CONN. TO RETR. FRAME. WORKED TO ENGAGE RETR. FRAME INTO HATCH.
06:00	09:00	0	drilling -- other	ok	RETRIEVED PROTECION HATCH FROM SLOT S3. PARKED SAME ON TOP OF TEMPLATE STRUCTURE.
09:00	11:00	0	drilling -- other	ok	CONNECTED GUIDE-LINES ON POSTS NO. 2 AND NO. 3, ASSISTED BY ROV. POOH W/ DP AND SLINGS. MOVED RIG OFF LOCATION.
11:00	12:00	0	drilling -- other	ok	M/U CORROSION CAP RT ON DP.
12:00	14:30	0	drilling -- other	ok	MOVED RIG OVER LOCATION.
14:30	18:30	0	drilling -- other	ok	ATTEMPTED TO RETR. CORR. CAP ON DP. NEG. RAN RETR. TOOL ON TUGGER. RETRIEVED CORR. CAP ASSISTED BY ROV.
18:30	20:30	0	drilling -- other	ok	MOVED RIG OFF LOCATION.
20:30	21:30	0	drilling -- trip	ok	P/U AND M/U FMC EMERGENCY HANGOFF TOOL. RACKED SAME IN DERRICK.
21:30	00:00	0	drilling -- trip	ok	P/U 5" DP WHILE PREPARING BOP.