

Summary report

Wellbore: 15/9-19 ST2

Period: 1993-01-20 00:00 - 1993-01-21 00:00

Status:	normal
Report creation time:	2018-05-03 13:53
Report number:	82
Days Ahead/Behind (+/-):	
Operator:	Statoil
Rig Name:	TREASURE PROSPECT
Drilling contractor:	UNKNOWN
Spud Date:	1992-09-15 01:00
Wellbore type:	
Elevation RKB-MSL (m):	22
Water depth MSL (m):	84
Tight well:	Y
HPHT:	Y
Temperature (°):	
Pressure (°):	
Date Well Complete:	1993-01-28

Dist Drilled (m):	-999.99
Penetration rate (m/h):	-999.99
Hole Dia (in):	12.25
Pressure Test Type:	
Formation strength (g/cm3):	1.73
Dia Last Casing (°):	

Depth at Kick Off mMD:	
Depth at Kick Off mTVD:	
Depth mMd:	3580
Depth mTVD:	2405.8
Plug Back Depth mMD:	
Depth at formation strength mMD:	1482
Depth At Formation Strength mTVD:	1270
Depth At Last Casing mMD:	3569.3
Depth At Last Casing mTVD:	2399

Summary of activities (24 Hours)

DRILLED CMT IN 9 5/8" CASING FROM 2510 TO 3040 M

Summary of planned activities (24 Hours)

DRILL CMT, FLOAT AND SHOE
CIRC HOLE CLEAN
POOH
RETRIEVE WB
RETRIEVE SEAL ASSY
INSTALL SEAL ASSY
M/U RTTS PACKER AND RIH TO 195 M

Operations

Start time	End time	End Depth mMD	Main - Sub Activity	State	Remark
00:00	04:30	2502	drilling -- casing	ok	CONT RIH FROM 170 TO 2502 M BROKE CIRC EVERY 500 M
04:30	06:00	2510	drilling -- casing	ok	DRILLED DART PLUG FROM 2502 M, CONTINUED DRILLING CMT FROM 2502,5 TO 2510 M
06:00	00:00	2937	drilling -- casing	ok	CONTINUED DRILLING WITH 8 1/2" BIT IN 9 5/8" CASING FROM 2510 TO 2937 M

Drilling Fluid

Sample Time	22:30
Sample Point	Flowline
Sample Depth mMD	3580
Fluid Type	PETROFREE
Fluid Density (g/cm3)	1.55
Funnel Visc (s)	113
Mf (°)	
Pm (°)	
Pm filtrate (°)	
Chloride (°)	
Calcium (°)	
Magnesium (°)	
Ph	
Excess Lime (°)	
Solids	
Sand (°)	
Water (°)	
Oil (°)	
Solids (°)	
Corrected solids (°)	
High gravity solids (°)	
Low gravity solids (°)	
Viscometer tests	
Plastic visc. (mPa.s)	55
Yield point (Pa)	11
Filtration tests	
Pm filtrate (°)	
Filtrate Lthp (°)	
Filtrate Hthp (°)	
Cake thickn API (°)	
Cake thickn HPHT (°)	
Test Temp HPHT (°)	
Comment	

Casing Liner Tubing

Start Time	
End Time	
Type of Pipe	Casing
Casing Type	
Outside diameter (in)	9.625
Inside diameter ()	
Weight (lbm/ft)	53.5
Grade	C-95
Connection	AntaresMS
Length (m)	3464.3
Top mMD	105
Bottom mMD	3569.3
Description	
Comment	