

MATERIAL SAFETY DATA SHEET

1. CHEMICAL IDENTITY

Chemical Name : Jute Batching Oil
Synonyms : JBO/ Wash Oil

Chemical classification : *Fuel & Solvent*
Trade Name : *JBO*

Formula : *A Complex Mixture of hydrocarbons*

C.A.S. No.

U.N.No. : *1202*

Regulated Identification Shipping Name : *JBO*
Codes / Label : *Class C Petroleum Oil*

Hazchem No. : *3 Z*
Hazardous Waste I.D No. : *5*

HAZARDOUS INGREDIENTS

C.A.S. No.

2. PHYSICAL AND CHEMICAL DATA

Boiling Range : *240 to 371°C* Physical state : *Liquid @ 15°C & 1 atm* Appearance: *yellow to oily brown*
Vapour pressure: *< 0.1 psi @ 38°C* Odour : *Characteristic*
Freezing point: *9°C* Others: *Insoluble and floats in water*
Vapour Density: *3.0 to 5.0 (Air = 1)*
Specific Gravity: *0.850 gm/ml @ 15°C* pH: *Not pertinent*

3. FIRE AND EXPLOSION HAZARD DATA

Flammability : *Yes* LEL : *0.5 %* Flash Point : *> 130°C min* (CC)
TDG Flammability : *3* UEL : *5.0 %* Flash Point : *> 135°C min* (OC)

Auto ignition Temperature : *290 - 300°C*
Explosion sensitivity to impact : *Stable*
Explosion sensitivity to static Electricity : *Stable*
Hazardous Combustion Products : *Acrid smoke and irritating fumes of CO / CO₂ / NO_x*
Hazardous Polymerization : *Does not occur*

Combustible Liquid : *Yes* Explosive Material : *No* Corrosive Material : *No*
Flammable Material : *Yes* Oxidiser : *No* Others : *No*
Pyrophoric Material : *No* Organic Peroxide : *No*

4. REACTIVITY DATA

Chemical Stability : *Chemically Stable*
Incompatibility with other material : *Incompatible with strong oxidisers.*
Reactivity : *Does not react with common materials but may react with oxidising agents.*
Hazardous Reaction products : *Data not available*

5. HEALTH HAZARD DATA

Routes of entry: *Inhalation / Ingestion / Skin / Eye*

Effects of Exposure / : *Inhalation : Dizziness, headache*
Symptoms : *and bluish tint to the skin.*
: *Ingestion : Nausea and vomiting. Irritation of mouth and gastro intestinal tract may follow, rapidly developing potentially fatal chemical*
Skin : *Irritation, will remove fat from the skin. Prolonged or repeated contact should be avoided, otherwise skin chapping, cracking or possible contact dermatitis may occur. Dry skin, erythema, oil acne, and oil folliculitis & watery growth may occur which may become skin cancer subsequently on repeated exposure.*

Emergency Treatment : *If inhaled, Remove victim to fresh air, give artificial respiration if required, remove contaminated clothing quickly, do not induce vomiting if ingested, keep victim warm and quiet. Wash all the affected skin thoroughly with soap and water. Irrigate affected eyes with copious amount of water. Administration of Olive oil or any other vegetable oil may reduce adsorption thru digestive tract. Gastric lavage should be done only after endotracheal intubation in view of respiration which may cause serious chemical pneumonitis for which antibiotic and corticosteroid therapy may be indicated.*

NFPA Hazard signal Health : 1 Flammability : 3 Reactivity : 0 Special : Nil

Personnel Protective Equipment : Avoid contact with liquid or vapour.
Use gum boots, gloves while handling the product.

Handling & Storage Precautions : *Store in dry, cool, ventilated area away from heat and flame.
Keep away from oxidising agents*

FIRE	Fire Extinguishing Media	: Foam / DCP / CO ₂ .
	Special Procedures	: <i>Keep the containers cool by spraying water if exposed to fire.</i>
	Unusual Hazards	: <i>Flashback may occur along vapour trail.</i>

EXPOSURE	First Aid Measures : <i>A/a</i>	Antidotes / Dosages : <i>Not available</i>
----------	---------------------------------	--

SPILLS	Steps to be Taken	: Shut off leaks without risk. Contain leaking liquid on sand or earth Prevent liquid from entering into sewers.
	Waste Disposal Method	: Seal all the waste in vapour tight plastic bags for eventual disposal.

8. ADDITIONAL INFORMATION / REFERENCES

9. MANUFACTURERS / SUPPLIERS DATA : HINDUSTAN PETROLEUM CORPORATION LIMITED

Information contained in this material data sheet is believed to be reliable but no representation, guarantee or warranties of any kind are made as to its accuracy, suitability for a particular application or results to be obtained from them. It is upto the end user to ensure that information contained in the material safety data sheet is relevant to the product manufactured / handled or sold by him as the case may be and H.P.C.L. makes no warranties expressed or implied in respect of adequacy of this document for any particular purpose.