

	HINDUSTAN PETROLEUM GREEN R&D CENTRE, KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, HOSKOTE TALUK, BANGALORE-560067 Ph: 080-28078521/080-28078524 MATERIAL SAFETY DATA SHEET- HP-CIC
---	--

SECTION I - PRODUCT IDENTIFICATION

Product Name	HP-CIC
Chemical Application	To provide thermal insulating coating on containers/vessels operating in cold conditions
Address	Hindustan Petroleum Green R&D Centre, KIADB industrial area, Tarabahalli village, Devanagundi, Hoskote Taluk, Bangalore-560067 Contact No: +91 802-807-8691

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT(S)	Amount
100% solids epoxy resin & Amido-amine hardener	60-80%
Trade Secret Insulation Media	7-15%
Proprietary fillers	3 - 8%

The product has a shelf life of 1 year if it is stored in the original container between 18-25 degC away from humidity and excessive heat. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION III - HAZARDS IDENTIFICATION

The product has been classified as per GHS Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)



Skin Irritant (Category 2), H315
 Skin Sensitizer (Category 1), H317
 Eye Irritant (Category 2), H319 Eye Damage (Category 1); H318
 Single Target Organ Toxicity (STOT) – single exposure (Category 3) Respiratory, H335
 Hazardous to the aquatic environment, (Acute, Category 2), H401
 Hazardous to the aquatic environment, (Chronic, Category 2), H411
 Acute Toxicity (Oral, Category 4); H302
 Acute Toxicity (Category 3); H312




HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE,
HOSKOTE TALUK, BANGALORE-560067
Ph: 080-28078521/080-28078524

MATERIAL SAFETY DATA SHEET- HP-CIC

Skin Corrosion, (Category 2); H314
Skin Sensitization (Category 1); H317 Serious
Specific Target organ Toxicity (Oral, Category 2); H373a
Aquatic Toxicity (Acute, Category 2); H401
Aquatic Toxicity (Chronic, Category 3); H412

Hazard determining component(s): Epoxy phenol novolac resin, Trimethylol propane triglycidyl ether Benzene-1,3-dimethanamine (MXDA), Methylene oxide, polymer with benezamine, hydrogenated Benzyl Alcohol, Methylenebiscyclohexane, 4-4'-Polyoxypropylenediamine

NFPA Rating



SECTION IV - FIRST AID MEASURES

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Immediately move the exposed person to fresh air. If breathing is difficult, properly trained personnel may administer oxygen. If breathing has stopped, perform artificial respiration. Get medical attention immediately.

After skin contact:

Immediately wash the contaminated skin with soap and water. If this chemical penetrates the clothing, immediately remove the clothing, wash the skin with soap and water, and get medical attention.

After eye contact:

Immediately wash the eyes with large amounts of water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately. Contact lenses should not be worn when working with this chemical.



HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE,
HOSKOTE TALUK, BANGALORE-560067
Ph: 080-28078521/080-28078524

MATERIAL SAFETY DATA SHEET- HP-CIC

After swallowing:

If large quantities have been swallowed, DO NOT INDUCE VOMITING. If victim is conscious and alert, give 2 - 4 cups of lukewarm water. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to help prevent aspiration. Get medical attention immediately.

SECTION V - FIRE- FIGHTING MEASURES

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

Unusual Fire and Fire explosion:

Isolate fire area and deny unnecessary entry.

Fire fighters should wear positive-pressure self-contained breathing apparatus (SCBA) and protective clothing.

Cool container with WATER SPRAY to prevent rupture.

Heat and fire can generate toxic or irritating decomposition products that may cause a health hazard. Sudden reaction and fire may result if product is mixed with an oxidizing agent.

Protective equipment:

Wear a self-contained respiratory protective device

Mouth respiratory protective device.

SECTION VI- ACCIDENTAL RELEASE MEASURES

Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into the water course or sewage system.

Do not allow to enter sewers/ surface or groundwater.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste accordingly.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents



HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE,
HOSKOTE TALUK, BANGALORE-560067
Ph: 080-28078521/080-28078524

MATERIAL SAFETY DATA SHEET- HP-CIC

SECTION VII - HANDLING AND STORAGE

Handling:

Information for safe handling:

Ensure good ventilation/exhaustion at the workplace. Prevent the formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep the lid tightly sealed.

Store material in a clean, cool, ventilated area away from all sources of ignition. Clean up spills at once. Keep container tightly closed when not in use. Always wear protective equipment.

This material adheres readily to human skin (e.g. hands) and may be inadvertently ingested while eating. Wash hands and other exposed areas thoroughly after handling. Launder all clothes after each use.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure eyewash stations and safety showers are close to the workstation location
PERSONAL PROTECTIVE EQUIPMENT	
Eyes and Face	Avoid contact with eyes. Wear chemical splash goggles or safety glasses with a side shield
Skin	Wear chemical-resistant gloves and other clothing as required to minimize contact
Respiratory	Use respiratory protection if ventilation is improper
Comments	Use a face shield, PVC gloves, and safety boots while handling



HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE,
HOSKOTE TALUK, BANGALORE-560067
Ph: 080-28078521/080-28078524

MATERIAL SAFETY DATA SHEET- HP-CIC

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Color	Off-white
Boiling Point/ range	201°C
Density (at 25°C)	1.18 - 1.19 g/cm ³
Solubility In Water	Not miscible or difficult to mix

SECTION X - STABILITY AND REACTIVITY

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Materials to be avoided: Strong Oxidising agents, Strong Alkalis, Strong Bases, Amines

Dangerous reactions

Reacts with amines with exothermic reaction liberating heat and fumes

Dangerous products of decomposition: No dangerous decomposition products are known

SECTION X - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS

- Harmful if swallowed, inhaled, or absorbed through the skin
- Practically non-toxic if absorbed following acute (single) exposure.
- May cause skin irritation with prolonged or repeated contact. The liquid may be absorbed through the skin in toxic amounts if large areas of skin are exposed repeatedly
- Contact with the eyes may cause moderate to severe irritation
- Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting, and diarrhea

SECTION XI - ECOLOGICAL INFORMATION

Ecological effects:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow the product to reach groundwater, water course, or sewage system.

Danger to drinking water if even small quantities leak into the ground.

	HINDUSTAN PETROLEUM GREEN R&D CENTRE, KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, HOSKOTE TALUK, BANGALORE-560067 Ph: 080-28078521/080-28078524 MATERIAL SAFETY DATA SHEET- HP-CIC
---	--

SECTION XII - DISPOSAL CONSIDERATIONS

- Ensure waste disposal conforms to central (Govt. of India), State, and local environmental regulations
- Material may be solidified with cement and disposed of according to local, state, regional, and Federal regulations.
- Must not be disposed of together with household garbage. Do not allow products to reach the sewage system
- Recommended landfill at the approved land waste site.

SECTION XIII - TRANSPORT INFORMATION

DOT	UN1866, Resin Solution,3,III, Hazard Class 3
IATA	UN1866,Resin Solution,3,III, Hazard Class 3
IMDG	UN1866,Resin Solution,3,III, Hazard Class 3

SECTION XIV – REGULATORY INFORMATION

The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer 's responsibility to ensure that its activities comply with federal, state or provincial and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial and local laws and regulations.

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Sec. 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Sec. 313.

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right to Know Components

Benzyl Alcohol

Pennsylvania Right to Know Components

Benzyl Alcohol

Polyoxypropylene diamine

CAS #	Revision
	Date
100-51-6	1993-04-24
CAS #	Revision
	Date
100-51-6	1993-04-24
9046-10-0	

	HINDUSTAN PETROLEUM GREEN R&D CENTRE, KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, HOSKOTE TALUK, BANGALORE-560067 Ph: 080-28078521/080-28078524 MATERIAL SAFETY DATA SHEET- HP-CIC
---	--

New Jersey Right to Know Components

Benzyl Alcohol
Polyoxypropylene diamine

CAS #

100-51-6
9046-10-0

Revision

Date

1993-04-24

SECTION XV – Other information, including date of preparation and revision

The information and recommendations in this sheet and on the labels are to the best of our knowledge reliable. However, nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purpose.

Disclaimer: Any concentration shown as a range is to project confidentially or is due to batch variation.

Issue Date: 15.05.2024

Version: 1

Contact Person:

Deepashri D. Nage
DGM- Corrosion Research Lab
HP-Green R & D Center, Bengaluru
Contact No: +91 802-807-8691