

	CONFIDENTIAL
	HP DWA V2 for BS grade at Propane Dewaxing Unit

MATERIAL SAFETY DATA SHEET (MSDS) (HP DWA Version 2)



	CONFIDENTIAL
	HP DWA V2 for BS grade at Propane Dewaxing Unit

Section 1. Chemical Product and Company Identification

Product Name	HP DWA Version 2
Product No.	NA
Application	Lube Oil
Supplier	HPCL R&D Centre, Bangalore
Emergency Telephone	080-28078520

Identified uses: Used for improving BS grade lube oil properties. HPCL R&D product

Section 2. Hazards Identification

Hazard Identification:

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2) H225

Skin irritation (Category 2), H315

Reproductive toxicity (Category 2), H361d

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Specific target organ toxicity - repeated exposure (Category 2), H373

Aspiration hazard (Category 1), H304

Gummy and high viscous liquid; slight odor

Label elements:

Labelling according Regulation (EC) No 1272/2008

Pictogram



Hazard statement(s)

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

HPCL Green R&D Center

	CONFIDENTIAL
	HP DWA V2 for BS grade at Propane Dewaxing Unit

Precautionary statement(s):

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapors.

P281 Use personal protective equipment as required.

P301 + P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

Supplemental Hazard Statements: None

Safety Phrases

Use personal protection equipment and ammonia risk methods. This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Section 3. First Aid Measures

Description of first aid measures:

- General advice: ***Always seek professional medical attention after first aid measures are provided.*** Show this safety data sheet to the doctor in attendance.
- If inhaled: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
- In case of skin contact: Wash off with soap and plenty of water. Consult a physician.
- In case of eye contact: Flush eyes with water as a precaution.
- If swallowed: Do NOT induce vomiting. Never give anything by mouth to an unconscious person.
- Rinse mouth with water. Consult a physician.
- Most important symptoms and effects, both acute and delayed
- The most important known symptoms and effects are described in the labelling
- Indication of any immediate medical attention and special treatment needed: No data available



CONFIDENTIAL

HP DWA V2 for BS grade at Propane Dewaxing Unit

Section 4. Composition and Information on Ingredients

Name	CAS No:	Content
Polymer (M. Wt. 5000-40000)		70 to 95 %
Organic aromatic solvent		5 to 30 %

SECTION 5: Firefighting measures

- Extinguishing media: Suitable extinguishing media
- Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Special hazards arising from the substance or mixture: Carbon oxides
- Advice for firefighters: Wear self-contained breathing apparatus for firefighting if necessary.
- Further information: Use water spray to cool unopened containers

SECTION 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.
- Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.
- Methods and materials for containment and cleaning up: Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

SECTION 7: Handling and storage

- Precautions for safe handling: Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.
- Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.
- Conditions for safe storage, including any incompatibilities: Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Storage class (TRGS 510): Flammable liquids
- Specific end use(s): Apart from the uses mentioned in section 1 no other specific uses are stipulated



CONFIDENTIAL

HP DWA V2 for BS grade at Propane Dewaxing Unit

SECTION 8: Exposure controls/personal protection

Control parameters

- Exposure controls: Appropriate engineering controls
- Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
- Personal protective equipment: Eye/face protection
- Face shield and safety glasses. Use equipment for eye protection tested and approved under
- Appropriate government standards such as NIOSH (US) or EN 166(EU).
- Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.
- The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and The standard EN 374 derived from it.
- Body Protection: Complete suit protecting against chemicals, Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
- Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use (US) or type ABEK (EN 14387) respirator cartridges as a backup to enginee protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Control of environmental exposure
- Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

- a) Appearance Form: Viscous Liquid
- b) Odour: Odourless
- c) Odour Threshold: NA
- d) pH: NA
- e) Melting point: ~ 30 °C
- f) Initial boiling point and boiling range: 375 °C, boiling range: 370-460 °C
- g) Flash point: > 50 °C
- h) Evaporation rate : NA
- i) Flammability (solid, gas): NA
- j) Upper/lower flammability or explosive limits: No data available
- k) Vapour pressure: No data available
- l) Vapour density: No data available
- m) Relative density: 0.915 g/mL at 25 °C

	CONFIDENTIAL
	HP DWA V2 for BS grade at Propane Dewaxing Unit

- n) Water solubility: Not soluble
- o) Auto-ignition temperature: NA
- p) Decomposition: temperature: 380-430 °C
- q) Viscosity: @40 °C: 110-130 mm²/s, @100 °C: 25-28 mm²/s
- r) Explosive properties: Stable
- s) Oxidizing properties: NA

SECTION 10: Stability and reactivity

- Reactivity: polymer material and not reactive
- Chemical stability: Stable under recommended storage conditions.
- Possibility of hazardous reactions: No
- Conditions to avoid: Heat, flames and sparks.
- Incompatible materials: Strong oxidizing agents
- Hazardous decomposition products: Hazardous decomposition products formed under fire conditions. - Carbon oxides
- Other decomposition products – acrylates
- In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects:

Acute toxicity: No data available

Skin corrosion/irritation: No data available

Serious eye damage/eye irritation: No data available

Respiratory or skin sensitization: No data available

Germ cell mutagenicity: No data available

Carcinogenicity: IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene)

Reproductive toxicity: No data available

Specific target organ toxicity - single exposure: No data available

Specific target organ toxicity - repeated exposure: No data available

Aspiration hazard: No data available

Additional Information: RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been

	CONFIDENTIAL
	HP DWA V2 for BS grade at Propane Dewaxing Unit

thoroughly investigated.

SECTION 12: Ecological information

- Toxicity: No data available
- Persistence and degradability: No data available
- Bioaccumulative potential: No data available
- Mobility in soil: No data available
- Results of PBT and vPvB assessment: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
- Other adverse effects: Toxic to aquatic life.

SECTION 13: Disposal considerations

Waste treatment methods:

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging: Dispose of as unused product.

SECTION 14: Transport information

UN number

ADR/RID: 1294 or similar IMDG: 1294 or similar IATA: 1294 or similar

UN proper shipping name ADR/RID: m-Xylene, SOLUTION IMDG: m-Xylene, SOLUTION IATA: Xylene, SOLUTION

Transport hazard class(es) ADR/RID: 3 IMDG: 3 IATA: 3 or similar

Packaging group ADR/RID: II IMDG: II IATA: II or similar

Environmental hazards ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Chemical safety assessment: For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

	CONFIDENTIAL
	HP DWA V2 for BS grade at Propane Dewaxing Unit

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Further information

The information in the MSDS is based on data which is considered to be accurate. However, we makes no guarantees or warranty, either expressed or implied on the accuracy or completeness of this information. The conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. This MSDS was prepared and is to be used for this product. If the product is used as a component in another product, this MSDS information may not be applicable