

	HINDUSTAN PETROLEUM GREEN R&D CENTRE, KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, HOSKOTE TALUK, BANGALORE-560067 Ph: 080-28078521/080-28078524 MATERIAL SAFETY DATA SHEET- HP-TIC
---	--

SECTION I - PRODUCT IDENTIFICATION

Chemical Name	HP-TIC
Chemical Application	To provide thermal insulation and corrosion protection

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT(S)	Amount
Epoxy resin & Polyamine hardener	50-70%
TiO ₂	5-10%
Trade Secret Insulation Media	7-15%
Extender Pigments	8-15%

The product has a shelf life of 1 year if it is stored in the original container between 18-25 degC away from humidity and excessive heat. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION III - HAZARDS IDENTIFICATION


The product has to be labeled due to the calculation procedure of international guidelines.

H373 May cause damage to organs through prolonged or repeated exposure
H314 Causes severe skin burns and eye damage
H318 Causes serious eye damage.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction



	HINDUSTAN PETROLEUM GREEN R&D CENTRE, KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, HOSKOTE TALUK, BANGALORE-560067 Ph: 080-28078521/080-28078524 MATERIAL SAFETY DATA SHEET- HP-TIC
---	--

NFPA Rating



SECTION IV - FIRST AID MEASURES

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor. In case of unconsciousness place the patient stably in the side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eyes for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

If symptoms persist consult a doctor.

SECTION V - FIRE- FIGHTING MEASURES

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

Protective equipment:

Wear a self-contained respiratory protective device

Mouth respiratory protective device.

SECTION VI- ACCIDENTAL RELEASE MEASURES

Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into the water course or sewage system.

	HINDUSTAN PETROLEUM GREEN R&D CENTRE, KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, HOSKOTE TALUK, BANGALORE-560067 Ph: 080-28078521/080-28078524 MATERIAL SAFETY DATA SHEET- HP-TIC
--	---

Do not allow to enter sewers/ surface or groundwater.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste accordingly.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

SECTION VII - HANDLING AND STORAGE

Handling:

Information for safe handling:

Ensure good ventilation/exhaustion at the workplace. Prevent the formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep the lid tightly sealed.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure eyewash stations and safety showers are close to the workstation location
PERSONAL PROTECTIVE EQUIPMENT	
Eyes and Face	Avoid contact with eyes. Wear chemical splash goggles or safety glasses with a side shield
Skin	Wear chemical-resistant gloves and other clothing as required to minimize contact
Respiratory	Use respiratory protection if ventilation is improper
Comments	Use a face shield, PVC gloves, and safety boots while handling

	HINDUSTAN PETROLEUM GREEN R&D CENTRE, KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, HOSKOTE TALUK, BANGALORE-560067 Ph: 080-28078521/080-28078524 MATERIAL SAFETY DATA SHEET- HP-TIC
--	--

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Color	Off-white
Boiling Point/ range	201°C
Density (at 25°C)	1.18 - 1.19 g/cm ³
Solubility In Water	Not miscible or difficult to mix

SECTION X - STABILITY AND REACTIVITY

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Materials to be avoided: Strong Oxidising agents, Strong Alkalis, Strong Bases, Amines

Dangerous reactions

Reacts with amines with exothermic reaction liberating heat and fumes

Dangerous products of decomposition: No dangerous decomposition products are known

SECTION X - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS

- Harmful if swallowed, inhaled, or absorbed through the skin
- Practically non-toxic if absorbed following acute (single) exposure.
- May cause skin irritation with prolonged or repeated contact. The liquid may be absorbed through the skin in toxic amounts if large areas of skin are exposed repeatedly
- Contact with the eyes may cause moderate to severe irritation
- Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting, and diarrhea

SECTION XI - ECOLOGICAL INFORMATION

Ecological effects:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow the product to reach groundwater, water course, or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION XII - DISPOSAL CONSIDERATIONS

	HINDUSTAN PETROLEUM GREEN R&D CENTRE, KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, HOSKOTE TALUK, BANGALORE-560067 Ph: 080-28078521/080-28078524 MATERIAL SAFETY DATA SHEET- HP-TIC
---	--

- Ensure waste disposal conforms to central (Govt. of India), State, and local environmental regulations
- Material may be solidified with cement and disposed of according to local, state, regional, and Federal regulations.
- Must not be disposed of together with household garbage. Do not allow products to reach the sewage system
- Recommended landfill at the approved land waste site.

SECTION XIII - TRANSPORT INFORMATION

DOT	UN1866, Resin Solution,3,III, Hazard Class 3
IATA	UN1866,Resin Solution,3,III, Hazard Class 3
IMDG	UN1866,Resin Solution,3,III, Hazard Class 3

SECTION XIV - OTHER INFORMATION

The information and recommendations in literature and on labels are to the best of our knowledge reliable. However, nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purpose.

Disclaimer: Any concentration shown as a range is to project confidentially or is due to batch variation.

Contact Person:

Deepashri Dattatray Nage
DGM- Corrosion Research Lab
HP-Green R & D Center, Bengaluru
Contact No: 802-807-8691