

Material Safety Data Sheet

**HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, DEVANAGUNDI,
HOSKOTE TALUK, BANGALORE-560067.**

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT (Product Name): HP- PoWer 100 additive

Product Description: Fuel Additive for BSVI Gasoline/ Motor Spirit

COMPANY IDENTIFICATION (Supplier):

Hindustan petroleum green R&D Centre, KIADB industrial area, Tarabahalli village, Devanagundi, Hoskote Taluk, Bangalore-560067. Ph: 080-2807 8521 / 25

2.COMPOSITION / INFORMATION ON INGREDIENTS

CAS No: NA, Blend of chemicals

Composition: Mix of Hydrocarbons

Name	Content, % by Vol
Olefinic Hydrocarbon	30-40
Aromatic Hydrocarbon	60-70

3. HAZARDS IDENTIFICATION

Primary Entry Routes: Inhalation, skin and eyes

Flammable liquids: Category 4

Acute oral toxicity: Category 4

Acute dermal toxicity: Category 3

Acute Inhalation Toxicity: Category 3 (Vapors)

Specific target organ toxicity (repeated exposure): Category 2

GHS classification:

NFPA Rating



Health hazard: 4

Fire: 3

Reactivity Hazard: 0

Potential Health Effects

Inhalation Toxic if inhaled. Causes respiratory tract irritation.

Skin Harmful if absorbed through skin. Causes skin irritation.

Eyes Causes eye irritation.

Ingestion Harmful if swallowed.

Material Safety Data Sheet

**HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, DEVANAGUNDI,
HOSKOTE TALUK, BANGALORE-560067.**

4. FIRST AID MEASURES

- **In case of skin contact:** Wash off with soap and plenty of water. Consult a physician. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse
- **In case of eye contact:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Ensure adequate flushing of the eyes
- **If inhaled:** If breathed in, move person into fresh air. If not breathing properly, give artificial respiration/ oxygen. Consult a physician.
- **If swallowed:** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician

5. FIRE FIGHTING MEASURES

- Suitable Extinguishing Media: Carbon dioxide (CO₂). Chemical foam.
- Water may be used to cool closed containers.
- Unsuitable Extinguishing Media: Water jet based fire fighting
- Hazardous Combustion Products: Nitrogen oxides (NO_x). Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters: As in any hydrocarbon based fire, wear self-contained breathing apparatus pressure-demand, MSHA / NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Ensure adequate ventilation. Use personal protective equipment as required. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges. Do not operate electrical equipment.

Environmental Precautions:

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Remove all

Material Safety Data Sheet

**HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, DEVANAGUNDI,
HOSKOTE TALUK, BANGALORE-560067.**

possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination.

Methods for Containment and Clean Up:

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Keep away from sources of ignition. Take measures to prevent the build-up of electrostatic charge.

Conditions / Precautions for storage: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye/face Protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection: Wear appropriate protective neoprene gloves and clothing to prevent skin exposure. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures: Handle in accordance with good industrial hygiene

Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Power 100 Additive	TWA	0.5 ppm	ACGIH
	STEL	1 ppm	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Appearance: Dark yellow

Specific Gravity: 0.99

Material Safety Data Sheet

**HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, DEVANAGUNDI,
HOSKOTE TALUK, BANGALORE-560067.**

Water Solubility: sparingly soluble

Boiling range: 160°C to 200°C

Vapour density: No data

Autoignition temperature: No data

Lower explosion limit: 1 %(V)

Upper explosion limit: 10 %(V)

10. STABILITY AND REACTIVITY

Reactive Hazard: None

Stability: Stable under recommended storage conditions. Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

Incompatible Materials: Acids, Acid anhydrides, Acid chlorides, Carbon dioxide (CO₂), Oxidizing agent, Nitrile Gloves, Copper alloys

Hazardous Decomposition Products: Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

Hazardous polymerization does not occur. Hazardous Reactions None under normal processing.

11. TOXICOLOGICAL INFORMATION

Toxicity Data: LD50 (Oral-Rat): 540 mg / Kg

12. ECOLOGICAL INFORMATION

Eco-toxicity: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

13. DISPOSAL CONSIDERATIONS

Disposal : Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification

14. TRANSPORT INFORMATION

Shipping Name : PoWer 100 additive

Material Safety Data Sheet

**HINDUSTAN PETROLEUM GREEN R&D CENTRE,
KIADB INDUSTRIAL AREA, TARABAHALLI VILLAGE, DEVANAGUNDI,
HOSKOTE TALUK, BANGALORE-560067.**

15. REGULATORY INFORMATION

OSHA : Flammable liquid, Target Organ Effect, Toxic by inhalation., Harmful by ingestion., Irritant

16. OTHER INFORMATION

Preparation Date: 15-7-2020