Ram Calculus and the Exponential Time Hypothesis

Exact Finite-Algebra Reformulations, Aggregated Boolean Jets, and Precision-Certified Counting

Revision 3: Expanded Corpus, Exact Recovery, and Certified Compression

Dr. Muralidhara Subbarao
Technical Report Prepared with the Assistance of AI Models
https://www.integralresearch.net

October 26, 2026

Abstract

We investigate the October 25, 2026 OpenAI manuscript *The Exponential Time Hypothesis is False*, using the supplied PDF and its matching public source. Its proof architecture is algebraic and combinatorial: polynomial deformation, shared integer measurements, Boolean finite differences, modulus-amplifying parity indicators, exact interpolation, and recursive tensor contraction. No auxiliary partial differential equation is identified in this manuscript. The relevant Ram Calculus connections are instead finite moment coordinates, polynomial operators, characteristic-safe jets, exact coupling states, and residual certificates. We give self-contained proofs of these connections and derive an aggregated Boolean-jet identity that replaces the source routine's $\sum_{j\le q} 2^j \binom{n}{j}$ restricted-count calls by $\sum_{j\le q} \binom{n}{j}$ calls over a polynomially enlarged coefficient algebra. A weighted-filtration extension handles unequal correction orders. We also derive target-specific two-adic precision certificates and demonstrate strictly smaller certified budgets for two finite Hermite configurations. Exact rational and integer tests check the identities, fiber factorization, parity lifts, and local Cauchy kernels. The assessment distinguishes rederivations of source results, adaptations of established algebra, additions proved here, and unimplemented proposals. Revision 2 adds matched implementations on 21 certified finite layouts, with exact count and coefficient agreement, seven repeated timings per method, and separate memory measurements. The aggregate routine has a lower median on all 18 cases with positive jet order, while zero-order controls expose overhead and phase profiles show the memory tradeoff. Neither a stronger general SAT time exponent nor a new independent refutation of ETH is established by this report. The source's full algorithm and its Lean dependency closure have not been independently executed here. The contributions are exact local algorithmic refinements and a more explicit verification framework, not a claim that a change of transform alone removes exponential complexity.

Revision 3 adds a 13-volume corpus crosswalk, a target-identifiability criterion, optimal common extra-bit losses of one, four, and seven on specified degree-one, degree-three, and degree-five Hermite classes, and exact orbit aggregation under certified permutation symmetry. The new exact tests include invalid-degree and invalid-symmetry controls. They establish local or restricted-class improvements, not a faster general SAT bound; all previous matched benchmarks are retained.

Contents

1 Scope, source status, and principal conclusions **5**
- 1.1 The manuscript actually examined . . . 5
- 1.2 Three separate evidential questions . . . 5
- 1.3 What was checked, and what was not . . . 5

2 The problem and its exact computational contract **6**
- 2.1 State space, arithmetic, and unresolved quantifiers . . . 6
- 2.2 The available formalization and its limits here . . . 6

3 Relevant Ram corpus and the exactness boundary **7**
- 3.1 A concrete finite Ram representation . . . 8
- 3.2 Which information is being represented? . . . 8

4 Proof architecture of the source and opportunities for Ram methods **9**
- 4.1 What the hard construction accomplishes . . . 9
- 4.2 The swap construction in explicit operator form . . . 10
- 4.3 Pullback to actual variables, coefficient size, and parameters . . . 11
- 4.4 Why the rational spectral proof cannot simply move to characteristic two . . . 11

5 Exact shared-summary counting as a Ram finite-state formulation **12**
- 5.1 Polynomial deformation and degree . . . 12
- 5.2 Why rank alone is the wrong parameter . . . 13

6 Finite jets, interpolation, and the auxiliary-PDE question **13**
- 6.1 The exact jet algebra . . . 13
- 6.2 Finite Ram polynomial operators and their limits . . . 13
- 6.3 No auxiliary PDE is present in the inspected paper . . . 14

7 Boolean-jet recovery: a self-contained rederivation **14**

8 A proved refinement: aggregating the Boolean-pair loop **15**
- 8.1 Why aggregation preserves local factorization . . . 15
- 8.2 What improves and what does not . . . 16
- 8.3 A transparent worked example . . . 17

9 A weighted-filtration extension **17**

10 Rank-aware summaries and exact structural special cases **17**
- 10.1 Deleting redundant rows without losing the count . . . 17
- 10.2 A bounded-width alternative independent of the source claim . . . 18
- 10.3 A rank identity that is exact but not efficient by itself . . . 18

11 Sparse equations, parity lifting, and the total-degree budget **19**
11.1 An explicit modulus-amplifying polynomial . . . 19
11.2 Why the truncation is shared across all factors . . . 19
11.3 Reduction from SAT without circular selection . . . 20

12 The sharper tensor route and its valuation structure **20**
12.1 What is being contracted . . . 20
12.2 Cauchy deformation and scaled integral coordinates . . . 21
12.3 Tapering, weighted modes, and recursion . . . 21

13 Target-specific Hermite recovery and precision certificates **22**
13.1 The target functional rather than the whole polynomial . . . 22
13.2 A finite demonstrated reduction in precision . . . 23
13.3 Archimedean residuals require a different certificate . . . 23

14 Complex, quaternionic, and nonlinear extensions: relevant limits **24**

15 Exact tests and reproducible evidence **24**
15.1 A complete small SAT deformation . . . 25
15.2 The exact call counts, not elapsed-time claims . . . 25
15.3 Failure cases that must remain visible . . . 26

16 Revision 2: matched implementation, runtime, and memory **26**
16.1 What is implemented and what is not . . . 26
16.2 Construction and exact certificates for every fixture . . . 27
16.3 Matched computational work and fairness controls . . . 28
16.4 Measurement protocol and reproducibility . . . 28
16.5 Exact agreement and measured runtime . . . 29
16.6 Memory, arithmetic work, and the structural control . . . 30
16.7 What has advanced and what remains open . . . 32

17 Revision 3: degree-aware recovery and certified quotient compression **33**
17.1 What the 13-volume investigation adds . . . 33
17.2 Recovering the target is weaker than recovering every coefficient . . . 33
17.3 A sharp finite degree-aware precision improvement . . . 35
17.4 Symmetry can remove more Boolean-jet calls, but only with a certificate . . . 36
17.5 Why a small summary or Hamming weight alone is insufficient . . . 37
17.6 New exact tests and their limited computational meaning . . . 37
17.7 Incremental conclusions, costs, and remaining work . . . 38

18 Equation comparison and attribution of improvements **38**
18.1 Advantages of the Ram-based organization . . . 39

18.2 Disadvantages and comparisons with existing methods 39

19 Research directions with explicit success criteria **40**
19.1 Implement the aggregated routine inside the actual construction 40
19.2 Search for higher-order correction designs 40
19.3 Deploy exact target weights in recursive two-adic recovery 40
19.4 Finite-domain and weighted-count extensions 40
19.5 Formal verification and negative results 40

20 Conclusion **41**

A Bounded-audit findings and arithmetic safeguards **41**

B Source register and reproducibility **42**

C Revision 3 corpus register, provenance, and reproducibility **42**

1 Scope, source status, and principal conclusions

1.1 The manuscript actually examined

The primary source is OpenAI's manuscript dated October 17, 2026 and revised October 25, 2026, in the repository folder named `The-Exponential-Time-Hypothesis-is-False-October-25-2026` [1]. The attached `paper(2).pdf` has 887,884 bytes. Its Git blob hash, computed locally, is

`0503566e95bc587a4076573a45132d97531b8ba6`.

This matches the repository PDF. The four TeX files used for the analysis are pinned to commit

`42907c9e999cc00d6abe7a50bfc1023250edd1b9`.

They are `main_full_version.tex`, `quantitative-reduction.tex`, `quantitative-contraction.tex`, and `quantitative-circuits.tex`. This fixes the object of analysis even if the live repository changes. The supplied PDF contains 66 pages.

The source announces a deterministic exact-counting algorithm for every fixed clause width k. Its headline is therefore much stronger than a heuristic SAT solver or a result on a selected instance distribution. The repository's general description also distinguishes different stages of verification and does not warrant treating every hosted manuscript as a fully independently audited publication [2]. Our analysis is correspondingly explicit about its own scope.

1.2 Three separate evidential questions

The following questions have different answers.

1. *Is Ram Calculus relevant?* Yes, particularly its corrected finite-algebra, moment, jet, state-aggregation, and certified-inversion interfaces. These can be connected to exact counting without an analogy to continuous PDEs.
2. *Can useful refinements be proved?* Yes. Sections 8–13 prove a reduction in the number of restricted-count calls, a weighted support extension, exact summary reductions under stated hypotheses, and a target-specific precision rule.
3. *Does this report improve the source's general exponent or independently establish its headline?* No. The new call-count result applies to the source's Section 3 routine, whereas its sharpest bound uses Appendix D. The local precision improvement has no proved better worst-case growth rate. The full low-degree construction, reduction, and recursive implementation have not been reproduced end to end in software or in Lean here.

The word *new* below means an addition to this comparative report, with a supplied proof or computation, not a verified claim of historical priority. Finite differences, generating functions, Hermite interpolation, quotient algebras, and valuation error propagation have substantial classical antecedents. Their use in Ram terminology does not erase that provenance.

1.3 What was checked, and what was not

The investigation follows the main proof dependencies: the counting identity, design interface, low-degree replacement mechanism, sparse polynomial parity lift, greedy parity tests, sparsification, exact arithmetic, and the sharper contraction route. Independent corpus research and a separate

mathematical audit were used. The detailed proofs in this report establish their own stated lemmas, rather than assuming that searching the large corpus constitutes verification of every report in it.

The initial experiments are exact small-instance identity checks. Revision 2 adds the matched finite implementation benchmark in Section 16. Neither experiment is a performance test of the full ETH algorithm or certifies all large-n parameter inequalities. The finite timings do not establish general practical crossover sizes. No inconsistency found in a proposed Ram shortcut is attributed to the source when the source itself preserves the necessary condition.

2 The problem and its exact computational contract

2.1 State space, arithmetic, and unresolved quantifiers

Let F be a CNF formula on n *declared* Boolean variables with m clauses, each of width at most a fixed integer $k \geq 2$. Its exact count is

$$Z(F) = \sum_{x \in \{0,1\}^n} \mathbf{1}_{\{F(x)=1\}} \in \{0, 1, \ldots, 2^n\}. \tag{1}$$

Unused variables contribute a factor of two each. An empty clause gives zero; an empty conjunction has count 2^n. Tautologies may be removed. Clause and literal normalization must preserve these conventions.

There is no spatial boundary condition or gauge constraint in this problem. The state space is a finite cube, and the observation of interest is the unnormalized sum functional. The relevant operator domains are finite polynomial spaces, Boolean quotient algebras, truncated coefficient rings, and explicitly described tensors. The complexity model counts bit operations, including construction, coefficient access, exact arithmetic, and output, rather than treating arbitrarily long rationals as unit-cost scalars.

ETH, in its usual bounded-width form, posits an exponential lower-time barrier for 3-SAT. Its precise relationships to sparse formulas depend on sparsification and size-preserving reductions [4]. The source claims the following bounds for each *fixed* k:

$$T(n, m) = (n + m)^{O_k(1)} 2^{O_k(n \log\log n / \sqrt{\log n})}, \tag{2}$$

$$T(n, m) = (n + m)^{O_{k,D}(1)} 2^{O_{k,D}(n/\sqrt{\log n})} \quad (m \leq Dn), \tag{3}$$

with polynomial bit space. Its earlier interpolation route gives

$$(n + m)^{O_k(1)} 2^{O_k(n(\log\log n)^2/\sqrt{\log n})}. \tag{4}$$

These are source claims, not improved bounds obtained in this report. For fixed parameters their exponents are $o(n)$. They do not give a polynomial-time algorithm, a useful finite-size threshold, or uniform constants when k or D grow with the input.

2.2 The available formalization and its limits here

The public Lean library has a solution entry point `OAI.Algorithms.SubexponentialSAT.Main`, importing `SqrtLogSpace.Final`. Its theorem `exact_count_and_sat` states exact counting, decision, a fixed primitive machine, and polynomial all-prefix visited-tape space. The comparator statement uses the runtime scale

$$n \frac{(\log\log(n + 16))^2}{\sqrt{\log(n + 16)}}.$$

Thus the inspected interface supports the weaker square-root-logarithmic scale (4), not by itself the sharper Appendix D bounds (2)–(3). The comparator specification contains an intentional `sorry`; its JSON points to the separate solution module. That placeholder is not evidence of a gap in the solution module. The inspected solution theorem invokes other proved declarations rather than a local placeholder [3].

The downloaded interface files were pinned to repository head `7ef5c0cc5ca4b0e072b7a050fca09ab24bc6fa3a` during this investigation. We did not compile their complete dependency closure, run the comparator, audit all permitted axioms, or check every encoding-to-paper correspondence. Accordingly, we report the existence and visible scope of the formalization, not a new independent machine-checked verification.

3 Relevant Ram corpus and the exactness boundary

The closest sources are listed in Table 1. Later corrected versions are used where they explicitly restrict earlier claims. The survey covered targeted parts of the requested directories, not every page of every book or report. This distinction matters because some older statements about universal nilpotence or automatic inversion were subsequently corrected.

Table 1: Corpus connections and non-transferable claims.

Source	Useful result or interface	Limitation for this problem
RamOperator Foundations; revised Series [9, 10]	Exact finite polynomial operators, nilpotent inverses, coefficient duality, projection leakage, coordinate invariance.	Finite inversion does not imply cheap global Boolean counting or safe arbitrary projection.
TR-item-010 [11]	Boolean quotient, moment aliasing, exact closure with a supplied tree decomposition.	Bounded clause width is not bounded treewidth; low moments need not identify the count.
M012 [12]	Exact finite-alphabet moment coordinates and explicit support-size cost.	An exact tensor basis can still have exponentially many coefficients.
M231 [13]	Hasse jets, transported multiplication, structured Toeplitz actions, field-aware bit accounting.	Noncommutative PIT is not common-zero counting; its special recurrences require their own hypotheses.
Corrected TR166 [14]	Separates coordinate conversion from model inversion and requires rank and residual closure.	A finite matrix need not be unit triangular or invertible.
Revised Volume 1 [15]	Newton/divided-difference coordinates and the correct product rule.	Confluent nodes and modular nonunits require separate arithmetic; changing basis alone is not a speedup.
RMT extension TR1 [16]	Exact signed aggregate-state recursion and explicit attainable-state cost.	Counting adds multiplicities; the optimization rule of retaining a minimum does not preserve counts.

Source	Useful result or interface	Limitation for this problem
RMT extension TR2 [17]	Multiplicity, jet information, and terminal polynomial degree budgets.	Complex-order endpoint models are not Boolean counting algorithms.
RMT extension TR3 [18]	Ordered hypercomplex channels, physical metrics, projection and finite-bank losses.	Physical tensor reconstruction is not scalar combinatorial tensor contraction.
RMT extension TR4 [19]	Range-consistent nonlinear representations, transported products, residual and root-isolation limits.	Local root certificates do not count every Boolean solution without complete coverage.

3.1 A concrete finite Ram representation

For a finite alphabet $A_i \subset \mathbb{Q}$ of distinct values, put

$$\mathcal{B}_A = \mathbb{Q}[X_1, \dots, X_n] / \left(\prod_{a \in A_i} (X_i - a) : 1 \le i \le n \right). \tag{5}$$

Evaluation identifies this algebra with functions on $\prod_i A_i$. Univariate Lagrange interpolation proves the identification in one coordinate; tensoring the maps proves the multivariate statement. Its dimension is $\prod_i |A_i|$, not the number of input factors.

In the Boolean case, a unique representative is $f(X) = \sum_{S \subseteq [n]} c_S X_S$, where $X_S = \prod_{i \in S} X_i$. The exact counting functional is

$$\Lambda(f) = \sum_{S \subseteq [n]} 2^{n-|S|} c_S. \tag{6}$$

Each X_S is one on exactly $2^{n-|S|}$ assignments, proving the formula. Normalized expectation is $2^{-n}\Lambda$, so an expectation is not a count.

Ram moment rows give one way to organize these functionals. An invertible coordinate map R produces an equivalent representation only if

$$u \star v = R((R^{-1}u)(R^{-1}v)), \qquad \Lambda_R(u) = \Lambda(R^{-1}u). \tag{7}$$

Entrywise multiplication in arbitrary transformed coordinates is generally wrong. Equation (7) preserves the same finite algebra and does not reduce its dimension. Over $\mathbb{F}_2$ the analogous scalar sum gives only parity, not the integer count.

3.2 Which information is being represented?

Three objects must not be conflated: moments of assignments on the Boolean cube; jets in a scalar deformation parameter; and point jets of a physical field. The first may require 2^n independent coordinates. The second can be small because a *separately proved* polynomial-degree bound applies. The third requires its own regularity and domain assumptions. The source's algorithm exploits the second together with specially constructed summaries; it does not recover an arbitrary Boolean function from a few moments.

4 Proof architecture of the source and opportunities for Ram methods

Table 2: Dependency map. Source section numbers refer to the pinned manuscript.

Stage	Substantive source step	Ram connection and audit obligation
Sections 2–3	Encode the count as a product-sum and deform incidence rows while restoring each original variable at parameter zero.	Exact moment functional; degree, measure, and multiplication must be retained.
Section 3	Condition on bounded integer summaries so factors separate by groups; use Boolean finite differences to recover jets.	Exact aggregate states; new call aggregation in Section 8.
Section 4	Build low-degree rows meeting many partition/measurement constraints by auxiliary arrays, spectral structure and annihilation.	No replacement construction supplied by existing Ram frames; certify row kernels and coefficient heights exactly.
Section 5	Lift evenness modulo 2^ℓ and truncate a common order variable, keeping total degree linear.	Filtered coefficient algebras; truncation is global, and final coefficient summation is not multiplicative.
Section 6; Appendix A	Use parity checks and disjoint sparsification to reduce general formulas to sparse polynomial zero counts.	Preserve solution multiplicities and query size; do not assume tests already isolate the solutions before proving they do.
Appendix B	Bound denominators, intermediate bit sizes, and streamed storage.	Exact structured linear algebra; no unit-cost rational shortcut.
Appendix D.1–D.3	Encode sparse and general systems as Boolean tensor networks with controlled wires and evaluable entries.	Transported tensor coordinates preserve scalar contraction, but not automatically small size.
Appendix D.4	Cauchy deformation, scaled integral jets, tapered Hermite precision, weighted modes, and recursive contraction.	Finite inverse and valuation certificates; target-specific precision in Section 13.
Appendix C	Consequences for circuit lower bounds and other reductions.	Consequences require the upstream algorithm and the precise reductions; not new Ram theorems here.

4.1 What the hard construction accomplishes

For factors Φ_f on scopes I_f, each incidence (f, v) receives its own polynomial row $P_{f,v}(T) \in \mathbb{Q}[T]^n$. Different occurrences of the same variable may have different rows. The requirements include $P_{f,v}(0) = e_v$, degree at most $R < Q$, and, at each interpolation node, small groups and few bounded integer measurements through which every off-group dependence factors. Simply interpolating arbitrary prescribed rows at Q nodes would usually require degree of order Q, defeating the intended

R/Q saving.

The source instead arranges auxiliary coordinates, uses a structured matrix/spectral construction, and annihilates selected bad-node contributions with low-degree factors that preserve the value at zero. The matrix-rigidity background includes Alman and Williams [5]; their results by themselves are not a complete construction of the source's simultaneous incidence design. Scope size, variable incidence, group balance, row range, common denominators, and the construction's own time are all essential. Replacing the construction with a generic tight frame or a low-rank approximation does not establish these properties.

The rational design in Section 4 and the recursive two-adic deformation in Appendix D are also different constructions. A refinement of one must not be silently advertised as a refinement of the other.

4.2 The swap construction in explicit operator form

Here is a closer derivation of the central Section 4 mechanism. Index an auxiliary array by pairs of labels $(a_u, d_u) \in [r]^Q \times [r]^Q$, with $D = r^{2Q}$ positions. Let Π_s exchange the two symbols in coordinate s. These are commuting rational permutation involutions. Set

$$V_0 = \prod_{s=1}^{Q} \Pi_s, \qquad W_0 = \frac{1}{2}\sum_{s=1}^{Q}(I - \Pi_s). \tag{8}$$

If a simultaneous eigenvector has j minus signs, then W_0 acts by j and V_0 acts by $(-1)^j$. At one coordinate the minus eigenspace has dimension $r(r-1)/2$ out of r^2; therefore the distribution of j among a tensor-product eigenbasis is $\mathrm{Bin}(Q, (r-1)/(2r))$.

Choose an interval $\mathcal{I} = \{A_0, \ldots, A_0 + R - 1\}$ and define

$$f_{\mathcal{I}}(z) = (-1)^{A_0} \sum_{j=0}^{R-1} (-2)^j \binom{z - A_0}{j}, \qquad M_0 = V_0 f_{\mathcal{I}}(W_0). \tag{9}$$

At $z = A_0 + h$, $0 \le h < R$, the binomial theorem gives $f_{\mathcal{I}}(z) = (-1)^z$. Thus M_0 is identity on the spectral subspace with $j \in \mathcal{I}$. Select the excluded orthogonal basis vectors as integer measurement rows $C^{\mathcal{B}}$. Their entries are $0, 1, -1$, and their number is $D \Pr[\mathrm{Bin}(Q, (r-1)/(2r)) \notin \mathcal{I}]$. It follows over $\mathbb{Q}$ that $M_0\xi = \xi$ whenever $C^{\mathcal{B}}\xi = 0$.

The second requirement is support, not just rank. A degree-at-most-$R-1$ polynomial in the commuting Π_s is a sum of products involving at most $R-1$ distinct swaps, because $\Pi_s^2 = I$. Multiplication by V_0 swaps every remaining coordinate. Consequently

$$M_0[u, y] \neq 0 \implies |\{s : a_y(s) \neq d_u(s)\}| \le R - 1.$$

Write that mismatch set as $E_{u,y}$, and let

$$\begin{aligned} \varphi_{u,y}(T) &= \prod_{s \in E_{u,y}} (1 - T/s), \\ P_u(T) &= e_u^T(I - M_0) + \sum_y M_0[u, y]\varphi_{u,y}(T)e_y^T. \end{aligned} \tag{10}$$

The sum need only include nonzero entries of M_0. At zero, $P_u(0) = e_u^T$. At node t, a term using a coordinate outside the assigned group vanishes because its mismatch set contains t. The remaining

nonlocal term $(I - M_0)\xi$ is determined by the shared measurements, since it vanishes on their kernel. This proves the desired separation on the auxiliary array.

This construction is legitimately an exact finite operator calculus, but its effectiveness depends on the simultaneous spectral and support properties. A Ram polynomial representation of $f_{\mathcal{I}}(W_0)$ does not establish those properties anew; it records the source's proof in compatible coordinates. The low-degree interpolation polynomial is not an approximate spectral filter on the retained eigenspaces: it has exact prescribed values there.

4.3 Pullback to actual variables, coefficient size, and parameters

The auxiliary slots contain copies of original variables, with unused slots set to zero. Copies are not independently summed Boolean variables. All copies of a variable retain the same group label, so pulling a row back through the embedding preserves its off-group kernel implication. Identifying columns cannot increase a row's absolute sum. The source's label assignment uses a conditional-expectation argument that includes dependencies from both shared variables and shared factors; treating all incidences as independent would not justify its packing bounds.

The factor $(-2)^j$ in (9) clears the halves in W_0; the remaining interpolation denominators divide $j!$. The annihilation factors in (10) have denominators dividing $Q!$. Thus $(R-1)!Q!$ clears all row coefficients. The source bounds their bit length using row-sum and polynomial coefficient norms. This is the arithmetic information missing from a mere statement that a basis change exists.

For $\lambda = \lceil \log_2 n \rceil$, $\nu = \lceil \log_2 \lambda \rceil$, and a fixed incidence exponent β, the source balances parameters of the form

$$r = \left\lfloor \frac{\sqrt{\lambda}}{\nu^2} \right\rfloor, \quad Q = \left\lfloor \frac{\lambda}{128\nu} \right\rfloor, \quad R = (\beta + 3)\lceil \sqrt{\lambda} \rceil, \quad \tau = \frac{1}{r\lambda}, \quad D = r^{2Q}.$$

A binomial-tail estimate makes the number of excluded measurements small, and $\log_2 D \le \lambda/128$ controls their magnitude budget. All required inequalities are asserted for sufficiently large n, with finite exceptions handled by direct enumeration. These thresholds can be extremely large. For example, $6R \le Q$ with $\beta \ge 1$ already requires approximately $\sqrt{\lambda} \ge 3072\nu$. This is consistent with an asymptotic theorem but supplies no practical-size advantage.

4.4 Why the rational spectral proof cannot simply move to characteristic two

On an orbit of four slots, let two swaps flip its two orientation bits. Choose $R = 1$ and $\mathcal{I} = \{1\}$. Then $M_0 = -\Pi_1\Pi_2$. The excluded eigenspace rows are $(1,1,1,1)$ and $(1,-1,-1,1)$. Modulo two those rows coincide, so $\xi = (1,1,0,0)^T$ is in their modular kernel. But $M_0\xi = (0,0,1,1)^T \neq \xi$ modulo two. This does not contradict the source, whose kernel proof is over $\mathbb{Q}$; it disproves an invalid finite-field shortcut. A Ram implementation must retain the declared field and multiplication law, not only the appearance of the matrix formulas.

5 Exact shared-summary counting as a Ram finite-state formulation

5.1 Polynomial deformation and degree

Let $\mathcal{A}$ be a commutative $\mathbb{Q}$-algebra and suppose the product of the incidence-separated factors has total degree at most d. Define

$$H(T) = \sum_{x\in\{0,1\}^n} \prod_f \Phi_f((P_{f,v}(T)\cdot x)_{v\in I_f}). \tag{11}$$

Then $H(0) = Z$ and $\deg H \le dR$. The degree is measured before identifying separate incidence indeterminates. A small degree for one factor is not a bound for their full product.

Fix a node t, a partition $[n] = S_1 \sqcup \cdots \sqcup S_r$, and an integer matrix C_g on each group. Write $y_g = C_g x_g$. Assign each factor to one group g. For every off-group $h \neq g$, require

$$P_{f,v}(t)|_{S_h} \in \mathrm{rowspan}_{\mathbb{Q}}(C_h). \tag{12}$$

Equivalently, the row vanishes on $\ker C_h$. This can be certified by an explicit rational row λ satisfying $P_{f,v}(t)|_{S_h} = \lambda C_h$. A factor assigned to g is then a function of its local assignment x_g and the off-group measurements.

Theorem 5.1 (Exact fiber factorization)**.** *Let $A_g(x) = a_g(x_g, y_{-g})$ take values in a commutative ring. For $E \subseteq [n]$, define*

$$B_{g,E}(y) = \sum_{\substack{x_g\in\{0,1\}^{S_g}\\ C_g x_g = y_g,\ x_i = 1\ (i\in E\cap S_g)}} a_g(x_g, y_{-g}).$$

Then

$$\sum_{\substack{x\in\{0,1\}^n\\ x_E = 1}} \prod_g A_g(x) = \sum_y \prod_g B_{g,E}(y), \tag{13}$$

where y ranges over all attainable measurement tuples, or any containing integer box with empty fibers assigned zero.

Proof. Every assignment belongs to exactly one measurement fiber. For fixed y the permitted assignments form the Cartesian product of local fibers. Each factor in that fiber depends only on its own local assignment. Distributing the finite product of sums proves the identity. No positivity, probabilistic independence, or approximate equality is used. □

This is a rederivation of the source's measurement-separation lemma. Its Ram interpretation is an exact coupling-state representation, consistent with TR1's rule that outside completions must see the same retained state [16]. For counting, equivalent states carry the *sum* of their weights; retaining only the cheapest representative would lose multiplicity.

If each measurement row has ℓ^1 norm at most D and there are c rows altogether, a safe box has $(2D+1)^c$ tuples. A streamed implementation uses at most

$$2(2D+1)^c \sum_g 2^{|S_g|} \tag{14}$$

local-assignment examinations, allowing one scan to find representatives and one to accumulate the local sum. Factor evaluation, arithmetic, and state-description costs remain additional. Polynomial space requires polynomial-length ring elements and evaluators, not just streaming indices.

5.2 Why rank alone is the wrong parameter

The rank-one row $(1, 2, 4, \dots, 2^{n-1})$ gives 2^n distinct values on the cube. Thus rank one does not give a small summary alphabet. Conversely, rows $(1, 1, 1)$ and $(2, 2, 2)$ have redundant information: retaining the first preserves their common kernel and leaves only four attainable values. The source itself emphasizes this distinction. Ram rank-aware methods are useful only together with range and coefficient-height accounting.

6 Finite jets, interpolation, and the auxiliary-PDE question

6.1 The exact jet algebra

For any commutative ring K, a node $t \in K$, and an integer $J \geq 1$,

$$\mathcal{J}_{t,J}p = p(t + z) \pmod{z^J} \in K[z]/(z^J) \tag{15}$$

is an algebra homomorphism. Its coefficients are Hasse coefficients, $[z^j]p(t + z)$. Over $\mathbb{Q}$ they equal $p^{(j)}(t)/j!$; the coefficient definition remains meaningful when $j!$ is not invertible. Multiplication is truncated convolution, not entrywise multiplication. This is precisely the characteristic-safe interface used in M231 [13].

For distinct rational nodes t_a and multiplicities J_a, put $N = \sum_a J_a$. Jets determine every polynomial of degree less than N. Indeed, a polynomial with all jets zero is divisible by $\prod_a (T - t_a)^{J_a}$, a degree-N polynomial, and must vanish if it has smaller degree. This proves injectivity; equality of finite dimensions proves unique reconstruction. The same statement over a general ring requires suitable unit differences or comaximal ideals.

Example 6.1 (Distinct modular nodes need not be sufficient)**.** The nonzero polynomial $2T$ over $\mathbb{Z}/4\mathbb{Z}$ vanishes at both 0 and 2. The nodes are distinct, but their difference is not a unit. Rational interpolation cannot simply be reduced modulo a power of two.

6.2 Finite Ram polynomial operators and their limits

On $\mathcal{P}_D = \{p : \deg p \leq D\}$, ordinary differentiation $N_D = d/dT$ is nilpotent, so

$$p(t + z) = \exp(zN_D)p(t) = \sum_{j=0}^{D} \frac{z^j}{j!} p^{(j)}(t). \tag{16}$$

This is an exact finite identity over $\mathbb{Q}$. The Ram polynomial moment calculus organizes related actions as finite rows in N_D; a unit constant plus a nilpotent operator has a terminating geometric inverse [9, 10]. The existence of this representation is useful for checking the arithmetic, but it does not make the coefficients of H cheap to obtain.

There is an important distinction between polynomials of bounded degree as a vector space and a quotient algebra with truncated multiplication. Ordinary differentiation does *not* descend to a derivation of $\mathbb{Q}[z]/(z^J)$: the ideal (z^J) is not differentiation-invariant. For $J = 2$, $z^2 = 0$ in the quotient, while a purported Leibniz rule gives $D(z^2) = 2z \neq 0$. Canonical representative differentiation is a linear matrix but not a derivation of this truncated algebra. Substitution followed by the quotient map (15) is the safe operation.

6.3 No auxiliary PDE is present in the inspected paper

The mathematical auxiliaries used here are a scalar polynomial $H(T)$, formal variables recording order, finite differences on subsets, integer linear summaries, and finite-ring tensor networks. The source does not introduce an elliptic, parabolic, hyperbolic, or quaternionic PDE whose solution supplies the counting result.

One may define $u(t, z) = H(t + z)$ and write the formal transport relation $\partial_t u = \partial_z u$ in characteristic zero. This is a rewriting of a polynomial identity, not an auxiliary PDE solver with a new complexity bound: its initial coefficients already contain the difficult count. Calling this relation a Ram partial differential operator does not provide missing information or reduce the cost of evaluating it. The auxiliary Dirichlet equation in the earlier local-smoothing manuscript is a different matter and must not be transferred into this paper.

7 Boolean-jet recovery: a self-contained rederivation

At a node t, write $\Delta P_{f,v}(z) = P_{f,v}(t + z) - P_{f,v}(t)$ and introduce independent variables $X_1, \dots, X_n$:

$$G_x(X, z) = \prod_f \Phi_f\big((P_{f,v}(t) \cdot x + \Delta P_{f,v}(z) \cdot X)_{v \in I_f}\big). \tag{17}$$

Each occurrence of X_i costs at least one power of z. Therefore

$$\deg_X\big([z^j] G_x(X, z)\big) \le j. \tag{18}$$

Moreover $\sum_x G_x(x, z) = H(t + z)$. Holding X fixed preserves the summary condition in x, whereas setting $X = x$ prematurely can destroy the factor separation. This explains the source's finite-difference step.

Lemma 7.1 (Boolean difference identity)**.** *Let $p_x(X)$, one for each Boolean x, be polynomials over a commutative ring of degree at most q. Then*

$$\sum_x p_x(x) = \sum_{\substack{E \subseteq [n] \\ |E| \le q}} \sum_{U \subseteq E} (-1)^{|E|-|U|} \sum_{x_E = 1} p_x(\mathbf{1}_U). \tag{19}$$

Proof. Reduce positive powers of each X_i to X_i, preserving Boolean evaluations and not increasing degree. Write the resulting polynomial as $\sum_E c_{x,E} X_E$. Subset inversion gives $c_{x,E} = \sum_{U \subseteq E} (-1)^{|E|-|U|} p_x(\mathbf{1}_U)$. Coefficients with $|E| > q$ vanish. At $X = x$, X_E is the indicator of $x_E = 1$. Summing proves the result. □

Take $q = \lfloor dR/Q \rfloor$ and $J = q + 1$ at Q rational nodes. Then $QJ > dR$, so the jets determine $H(0)$. Applying Lemma 7.1 coefficientwise to (17) computes those jets with

$$C_q(n) = \sum_{j=0}^{\min(q,n)} 2^j \binom{n}{j} \tag{20}$$

restricted calls per node. With the source design, $c \le 2\tau n$ and $|S_g| \le 2n/r$, giving the assignment-examination bound

$$2Qr\, C_q(n)(2D + 1)^{2\tau n} 2^{2n/r}. \tag{21}$$

All ring and factor costs still have to be included.

For $d = O(n)$ and $R/Q \to 0$, the three exponential costs have logarithm

$$O\left(n\left[\frac{R}{Q}\log\frac{2Q}{R} + \tau\log(2D+1) + \frac{1}{r}\right]\right). \tag{22}$$

The source's parameters make this the scale in (4) for appropriate polylogarithmic incidence bounds. Merely accelerating a polynomial-sized matrix inversion does not change these three costs.

8 A proved refinement: aggregating the Boolean-pair loop

This section is the main local algorithmic addition. It eliminates the outer restriction index E by retaining a small generating jet for the number of remaining selected bits. It does not assume the truth of the source's full ETH theorem.

Theorem 8.1 (Aggregated Boolean identity)**.** *Under Lemma 7.1, define, for $u \le q$ and $h \ge u$,*

$$w_q(h,u) = \sum_{k=0}^{\min(q-u,h-u)} (-1)^k \binom{h-u}{k}. \tag{23}$$

Then

$$\sum_x p_x(x) = \sum_{\substack{U\subseteq[n]\\ |U|\le q}} \sum_{x_U=1} w_q(|x|,|U|)\,p_x(\mathbf{1}_U). \tag{24}$$

Proof. In (19), interchange the finite sums over x, E, U. For fixed $U \subseteq \operatorname{supp} x$, the admissible sets E are $U \cup K$, where $K \subseteq \operatorname{supp} x \setminus U$ and $|K| \le q - |U|$. There are $\binom{|x|-|U|}{k}$ such sets of added size k, and their sign is $(-1)^k$. Their sum is exactly (23). □

For $h > u$, the weight is zero if $q - u \ge h - u$; otherwise it equals $(-1)^{q-u}\binom{h-u-1}{q-u}$. For $h = u$, it equals one. These follow from the alternating binomial sum. The defining finite sum is preferable in rings where generalized binomial notation would obscure integrality.

8.1 Why aggregation preserves local factorization

For a fixed U put $r_U = q - |U|$ and introduce one formal variable w:

$$K_U(z,w) = \sum_{x_U=1} G_x(\mathbf{1}_U, z)(1+w)^{|x|-|U|} \pmod{z^J, w^{r_U+1}}. \tag{25}$$

Define the *linear* final functional

$$\mathcal{L}_{r_U}\left(\sum_{k=0}^{r_U} b_k w^k\right) = \sum_{k=0}^{r_U} (-1)^k b_k. \tag{26}$$

The binomial theorem and Theorem 8.1 give

$$H(t+z) \equiv \sum_{|U|\le q} \mathcal{L}_{r_U} K_U(z,w) \pmod{z^J}. \tag{27}$$

For a group S_g, the extra factor is simply $(1+w)^{|x_g|-|U\cap S_g|}$ on the restricted assignments. It is local to that group. Thus Theorem 5.1 computes (25) in

$$\mathcal{A}[z,w]/(z^J, w^{r_U+1}) \tag{28}$$

with the original measurements and with $x_U = 1$ as the sole fixed-bit restriction. No new cross-group measurements are required.

The final functional must be applied *after* group multiplication. It is evaluation at -1 of the retained representative, not a ring homomorphism of the quotient. For example, modulo w^2, the product of w and w is zero, but the product of their representative evaluations at -1 is one. Applying the functional early would invalidate the count.

Corollary 8.2 (Restricted-call bound and polynomial workspace)**.** *The Section 3 jet stage can replace $C_q(n)$ calls per node by*

$$B_q(n) = \sum_{j=0}^{\min(q,n)} \binom{n}{j}, \tag{29}$$

using at most $J(q+1)$ coefficient slots per algebra element. With the source design, the number of local-assignment examinations is at most

$$2Qr\, B_q(n)(2D+1)^{2\tau n} 2^{2n/r}. \tag{30}$$

When q, J and coefficient bit sizes are polynomial in the input size, the enlarged arithmetic and streamed workspace remain polynomial per examined assignment.

Proof. There is one call (25) for each U, and each uses precisely the fiber algorithm in the larger ring. A naive multiplication costs $O(J^2(q+1)^2)$ operations in $\mathcal{A}$. The extra binomial coefficients have at most $n+1$ bits; their products and sums obey a polynomial additional bit budget under the same finite-degree assumptions. The loops over nodes, U, measurements, and local assignments can be streamed. Only polynomially many coefficients are live; no 2^n assignment table is required by the identity's implementation. □

8.2 What improves and what does not

The inequalities $B_q \le C_q \le 2^{\min(q,n)} B_q$ are immediate. For $q = o(n)$, the leading combinatorial logarithm remains $q\log(n/q) + O(q)$ in both cases. The new identity removes the extra factor attached to enumerating subsets of E, but introduces polynomial coefficient work. It therefore proves fewer restricted calls, not an unconditional wall-clock speedup. For small q, polynomial overhead can outweigh the call reduction. Section 16 now measures this tradeoff on finite matched implementations without changing that asymptotic limitation.

When $q \ge n$, $C_q = 3^n$ whereas $B_q = 2^n$; in that case the weights select only $x = \mathbf{1}_U$, so the identity reduces to direct enumeration. It is not a subexponential algorithm in that regime. For the source's sublinear q, the improved call count does not remove the other two costs in (22), and does not improve the published big-O exponent. Its relationship to Ram Calculus is the use of a small exact moment/jet state to aggregate a repeated summation. The proof is also expressible entirely in conventional generating-function algebra.

8.3 A transparent worked example

Let $n = 3$, $q = 1$, and $p_x(X) = a_x + \sum_i b_{x,i} X_i$. For $U = \varnothing$, $w_1(|x|, 0) = 1 - |x|$; for a singleton $U = \{i\}$ the weight is one. Thus the contribution of a fixed x on the right side is

$$(1 - |x|)a_x + \sum_{i:x_i=1} (a_x + b_{x,i}) = a_x + \sum_i b_{x,i} x_i = p_x(x).$$

The source pair loop uses $1 + 2n = 7$ calls. The aggregated loop uses $1 + n = 4$, with a degree-one generating jet for $U = \varnothing$. The cancellation of the repeated a_x terms explains the mechanism.

9 A weighted-filtration extension

Suppose the correction in coordinate i is divisible by z^{ν_i}, where $\nu_i \geq 1$ is a known integer. A monomial involving a support E then costs at least $\nu(E) = \sum_{i \in E} \nu_i$ powers of z. This is a strengthened structural assumption, not a property established for every source instance.

Theorem 9.1 (Weighted support aggregation)**.** *Assume the Boolean normal form of every p_x has support only on E with $\nu(E) \leq q$. Then*

$$\sum_x p_x(x) = \sum_{\nu(U) \leq q} \sum_{x_U = 1} p_x(\mathbf{1}_U) \sum_{\substack{K \subseteq \operatorname{supp} x \setminus U \\ \nu(K) \leq q - \nu(U)}} (-1)^{|K|}. \tag{31}$$

For each U, the inner weight is the sum of coefficients through degree $q - \nu(U)$ in

$$\prod_{i \in \operatorname{supp} x \setminus U} (1 - s^{\nu_i}). \tag{32}$$

Consequently it is computable by the same group factorization with one truncated generating variable and only $|\{U : \nu(U) \leq q\}|$ restricted calls.

Proof. Subset inversion reconstructs precisely the supported coefficients; the family $\{E : \nu(E) \leq q\}$ is downward closed. Interchanging sums as in Theorem 8.1 leaves $E = U \cup K$ with the stated weight budget. Expanding (32) supplies sign $(-1)^{|K|}$ and degree $\nu(K)$. Each factor in that product is local to its variable, so it can be multiplied into its own group's factor. Final coefficient summation is linear and is applied after multiplication. □

The new call count is no larger than $B_q(n)$, since $\nu_i \geq 1$. For example, with weights $(1, 2, 3)$ and $q = 2$, only $U = \varnothing, \{1\}, \{2\}$ occur: three calls rather than seven unweighted subset calls. Establishing such higher-order vanishing in an actual replacement design could be valuable. Imposing it can also raise the replacement degree R, so an overall gain requires balancing both changes. The theorem does not license declaring weights without proving the corresponding divisibilities.

10 Rank-aware summaries and exact structural special cases

10.1 Deleting redundant rows without losing the count

Proposition 10.1 (Exact row-basis reduction)**.** *Let C be an integer measurement matrix and let C' consist of a subset of its rows spanning its rational row space. Then $Cx = Cx'$ if and only if $C'x = C'x'$. Every off-group certificate through C factors through C'. The same summary fibers and exact weighted counts are retained.*

Proof. The two matrices have the same rational kernel. Each omitted row is a rational linear combination of retained rows, so equality of retained measurements implies equality of all measurements. The reverse implication is immediate. The row-space certificate (12) is unchanged as a condition. □

Selecting existing rows avoids increasing their integer magnitudes, unlike an arbitrary rational change followed by denominator clearing. If retained row j has norm D_j, the safe box bound can be sharpened to $\prod_j (2D_j + 1)$. This is a valid instance-specific preprocessing step; it may do nothing when the source design already has independent rows.

One can reduce the box further to actual attainable summaries, but producing and enumerating that set is not free. Storing all reachable values may use exponential space. A sparse-state implementation must account for its construction and memory; the source's full-box streaming remains a safe polynomial-workspace fallback. Rank one still permits 2^n attainable states, as Section 5 shows.

10.2 A bounded-width alternative independent of the source claim

Proposition 10.2 (Exact counting with a supplied tree decomposition)**.** *Given a CNF and a tree decomposition of its primal graph of width w, the count is computable in $2^{w+1}\,\mathrm{poly}(n, m, |\mathcal{T}|)$ bit operations, with the polynomial factor covering count arithmetic. Storing all messages may require $2^{w+1}\,\mathrm{poly}(n, |\mathcal{T}|)$ bits.*

Proof. Assign each clause to one containing bag. A message indexed by a separator assignment counts the satisfying extensions in the subtree interior, excluding the separator variables from multiplicity. Running intersection makes different child interiors disjoint conditional on the bag. Multiply child counts, enforce local clauses, and sum newly eliminated variables. Induction proves exactness; every global satisfying assignment is counted once. A nice decomposition has tables of at most 2^{w+1} entries. Partial counts are at most 2^n and therefore have at most $n + 1$ bits. □

This is the counting version of the finite closure in TR-item-010 [11], expressed by standard sum-product messages. It provides a legitimate structural alternative when w is small, not a new general SAT bound. Decomposition-finding cost must be added if one is not supplied. Width $o(n)$ gives a structural subexponential bound under polynomial remaining costs; arbitrary bounded-width clauses do not ensure $w = o(n)$.

10.3 A rank identity that is exact but not efficient by itself

For reduced Boolean polynomials P_i over $\mathbb{F}_2$, let $A = \mathbb{F}_2[X]/(X_i^2 - X_i)$ and let $M_i : A \to A$ be multiplication by P_i. Then the integer number of common zeros is

$$N = 2^n - \mathrm{rank}_{\mathbb{F}_2}[M_1 \ \cdots \ M_m]. \tag{33}$$

Evaluation identifies A with a product of 2^n copies of $\mathbb{F}_2$. The ideal generated by the P_i has coordinate zero at a common zero and the whole field elsewhere. The quotient dimension is therefore the number of common zeros; rank-nullity proves (33). This is a useful small-instance reference identity, but its matrices have 2^n rows. Sparse columns do not by themselves yield a subexponential rank algorithm. Neither this identity nor a finite Ram inverse proves the source's difficult algorithmic bound.

11 Sparse equations, parity lifting, and the total-degree budget

For $P_i \in \mathbb{F}_2[X]$ given as a short sum of degree-at-most-k monomials, replace powers by first powers and combine duplicate monomials modulo two. Let L_i be the same sum with integer coefficients. Then $P_i(x) = 0$ exactly when $L_i(x)$ is even. Put $\ell = n + 1$ so that a count in $[0, 2^n]$ is determined by its residue modulo 2^ℓ.

11.1 An explicit modulus-amplifying polynomial

Define

$$p_\ell(Y) = (1 - Y)^\ell \sum_{j=0}^{\ell-1} \binom{\ell + j - 1}{j} Y^j. \tag{34}$$

The sum is the inverse of $(1 - Y)^\ell$ modulo Y^ℓ, so $p_\ell \equiv 1 \pmod{Y^\ell}$ and $p_\ell \equiv 0 \pmod{(1 - Y)^\ell}$. For even integers y the first congruence gives one modulo 2^ℓ; for odd integers the second gives zero. This is the source's complement of a modulus-amplifying construction with antecedents in Beigel–Tarui and Chan–Williams [6, 7].

Write $h(Y) = Y(Y - 1)$. Repeated division by this monic quadratic gives

$$p_\ell(Y) = \sum_{j=0}^{\ell-1} e_j(Y) h(Y)^j, \qquad e_j \in \mathbb{Z}[Y], \quad \deg e_j \le 1. \tag{35}$$

This is an exact polynomial basis change with affine remainder coefficients. Its significance is arithmetic: $h(y)$ is always even.

11.2 Why the truncation is shared across all factors

Work in $\mathbb{Q}[V]/(V^\ell)$ and define

$$B_i(X, V) = \sum_{j<\ell} e_j(L_i(X)) h(L_i(X))^j V^j. \tag{36}$$

Multiply *all* factors first, discarding only total V-degree at least ℓ, and then sum the retained coefficients by $\mathcal{S}_\ell$. At integer assignments, each omitted term is divisible by 2^ℓ. Consequently

$$\mathcal{S}_\ell \left(\prod_i B_i(x, V) \bmod V^\ell \right) \equiv \prod_i \mathbf{1}_{\{P_i(x)=0\}} \pmod{2^\ell}. \tag{37}$$

The retained input degree is at most

$$k\big(m_{\text{test}} + 2(\ell - 1)\big). \tag{38}$$

Indeed a product term indexed by j_i has degree at most $\sum_i k(1 + 2j_i)$, and $\sum_i j_i < \ell$. With $m_{\text{test}} = O(n)$ this is linear in n, unlike independent full-degree lifts multiplied without the shared filtration.

This is a strong match to the Ram discipline of retaining the exact algebra, product, and projection contract. It is not a new parity lift introduced by Ram Calculus. The valuation certificate is essential: an arbitrary low-degree projection would not preserve the count.

Example 11.1 (Order two)**.** For $\ell = 2$,

$$p_2(Y) = 1 - 3Y^2 + 2Y^3 = (1 - Y) + (2Y - 1)h(Y).$$

The product for two equations retains constant and first total order in V. The discarded cross term contains $h(y_1)h(y_2)$ and is divisible by four at integer arguments. Its input degree is six, whereas the retained part has degree at most four. The coefficient-sum functional $\mathcal{S}_2$ is not multiplicative on the truncated ring; applying it before multiplication would retain the wrong cross term.

11.3 Reduction from SAT without circular selection

Let $v(x)$ be the vector of clause violations. A true solution has $v(x) = 0$. The source constructs initial parity checks that exclude small nonzero violation supports using coding-theoretic structure related to expander codes [8]. It then adds sparse parity rows greedily. For a surviving nonzero violation vector, a random candidate list hits its support with sufficient probability and rejects it with probability at least $1/4$. Thus some row removes at least a quarter of the remaining false positives.

The candidate is chosen by minimizing the *total* number accepted, computed by the sparse polynomial counter. All candidates keep every true solution, so the unknown true count is the same additive constant in every comparison. After $3n$ rows, false positives are fewer than $(3/4)^{3n}2^n = (27/32)^n < 1$, hence zero. This explains why the greedy step need not know the answer in advance. Its count queries must work on arbitrary candidate systems, not only on systems already isolating true solutions.

Finally, a disjoint sparsification partitions satisfying assignments. Overlapping disjunctions would not permit adding leaf counts. Candidate enumeration, incidence reduction, and sparsification overheads are part of the source proof and are not supplied automatically by a Ram transform.

12 The sharper tensor route and its valuation structure

12.1 What is being contracted

A Boolean tensor network assigns one bit to each edge and a ring-valued table to each vertex. Its contraction is

$$Z_G = \sum_{x \in \{0,1\}^{E(G)}} \prod_v T_v(x|_{\delta(v)}). \tag{39}$$

For fixed clause density, clause tensors and equality trees give $O_{k,D}(n)$ edges and bounded degree. Subdividing each edge with an equality tensor makes the network bipartite without changing its scalar value. Unused variables are accounted for separately. Reduction modulo 2^{n+1} recovers the integer count uniquely.

For general formulas the source encodes retained incidence monomials of the parity lift. The total-degree budget (38) permits indexing selected incidences with $O_k(n \log\log n)$ Boolean wires. High-incidence variables and degree arrays are enumerated with separately bounded overhead. Tensor entries are implicit but must remain evaluable within the allowed time and space. A short tensor description alone is not sufficient if evaluating one entry hides an equally hard problem.

The source contraction theorem assumes $O(s)$ edges, maximum degree at most $\lceil s^{9/10} \rceil$, polynomially many vertices, initial precision and order $P_0, \ell = O(s)$, and entries over

$$\mathcal{B}_{P_0,\ell} = (\mathbb{Z}/2^{P_0}\mathbb{Z})[V]/(V^\ell)$$

with explicitly bounded evaluation cost. Its claimed contraction time is $\mathrm{poly}(s+\mathcal{L})2^{O(s/\sqrt{\log s})}$ and polynomial space. Substituting $s = O(n)$ or $s = O(n \log\log n)$ gives the two headline scales.

12.2 Cauchy deformation and scaled integral coordinates

At a recursive call with M edges, ports are packed into slots of length $L = 2^a$. Set

$$S = \{-L, \dots, L-1\}, \quad C(T) = \prod_{t \in S}(T - t), \quad \alpha = 2L, \qquad W_{xy}(T) = \frac{C(T)}{C'(0)(T - (y - x))}. \tag{40}$$

The apparent pole cancels because $y - x \in S$. The entries are polynomials of degree $2L - 1$, with $W(0) = I$ on the original matched slots. If $l_0(z) = 1 - z$ and $l_1(z) = z$, the deformed contraction is

$$F(T) = \sum_{X,Y \in \{0,1\}^M} A(Y)B(X) \prod_x l_{Y_x}((W(T)X)_x). \tag{41}$$

Its value at zero is the desired contraction and its degree is at most $M(2L - 1)$. Nonzero values need not be positive or count assignments.

The grid S is a full residue system modulo 2^{a+1}. At any node t, the valuations of nonzero differences $t - q$ balance the valuation of $C'(0)$. Substituting $T = t + \alpha z$ allows the known powers of two in each factor to be canceled before division. The resulting coefficients are integral at two, and the remaining inverses are of odd units. This is the source's scaled-integrality mechanism. It is not the statement that every rational polynomial has integral local Taylor coefficients.

The source also uses an unramified extension of the two-local rationals, with residue field large enough to provide many interpolation nodes with unit differences. Ordinary integer nodes alone would not supply that property modulo 2^p. Canonical lifts of tensor entries are fixed at their creation precision; a later recursive call cannot arbitrarily relift algebraically equivalent residues and assume that polynomial deformation commutes with the change.

12.3 Tapering, weighted modes, and recursion

For a retained valuation level $i = v_2(t) < u$, the source assigns multiplicity

$$q_t = h(u - i), \qquad h = \lceil 3M/u \rceil, \quad D_t = L/2^i, \quad p_t = p + 8hD_t + 8M(a+1). \tag{42}$$

The total multiplicity exceeds $\deg F$, and the precision budget accounts for denominators in reconstruction at zero. Near a node, crossing interactions expand into modes of weight $b+1$ whose coefficients are divisible by 2^{b+1}. Only monomials of total mode weight less than p_t can contribute modulo 2^{p_t}.

If there are at most $6M/D_t$ modes of each weight, their number is bounded using

$$\exp\left(\theta p_t + \frac{6M}{D_t} \sum_{j \geq 1} -\log(1 - e^{-\theta j})\right).$$

The sum is at most $\theta^{-1} \sum_{h \geq 1} h^{-2}$. Choosing $\theta = \sqrt{M/(D_t p_t)}$ gives $\exp(O(\sqrt{M p_t / D_t})) = \exp(O(M/\sqrt{u}))$ under the source budget. Each retained monomial separates into smaller group contractions, with at most $M/8$ edges per child. The source chooses a depth-dependent $u_d \asymp (\log s)/2^d$, so the exponents sum geometrically.

The power-of-two divisibility is an exact vanishing certificate, not a small real norm. Conventional low-rank truncation or an L^2-small Ram residual does not imply it. The source's packet construction, lift consistency, precision inheritance, and implicit-entry bounds remain independent obligations. Our finite tests below probe selected local identities, not the entire recursive theorem.

13 Target-specific Hermite recovery and precision certificates

13.1 The target functional rather than the whole polynomial

Let distinct rational nodes t have multiplicities q_t, with $N = \sum_t q_t > \deg F$, and use scaled jets $h_{t,j} = [z^j]F(t + \alpha z)$. There are unique rational coefficients $\lambda_{t,j}$ for the canonical degree-less-than-N Hermite map such that

$$F(0) = \sum_t \sum_{j<q_t} \lambda_{t,j} h_{t,j}. \tag{43}$$

If A is the confluent matrix with entries $A_{(t,j),k} = \binom{k}{j} t^{k-j}\alpha^j$ for $k \geq j$ and zero otherwise, then $A^T\lambda = e_0$. Exact rational elimination computes the weights. Equivalently, one may use cardinal Hermite polynomials. The source already uses a target-at-zero Hermite formula in Appendix D; the contribution here is to use its *actual* coefficient valuations as a certificate.

Theorem 13.1 (Coordinatewise two-adic precision certificate)**.** *Suppose $F(0)$ is integral at two and approximations to its scaled jets satisfy $v_2(\widehat{h}_{t,j} - h_{t,j}) \geq b_{t,j}$ coordinatewise in the declared coefficient basis. If*

$$b_{t,j} + v_2(\lambda_{t,j}) \geq p \quad \textit{for every nonzero } \lambda_{t,j}, \tag{44}$$

then the reconstructed value is correct modulo 2^p. A sufficient common precision at node t is

$$p_t^{\mathrm{cert}} = p + \ell_t, \qquad \ell_t = \max(0, \max_{j:\lambda_{t,j}\neq 0} -v_2(\lambda_{t,j})). \tag{45}$$

For a recursion requiring strictly increasing creation precisions, use $p + \max(1, \ell_t)$ instead.

Proof. Each weighted jet error belongs to 2^p times the integral coefficient module by (44). Their finite sum also belongs to that module, since the two-adic valuation of a sum is at least the minimum of the valuations of its summands. Subtracting (43) proves the claim. The nodewise bound enforces the coordinatewise inequalities. □

For fixed nonzero weights and independently variable coefficient errors, the coordinatewise requirement is sharp: changing just one coefficient at valuation $p - v_2(\lambda_{t,j}) - 1$ changes the target at valuation $p - 1$. This is not a global optimality theorem for interpolation. The source polynomial may have degree well below $N - 1$, allowing other reconstruction functionals, and correlated errors can obey extra relations.

The source's conservative precision bound (42) is justified by bounding the same reconstruction map through an integral reciprocal series and rational evaluation. Directly computing the weights can give smaller losses. Their calculation has polynomial cost in the number of jets and their explicit bit sizes. It does not remove the need for the source's polynomial bound on those sizes. Within a recursive implementation, one must retain the source's fixed-lift convention and use a certified budget before changing any child precision.

For completeness, the weights can be obtained without inverting the entire matrix. Put

$$E_t(T) = \prod_{v \neq t} \left(\frac{T - v}{t - v} \right)^{q_v}, \qquad b_{t,m} = [z^m] \frac{1}{E_t(t + \alpha z)}.$$

The cardinal Hermite construction gives

$$\lambda_{t,j} = E_t(0) \sum_{k=j}^{q_t - 1} b_{t,k-j} (-t/\alpha)^k. \tag{46}$$

Indeed, multiply the truncated quotient $[F(t + \alpha z)/E_t(t + \alpha z)]_{<q_t}$ by $E_t(T)$ and substitute $z = (T - t)/\alpha$. Summing over nodes reproduces each jet, so uniqueness of interpolation proves the formula; collecting each $h_{t,j}$ at $T = 0$ gives (46).

In the tapered construction $b_{t,m}$ are integral at two because $E_t(t + \alpha z)$ is integral with constant term one. Counting valuations of grid differences yields

$$v_2(E_t(0)) = D_t \sum_{j=1}^{a-i} \frac{j}{2^j} (q(i + j) - q(i)) \geq -6 D_t h,$$

where $q(i) = h \max(0, u - i)$ and $\sum_{j \geq 1} j^2/2^j = 6$. Evaluation at $-t/\alpha$ loses at most $4M(a + 1)$ additional powers of two because $q_t \leq 4M$. Therefore

$$\ell_t \leq 6 h D_t + 4M(a + 1) \leq 8 h D_t + 8M(a + 1). \tag{47}$$

Thus the proposed direct certificate is bounded by the source allowance for the same map. It can exploit cancellations in the actual weights, but (47) alone has the same asymptotic scale.

13.2 A finite demonstrated reduction in precision

We computed the exact rational weights of (43) for two small grids. The comparison in Table 3 lists extra bits *above* the desired output precision p. For $a = 1$, $L = 2$, $h = 3$, and $q_{-1} = q_1 = 3$.

a	u	M	Nodes	Source allowance	Certified loss
1	1	1	$-1, 1$	64	7
2	2	2	$-3, -1, 1, 3$	144	33
2	2	2	$-2, 2$	96	7

Table 3: Exact finite Hermite precision calculations.

For $a = 2$, $L = 4$, $h = 3$, the odd nodes have multiplicity six and the valuation-one nodes have multiplicity three. The scaling is $\alpha = 2L$. These configurations satisfy the local interpolation hypotheses but not the large-size packing conditions of the full recursive algorithm. They establish a local certificate improvement, not a measured acceleration of that algorithm.

13.3 Archimedean residuals require a different certificate

For ordinary absolute errors $|e_{t,j}| \leq \delta_{t,j}$,

$$|\widehat{F}(0) - F(0)| \leq \sum_{t,j} |\lambda_{t,j}| \delta_{t,j}. \tag{48}$$

If the target is known to be an integer and the right side is strictly less than $1/2$, nearest-integer rounding is correct. This follows from the triangle inequality and separation of distinct integers. It is a useful Ram-style residual certificate, but the weights can be large. For a normalized expectation over 2^n assignments, a raw expectation error must be less than 2^{-n-1} to ensure count rounding. Ordinary relative accuracy or a small unweighted coefficient residual does not suffice. Exact modular arithmetic is therefore not casually replaceable by floating point.

14 Complex, quaternionic, and nonlinear extensions: relevant limits

The source's factorization and reordering require an associative commutative coefficient algebra. Complex coefficients are compatible with that algebraic condition, but exact bit complexity still needs an explicit finite representation. A complex phase encoding does not reduce the number of assignments or certify cancellation for free.

Quaternion-valued Ram channels in corrected TR60 and RMT extension TR3 require specified left/right multiplication, physical metrics, and ordered operators [18]. They are useful for vector or spinor observables, but substituting quaternions for the scalar coefficient ring here invalidates unrestricted factor reordering: $ij = k$ whereas $ji = -k$. Realification represents a fixed linear quaternion operation by a real matrix and keeps composition ordered. It does not make those matrices commute, reduce the network's width, or prove an exact-counting speedup. Octonions additionally require explicit parentheses; an associative scalar-ring proof cannot be imported unchanged.

Similarly, TR4's nonlinear range-consistency theorems [19] explain how to avoid false roots in transformed systems. They do not guarantee exhaustive isolation of every root of a general Boolean polynomial system. A local Newton certificate, an invertible projected Jacobian, and a small residual each answer a different question from the exact cardinality in (1). For this source, the scalar finite-algebra branch of Ram Calculus is substantially more directly relevant than its hypercomplex or continuous nonlinear PDE branch.

15 Exact tests and reproducible evidence

The accompanying program `eth-support/exact_identity_tests.py` uses Python integers and `fractions.Fraction`, with random seed `20261026`. It writes `eth-support/test-results.json`. No external private data or numerical fitting is used. The tests are small enough to compare against direct enumeration, which is a reference method here, not the proposed asymptotic implementation.

Table 4: Executed exact checks; all passed.

Check	Cases	What the equality establishes
Boolean rational polynomials	132	Direct diagonal sum, original subset-pair formula, aggregated formula, and generating-jet evaluation agree for $1 \le n \le 6$, $0 \le q \le n+1$.

Check	Cases	What the equality establishes
Weighted support filtration	120	The weighted subset aggregation equals the direct sum for weights in $\{1, 2, 3\}$ and varied budgets.
Shared-fiber generating jets	24	Two groups of three bits with cross-group sum dependence give identical global and factored coefficient vectors.
Rational Hermite recovery	36	Exact reconstruction with two unequal multiplicities, degrees one through nine.
Parity lift and global truncation	360	Modulus-amplifying indicators, quadratic remainder expansions, and common-order products agree modulo 2^ℓ, for $1 \le \ell \le 8$.
Cauchy scaled-integrality rows	1,168	All slot pairs and nodes for $L = 2, 4, 8$ have odd-denominator scaled coefficients; origin identity and cross-group divisibility hold in the checked configurations.
Tapered Hermite configurations	2	Exact weight valuations give Table 3; ten further polynomial reconstructions agree with the true origin value.
Negative controls	4	Detect invalid early functional application, rank-only state counting, floating cancellation, and a false derivative rule in a truncated ring.

15.1 A complete small SAT deformation

Consider

$$F = (x_1 \vee x_2) \wedge (\neg x_1 \vee x_3).$$

Its satisfaction polynomial is $(x_1 + x_2 - x_1x_2)(1 - x_1 + x_1x_3)$. Replacing each variable by $(1 - T)x_i$ and summing over all eight assignments gives, exactly,

$$H(T) = 4 - 3T + T^2 - T^3 - T^4. \tag{49}$$

Thus $H(0) = 4$, matching direct counting, and

$$H(1 + z) = -8z - 8z^2 - 5z^3 - z^4.$$

Reconstruction at zero gives $8-8+5-1 = 4$. At $T = 2$, however, $H(2) = -22$: deformed evaluations are not nonnegative counts. This example checks the algebra but does not meet the asymptotically useful $R < Q$ design conditions and is not presented as a fast solver.

15.2 The exact call counts, not elapsed-time claims

The large entries in Table 5 were computed by binomial arithmetic; those many calls were *not executed*. The table quantifies the proven loop reduction, not observed runtime or memory. In particular, the $n = 80$ entry remains enormous and says nothing about practical utility.

n	q	Original C_q	Aggregated B_q
20	2	801	211
40	4	1,544,481	102,091
80	8	7,847,456,478,273	32,490,460,747
6	6	729	64

Table 5: Combinatorial counts evaluated exactly from the formulas.

15.3 Failure cases that must remain visible

Four exact controls illustrate specific invalid substitutions.

1. In $\mathbb{Q}[w]/(w^2)$, multiplying first gives $w^2 = 0$; evaluating each retained factor at one first gives one. A linear final functional must not be treated as a ring homomorphism.
2. An eight-coordinate rank-one binary-weight row has 256 distinct Boolean measurements. Low rank need not mean a small state space.
3. Integer arithmetic gives $(2^{60} + 1) - 2^{60} = 1$, while binary64 floating arithmetic gives zero. Exact cancellation needs a precision certificate or exact arithmetic.
4. Canonical differentiation of the zero product z^2 modulo z^2 is zero, while a purported Leibniz calculation yields $2z$. Truncated coefficient multiplication is not compatible with that derivative.

Another analytic obstruction, used in the corpus, is moment aliasing: uniform even- and odd-parity distributions have identical proper-coordinate marginals but disjoint supports. Low-order assignment moments cannot identify arbitrary constraints. None of these examples disproves the source, which uses more carefully specified objects.

16 Revision 2: matched implementation, runtime, and memory

16.1 What is implemented and what is not

Revision 2 goes beyond the earlier identity tests: it implements the source's Section 3 restricted subset-pair routine and the aggregated routine of Section 8 on identical exact inputs. Both compute all required jets and reconstruct the entire Hermite polynomial, whose constant term is checked against independent exhaustive CNF counting. The implementation is original Python code derived from the published formulas, not an OpenAI-supplied executable and not a timing of its Lean development. The paper directory currently contains its README, PDF, and four TeX build files; the checked PDF and main TeX Git hashes match the versions already analyzed in this report.

The fixtures satisfy the finite Section 3 interface, including $R < Q$, integer summary bounds, row-kernel certificates, and exact denominator control. They are *not* outputs of the source's general Section 4 asymptotic construction. The first 16 are deliberately small, structurally easy CNFs with bounded cross-group interfaces. Their factors already separate at $T = 0$, so a direct fiber calculation is available without jets. This stronger conventional control is measured separately below. Five additional node-varying fixtures remove that particular shortcut: their factor assignments change between interpolation nodes, and their clauses couple unmeasured variables on both sides at zero. The comparison answers whether aggregation helps the specified jet routine on matched instances,

not whether it improves the fastest SAT solver or the source's sharper Appendix D bound.

16.2 Construction and exact certificates for every fixture

In the first suite, the n declared variables are split into two contiguous groups, each with one distinguished boundary bit b_g. A clause assigned to group g may contain arbitrary variables of that group and the other group's boundary bit, but no other off-group variable. Its summary is $C_g x_g = x_{b_g}$, so $D = 1$, the total number of rows is $c = 2$, and $\tau = 1/n$ satisfies $c = 2\tau n$ and $\tau \le 1/2$. The group sizes satisfy the source's required bound.

For every clause-variable incidence, the implementation constructs

$$P_{f,v}(T) = e_v + T a_{f,v}, \qquad \operatorname{supp} a_{f,v} \subseteq S_{\sigma_f} \cup \{b_{1-\sigma_f}\}. \tag{50}$$

The coefficients on that support are seeded signed values in $\{-2, -1, 1, 2\}$; the rational fixture divides them by two. Thus $R = 1$, and $Q \ge 2$ ensures $R < Q$ and that the source's denominator factor $(R-1)!Q! = Q!$ clears the coefficients. Their integer heights meet the stated finite coefficient bound. At zero the rows restore e_v. At every node $t = 1, \dots, Q$, every off-group coordinate other than the measured boundary bit is exactly zero. This proves the row-kernel condition; the code checks it for every incidence and node.

For clause widths k_f, the code uses the valid degree bound $d = \sum_f k_f$, $q = \lfloor d/Q \rfloor$, and $J = q + 1$. Hence $QJ > dR$. The satisfaction factor for a positive literal uses the unsatisfied factor $1 - y_v$, and a negative literal uses y_v; one minus the product of unsatisfied factors is the clause indicator. Products are computed with exact integers, or `Fraction` objects for the rational fixture. Hermite reconstruction uses exact rationals for both methods.

The second suite uses $Q = 2, R = 1$ and the same boundary-bit measurements, but assigns every factor to group zero at node one and group one at node two. For a nonboundary variable v, the replacement is

$$P_v(T) = \begin{cases} (1 - T/2)e_v + TB_v, & v \in S_0, \\ (1 - T)e_v + TB_v, & v \in S_1, \end{cases}$$

where B_v is a small signed row supported only on the two boundary bits. Boundary variables use $e_v + TB_v$. At $t = 1$, the nonboundary coordinates of S_1 vanish; at $t = 2$, those of S_0 vanish. This proves the two nodewise kernel conditions, while restoration at zero is exact. Each clause contains nonboundary variables from both groups, so the constant-partition direct fiber shortcut is not certified there. These are finite input-specific designs, not a new asymptotic construction. With only two or three clauses in the second suite, elementary clause inclusion–exclusion is another small conventional counting alternative. Node-varying separation tests the mechanism more directly; it does not make these fixtures hard SAT instances.

Table 6 describes all 21 fixtures. Each suite was fixed before its own run. The node-varying suite was added after the independent audit identified the all-T separation of the first family; it is an explicitly disclosed follow-up, not a hidden replacement of unfavorable trials. A preliminary two-repetition pilot on S08 is retained separately and excluded from the reported statistics. Empty and contradictory formulas, $q = 0$, rational rows, higher jet orders, and a $q \ge n$ case are retained rather than screened out for poor performance. No result is extrapolated to larger input sizes.

Table 6: Certified fixtures and exact counts. Calls are totals over all nodes. S cases use fixed layouts; N cases use node-varying factor assignments.

ID	n	m	d	Q	q	Z	Calls O/A
S01	4	0	0	2	0	16	2/2
S02	6	2	2	3	0	0	3/3
S03	6	2	4	5	0	32	5/5
S04	4	2	4	3	1	10	27/15
S05	6	3	6	4	1	30	52/28
S06	8	3	6	4	1	96	68/36
S07	6	2	6	3	2	50	219/66
S08	8	2	6	3	2	192	387/111
S09	10	2	6	3	2	784	603/168
S10	6	2	6	2	3	48	466/84
S11	8	3	9	3	3	168	1,731/279
S12	6	2	6	3	2	50	219/66
S13	10	3	9	3	3	704	3,483/528
S14	8	3	9	2	4	168	3,394/326
S15	4	4	12	2	6	8	162/32
S16	8	6	12	5	2	24	645/185
N17	4	2	4	2	2	8	66/22
N18	6	2	4	2	2	40	146/44
N19	6	2	6	2	3	52	466/84
N20	8	2	6	2	3	192	1,154/186
N21	6	3	9	2	4	44	946/114

16.3 Matched computational work and fairness controls

Both algorithms use the same factor evaluator, exact polynomial convolution, full measurement box $\{-1, 0, 1\}^2$, node order, local assignment order, and full Hermite elimination. For each measurement tuple they first scan for representatives and then scan for local restricted sums, as in the source proof. Unattainable tuples are skipped. There is no precomputed table of all global assignment values in either timed solver. Exhaustive enumeration is an untimed independent oracle.

The original loop is ordered with U outermost so its fixed correction rows can be prepared once per U, exactly as for aggregation. It still executes every pair (E, U), with $U \subseteq E$ and $|E| \leq q$. This benign loop interchange is an optimization of the reference implementation, not an application of the aggregated identity. The aggregate implementation performs one restricted fiber calculation per U over the enlarged (z, w) coefficient array. The final alternating functional is applied only after group multiplication. Both kernels skip zero scalar products; neither uses global memoization, rank compression, weighted-support pruning, or target-only Hermite recovery.

These controls isolate the change under study. They do not establish that either Python implementation is optimal. More sophisticated shared work across restricted calls could improve the original algorithm too.

16.4 Measurement protocol and reproducibility

The main suite uses seven matched repetitions per fixture. Each method runs in a fresh sequential Python subprocess; their order within each repetition is randomized with seed `20261026`. Wall

time includes row construction, validation, Hermite-matrix construction, all node jets, and full polynomial recovery. Process launch, imports, input JSON reading, oracle construction, post-run comparisons, and result serialization are excluded. Preparation, kernel, and recovery times are also recorded separately. The runtime samples do not use `tracemalloc` or the optional detailed arithmetic counters.

The machine is Windows 11 with an Intel Core i7-1165G7, four physical cores/eight logical processors, and CPython 3.12.14. Execution is single-process per solver, without CPU-affinity pinning or control of background activity and power management. The observed timing spread is substantial. Medians and ranges are descriptive measurements, not statistical confidence intervals or universal speed guarantees.

Memory is measured in separate fresh workers. The primary measure is peak Python-traced allocation from preparation through recovery; it excludes the already loaded interpreter and input object, but includes the constructed layout, coefficient arrays, and recovery data. Windows peak working set is also recorded and includes the interpreter and tracing overhead. Additional phase profiles separate kernel allocations from the common recovery peak. Kernel incremental peak means peak traced allocation during the kernel minus the live traced allocation immediately after preparation, not an operating-system RSS difference.

Raw instances, every timing sample, exact oracle coefficients, diagnostic counters, code hash, and memory profiles are retained under `eth-benchmark-v2/matched-run01/` and `eth-benchmark-v2/matched-run02/`. The original run used the frozen `benchmark.py`; the second used `benchmark_v2.py`, which adds node-varying factor assignments and rejects noncontiguous partitions unsupported by its bit embedding. Both routines within each run use exactly the same code version. The first suite's contiguous fixtures were unaffected by that validator limitation. The new entry point also rejects Python's assertion-disabling `-O` option. The supported node-varying fixture generator always uses $Q = 2$ and complete assignments for both nodes. The frozen validator is not a general input-schema validator: a manually edited incomplete node map can pass its fallback check and fail during jet evaluation. Imported calls also require ordinary, nonoptimized Python because the assertion guard is at the CLI entry point. Neither limitation is exercised by the recorded invocations. They should be hardened before broader reuse. `phase_profile.py` and `phase_profile_v2.py` supply the separately executed phase and direct-fiber controls. The README gives commands that require new output directories and refuse to overwrite prior measurements.

16.5 Exact agreement and measured runtime

All 21 fixtures produced identical exact counts under both methods. More strongly, every jet coefficient and every reconstructed polynomial coefficient agreed with an independently enumerated deformation polynomial; unused high-degree recovery coefficients were zero. The direct Boolean truth-table count independently checked the constant term. All 294 timed solver executions, 42 separate memory runs, and 42 diagnostic runs passed these comparisons. The code's initial self-test also passed 100 convolution checks and 24 matched method checks, and rejected an intentionally invalid off-group layout. The deformation oracle has independent enumeration and convolution, but shares row construction and the row-dot-product helper with the tested implementation. Its independence is therefore not total; the explicit layout proofs and independent static review address that shared part. A separate post-timing regression run passed 100 mixed (z, w) convolution checks, 20 method/oracle comparisons including odd group sizes and an empty clause, and four alternating node-reentry checks. It also confirmed rejection of two corrupted node rows, a noncontiguous partition, and the CLI's optimized-Python invocation. Those runs are not added to the timing

statistics; their records are in `eth-benchmark-v2/regression-results.json`.

Table 7: Matched pipeline wall time in milliseconds: seven fresh-worker samples per method. O is original, A is aggregated; ratio is median O divided by median A. Ranges are observed minima and maxima.

ID	O median	A median	O/A	O range	A range
S01	0.466	0.539	0.87	0.259–0.612	0.312–0.626
S02	1.069	1.135	0.94	0.932–1.331	1.062–2.115
S03	3.804	3.779	1.01	1.913–5.723	2.121–4.487
S04	4.843	3.756	1.29	4.444–6.908	3.283–4.475
S05	18.564	12.461	1.49	17.223–21.319	11.570–15.463
S06	48.059	33.333	1.44	42.129–195.158	25.539–115.111
S07	196.037	70.523	2.78	143.456–268.470	38.056–94.696
S08	250.717	86.236	2.91	228.720–309.371	80.580–187.967
S09	1,889.863	546.129	3.46	878.564–2,927.368	283.576–852.221
S10	398.996	119.954	3.33	250.171–455.454	89.963–195.760
S11	3,042.474	607.451	5.01	1,878.445–3,416.439	238.840–828.481
S12	907.584	354.187	2.56	540.101–1,539.021	298.076–543.378
S13	9,833.618	1,643.942	5.98	7,881.177–11,138.673	805.800–3,016.550
S14	3,895.762	291.173	13.38	1,945.820–5,340.162	261.424–455.089
S15	140.890	38.303	3.68	102.853–156.422	35.260–55.006
S16	1,987.977	655.549	3.03	1,790.097–3,074.709	608.762–843.923
N17	50.535	24.907	2.03	23.570–59.050	10.283–92.737
N18	208.674	131.844	1.58	146.835–308.129	72.790–162.887
N19	880.379	225.510	3.90	709.463–1,015.560	188.610–706.896
N20	3,488.846	501.599	6.96	2,354.011–5,856.887	373.619–917.970
N21	2,667.340	473.529	5.63	2,419.055–3,238.591	337.451–816.178

Every one of the 18 cases with $q > 0$ had a shorter aggregate median in these runs, with median ratios from 1.29 to 13.38. The largest ratio occurs at S14; it is descriptive and not a forecast of scaling. The two smallest controls S01 and S02 were slower with aggregation, while S03 was nearly tied. These three have $q = 0$ and exactly the same number of restricted calls. The wide raw ranges, particularly on the busier runs, preclude a strong claim based on the precise ratio digits. Exact call and assignment-visit reductions corroborate the mechanism independently of wall-time noise.

The gains are *observed finite implementation gains*, in contrast to the earlier report's call-count-only evidence. They do not strengthen the asymptotic theorem. The $q = 0$ cases have no pair-loop reduction, so the aggregate representation can be pure overhead. The $q \geq n$ case remains an exponential enumeration regime despite its finite speed ratio. The largest tested fixture has only ten variables. The suite is not a sample of difficult unrestricted random SAT instances.

16.6 Memory, arithmetic work, and the structural control

Table 8: Memory in KiB (1 KiB = 1,024 bytes). Whole-run peaks come from separate tracing workers. Kernel increments are phase peaks minus the live post-preparation baseline, not allocation-exclusive coefficient sizes.

ID	Whole O	Whole A	Kernel increment O	Kernel increment A
S01	4.48	4.48	2.66	2.51
S02	6.73	6.66	3.61	3.27
S03	9.10	9.12	3.86	3.55
S04	9.51	9.77	3.86	3.92
S05	14.52	14.63	4.52	4.43
S06	15.17	15.25	4.62	4.52
S07	16.53	16.69	4.56	5.05
S08	17.11	17.27	4.62	5.21
S09	17.62	17.65	5.05	5.35
S10	13.59	14.05	4.63	6.29
S11	25.62	25.85	5.37	7.25
S12	18.78	18.94	6.00	7.52
S13	26.29	26.37	5.75	7.31
S14	20.41	20.96	5.54	8.65
S15	29.78	30.73	6.11	11.34
S16	38.55	38.38	6.28	6.85
N17	11.29	11.67	4.93	5.98
N18	11.37	11.64	4.95	5.88
N19	14.91	15.37	5.73	7.45
N20	15.23	15.65	6.17	8.70
N21	21.21	21.84	6.98	12.19

Whole-pipeline traced peak ratios A/O range from 0.991 to 1.033; there is no uniform memory reduction. Common layout and dense Hermite-recovery allocations can dominate the peak. For $q > 0$, observed kernel incremental-peak ratios range from 0.98 to 1.86. These are net phase measurements, not a count of just the extra generating coefficients; released buffers and stored output jets affect them. The logical coefficient capacity per ring element grows from J to at most $J(q+1)$, so a speed benefit is compatible with a larger kernel memory footprint. Untraced timing workers had lifetime process peaks between 24.56 and 25.24 MiB, including interpreter and imports. Traced-worker process peaks, retained in the raw data, also contain tracer overhead; neither process measure is an isolated solver-workspace bound.

Table 9: Diagnostic work on selected cases, measured outside timing. Products means nonzero convolution coefficient products only; bits are maximum inspected kernel coefficient numerator/denominator lengths.

ID/method	Assignment visits	Factor evaluations	Products	Bits N/D
S03 O	595	160	478	19/1
S03 A	595	160	478	19/1
S08 O	86,301	14,400	109,927	22/1
S08 A	24,753	4,320	43,732	22/1
S13 O	1,501,173	291,456	3,081,055	37/1
S13 A	227,568	47,376	644,412	37/1
S14 O	756,862	110,592	1,400,047	29/1

ID/method	Assignment visits	Factor evaluations	Products	Bits N/D
S14 A	72,698	12,492	205,851	29/1
S15 O	10,854	2,304	36,576	34/1
S15 A	2,144	576	13,276	34/1
N20 O	257,342	32,640	307,459	22/4
N20 A	41,478	5,760	76,747	22/4
N21 O	112,574	16,512	215,200	28/5
N21 A	13,566	2,472	43,290	28/5

The diagnostic scalar-product count covers nonzero products in the implemented polynomial convolutions, not every CPU instruction or the rational operations in Hermite elimination. Reported coefficient bit lengths describe inspected kernel polynomial values, not a proof of a uniform bit bound for all instances. Traced peaks are measured in separate runs and should not be conflated with the timed-run working set.

Because the first 16 fixtures already satisfy separation at zero, one direct shared-summary sum computes the count without jets or Hermite reconstruction. A separate control executes exactly that calculation, using the same local evaluator with $J = 1$. It matches every applicable exact count. The control is not applied to the five node-varying fixtures because its separation premise fails there. It is measured in three later fixed-order runs, including preparation of an unnecessary Hermite matrix, and is not part of the seven-repetition paired timing protocol. The direct-control medians range from 0.145 to 4.390 ms (all individual samples: 0.139–9.446 ms). They are shorter than the corresponding aggregate medians in every first-suite fixture, although these later, unpaired measurements are not suitable for a precise speedup estimate. The control even includes unnecessary Hermite-matrix preparation, so it is not a fully optimized direct implementation. This is an important limitation, not a failed correctness test: aggregation can improve the chosen jet routine while an easier structural method is better for this particular input family.

16.7 What has advanced and what remains open

Revision 2 establishes a reproducible implementation-level comparison, not merely agreement of abstract identities. It demonstrates the local call reduction in actual streamed fiber calculations, measures its coefficient-state cost, and exhibits both gains and overhead cases. An independent review of the new implementation and fixture assumptions is included in `eth-benchmark-v2/independent-audit.txt`, with the node-varying follow-up in `independent-node-audit.txt`. Its scope is static code and finite-layout reasoning, not independent execution or a global proof of the source paper.

The next substantial step is to generate instances from the source's actual general construction at feasible parameter values, or develop a different nontrivial design with equivalent certified guarantees. Additional baselines should share more work across the original calls and use optimized exact arithmetic. Larger controlled benchmarks would need power/load controls, more independent instances per parameter setting, and a complete account of construction cost. Incorporating the precision certificates into Appendix D remains unimplemented here. No result establishes a stronger general SAT exponent, an advantage unique to Ram terminology, or an optimality lower bound.

17 Revision 3: degree-aware recovery and certified quotient compression

17.1 What the 13-volume investigation adds

The 627-topic inventory and targeted mathematical reading are documented in Appendix C. The expanded entries often make explicit an assumption or remainder that was only implicit in a shorter corpus report. This is valuable, but explicit exposition is not by itself a new theorem. We distinguish (i) retained results already proved in the preceding report, (ii) classical consequences made explicit by the books, and (iii) additional application-level deductions proved below. No worldwide priority claim is inferred from a result's absence in the preceding report. The useful Ram contribution is the connected treatment of exact representation, information retained, physical norms, defects, and the conditions under which a finite computation answers the original question. The same proved bounds are available by conventional methods under the same hypotheses.

The additional deductions are exact target-identifiability tests, sharp finite degree-aware precision budgets, and orbit compression under proved permutation symmetry. The first two attach to Hermite recovery; the third attaches to the Section 3 Boolean-jet routine. They do not replace the source's general circuit/measurement construction or Appendix D recursive tensor contraction. The auxiliary-PDE question is unchanged: no such PDE occurs in the inspected ETH manuscript.

Corpus connection	Additional deduction	Essential limit
M225, R106, R112, R69	Row-space target recovery and sharp 1/4/7-bit losses for three certified degree classes	Fixed finite grid; the degree-three case is already licensed by the local source lemma
M310, R117, R198	One Boolean-jet call per certified permutation orbit	Equivariance of the entire deformed family is required
R103, R111, R135, R152, R189	Exact closure and complete coefficient contracts; explicit failure witnesses	Reencoding a state does not remove distinguishable information

17.2 Recovering the target is weaker than recovering every coefficient

M225 treats confluent Hermite interpolation, while R106 and R112 describe compatible displaced polynomial jets and full-state rank. R69 and R165 motivate goal-sensitive measurement choices, but their real-norm error and variance formulas are not modular precision theorems. This makes the degree-freedom remark in Section 13 into a precise usable criterion. Let V be a specified finite-dimensional rational polynomial space, with coefficient vector $c \in \mathbb{Q}^d$. Let the available exact measurements be $h = Ac \in \mathbb{Q}^m$ and the desired scalar be ℓc. The matrix A may be rectangular or rank deficient. In the ETH application the rows are scaled Hermite jets, and ℓ evaluates at zero.

Theorem 17.1 (Target identifiability and a certificate for deleting jets)**.** *The target is determined by the measurements for every $c \in \mathbb{Q}^d$ if and only if*

$$\ker A \subseteq \ker \ell, \qquad \textit{equivalently} \qquad A^T\lambda = \ell^T \textit{ for some } \lambda \in \mathbb{Q}^m.$$

For a selected subset S of the measurement rows, deletion of the other rows preserves exact target recovery if and only if $A_S^T\lambda_S = \ell^T$ is solvable. If it is not solvable, a vector $c_* \in \ker A_S$ with $\ell c_* \neq 0$ is an explicit impossibility witness. These tests concern exact data and are separate from precision or runtime optimization.

Proof. Equal measurements of c and c' mean $c - c' \in \ker A$. Their targets agree exactly when ℓ annihilates this kernel. Finite-dimensional row-space/kernel duality gives the displayed linear equation. A solution gives $\ell c = \lambda^T h$ for every c. Applying the same argument to A_S proves the deletion criterion and its witness statement. In particular 0 and c_* are indistinguishable from the retained data when deletion fails. □

There is an important limit for ordinary prefix jets. Suppose the retained nodes are all nonzero, with consecutive derivatives $j = 0, \dots, r_t - 1$, and put $N_S = \sum_t r_t$. On the full space $\deg F \le D$, these data determine $F(0)$ if and only if $N_S > D$. If $N_S \le D$, the polynomial $\prod_t (T - t)^{r_t}$ has all retained jets zero but a nonzero constant term. Conversely, if $N_S > D$, any polynomial in the measurement kernel is divisible by that product and has smaller degree, hence is zero. Target-only recovery therefore does not permit arbitrary deletion of ordinary Hermite data; its advantage comes from the actual degree class, a target-specific functional, or other certified structure.

For integer nodes and scaling, the Hermite rows on the monomial basis $1, T, \dots, T^D$ are

$$A_{(t,j),k} = \begin{cases} \binom{k}{j} t^{k-j} \alpha^j, & k \ge j, \\ 0, & k < j. \end{cases}$$

Every proposed degree reduction must be proved for the *actual* polynomial being recovered. Observing small high-degree coefficients numerically is not a certificate. When more rows than needed are available, the family of target formulas is the affine solution set of $A^T \lambda = e_0$. This is the appropriate place to choose cheaper channels or better precision budgets, without requiring an inverse for the entire ambient Hermite space.

For any chosen formula, the already proved condition $b_i + v_2(\lambda_i) \ge p$ remains necessary and sufficient for a uniform guarantee against independently variable errors of valuations at least b_i in each retained coordinate. A vanishing weight needs no measurement. Row-space membership does not by itself minimize the valuation loss or the cost of obtaining the retained rows.

Theorem 17.2 (A precision-plan criterion over the two-local rationals)**.** *Let $\mathcal{O} = \{a/b \in \mathbb{Q} : b \text{ odd}\}$, and suppose the exact jet coordinates and target are integral in this ring. For proposed integer channel precisions b_i and desired output precision p, an exact rational linear decoder on the specified coefficient space can guarantee the target modulo 2^p for all independent coordinate errors in $2^{b_i}\mathcal{O}$ if and only if*

$$\ell^T \in A^T \operatorname{diag}(2^{p-b_i}) \mathcal{O}^m. \tag{51}$$

When A and ℓ are integral at two, the least nonnegative common extra loss among exact linear decoders is

$$\delta_* = \min\{\delta \ge 0 : 2^\delta \ell^T \in A^T \mathcal{O}^m\},$$

provided the target-row equation is solvable.

Proof. A fixed decoder is exact when $A^T \lambda = \ell^T$. Its output error always belongs to $2^p\mathcal{O}$ exactly when $\lambda_i \in 2^{p-b_i}\mathcal{O}$ for each coordinate. Sufficiency follows by summing integral errors; necessity follows by taking a single nonzero coordinate error 2^{b_i}. Substituting $\lambda = \operatorname{diag}(2^{p-b_i})\mu$, $\mu \in \mathcal{O}^m$, gives (51). For $b_i = p + \delta$, multiply the target equation by 2^δ. A rational decoder has finite denominator valuations, so the minimum exists whenever one decoder exists. □

This extends the fixed-decoder certificate to all exact decoders on a known space. It is a classical module-membership criterion, not a new general interpolation theorem or a proved cheapest mixed-precision schedule. Smith normal form over $\mathcal{O}$ can decide membership after clearing denominators.

A nilpotent coefficient algebra is not a discrete valuation ring: the scalar certificate is used coefficientwise, as in the source, not by asserting a Smith form over that algebra. No general Smith-form optimizer was implemented in the new tests. R78's real-norm mixed-precision iteration and R165's Gram-variance formula are useful conceptual comparisons but are not substitutes for this divisibility argument. R43 describes Gaussian orthogonal Hermite panels, not confluent Hermite interpolation; the shared word does not make its formulas applicable here.

17.3 A sharp finite degree-aware precision improvement

Use the same local six-channel grid as the first precision example in Section 13: nodes $t = -1, 1$, scaling $\alpha = 4$, and available jets $h_{t,j} = [z^j]F(t + 4z)$ for $j = 0, 1, 2$. The following formulas are exact on the indicated degree classes:

$$\deg F \le 1: \quad F(0) = \tfrac{1}{2}(h_{-1,0} + h_{1,0}), \tag{52}$$

$$\deg F \le 3: \quad F(0) = \tfrac{1}{2}(h_{-1,0} + h_{1,0}) + \tfrac{1}{16}(h_{-1,1} - h_{1,1}), \tag{53}$$

$$\deg F \le 5: \quad F(0) = \tfrac{1}{2}(h_{-1,0} + h_{1,0}) + \tfrac{5}{64}(h_{-1,1} - h_{1,1}) + \tfrac{1}{128}(h_{-1,2} + h_{1,2}). \tag{54}$$

One verifies them by substitution of $F(T) = T^k$ for every k in the specified class; linearity then proves the all-polynomial claim. Odd terms cancel in the symmetric combinations. The remaining even terms determine the coefficients in the displayed triangular system.

Proposition 17.3 (Optimal common losses for this grid and these classes)**.** *For exact rational linear target formulas on the six available channels, the smallest nonnegative common extra-precision losses for degrees at most* $1, 3, 5$ *are respectively* $1, 4, 7$ *bits. Thus a certified degree-three class reduces the degree-five certificate by three bits, and a certified degree-one class by six bits, in addition to deleting two or four unnecessary channels.*

Proof. Equations (52)–(54) give the upper bounds: all weighted errors are in $2^p\mathbb{Z}_{(2)}$ when every retained jet is known modulo $2^{p+1}, 2^{p+4}, 2^{p+7}$, respectively. For the lower bounds use

$$F_m(T) = (T + 1)^m(T - 1)^{m+1}, \qquad m = 0, 1, 2.$$

These have degrees $1, 3, 5$ and odd constant term. Their six scaled jets are all divisible by 2^{1+3m}. Direct expansion at -1 and 1 gives at least one jet of valuation exactly $1 + 3m$. If every coefficient of an exact target formula had valuation strictly greater than $-(1 + 3m)$, its value on F_m would be even, contradicting the odd target. Hence a coefficient with at least the claimed denominator loss is unavoidable, even if all six channels are retained. This is optimality within the stated exact linear recovery and independent-error contract, not a lower bound for all counting algorithms or for correlated-error encodings. □

An indistinguishability argument strengthens the lower bound for this data contract. The admissible polynomials 0 and $2^{p-1}F_m$ have identical six-channel residues modulo $2^{p+1+3m-1}$, but their targets differ modulo 2^p. Therefore one fewer common bit cannot suffice even for a nonlinear decoder using only these residues. This does not assert that the witnesses are realized by every source tensor network; additional tensor-realizability information changes the data contract.

For completeness, the optimal common losses for all six degree classes $D = 0, 1, 2, 3, 4, 5$ are $0, 1, 3, 4, 6, 7$. Besides the odd-degree formulas, upper weights in the six-channel order

$(-1,0),(-1,1),(-1,2),(1,0),(1,1),(1,2)$ are

$$\lambda^{(0)} = (1,0,0;0,0,0),$$
$$\lambda^{(2)} = (1/4,0,0;3/4,-1/8,0),$$
$$\lambda^{(4)} = (11/16,1/8,1/64;5/16,-1/32,0).$$

They are checked on the monomial bases. The witnesses 1, T^2-1, and $(T^2-1)^2$ have odd constants and minimum six-jet valuations $0,3,6$, proving the matching lower bounds. In particular, forcing weights to be symmetric can miss the degree-four optimum.

The distinction from revision 2 is substantive but local. Revision 2 computed the exact weights for the full degree-five space and obtained seven extra bits rather than the source's conservative 64-bit allowance. For the particular source-lemma fixture $a=1, L=2, u=1, M=1$, the degree bound $M(2L-1)$ is already three. Thus four extra bits are certified for that same local configuration, without assuming an additional degree reduction. Degree one requires an additional certificate. This reads the surplus channels against the actual source degree bound, rather than against the larger canonical interpolation space. For a genuinely degree-five polynomial the seven-bit result remains unchanged.

These small parameters are not a complete instance of all large-size packing conditions in the source's recursion. Creation-time canonical lifts must remain fixed, and a child precision must still obey any inherited strictly increasing requirement. Moreover, Appendix D obtains the entire polynomial at each active node using $M(2L-1)+1$ evaluations. Deleting two jet channels does not by itself delete those evaluation calls. Smaller valid node precision can reduce arithmetic cost, but no full recursive runtime improvement has been measured here.

Misidentifying the degree gives immediate failures. Applying (52) to T^2 returns 1 instead of 0; applying (53) to T^4 returns -1; applying (54) to T^6 returns 1. All three failures are exact, not floating-point effects.

17.4 Symmetry can remove more Boolean-jet calls, but only with a certificate

M310 (Krawtchouk polynomials), R117 (quotient closure), and R198 (lumpability) suggest looking for exact permutation orbits in the aggregated U loop. The relevant fact is symmetry of the complete deformed family, not just equal Hamming weights of the selected sets.

Theorem 17.4 (Orbit aggregation of the existing Boolean identity)**.** *Let a permutation group $G \le S_n$ act on assignments and subsets. Assume the family in Theorem 8.1 obeys*

$$p_{gx}(gX) = p_x(X) \qquad (g \in G)$$

as an exact polynomial identity in the declared coefficient algebra. Put

$$S_U = \sum_{x_U=1} w_q(|x|,|U|)p_x(\mathbf{1}_U).$$

Then $S_{gU} = S_U$, and the count or weighted target is

$$\sum_x p_x(x) = \sum_{\mathcal{O}\subset\{U:|U|\le q\}} |\mathcal{O}| S_{U_\mathcal{O}},$$

where the sum is over G-orbits and one representative is chosen in each orbit. For full permutation symmetry this needs only $\min(q,n)+1$ representative restricted calls. The same conclusion holds coefficientwise for the truncated z,w jets when the full deformed $G_x(X,z)$ is equivariant.

Proof. Replace x by gy in S_{gU}. This is a bijection between the restricted assignments, preserves cardinalities, and transforms $p_{gy}(\mathbf{1}_{gU})$ into $p_y(\mathbf{1}_U)$. Thus the summands agree. Group the finite U sum in Theorem 8.1 by its orbits. For S_n, subsets of each fixed size are one orbit, with cardinality $\binom{n}{|U|}$. All manipulations preserve integer multiplicities; no averaging by a possibly noninvertible group order is required. □

The permutation condition must hold at the actual interpolation node, for its factor assignment, summary measurements, correction jets, and output functional. Generic labelled 3-CNF formulas need not have such symmetry. Discovering a useful group and certifying equivariance has a cost. Even after call reduction, each representative call can remain expensive; this is a restricted-instance refinement, not a new general SAT exponent. The source's general construction has not been shown to satisfy the condition.

17.5 Why a small summary or Hamming weight alone is insufficient

In a finite state algebra let J be a retained linear measurement map and T_a the operator for multiplication by a factor a. There is an exact coarse update $\widehat{T}_a$ for *every* state, with $JT_a = \widehat{T}_a J$, exactly when $\ker J$ is invariant under T_a. Indeed, kernel invariance makes $\widehat{T}_a(Jv) = JT_a v$ well-defined; the converse follows by applying the intertwining to $v \in \ker J$. For a sequence of factors, this condition is needed for each update, and the final target must factor through J as well. This is R117 applied to the paper's exact finite algebra. A complete exact quotient may offer no compression: if multiplication and the target distinguish every state, all of those distinctions must remain represented.

On two labelled bits, states $(1, 0)$ and $(0, 1)$ have the same Hamming weight but multiplication by x_1 distinguishes them. Thus a Hamming-weight summary is not closed for an arbitrary labelled factor. M310's exact Krawtchouk closure relies on the symmetry of its specific operators. It does not license replacing the source's carefully designed shared measurements by weight alone. R103 and R152 supply a related warning: one coordinate-line or total-sum check cannot certify all mixed coefficients of a multivariate jet. The full coefficient agreement retained from the v2 tests is therefore more informative than agreement of a single recovered count.

17.6 New exact tests and their limited computational meaning

The standard-library script `mathworld-v3-support/test_eth_refinements.py` checks all basis monomials for the three Hermite formulas, their precision certificates, and the three out-of-class failures. The separate lower-bound checks verify all six jets of each F_m. The script `mathworld-v3-support/test_degree_table.py` also checks all 21 basis monomials across degrees zero through five, the even-degree weights, and the residue-indistinguishability controls. Its record is `mathworld-v3-support/degree-table-results.json`. For the symmetry test it uses

$$p_x(X) = (1 + |x|)\left(1 + \sum_{i=1}^{n} X_i\right)^q.$$

This is an exactly symmetric, integer-valued, degree-q family. Direct assignment summation, the ordinary aggregated identity, and the orbit-reduced identity give identical *weighted sums*:

n	q	Exact weighted sum	Source pair calls	v2 U calls	Orbit calls
6	2	5,248	73	22	3
8	3	239,616	577	93	4
10	4	14,029,824	4,521	386	5

These are not SAT solution counts, and the reference implementation enumerates assignments inside the calls. The table tests identities and counts representative calls; it reports no measured wall-clock or memory advantage. Such a benchmark would require the same factorized implementation, symmetry-detection cost, and bit arithmetic on each method.

For a negative control, let $n = 4, q = 1$ and $p_x(X) = 1 + 3X_1 + X_2$. The true weighted sum is 48. Invalidly treating all singleton subsets as symmetric and using $\{1\}$ as their representative returns 112. A valid implementation must reject that compression, rather than accept an apparent reduction in work. The results are recorded in `mathworld-v3-support/eth-refinement-results.json`.

17.7 Incremental conclusions, costs, and remaining work

The preceding v2 runtime and memory results are retained without change. The new tests establish exact local identities, smaller certified precision on specified degree classes, and fewer representative calls on symmetric fixtures. They do not add a measured speedup on generic instances. Rank tests and exact target solves cost rational linear algebra; symmetry must be certified; a target-optimal formula may have expensive coefficients; and the source's recursive lifting and valuation contracts must still be obeyed.

A next implementation should derive certified degree bounds inside each actual recursive node, measure the complete cost of a selected target formula, and detect only symmetries that survive all correction and measurement maps. It should compare all coefficients and exact counts, not just floating-point target values, and retain negative controls like the ones above. These are concrete routes to additional local improvements, not completed improvements to the source's asymptotic exponent or an independent proof of its full ETH claim.

18 Equation comparison and attribution of improvements

Table 10: Equivalent representations and their actual benefit.

Conventional/source form	Ram-compatible form or refinement	Assessment
Sum over Boolean assignments	Boolean quotient plus moment functional $\Lambda(X_S) = 2^{n-\lvert S\rvert}$	Exact rederivation; no automatic compression.
Condition on shared linear measurements	Exact aggregate-state/fiber operator with multiplicity sums	Same source identity; clearer certificate and state-cost accounting.
Subset-pair Boolean jets	One restricted call per U plus a local Hamming generating jet	Proved fewer calls; polynomial arithmetic overhead; no better headline exponent.

Conventional/source form	Ram-compatible form or refinement	Assessment
Uniform first-order correction budget	Weighted downward-closed support family	Proved conditional extension when higher correction orders exist.
Conservative Hermite precision envelope	Actual valuation of the target-functional weights	Proved certificate; strict finite examples; no general asymptotic gain shown.
Arbitrary summary row list	Exact row-basis selection and row-specific integer boxes	Proved instance-dependent reduction without changing fibers.
Tensor basis replacement	Dual inverse transforms on contracted legs; transported product	Exact equivalence; dimensions and hidden contraction costs remain.
Ordinary low-rank or L^2 truncation	Quotient-ideal or valuation-certified truncation; otherwise explicit target error	Prevents unsupported exact-count claims; may require more computation.
Physical quaternionic channels	Ordered real block representation	Methodological relevance only; no demonstrated SAT improvement.

18.1 Advantages of the Ram-based organization

The strongest advantage is a disciplined modular description: state space, coefficient algebra, multiplication, observation functional, and error certificate are all explicit. The new generating-jet aggregation exemplifies how an extra small coefficient state can eliminate a repeated combinatorial index. Weighted order budgets make stronger local vanishing useful without discarding necessary contributions. The precision certificate targets the count itself rather than an unnecessarily uniform coefficient accuracy.

The corpus also contributes useful safeguards: projection leakage is distinguished from quotient reduction; rank is distinguished from attainable state count; finite inverses are distinguished from unrestricted inverses; and nonlinear transformed products retain their range constraints. These are valuable for an implementer deciding where a local optimization remains mathematically exact.

18.2 Disadvantages and comparisons with existing methods

The scalar proof can already be expressed concisely using conventional finite differences, quotient rings, generating functions, and Hermite interpolation. Calling these objects Ram operators does not confer a unique speed advantage. More coefficient dimensions can increase constants and bit arithmetic. Exact row compression may be redundant, sparse-state storage can destroy polynomial-space guarantees, and complex or hypercomplex coordinates can make a purely rational problem harder to implement.

The source's main innovations are precisely where a generic representation is insufficient: simultaneous low-degree incidence designs, arithmetic degree control, and a valuation-sensitive contraction recursion. Those ingredients are retained rather than replaced. A fair implementation comparison must use the source's streamed and structured baseline, not only a naive dense interpolation

algorithm or exhaustive assignment sum.

19 Research directions with explicit success criteria

19.1 Implement the aggregated routine inside the actual construction

Revision 2 implements both routines on checked finite rows, including node-varying layouts, and records the matched work, runtime, and memory in Section 16. A next implementation should exercise the source's actual general Section 4 construction and more optimized baselines, rather than only these small input-specific designs. A useful result would identify the range of q, J and group sizes in which the saved calls outweigh the extra generating dimension. Correct output must be compared to exact counts on every tractable instance.

19.2 Search for higher-order correction designs

Theorem 9.1 becomes useful if real designs give $\nu_i > 1$ for many coordinates. The optimization problem is to reduce the weighted subset family without increasing R, the number or range of measurements, or construction cost enough to cancel the saving. An asserted improvement to (22) must display all three terms after the redesign. A formal higher-order zero is not free.

19.3 Deploy exact target weights in recursive two-adic recovery

The nodewise certificate can be inserted into a prototype of Appendix D while preserving immutable creation-time lifts. A first goal is a measured reduction in working precision and mode enumeration on nontrivial recursive instances. A stronger goal would be an improved *uniform* upper bound on the valuations of the Hermite weights. Only the latter, combined with the recursion and packing bounds, could justify a better asymptotic exponent. The finite numbers in Table 3 do not establish it.

19.4 Finite-domain and weighted-count extensions

The finite-alphabet algebra (5) and weighted factors permit formal extensions to fixed-domain constraint satisfaction and rational partition functions. The source Section 3 already allows commutative $\mathbb{Q}$-algebras, so that observation alone is not new. A new complexity theorem would require a compatible low-degree design, bounds on domain encoding, factor scopes, coefficient sizes, and a final modulus sufficient to recover the weighted answer. Positivity and an $n + 1$-bit count bound cannot be assumed for arbitrary signed weights.

19.5 Formal verification and negative results

The aggregation and weighted-support theorems are finite-sum identities well suited to Lean formalization. Their implementation should be linked to explicit coefficient arrays and the streamed state machine, rather than proving only an abstract equality. The target-precision theorem similarly needs a verified valuation calculation and fixed-lift interface.

No argument here proves that the source's exponent is optimal. A lower bound for a selected moment representation, an example with many summary values, or an inability to improve an interpolation estimate is not a lower bound for all algorithms. Proving a genuine general lower

bound would require a separate computational-model theorem. Conversely, an equivalent Ram formulation does not by itself overcome such a barrier.

20 Conclusion

Ram Calculus is substantively relevant to the source's finite algebra and verification interfaces, not because the paper secretly solves an auxiliary PDE. The most concrete addition is the aggregated Boolean-jet identity, which replaces a subset-pair enumeration by a subset enumeration with a small exact generating state. The weighted version and exact row-basis reduction give conditional instance-sensitive extensions. Target-specific two-adic Hermite weights yield provably valid precision budgets, with strict improvements in the executed finite examples.

These results improve selected calculations and clarify their limitations. The added finite benchmarks demonstrate exact agreement and local implementation speed gains with a memory tradeoff, but they do not supply a stronger unrestricted SAT time bound, certify performance on general hard instances, or replace the source's difficult construction and recursive proof. The mathematical contribution is therefore a collection of exact, testable refinements and a precise separation of representation, information, arithmetic precision, and computational complexity. The positive research opportunity is to integrate these refinements into the actual algorithm and determine, with full bit and memory accounting, which local advantages survive at scale.

A Bounded-audit findings and arithmetic safeguards

The separate source-level audit did not find a demonstrated error in the examined Section 3–5 identities, Section 4 construction, Appendix B arithmetic accounting, and Appendix D precision and recursion arguments. This statement is deliberately narrower than global certification. Appendix A's complete combinatorial proof, all external prerequisites, and the circuit-lower-bound consequences were not independently re-proved; the Lean dependency graph was not rebuilt.

Two arithmetic details deserve emphasis. First, parity divisibility in Section 5 is used at the restored integer inputs at $T = 0$, not at the rational deformed inputs at other nodes. Second, the source bounds intermediate numerators, not merely the final answer. A common denominator for a full contribution can be fixed in advance. Adding exponentially many signed contributions increases the numerator bit length by the logarithm of their number, provided each contribution already has a uniform height bound. It is not necessary to multiply every accumulated term into the next one. Polynomial-sized interpolation then admits exact fraction-free elimination with bounded minors. "Fraction-free" includes exact integer division and is not synonymous with division-free inversion.

The contraction audit likewise preserves the distinction between the scalar two-local field and the truncated coefficient algebra containing nilpotents. Only scalar units are inverted. Canonical lifting is not a ring homomorphism: the canonical lift of $1 + 1$ modulo two is zero, while the sum of the two lifts is two. The creation-time convention avoids needing that false homomorphism property. Reducing precision without preserving this convention would not be justified by Theorem 13.1 alone.

These observations explain why the report offers refinements rather than claiming repairs to proven source errors. The negative controls reject tempting but invalid alternative implementations. They are not findings against the original manuscript.

B Source register and reproducibility

Revision 2 benchmark code, frozen instances, per-trial data, and independent static audits are retained in `eth-benchmark-v2/`. The first timed code version and its data remain unchanged; the second version adds node-varying fixtures and a stricter partition contract. Public source TeX files are stored in `eth-support/source-42907c9/`. Extracted PDF text is `eth-support/source-paper-layout.txt`. The small test program and its JSON output are in `eth-support/`. Independent research notes record corpus paths and bounded-audit findings there. Existing research reports and supplied files were not changed.

The mathematical claims proved in this report do not require the entire private corpus as an axiom system. The specific imported ideas and their limitations are identified in Section 3; the main new identities have self-contained proofs. In particular, the aggregation theorem uses only finite subset inversion and distributivity, and the precision theorem uses only a fixed exact recovery functional and the valuation inequality for sums.

C Revision 3 corpus register, provenance, and reproducibility

The 13 source volumes were inventoried by their stable topic markers, not by inferred page headings. The inventory contains exactly 627 unique entries: 428 MathWorld-linked topics and 199 Ram-specific topics. The corpus reference is [20]. A complete topic register, with volume, source line anchors, and separate dispositions for the two OpenAI papers, is supplied as `mathworld-v3-support/topic-relevance-register.csv`. It includes topics not selected for a further application. That disposition is not a theorem that a topic can never be useful.

All 627 entries were included in the structural and broad relevance screen. Mathematical inspection was targeted to the potentially useful formulations, hypotheses, examples, and limits, rather than an attempted fresh proof audit of every result in all 13 books. Broad keyword matches are not treated as evidence of substantive applicability or novelty. For this paper the register distinguishes 32 explicit crosswalk entries, 81 related background entries, and 514 entries from which no additional application was selected. The two papers' categories overlap and are not additive.

The following precise locators support the mathematical crosswalk. A line number is the start of the topic entry in `Ram-Calculus-MathWorld-Volume-NN.tex`; it is not a PDF page number. Topic IDs remain the preferred stable locators when a volume is edited.

Topic	Title	Volume / line
M024	Finite Difference	01 / 3772
M025	Binomial Transform	01 / 3956
M026	Generating Function	01 / 4131
M027	Moment	01 / 4303
M028	Moment-Generating Function	01 / 4481
M097	Divided Difference	02 / 8775
M101	Umbral Calculus	03 / 175
R43	Hermite Data Panels	05 / 7811
R69	Goal-Oriented Ram Error Budgets	06 / 2866
R78	Mixed-Precision Ram Error Budgets	06 / 4222
M225	Hermite's Interpolating Polynomial	07 / 3502
M248	Walsh Transform	07 / 7028
M249	Hadamard Transform	07 / 7180
M310	Krawtchouk Polynomial	09 / 2100

Topic	Title	Volume / line
R103	Mixed-Derivative Generation of the Full Jet Matrix	11 / 5040
R106	Polynomial Compatibility Map Between Displaced Jets	11 / 5490
R111	Degree-Closure Conditions for Variable-Coefficient Jet Rows	11 / 6241
R112	Tall Forward Jet Map of Polynomial-Coefficient Differential Operators	11 / 6393
R113	Graded Monomial Bandedness of Multi-Index Ram Operators	11 / 6549
R117	Quotient Closure of Retained Information and the Invariant Lifting Equation	11 / 7160
R123	Composing Coefficients Force Binomial-Type Bases	12 / 175
R135	Finite Closure Characterizes the Taylor Jet; Scale-b Jets Do Not Close	12 / 2905
R152	Coefficient-Sum Spectral Constraint	12 / 6259
R165	One-Channel Pruning Identity for Ram Measurement Banks	12 / 8325
R173	Noncharacteristic Jet Recurrence and the Boundary Closure Determinant	13 / 175
R185	Difference-Jet Representation of Discrete Shift-Variant Kernels	13 / 1948
R187	Shifted Leibniz Rule for Forward Differences	13 / 2236
R189	Graph-Local Moment Matrices and Multilinear Exactness	13 / 2517
R190	Nilpotent Policy-Graph Inverse and the Soft-Value Path Partition	13 / 2662
R195	Hop-Shell Aggregation with Covariance Remainder	13 / 3364
R198	Lumpability Intertwining Defect	13 / 3780
R199	Dynamic Kron Elimination as Graph Volterra Memory	13 / 3939

Public-source verification was repeated on October 26, 2026. The current GitHub PDF blob identifiers for both manuscripts were unchanged from the previously retained versions. The wave manuscript's two root source files and all 19 section files matched the local pinned blobs; the ETH manuscript's four build TeX files also matched. This checks version identity, not the correctness of the source theorems. The records are `mathworld-v3-support/public-source-provenance.json` and `mathworld-v3-support/public-wave-sections.json`. Only public repository identifiers were requested online; private corpus text was not included in public search queries.

The original 13 volume sources and the two baseline reports and their PDFs are protected by the SHA-256 register `mathworld-v3-support/input-sha256.json`. Revision 3 is a new, standalone TeX source retaining the preceding report's full technical body, examples, comparison tables, and recorded checks. The additional material is separately identified; the earlier experiments were not silently relabelled as new tests. No original source or PDF was replaced. The code and JSON outputs in the new support directory distinguish exact arithmetic tests from floating-point manufactured diagnostics. Neither kind of test substitutes for the stated analytic proofs or for execution of the source's full algorithm/proof construction.

References

[1] OpenAI. *The Exponential Time Hypothesis is False*. October 17, revised October 25, 2026. Supplied PDF and source at commit `42907c9e999cc00d6abe7a50bfc1023250edd1b9`. https://github.com/openai/math/tree/42907c9e999cc00d6abe7a50bfc1023250edd1b9/preprints/The-Exponential-Time-Hypothesis-is-False-October-25-2026.

[2] OpenAI. *Math repository: description and verification status*. Accessed October 26, 2026. https://github.com/openai/math/blob/main/README.md.

[3] OpenAI. *SubexponentialSAT Lean interfaces and comparator challenge*. Repository snapshot `7ef5c0cc5ca4b0e072b7a050fca09ab24bc6fa3a`; `lean/OAI/Algorithms/SubexponentialSAT/Main.lean`, `SqrtLogSpace/Final.lean`, and `lean/ComparatorChallenges/SubexponentialSAT.json`. https://github.com/openai/math/tree/7ef5c0cc5ca4b0e072b7a050fca09ab24bc6fa3a/lean/OAI/Algorithms/SubexponentialSAT.

[4] R. Impagliazzo, R. Paturi, and F. Zane. Which problems have strongly exponential complexity? *Journal of Computer and System Sciences* 63 (2001), 512–530. https://cseweb.ucsd.edu/~paturi/myPapers/pubs/ImpagliazzoPaturiZane_2001_jcss.pdf.

[5] J. Alman and R. Williams. *Probabilistic Rank and Matrix Rigidity*. STOC 2017; arXiv:1611.05558. https://arxiv.org/abs/1611.05558.

[6] R. Beigel and J. Tarui. On ACC. *Computational Complexity* 4 (1994), 350–366. Author-hosted reference: https://www.cis.temple.edu/~beigel/papers/bt-acc-cc.html.

[7] T. M. Chan and R. Williams. Deterministic APSP, Orthogonal Vectors, and More: Quickly Derandomizing Razborov–Smolensky. *ACM Transactions on Algorithms* 17(1), 2021. https://people.csail.mit.edu/rrw/derand-apsp-ov-cr-talg.pdf.

[8] M. Sipser and D. A. Spielman. Expander codes. *IEEE Transactions on Information Theory* 42(6) (1996), 1710–1722. https://www.cs.yale.edu/homes/spielman/Research/expanders.html.

[9] M. Subbarao. *Foundations of Ram Operator Representations and Certified Inversion: Locality, Polynomial Rigidity, Orthogonal Panels, and Stable Recovery*. Local corpus, `RamOperator/RamOperator-Foundations.tex`, especially Sections 2–3, 6–7, and 13.

[10] M. Subbarao. *Local Operators, Orthogonal Bases, and the Ram-Series Question*, revision 2. Local corpus, `RamOperator/RamOperatorSeries-rev2.tex`, finite-jet and polynomial-inverse sections.

[11] M. Subbarao. *P versus NP through Audited Ram Reductions*. Local corpus, revised September 6, 2026, `res-math/TR-item-010-astra.tex`, Boolean quotient, tree closure, and parity-aliasing sections.

[12] M. Subbarao. *Exact Moment Coordinates, Block Mollifiers, and Uniform Rank-Tail Boundaries*. Local corpus, `OpenAI-722-math/M012-Mean-Analytic-Rank/TR-M012-Ram-Mean-Analytic-Rank.tex`.

[13] M. Subbarao. *Smaller Jets and Structured Arithmetic for Uniform Matrix Hitting Points in Positive Characteristic*. Local corpus, `OpenAI-722-math/M231-Positive-Characteristic-PIT/TR-M231-Ram-Positive-Characteristic-PIT.tex`.

[14] M. Subbarao. Corrected discrete shift-variant Ram report. Local corpus, `RamFoundationTRs/TR-rev-1-old-tr166/TR-rev-1-old-tr166.tex`, correction register, exact recovery, and divided-difference sections.

[15] M. Subbarao. Revised *Ram Calculus Foundations*, Volume 1, operator-foundations integration dated October 20, 2026. Local corpus, `RamCalBooks-v2/Operator-Foundations-Integration-20261020/Volume01-Operator-Foundations-rev2/source/volumes/volume1-rev2/chapters/ch08-measurements-C.tex`.

[16] M. Subbarao. RMT extension TR1: frames, atoms, and exact aggregate-state selection. October 2026. Local corpus, `RamRMT-extensions/TR1-rmt-ext-frames-atoms.tex`, Sections 7–9.

[17] M. Subbarao. RMT extension TR2: fractional and complex orders. October 23, 2026. Local corpus, `RamRMT-extensions/TR2-rmt-ext-fractional-complex.tex`, terminal polynomial and jet-channel sections.

[18] M. Subbarao. *Constraint-Preserving Tensor and Hypercomplex RMT*. October 23, 2026. Local corpus, `RamRMT-extensions/TR3-rmt-ext-hypercomplex-constraints.tex`; includes corrected TR60 conventions and references.

[19] M. Subbarao. Nonlinear RMT extension TR4. October 23, 2026. Local corpus, `RamRMT-extensions/TR4-rmt-ext-nonlinear.tex`, transported nonlinearities, range consistency, and residual counterexamples.

[20] M. Subbarao. *Ram Calculus MathWorld Companion Volumes*, Volumes 1–13, expanded 627-topic local edition, 2026. Source files `Ram-Calculus-MathWorld-Volume-01.tex` through `Ram-Calculus-MathWorld-Volume-13.tex`, in `C:/Users/mural/OneDrive/Documents/mathworld-supplement/RamCal-MathWorld-Volumes/`. Stable topic IDs and exact local locators are given in Appendix C. Private corpus source, not a claim of external endorsement or an independent novelty certification.