Ram Calculus and the Exponential Time Hypothesis

Exact Finite-Algebra Reformulations, Aggregated Boolean Jets, and Precision-Certified Counting

Dr. Muralidhara Subbarao
Technical Report Prepared with the Assistance of AI Models
https://www.integralresearch.net

October 26, 2026

Abstract

We investigate the October 25, 2026 OpenAI manuscript *The Exponential Time Hypothesis is False*, using the supplied PDF and its matching public source. Its proof architecture is algebraic and combinatorial: polynomial deformation, shared integer measurements, Boolean finite differences, modulus-amplifying parity indicators, exact interpolation, and recursive tensor contraction. No auxiliary partial differential equation is identified in this manuscript. The relevant Ram Calculus connections are instead finite moment coordinates, polynomial operators, characteristic-safe jets, exact coupling states, and residual certificates. We give self-contained proofs of these connections and derive an aggregated Boolean-jet identity that replaces the source routine's $\sum_{j\le q} 2^j \binom{n}{j}$ restricted-count calls by $\sum_{j\le q} \binom{n}{j}$ calls over a polynomially enlarged coefficient algebra. A weighted-filtration extension handles unequal correction orders. We also derive target-specific two-adic precision certificates and demonstrate strictly smaller certified budgets for two finite Hermite configurations. Exact rational and integer tests check the identities, fiber factorization, parity lifts, and local Cauchy kernels. The assessment distinguishes rederivations of source results, adaptations of established algebra, additions proved here, and unimplemented proposals. Neither a stronger general SAT time exponent nor a new independent refutation of ETH is established by this report. The source's full algorithm and its Lean dependency closure have not been independently executed here. The contributions are exact local algorithmic refinements and a more explicit verification framework, not a claim that a change of transform alone removes exponential complexity.

Contents

1 Scope, source status, and principal conclusions **4**
1.1 The manuscript actually examined 4
1.2 Three separate evidential questions 4
1.3 What was checked, and what was not 4

2 The problem and its exact computational contract **5**
2.1 State space, arithmetic, and unresolved quantifiers 5
2.2 The available formalization and its limits here 5

3 Relevant Ram corpus and the exactness boundary **6**
3.1 A concrete finite Ram representation . . . 7
3.2 Which information is being represented? . . . 7

4 Proof architecture of the source and opportunities for Ram methods **8**
4.1 What the hard construction accomplishes . . . 8
4.2 The swap construction in explicit operator form . . . 9
4.3 Pullback to actual variables, coefficient size, and parameters . . . 10
4.4 Why the rational spectral proof cannot simply move to characteristic two . . . 10

5 Exact shared-summary counting as a Ram finite-state formulation **11**
5.1 Polynomial deformation and degree . . . 11
5.2 Why rank alone is the wrong parameter . . . 12

6 Finite jets, interpolation, and the auxiliary-PDE question **12**
6.1 The exact jet algebra . . . 12
6.2 Finite Ram polynomial operators and their limits . . . 12
6.3 No auxiliary PDE is present in the inspected paper . . . 13

7 Boolean-jet recovery: a self-contained rederivation **13**

8 A proved refinement: aggregating the Boolean-pair loop **14**
8.1 Why aggregation preserves local factorization . . . 14
8.2 What improves and what does not . . . 15
8.3 A transparent worked example . . . 16

9 A weighted-filtration extension **16**

10 Rank-aware summaries and exact structural special cases **16**
10.1 Deleting redundant rows without losing the count . . . 16
10.2 A bounded-width alternative independent of the source claim . . . 17
10.3 A rank identity that is exact but not efficient by itself . . . 17

11 Sparse equations, parity lifting, and the total-degree budget **18**
11.1 An explicit modulus-amplifying polynomial . . . 18
11.2 Why the truncation is shared across all factors . . . 18
11.3 Reduction from SAT without circular selection . . . 19

12 The sharper tensor route and its valuation structure **19**
12.1 What is being contracted . . . 19
12.2 Cauchy deformation and scaled integral coordinates . . . 20
12.3 Tapering, weighted modes, and recursion . . . 20

13 Target-specific Hermite recovery and precision certificates **21**
13.1 The target functional rather than the whole polynomial 21
13.2 A finite demonstrated reduction in precision 22
13.3 Archimedean residuals require a different certificate 22

14 Complex, quaternionic, and nonlinear extensions: relevant limits **23**

15 Exact tests and reproducible evidence **23**
15.1 A complete small SAT deformation 24
15.2 The exact call counts, not elapsed-time claims 24
15.3 Failure cases that must remain visible 25

16 Equation comparison and attribution of improvements **25**
16.1 Advantages of the Ram-based organization 26
16.2 Disadvantages and comparisons with existing methods 26

17 Research directions with explicit success criteria **27**
17.1 Implement the aggregated routine inside the actual construction 27
17.2 Search for higher-order correction designs 27
17.3 Deploy exact target weights in recursive two-adic recovery 27
17.4 Finite-domain and weighted-count extensions 27
17.5 Formal verification and negative results 27

18 Conclusion **28**

A Bounded-audit findings and arithmetic safeguards **28**

B Source register and reproducibility **28**

1 Scope, source status, and principal conclusions

1.1 The manuscript actually examined

The primary source is OpenAI's manuscript dated October 17, 2026 and revised October 25, 2026, in the repository folder named `The-Exponential-Time-Hypothesis-is-False-October-25-2026` [1]. The attached `paper(2).pdf` has 887,884 bytes. Its Git blob hash, computed locally, is

`0503566e95bc587a4076573a45132d97531b8ba6`.

This matches the repository PDF. The four TeX files used for the analysis are pinned to commit

`42907c9e999cc00d6abe7a50bfc1023250edd1b9`.

They are `main_full_version.tex`, `quantitative-reduction.tex`, `quantitative-contraction.tex`, and `quantitative-circuits.tex`. This fixes the object of analysis even if the live repository changes. The supplied PDF contains 66 pages.

The source announces a deterministic exact-counting algorithm for every fixed clause width k. Its headline is therefore much stronger than a heuristic SAT solver or a result on a selected instance distribution. The repository's general description also distinguishes different stages of verification and does not warrant treating every hosted manuscript as a fully independently audited publication [2]. Our analysis is correspondingly explicit about its own scope.

1.2 Three separate evidential questions

The following questions have different answers.

1. *Is Ram Calculus relevant?* Yes, particularly its corrected finite-algebra, moment, jet, state-aggregation, and certified-inversion interfaces. These can be connected to exact counting without an analogy to continuous PDEs.
2. *Can useful refinements be proved?* Yes. Sections 8–13 prove a reduction in the number of restricted-count calls, a weighted support extension, exact summary reductions under stated hypotheses, and a target-specific precision rule.
3. *Does this report improve the source's general exponent or independently establish its headline?* No. The new call-count result applies to the source's Section 3 routine, whereas its sharpest bound uses Appendix D. The local precision improvement has no proved better worst-case growth rate. The full low-degree construction, reduction, and recursive implementation have not been reproduced end to end in software or in Lean here.

The word *new* below means an addition to this comparative report, with a supplied proof or computation, not a verified claim of historical priority. Finite differences, generating functions, Hermite interpolation, quotient algebras, and valuation error propagation have substantial classical antecedents. Their use in Ram terminology does not erase that provenance.

1.3 What was checked, and what was not

The investigation follows the main proof dependencies: the counting identity, design interface, low-degree replacement mechanism, sparse polynomial parity lift, greedy parity tests, sparsification, exact arithmetic, and the sharper contraction route. Independent corpus research and a separate

mathematical audit were used. The detailed proofs in this report establish their own stated lemmas, rather than assuming that searching the large corpus constitutes verification of every report in it.

The experiments are exact small-instance identity checks. They are not performance tests of the full ETH algorithm, do not certify all large-n parameter inequalities, and do not measure practical crossover sizes. No inconsistency found in a proposed Ram shortcut is attributed to the source when the source itself preserves the necessary condition.

2 The problem and its exact computational contract

2.1 State space, arithmetic, and unresolved quantifiers

Let F be a CNF formula on n *declared* Boolean variables with m clauses, each of width at most a fixed integer $k \geq 2$. Its exact count is

$$Z(F) = \sum_{x \in \{0,1\}^n} \mathbf{1}_{\{F(x)=1\}} \in \{0, 1, \ldots, 2^n\}. \tag{1}$$

Unused variables contribute a factor of two each. An empty clause gives zero; an empty conjunction has count 2^n. Tautologies may be removed. Clause and literal normalization must preserve these conventions.

There is no spatial boundary condition or gauge constraint in this problem. The state space is a finite cube, and the observation of interest is the unnormalized sum functional. The relevant operator domains are finite polynomial spaces, Boolean quotient algebras, truncated coefficient rings, and explicitly described tensors. The complexity model counts bit operations, including construction, coefficient access, exact arithmetic, and output, rather than treating arbitrarily long rationals as unit-cost scalars.

ETH, in its usual bounded-width form, posits an exponential lower-time barrier for 3-SAT. Its precise relationships to sparse formulas depend on sparsification and size-preserving reductions [4]. The source claims the following bounds for each *fixed* k:

$$T(n, m) = (n + m)^{O_k(1)} 2^{O_k(n \log\log n / \sqrt{\log n})}, \tag{2}$$

$$T(n, m) = (n + m)^{O_{k,D}(1)} 2^{O_{k,D}(n/\sqrt{\log n})} \quad (m \leq Dn), \tag{3}$$

with polynomial bit space. Its earlier interpolation route gives

$$(n + m)^{O_k(1)} 2^{O_k(n(\log\log n)^2/\sqrt{\log n})}. \tag{4}$$

These are source claims, not improved bounds obtained in this report. For fixed parameters their exponents are $o(n)$. They do not give a polynomial-time algorithm, a useful finite-size threshold, or uniform constants when k or D grow with the input.

2.2 The available formalization and its limits here

The public Lean library has a solution entry point `OAI.Algorithms.SubexponentialSAT.Main`, importing `SqrtLogSpace.Final`. Its theorem `exact_count_and_sat` states exact counting, decision, a fixed primitive machine, and polynomial all-prefix visited-tape space. The comparator statement uses the runtime scale

$$n \frac{(\log\log(n + 16))^2}{\sqrt{\log(n + 16)}}.$$

Thus the inspected interface supports the weaker square-root-logarithmic scale (4), not by itself the sharper Appendix D bounds (2)–(3). The comparator specification contains an intentional `sorry`; its JSON points to the separate solution module. That placeholder is not evidence of a gap in the solution module. The inspected solution theorem invokes other proved declarations rather than a local placeholder [3].

The downloaded interface files were pinned to repository head `7ef5c0cc5ca4b0e072b7a050fca09ab24bc6fa3a` during this investigation. We did not compile their complete dependency closure, run the comparator, audit all permitted axioms, or check every encoding-to-paper correspondence. Accordingly, we report the existence and visible scope of the formalization, not a new independent machine-checked verification.

3 Relevant Ram corpus and the exactness boundary

The closest sources are listed in Table 1. Later corrected versions are used where they explicitly restrict earlier claims. The survey covered targeted parts of the requested directories, not every page of every book or report. This distinction matters because some older statements about universal nilpotence or automatic inversion were subsequently corrected.

Table 1: Corpus connections and non-transferable claims.

Source	Useful result or interface	Limitation for this problem
RamOperator Foundations; revised Series [9, 10]	Exact finite polynomial operators, nilpotent inverses, coefficient duality, projection leakage, coordinate invariance.	Finite inversion does not imply cheap global Boolean counting or safe arbitrary projection.
TR-item-010 [11]	Boolean quotient, moment aliasing, exact closure with a supplied tree decomposition.	Bounded clause width is not bounded treewidth; low moments need not identify the count.
M012 [12]	Exact finite-alphabet moment coordinates and explicit support-size cost.	An exact tensor basis can still have exponentially many coefficients.
M231 [13]	Hasse jets, transported multiplication, structured Toeplitz actions, field-aware bit accounting.	Noncommutative PIT is not common-zero counting; its special recurrences require their own hypotheses.
Corrected TR166 [14]	Separates coordinate conversion from model inversion and requires rank and residual closure.	A finite matrix need not be unit triangular or invertible.
Revised Volume 1 [15]	Newton/divided-difference coordinates and the correct product rule.	Confluent nodes and modular nonunits require separate arithmetic; changing basis alone is not a speedup.
RMT extension TR1 [16]	Exact signed aggregate-state recursion and explicit attainable-state cost.	Counting adds multiplicities; the optimization rule of retaining a minimum does not preserve counts.

Source		Useful result or interface	Limitation for this problem
RMT TR2 [17]	extension	Multiplicity, jet information, and terminal polynomial degree budgets.	Complex-order endpoint models are not Boolean counting algorithms.
RMT TR3 [18]	extension	Ordered hypercomplex channels, physical metrics, projection and finite-bank losses.	Physical tensor reconstruction is not scalar combinatorial tensor contraction.
RMT TR4 [19]	extension	Range-consistent nonlinear representations, transported products, residual and root-isolation limits.	Local root certificates do not count every Boolean solution without complete coverage.

3.1 A concrete finite Ram representation

For a finite alphabet $A_i \subset \mathbb{Q}$ of distinct values, put

$$\mathcal{B}_A = \mathbb{Q}[X_1, \dots, X_n] / \left(\prod_{a \in A_i} (X_i - a) : 1 \le i \le n \right). \tag{5}$$

Evaluation identifies this algebra with functions on $\prod_i A_i$. Univariate Lagrange interpolation proves the identification in one coordinate; tensoring the maps proves the multivariate statement. Its dimension is $\prod_i |A_i|$, not the number of input factors.

In the Boolean case, a unique representative is $f(X) = \sum_{S \subseteq [n]} c_S X_S$, where $X_S = \prod_{i \in S} X_i$. The exact counting functional is

$$\Lambda(f) = \sum_{S \subseteq [n]} 2^{n-|S|} c_S. \tag{6}$$

Each X_S is one on exactly $2^{n-|S|}$ assignments, proving the formula. Normalized expectation is $2^{-n}\Lambda$, so an expectation is not a count.

Ram moment rows give one way to organize these functionals. An invertible coordinate map R produces an equivalent representation only if

$$u \star v = R((R^{-1}u)(R^{-1}v)), \qquad \Lambda_R(u) = \Lambda(R^{-1}u). \tag{7}$$

Entrywise multiplication in arbitrary transformed coordinates is generally wrong. Equation (7) preserves the same finite algebra and does not reduce its dimension. Over $\mathbb{F}_2$ the analogous scalar sum gives only parity, not the integer count.

3.2 Which information is being represented?

Three objects must not be conflated: moments of assignments on the Boolean cube; jets in a scalar deformation parameter; and point jets of a physical field. The first may require 2^n independent coordinates. The second can be small because a *separately proved* polynomial-degree bound applies. The third requires its own regularity and domain assumptions. The source's algorithm exploits the second together with specially constructed summaries; it does not recover an arbitrary Boolean function from a few moments.

4 Proof architecture of the source and opportunities for Ram methods

Table 2: Dependency map. Source section numbers refer to the pinned manuscript.

Stage	Substantive source step	Ram connection and audit obligation
Sections 2–3	Encode the count as a product-sum and deform incidence rows while restoring each original variable at parameter zero.	Exact moment functional; degree, measure, and multiplication must be retained.
Section 3	Condition on bounded integer summaries so factors separate by groups; use Boolean finite differences to recover jets.	Exact aggregate states; new call aggregation in Section 8.
Section 4	Build low-degree rows meeting many partition/measurement constraints by auxiliary arrays, spectral structure and annihilation.	No replacement construction supplied by existing Ram frames; certify row kernels and coefficient heights exactly.
Section 5	Lift evenness modulo 2^ℓ and truncate a common order variable, keeping total degree linear.	Filtered coefficient algebras; truncation is global, and final coefficient summation is not multiplicative.
Section 6; Appendix A	Use parity checks and disjoint sparsification to reduce general formulas to sparse polynomial zero counts.	Preserve solution multiplicities and query size; do not assume tests already isolate the solutions before proving they do.
Appendix B	Bound denominators, intermediate bit sizes, and streamed storage.	Exact structured linear algebra; no unit-cost rational shortcut.
Appendix D.1–D.3	Encode sparse and general systems as Boolean tensor networks with controlled wires and evaluable entries.	Transported tensor coordinates preserve scalar contraction, but not automatically small size.
Appendix D.4	Cauchy deformation, scaled integral jets, tapered Hermite precision, weighted modes, and recursive contraction.	Finite inverse and valuation certificates; target-specific precision in Section 13.
Appendix C	Consequences for circuit lower bounds and other reductions.	Consequences require the upstream algorithm and the precise reductions; not new Ram theorems here.

4.1 What the hard construction accomplishes

For factors Φ_f on scopes I_f, each incidence (f, v) receives its own polynomial row $P_{f,v}(T) \in \mathbb{Q}[T]^n$. Different occurrences of the same variable may have different rows. The requirements include $P_{f,v}(0) = e_v$, degree at most $R < Q$, and, at each interpolation node, small groups and few bounded integer measurements through which every off-group dependence factors. Simply interpolating arbitrary prescribed rows at Q nodes would usually require degree of order Q, defeating the intended

R/Q saving.

The source instead arranges auxiliary coordinates, uses a structured matrix/spectral construction, and annihilates selected bad-node contributions with low-degree factors that preserve the value at zero. The matrix-rigidity background includes Alman and Williams [5]; their results by themselves are not a complete construction of the source's simultaneous incidence design. Scope size, variable incidence, group balance, row range, common denominators, and the construction's own time are all essential. Replacing the construction with a generic tight frame or a low-rank approximation does not establish these properties.

The rational design in Section 4 and the recursive two-adic deformation in Appendix D are also different constructions. A refinement of one must not be silently advertised as a refinement of the other.

4.2 The swap construction in explicit operator form

Here is a closer derivation of the central Section 4 mechanism. Index an auxiliary array by pairs of labels $(a_u, d_u) \in [r]^Q \times [r]^Q$, with $D = r^{2Q}$ positions. Let Π_s exchange the two symbols in coordinate s. These are commuting rational permutation involutions. Set

$$V_0 = \prod_{s=1}^{Q} \Pi_s, \qquad W_0 = \frac{1}{2}\sum_{s=1}^{Q}(I - \Pi_s). \tag{8}$$

If a simultaneous eigenvector has j minus signs, then W_0 acts by j and V_0 acts by $(-1)^j$. At one coordinate the minus eigenspace has dimension $r(r-1)/2$ out of r^2; therefore the distribution of j among a tensor-product eigenbasis is $\mathrm{Bin}(Q, (r-1)/(2r))$.

Choose an interval $\mathcal{I} = \{A_0, \ldots, A_0 + R - 1\}$ and define

$$f_{\mathcal{I}}(z) = (-1)^{A_0} \sum_{j=0}^{R-1} (-2)^j \binom{z - A_0}{j}, \qquad M_0 = V_0 f_{\mathcal{I}}(W_0). \tag{9}$$

At $z = A_0 + h$, $0 \le h < R$, the binomial theorem gives $f_{\mathcal{I}}(z) = (-1)^z$. Thus M_0 is identity on the spectral subspace with $j \in \mathcal{I}$. Select the excluded orthogonal basis vectors as integer measurement rows $C^{\mathcal{B}}$. Their entries are $0, 1, -1$, and their number is $D \Pr[\mathrm{Bin}(Q, (r-1)/(2r)) \notin \mathcal{I}]$. It follows over $\mathbb{Q}$ that $M_0\xi = \xi$ whenever $C^{\mathcal{B}}\xi = 0$.

The second requirement is support, not just rank. A degree-at-most-$R-1$ polynomial in the commuting Π_s is a sum of products involving at most $R-1$ distinct swaps, because $\Pi_s^2 = I$. Multiplication by V_0 swaps every remaining coordinate. Consequently

$$M_0[u, y] \neq 0 \implies |\{s : a_y(s) \neq d_u(s)\}| \le R - 1.$$

Write that mismatch set as $E_{u,y}$, and let

$$\begin{aligned} \varphi_{u,y}(T) &= \prod_{s \in E_{u,y}} (1 - T/s), \\ P_u(T) &= e_u^T(I - M_0) + \sum_y M_0[u, y]\varphi_{u,y}(T)e_y^T. \end{aligned} \tag{10}$$

The sum need only include nonzero entries of M_0. At zero, $P_u(0) = e_u^T$. At node t, a term using a coordinate outside the assigned group vanishes because its mismatch set contains t. The remaining

nonlocal term $(I - M_0)\xi$ is determined by the shared measurements, since it vanishes on their kernel. This proves the desired separation on the auxiliary array.

This construction is legitimately an exact finite operator calculus, but its effectiveness depends on the simultaneous spectral and support properties. A Ram polynomial representation of $f_{\mathcal{I}}(W_0)$ does not establish those properties anew; it records the source's proof in compatible coordinates. The low-degree interpolation polynomial is not an approximate spectral filter on the retained eigenspaces: it has exact prescribed values there.

4.3 Pullback to actual variables, coefficient size, and parameters

The auxiliary slots contain copies of original variables, with unused slots set to zero. Copies are not independently summed Boolean variables. All copies of a variable retain the same group label, so pulling a row back through the embedding preserves its off-group kernel implication. Identifying columns cannot increase a row's absolute sum. The source's label assignment uses a conditional-expectation argument that includes dependencies from both shared variables and shared factors; treating all incidences as independent would not justify its packing bounds.

The factor $(-2)^j$ in (9) clears the halves in W_0; the remaining interpolation denominators divide $j!$. The annihilation factors in (10) have denominators dividing $Q!$. Thus $(R-1)!Q!$ clears all row coefficients. The source bounds their bit length using row-sum and polynomial coefficient norms. This is the arithmetic information missing from a mere statement that a basis change exists.

For $\lambda = \lceil \log_2 n \rceil$, $\nu = \lceil \log_2 \lambda \rceil$, and a fixed incidence exponent β, the source balances parameters of the form

$$r = \left\lfloor \frac{\sqrt{\lambda}}{\nu^2} \right\rfloor, \quad Q = \left\lfloor \frac{\lambda}{128\nu} \right\rfloor, \quad R = (\beta + 3)\lceil \sqrt{\lambda} \rceil, \quad \tau = \frac{1}{r\lambda}, \quad D = r^{2Q}.$$

A binomial-tail estimate makes the number of excluded measurements small, and $\log_2 D \le \lambda/128$ controls their magnitude budget. All required inequalities are asserted for sufficiently large n, with finite exceptions handled by direct enumeration. These thresholds can be extremely large. For example, $6R \le Q$ with $\beta \ge 1$ already requires approximately $\sqrt{\lambda} \ge 3072\nu$. This is consistent with an asymptotic theorem but supplies no practical-size advantage.

4.4 Why the rational spectral proof cannot simply move to characteristic two

On an orbit of four slots, let two swaps flip its two orientation bits. Choose $R = 1$ and $\mathcal{I} = \{1\}$. Then $M_0 = -\Pi_1\Pi_2$. The excluded eigenspace rows are $(1,1,1,1)$ and $(1,-1,-1,1)$. Modulo two those rows coincide, so $\xi = (1,1,0,0)^T$ is in their modular kernel. But $M_0\xi = (0,0,1,1)^T \neq \xi$ modulo two. This does not contradict the source, whose kernel proof is over $\mathbb{Q}$; it disproves an invalid finite-field shortcut. A Ram implementation must retain the declared field and multiplication law, not only the appearance of the matrix formulas.

5 Exact shared-summary counting as a Ram finite-state formulation

5.1 Polynomial deformation and degree

Let $\mathcal{A}$ be a commutative $\mathbb{Q}$-algebra and suppose the product of the incidence-separated factors has total degree at most d. Define

$$H(T) = \sum_{x\in\{0,1\}^n} \prod_f \Phi_f((P_{f,v}(T)\cdot x)_{v\in I_f}). \tag{11}$$

Then $H(0) = Z$ and $\deg H \le dR$. The degree is measured before identifying separate incidence indeterminates. A small degree for one factor is not a bound for their full product.

Fix a node t, a partition $[n] = S_1 \sqcup \cdots \sqcup S_r$, and an integer matrix C_g on each group. Write $y_g = C_g x_g$. Assign each factor to one group g. For every off-group $h \neq g$, require

$$P_{f,v}(t)|_{S_h} \in \mathrm{rowspan}_{\mathbb{Q}}(C_h). \tag{12}$$

Equivalently, the row vanishes on $\ker C_h$. This can be certified by an explicit rational row λ satisfying $P_{f,v}(t)|_{S_h} = \lambda C_h$. A factor assigned to g is then a function of its local assignment x_g and the off-group measurements.

Theorem 5.1 (Exact fiber factorization)**.** *Let $A_g(x) = a_g(x_g, y_{-g})$ take values in a commutative ring. For $E \subseteq [n]$, define*

$$B_{g,E}(y) = \sum_{\substack{x_g\in\{0,1\}^{S_g}\\ C_g x_g = y_g,\ x_i = 1\ (i\in E\cap S_g)}} a_g(x_g, y_{-g}).$$

Then

$$\sum_{\substack{x\in\{0,1\}^n\\ x_E = 1}} \prod_g A_g(x) = \sum_y \prod_g B_{g,E}(y), \tag{13}$$

where y ranges over all attainable measurement tuples, or any containing integer box with empty fibers assigned zero.

Proof. Every assignment belongs to exactly one measurement fiber. For fixed y the permitted assignments form the Cartesian product of local fibers. Each factor in that fiber depends only on its own local assignment. Distributing the finite product of sums proves the identity. No positivity, probabilistic independence, or approximate equality is used. □

This is a rederivation of the source's measurement-separation lemma. Its Ram interpretation is an exact coupling-state representation, consistent with TR1's rule that outside completions must see the same retained state [16]. For counting, equivalent states carry the *sum* of their weights; retaining only the cheapest representative would lose multiplicity.

If each measurement row has ℓ^1 norm at most D and there are c rows altogether, a safe box has $(2D+1)^c$ tuples. A streamed implementation uses at most

$$2(2D+1)^c \sum_g 2^{|S_g|} \tag{14}$$

local-assignment examinations, allowing one scan to find representatives and one to accumulate the local sum. Factor evaluation, arithmetic, and state-description costs remain additional. Polynomial space requires polynomial-length ring elements and evaluators, not just streaming indices.

5.2 Why rank alone is the wrong parameter

The rank-one row $(1, 2, 4, \dots, 2^{n-1})$ gives 2^n distinct values on the cube. Thus rank one does not give a small summary alphabet. Conversely, rows $(1, 1, 1)$ and $(2, 2, 2)$ have redundant information: retaining the first preserves their common kernel and leaves only four attainable values. The source itself emphasizes this distinction. Ram rank-aware methods are useful only together with range and coefficient-height accounting.

6 Finite jets, interpolation, and the auxiliary-PDE question

6.1 The exact jet algebra

For any commutative ring K, a node $t \in K$, and an integer $J \geq 1$,

$$\mathcal{J}_{t,J}p = p(t + z) \pmod{z^J} \in K[z]/(z^J) \tag{15}$$

is an algebra homomorphism. Its coefficients are Hasse coefficients, $[z^j]p(t + z)$. Over $\mathbb{Q}$ they equal $p^{(j)}(t)/j!$; the coefficient definition remains meaningful when $j!$ is not invertible. Multiplication is truncated convolution, not entrywise multiplication. This is precisely the characteristic-safe interface used in M231 [13].

For distinct rational nodes t_a and multiplicities J_a, put $N = \sum_a J_a$. Jets determine every polynomial of degree less than N. Indeed, a polynomial with all jets zero is divisible by $\prod_a (T - t_a)^{J_a}$, a degree-N polynomial, and must vanish if it has smaller degree. This proves injectivity; equality of finite dimensions proves unique reconstruction. The same statement over a general ring requires suitable unit differences or comaximal ideals.

Example 6.1 (Distinct modular nodes need not be sufficient)**.** The nonzero polynomial $2T$ over $\mathbb{Z}/4\mathbb{Z}$ vanishes at both 0 and 2. The nodes are distinct, but their difference is not a unit. Rational interpolation cannot simply be reduced modulo a power of two.

6.2 Finite Ram polynomial operators and their limits

On $\mathcal{P}_D = \{p : \deg p \leq D\}$, ordinary differentiation $N_D = d/dT$ is nilpotent, so

$$p(t + z) = \exp(zN_D)p(t) = \sum_{j=0}^{D} \frac{z^j}{j!} p^{(j)}(t). \tag{16}$$

This is an exact finite identity over $\mathbb{Q}$. The Ram polynomial moment calculus organizes related actions as finite rows in N_D; a unit constant plus a nilpotent operator has a terminating geometric inverse [9, 10]. The existence of this representation is useful for checking the arithmetic, but it does not make the coefficients of H cheap to obtain.

There is an important distinction between polynomials of bounded degree as a vector space and a quotient algebra with truncated multiplication. Ordinary differentiation does *not* descend to a derivation of $\mathbb{Q}[z]/(z^J)$: the ideal (z^J) is not differentiation-invariant. For $J = 2$, $z^2 = 0$ in the quotient, while a purported Leibniz rule gives $D(z^2) = 2z \neq 0$. Canonical representative differentiation is a linear matrix but not a derivation of this truncated algebra. Substitution followed by the quotient map (15) is the safe operation.

6.3 No auxiliary PDE is present in the inspected paper

The mathematical auxiliaries used here are a scalar polynomial $H(T)$, formal variables recording order, finite differences on subsets, integer linear summaries, and finite-ring tensor networks. The source does not introduce an elliptic, parabolic, hyperbolic, or quaternionic PDE whose solution supplies the counting result.

One may define $u(t, z) = H(t + z)$ and write the formal transport relation $\partial_t u = \partial_z u$ in characteristic zero. This is a rewriting of a polynomial identity, not an auxiliary PDE solver with a new complexity bound: its initial coefficients already contain the difficult count. Calling this relation a Ram partial differential operator does not provide missing information or reduce the cost of evaluating it. The auxiliary Dirichlet equation in the earlier local-smoothing manuscript is a different matter and must not be transferred into this paper.

7 Boolean-jet recovery: a self-contained rederivation

At a node t, write $\Delta P_{f,v}(z) = P_{f,v}(t + z) - P_{f,v}(t)$ and introduce independent variables $X_1, \dots, X_n$:

$$G_x(X, z) = \prod_f \Phi_f\big((P_{f,v}(t) \cdot x + \Delta P_{f,v}(z) \cdot X)_{v \in I_f}\big). \tag{17}$$

Each occurrence of X_i costs at least one power of z. Therefore

$$\deg_X\big([z^j] G_x(X, z)\big) \le j. \tag{18}$$

Moreover $\sum_x G_x(x, z) = H(t + z)$. Holding X fixed preserves the summary condition in x, whereas setting $X = x$ prematurely can destroy the factor separation. This explains the source's finite-difference step.

Lemma 7.1 (Boolean difference identity)**.** *Let $p_x(X)$, one for each Boolean x, be polynomials over a commutative ring of degree at most q. Then*

$$\sum_x p_x(x) = \sum_{\substack{E \subseteq [n] \\ |E| \le q}} \sum_{U \subseteq E} (-1)^{|E|-|U|} \sum_{x_E = 1} p_x(\mathbf{1}_U). \tag{19}$$

Proof. Reduce positive powers of each X_i to X_i, preserving Boolean evaluations and not increasing degree. Write the resulting polynomial as $\sum_E c_{x,E} X_E$. Subset inversion gives $c_{x,E} = \sum_{U \subseteq E} (-1)^{|E|-|U|} p_x(\mathbf{1}_U)$. Coefficients with $|E| > q$ vanish. At $X = x$, X_E is the indicator of $x_E = 1$. Summing proves the result. □

Take $q = \lfloor dR/Q \rfloor$ and $J = q + 1$ at Q rational nodes. Then $QJ > dR$, so the jets determine $H(0)$. Applying Lemma 7.1 coefficientwise to (17) computes those jets with

$$C_q(n) = \sum_{j=0}^{\min(q,n)} 2^j \binom{n}{j} \tag{20}$$

restricted calls per node. With the source design, $c \le 2\tau n$ and $|S_g| \le 2n/r$, giving the assignment-examination bound

$$2Qr\, C_q(n) (2D + 1)^{2\tau n} 2^{2n/r}. \tag{21}$$

All ring and factor costs still have to be included.

For $d = O(n)$ and $R/Q \to 0$, the three exponential costs have logarithm

$$O\left(n\left[\frac{R}{Q}\log\frac{2Q}{R} + \tau\log(2D+1) + \frac{1}{r}\right]\right). \tag{22}$$

The source's parameters make this the scale in (4) for appropriate polylogarithmic incidence bounds. Merely accelerating a polynomial-sized matrix inversion does not change these three costs.

8 A proved refinement: aggregating the Boolean-pair loop

This section is the main local algorithmic addition. It eliminates the outer restriction index E by retaining a small generating jet for the number of remaining selected bits. It does not assume the truth of the source's full ETH theorem.

Theorem 8.1 (Aggregated Boolean identity)**.** *Under Lemma 7.1, define, for $u \le q$ and $h \ge u$,*

$$w_q(h,u) = \sum_{k=0}^{\min(q-u,h-u)} (-1)^k \binom{h-u}{k}. \tag{23}$$

Then

$$\sum_x p_x(x) = \sum_{\substack{U\subseteq[n]\\ |U|\le q}} \sum_{x_U=1} w_q(|x|,|U|)\,p_x(\mathbf{1}_U). \tag{24}$$

Proof. In (19), interchange the finite sums over x, E, U. For fixed $U \subseteq \operatorname{supp} x$, the admissible sets E are $U \cup K$, where $K \subseteq \operatorname{supp} x \setminus U$ and $|K| \le q - |U|$. There are $\binom{|x|-|U|}{k}$ such sets of added size k, and their sign is $(-1)^k$. Their sum is exactly (23). □

For $h > u$, the weight is zero if $q - u \ge h - u$; otherwise it equals $(-1)^{q-u}\binom{h-u-1}{q-u}$. For $h = u$, it equals one. These follow from the alternating binomial sum. The defining finite sum is preferable in rings where generalized binomial notation would obscure integrality.

8.1 Why aggregation preserves local factorization

For a fixed U put $r_U = q - |U|$ and introduce one formal variable w:

$$K_U(z,w) = \sum_{x_U=1} G_x(\mathbf{1}_U, z)(1+w)^{|x|-|U|} \pmod{z^J, w^{r_U+1}}. \tag{25}$$

Define the *linear* final functional

$$\mathcal{L}_{r_U}\left(\sum_{k=0}^{r_U} b_k w^k\right) = \sum_{k=0}^{r_U} (-1)^k b_k. \tag{26}$$

The binomial theorem and Theorem 8.1 give

$$H(t+z) \equiv \sum_{|U|\le q} \mathcal{L}_{r_U} K_U(z,w) \pmod{z^J}. \tag{27}$$

For a group S_g, the extra factor is simply $(1+w)^{|x_g|-|U\cap S_g|}$ on the restricted assignments. It is local to that group. Thus Theorem 5.1 computes (25) in

$$\mathcal{A}[z,w]/(z^J, w^{r_U+1}) \tag{28}$$

with the original measurements and with $x_U = 1$ as the sole fixed-bit restriction. No new cross-group measurements are required.

The final functional must be applied *after* group multiplication. It is evaluation at -1 of the retained representative, not a ring homomorphism of the quotient. For example, modulo w^2, the product of w and w is zero, but the product of their representative evaluations at -1 is one. Applying the functional early would invalidate the count.

Corollary 8.2 (Restricted-call bound and polynomial workspace)**.** *The Section 3 jet stage can replace $C_q(n)$ calls per node by*

$$B_q(n) = \sum_{j=0}^{\min(q,n)} \binom{n}{j}, \tag{29}$$

using at most $J(q+1)$ coefficient slots per algebra element. With the source design, the number of local-assignment examinations is at most

$$2Qr\, B_q(n)(2D+1)^{2\tau n} 2^{2n/r}. \tag{30}$$

When q, J and coefficient bit sizes are polynomial in the input size, the enlarged arithmetic and streamed workspace remain polynomial per examined assignment.

Proof. There is one call (25) for each U, and each uses precisely the fiber algorithm in the larger ring. A naive multiplication costs $O(J^2(q+1)^2)$ operations in $\mathcal{A}$. The extra binomial coefficients have at most $n+1$ bits; their products and sums obey a polynomial additional bit budget under the same finite-degree assumptions. The loops over nodes, U, measurements, and local assignments can be streamed. Only polynomially many coefficients are live; no 2^n assignment table is required by the identity's implementation. □

8.2 What improves and what does not

The inequalities $B_q \le C_q \le 2^{\min(q,n)} B_q$ are immediate. For $q = o(n)$, the leading combinatorial logarithm remains $q\log(n/q) + O(q)$ in both cases. The new identity removes the extra factor attached to enumerating subsets of E, but introduces polynomial coefficient work. It therefore proves fewer restricted calls, not an unconditional wall-clock speedup. For small q, polynomial overhead can outweigh the call reduction.

When $q \ge n$, $C_q = 3^n$ whereas $B_q = 2^n$; in that case the weights select only $x = \mathbf{1}_U$, so the identity reduces to direct enumeration. It is not a subexponential algorithm in that regime. For the source's sublinear q, the improved call count does not remove the other two costs in (22), and does not improve the published big-O exponent. Its relationship to Ram Calculus is the use of a small exact moment/jet state to aggregate a repeated summation. The proof is also expressible entirely in conventional generating-function algebra.

8.3 A transparent worked example

Let $n = 3$, $q = 1$, and $p_x(X) = a_x + \sum_i b_{x,i} X_i$. For $U = \varnothing$, $w_1(|x|, 0) = 1 - |x|$; for a singleton $U = \{i\}$ the weight is one. Thus the contribution of a fixed x on the right side is

$$(1 - |x|)a_x + \sum_{i:x_i=1} (a_x + b_{x,i}) = a_x + \sum_i b_{x,i} x_i = p_x(x).$$

The source pair loop uses $1 + 2n = 7$ calls. The aggregated loop uses $1 + n = 4$, with a degree-one generating jet for $U = \varnothing$. The cancellation of the repeated a_x terms explains the mechanism.

9 A weighted-filtration extension

Suppose the correction in coordinate i is divisible by z^{ν_i}, where $\nu_i \geq 1$ is a known integer. A monomial involving a support E then costs at least $\nu(E) = \sum_{i \in E} \nu_i$ powers of z. This is a strengthened structural assumption, not a property established for every source instance.

Theorem 9.1 (Weighted support aggregation)**.** *Assume the Boolean normal form of every p_x has support only on E with $\nu(E) \leq q$. Then*

$$\sum_x p_x(x) = \sum_{\nu(U) \leq q} \sum_{x_U = 1} p_x(\mathbf{1}_U) \sum_{\substack{K \subseteq \operatorname{supp} x \setminus U \\ \nu(K) \leq q - \nu(U)}} (-1)^{|K|}. \tag{31}$$

For each U, the inner weight is the sum of coefficients through degree $q - \nu(U)$ in

$$\prod_{i \in \operatorname{supp} x \setminus U} (1 - s^{\nu_i}). \tag{32}$$

Consequently it is computable by the same group factorization with one truncated generating variable and only $|\{U : \nu(U) \leq q\}|$ restricted calls.

Proof. Subset inversion reconstructs precisely the supported coefficients; the family $\{E : \nu(E) \leq q\}$ is downward closed. Interchanging sums as in Theorem 8.1 leaves $E = U \cup K$ with the stated weight budget. Expanding (32) supplies sign $(-1)^{|K|}$ and degree $\nu(K)$. Each factor in that product is local to its variable, so it can be multiplied into its own group's factor. Final coefficient summation is linear and is applied after multiplication. □

The new call count is no larger than $B_q(n)$, since $\nu_i \geq 1$. For example, with weights $(1, 2, 3)$ and $q = 2$, only $U = \varnothing, \{1\}, \{2\}$ occur: three calls rather than seven unweighted subset calls. Establishing such higher-order vanishing in an actual replacement design could be valuable. Imposing it can also raise the replacement degree R, so an overall gain requires balancing both changes. The theorem does not license declaring weights without proving the corresponding divisibilities.

10 Rank-aware summaries and exact structural special cases

10.1 Deleting redundant rows without losing the count

Proposition 10.1 (Exact row-basis reduction)**.** *Let C be an integer measurement matrix and let C' consist of a subset of its rows spanning its rational row space. Then $Cx = Cx'$ if and only if $C'x = C'x'$. Every off-group certificate through C factors through C'. The same summary fibers and exact weighted counts are retained.*

Proof. The two matrices have the same rational kernel. Each omitted row is a rational linear combination of retained rows, so equality of retained measurements implies equality of all measurements. The reverse implication is immediate. The row-space certificate (12) is unchanged as a condition. □

Selecting existing rows avoids increasing their integer magnitudes, unlike an arbitrary rational change followed by denominator clearing. If retained row j has norm D_j, the safe box bound can be sharpened to $\prod_j (2D_j + 1)$. This is a valid instance-specific preprocessing step; it may do nothing when the source design already has independent rows.

One can reduce the box further to actual attainable summaries, but producing and enumerating that set is not free. Storing all reachable values may use exponential space. A sparse-state implementation must account for its construction and memory; the source's full-box streaming remains a safe polynomial-workspace fallback. Rank one still permits 2^n attainable states, as Section 5 shows.

10.2 A bounded-width alternative independent of the source claim

Proposition 10.2 (Exact counting with a supplied tree decomposition)**.** *Given a CNF and a tree decomposition of its primal graph of width w, the count is computable in $2^{w+1}\,\mathrm{poly}(n, m, |\mathcal{T}|)$ bit operations, with the polynomial factor covering count arithmetic. Storing all messages may require $2^{w+1}\,\mathrm{poly}(n, |\mathcal{T}|)$ bits.*

Proof. Assign each clause to one containing bag. A message indexed by a separator assignment counts the satisfying extensions in the subtree interior, excluding the separator variables from multiplicity. Running intersection makes different child interiors disjoint conditional on the bag. Multiply child counts, enforce local clauses, and sum newly eliminated variables. Induction proves exactness; every global satisfying assignment is counted once. A nice decomposition has tables of at most 2^{w+1} entries. Partial counts are at most 2^n and therefore have at most $n + 1$ bits. □

This is the counting version of the finite closure in TR-item-010 [11], expressed by standard sum-product messages. It provides a legitimate structural alternative when w is small, not a new general SAT bound. Decomposition-finding cost must be added if one is not supplied. Width $o(n)$ gives a structural subexponential bound under polynomial remaining costs; arbitrary bounded-width clauses do not ensure $w = o(n)$.

10.3 A rank identity that is exact but not efficient by itself

For reduced Boolean polynomials P_i over $\mathbb{F}_2$, let $A = \mathbb{F}_2[X]/(X_i^2 - X_i)$ and let $M_i : A \to A$ be multiplication by P_i. Then the integer number of common zeros is

$$N = 2^n - \mathrm{rank}_{\mathbb{F}_2}[M_1 \ \cdots \ M_m]. \tag{33}$$

Evaluation identifies A with a product of 2^n copies of $\mathbb{F}_2$. The ideal generated by the P_i has coordinate zero at a common zero and the whole field elsewhere. The quotient dimension is therefore the number of common zeros; rank-nullity proves (33). This is a useful small-instance reference identity, but its matrices have 2^n rows. Sparse columns do not by themselves yield a subexponential rank algorithm. Neither this identity nor a finite Ram inverse proves the source's difficult algorithmic bound.

11 Sparse equations, parity lifting, and the total-degree budget

For $P_i \in \mathbb{F}_2[X]$ given as a short sum of degree-at-most-k monomials, replace powers by first powers and combine duplicate monomials modulo two. Let L_i be the same sum with integer coefficients. Then $P_i(x) = 0$ exactly when $L_i(x)$ is even. Put $\ell = n + 1$ so that a count in $[0, 2^n]$ is determined by its residue modulo 2^ℓ.

11.1 An explicit modulus-amplifying polynomial

Define

$$p_\ell(Y) = (1 - Y)^\ell \sum_{j=0}^{\ell-1} \binom{\ell + j - 1}{j} Y^j. \tag{34}$$

The sum is the inverse of $(1 - Y)^\ell$ modulo Y^ℓ, so $p_\ell \equiv 1 \pmod{Y^\ell}$ and $p_\ell \equiv 0 \pmod{(1 - Y)^\ell}$. For even integers y the first congruence gives one modulo 2^ℓ; for odd integers the second gives zero. This is the source's complement of a modulus-amplifying construction with antecedents in Beigel–Tarui and Chan–Williams [6, 7].

Write $h(Y) = Y(Y - 1)$. Repeated division by this monic quadratic gives

$$p_\ell(Y) = \sum_{j=0}^{\ell-1} e_j(Y) h(Y)^j, \qquad e_j \in \mathbb{Z}[Y], \quad \deg e_j \le 1. \tag{35}$$

This is an exact polynomial basis change with affine remainder coefficients. Its significance is arithmetic: $h(y)$ is always even.

11.2 Why the truncation is shared across all factors

Work in $\mathbb{Q}[V]/(V^\ell)$ and define

$$B_i(X, V) = \sum_{j<\ell} e_j(L_i(X)) h(L_i(X))^j V^j. \tag{36}$$

Multiply *all* factors first, discarding only total V-degree at least ℓ, and then sum the retained coefficients by $\mathcal{S}_\ell$. At integer assignments, each omitted term is divisible by 2^ℓ. Consequently

$$\mathcal{S}_\ell \left(\prod_i B_i(x, V) \bmod V^\ell \right) \equiv \prod_i \mathbf{1}_{\{P_i(x)=0\}} \pmod{2^\ell}. \tag{37}$$

The retained input degree is at most

$$k\big(m_{\text{test}} + 2(\ell - 1)\big). \tag{38}$$

Indeed a product term indexed by j_i has degree at most $\sum_i k(1 + 2j_i)$, and $\sum_i j_i < \ell$. With $m_{\text{test}} = O(n)$ this is linear in n, unlike independent full-degree lifts multiplied without the shared filtration.

This is a strong match to the Ram discipline of retaining the exact algebra, product, and projection contract. It is not a new parity lift introduced by Ram Calculus. The valuation certificate is essential: an arbitrary low-degree projection would not preserve the count.

Example 11.1 (Order two)**.** For $\ell = 2$,

$$p_2(Y) = 1 - 3Y^2 + 2Y^3 = (1 - Y) + (2Y - 1)h(Y).$$

The product for two equations retains constant and first total order in V. The discarded cross term contains $h(y_1)h(y_2)$ and is divisible by four at integer arguments. Its input degree is six, whereas the retained part has degree at most four. The coefficient-sum functional $\mathcal{S}_2$ is not multiplicative on the truncated ring; applying it before multiplication would retain the wrong cross term.

11.3 Reduction from SAT without circular selection

Let $v(x)$ be the vector of clause violations. A true solution has $v(x) = 0$. The source constructs initial parity checks that exclude small nonzero violation supports using coding-theoretic structure related to expander codes [8]. It then adds sparse parity rows greedily. For a surviving nonzero violation vector, a random candidate list hits its support with sufficient probability and rejects it with probability at least $1/4$. Thus some row removes at least a quarter of the remaining false positives.

The candidate is chosen by minimizing the *total* number accepted, computed by the sparse polynomial counter. All candidates keep every true solution, so the unknown true count is the same additive constant in every comparison. After $3n$ rows, false positives are fewer than $(3/4)^{3n}2^n = (27/32)^n < 1$, hence zero. This explains why the greedy step need not know the answer in advance. Its count queries must work on arbitrary candidate systems, not only on systems already isolating true solutions.

Finally, a disjoint sparsification partitions satisfying assignments. Overlapping disjunctions would not permit adding leaf counts. Candidate enumeration, incidence reduction, and sparsification overheads are part of the source proof and are not supplied automatically by a Ram transform.

12 The sharper tensor route and its valuation structure

12.1 What is being contracted

A Boolean tensor network assigns one bit to each edge and a ring-valued table to each vertex. Its contraction is

$$Z_G = \sum_{x \in \{0,1\}^{E(G)}} \prod_v T_v(x|_{\delta(v)}). \tag{39}$$

For fixed clause density, clause tensors and equality trees give $O_{k,D}(n)$ edges and bounded degree. Subdividing each edge with an equality tensor makes the network bipartite without changing its scalar value. Unused variables are accounted for separately. Reduction modulo 2^{n+1} recovers the integer count uniquely.

For general formulas the source encodes retained incidence monomials of the parity lift. The total-degree budget (38) permits indexing selected incidences with $O_k(n \log\log n)$ Boolean wires. High-incidence variables and degree arrays are enumerated with separately bounded overhead. Tensor entries are implicit but must remain evaluable within the allowed time and space. A short tensor description alone is not sufficient if evaluating one entry hides an equally hard problem.

The source contraction theorem assumes $O(s)$ edges, maximum degree at most $\lceil s^{9/10} \rceil$, polynomially many vertices, initial precision and order $P_0, \ell = O(s)$, and entries over

$$\mathcal{B}_{P_0,\ell} = (\mathbb{Z}/2^{P_0}\mathbb{Z})[V]/(V^\ell)$$

with explicitly bounded evaluation cost. Its claimed contraction time is $\mathrm{poly}(s+\mathcal{L})2^{O(s/\sqrt{\log s})}$ and polynomial space. Substituting $s = O(n)$ or $s = O(n \log\log n)$ gives the two headline scales.

12.2 Cauchy deformation and scaled integral coordinates

At a recursive call with M edges, ports are packed into slots of length $L = 2^a$. Set

$$S = \{-L, \dots, L-1\}, \quad C(T) = \prod_{t \in S}(T - t), \quad \alpha = 2L, \qquad W_{xy}(T) = \frac{C(T)}{C'(0)(T - (y - x))}. \tag{40}$$

The apparent pole cancels because $y - x \in S$. The entries are polynomials of degree $2L - 1$, with $W(0) = I$ on the original matched slots. If $l_0(z) = 1 - z$ and $l_1(z) = z$, the deformed contraction is

$$F(T) = \sum_{X,Y \in \{0,1\}^M} A(Y)B(X) \prod_x l_{Y_x}((W(T)X)_x). \tag{41}$$

Its value at zero is the desired contraction and its degree is at most $M(2L - 1)$. Nonzero values need not be positive or count assignments.

The grid S is a full residue system modulo 2^{a+1}. At any node t, the valuations of nonzero differences $t - q$ balance the valuation of $C'(0)$. Substituting $T = t + \alpha z$ allows the known powers of two in each factor to be canceled before division. The resulting coefficients are integral at two, and the remaining inverses are of odd units. This is the source's scaled-integrality mechanism. It is not the statement that every rational polynomial has integral local Taylor coefficients.

The source also uses an unramified extension of the two-local rationals, with residue field large enough to provide many interpolation nodes with unit differences. Ordinary integer nodes alone would not supply that property modulo 2^p. Canonical lifts of tensor entries are fixed at their creation precision; a later recursive call cannot arbitrarily relift algebraically equivalent residues and assume that polynomial deformation commutes with the change.

12.3 Tapering, weighted modes, and recursion

For a retained valuation level $i = v_2(t) < u$, the source assigns multiplicity

$$q_t = h(u - i), \qquad h = \lceil 3M/u \rceil, \quad D_t = L/2^i, \quad p_t = p + 8hD_t + 8M(a+1). \tag{42}$$

The total multiplicity exceeds $\deg F$, and the precision budget accounts for denominators in reconstruction at zero. Near a node, crossing interactions expand into modes of weight $b + 1$ whose coefficients are divisible by 2^{b+1}. Only monomials of total mode weight less than p_t can contribute modulo 2^{p_t}.

If there are at most $6M/D_t$ modes of each weight, their number is bounded using

$$\exp\left(\theta p_t + \frac{6M}{D_t} \sum_{j \geq 1} -\log(1 - e^{-\theta j})\right).$$

The sum is at most $\theta^{-1} \sum_{h \geq 1} h^{-2}$. Choosing $\theta = \sqrt{M/(D_t p_t)}$ gives $\exp(O(\sqrt{M p_t / D_t})) = \exp(O(M/\sqrt{u}))$ under the source budget. Each retained monomial separates into smaller group contractions, with at most $M/8$ edges per child. The source chooses a depth-dependent $u_d \asymp (\log s)/2^d$, so the exponents sum geometrically.

The power-of-two divisibility is an exact vanishing certificate, not a small real norm. Conventional low-rank truncation or an L^2-small Ram residual does not imply it. The source's packet construction, lift consistency, precision inheritance, and implicit-entry bounds remain independent obligations. Our finite tests below probe selected local identities, not the entire recursive theorem.

13 Target-specific Hermite recovery and precision certificates

13.1 The target functional rather than the whole polynomial

Let distinct rational nodes t have multiplicities q_t, with $N = \sum_t q_t > \deg F$, and use scaled jets $h_{t,j} = [z^j]F(t + \alpha z)$. There are unique rational coefficients $\lambda_{t,j}$ for the canonical degree-less-than-N Hermite map such that

$$F(0) = \sum_t \sum_{j<q_t} \lambda_{t,j} h_{t,j}. \tag{43}$$

If A is the confluent matrix with entries $A_{(t,j),k} = \binom{k}{j} t^{k-j}\alpha^j$ for $k \geq j$ and zero otherwise, then $A^T\lambda = e_0$. Exact rational elimination computes the weights. Equivalently, one may use cardinal Hermite polynomials. The source already uses a target-at-zero Hermite formula in Appendix D; the contribution here is to use its *actual* coefficient valuations as a certificate.

Theorem 13.1 (Coordinatewise two-adic precision certificate)**.** *Suppose $F(0)$ is integral at two and approximations to its scaled jets satisfy $v_2(\widehat{h}_{t,j} - h_{t,j}) \geq b_{t,j}$ coordinatewise in the declared coefficient basis. If*

$$b_{t,j} + v_2(\lambda_{t,j}) \geq p \quad \textit{for every nonzero } \lambda_{t,j}, \tag{44}$$

then the reconstructed value is correct modulo 2^p. A sufficient common precision at node t is

$$p_t^{\mathrm{cert}} = p + \ell_t, \qquad \ell_t = \max(0, \max_{j:\lambda_{t,j}\neq 0} -v_2(\lambda_{t,j})). \tag{45}$$

For a recursion requiring strictly increasing creation precisions, use $p + \max(1, \ell_t)$ instead.

Proof. Each weighted jet error belongs to 2^p times the integral coefficient module by (44). Their finite sum also belongs to that module, since the two-adic valuation of a sum is at least the minimum of the valuations of its summands. Subtracting (43) proves the claim. The nodewise bound enforces the coordinatewise inequalities. □

For fixed nonzero weights and independently variable coefficient errors, the coordinatewise requirement is sharp: changing just one coefficient at valuation $p - v_2(\lambda_{t,j}) - 1$ changes the target at valuation $p - 1$. This is not a global optimality theorem for interpolation. The source polynomial may have degree well below $N - 1$, allowing other reconstruction functionals, and correlated errors can obey extra relations.

The source's conservative precision bound (42) is justified by bounding the same reconstruction map through an integral reciprocal series and rational evaluation. Directly computing the weights can give smaller losses. Their calculation has polynomial cost in the number of jets and their explicit bit sizes. It does not remove the need for the source's polynomial bound on those sizes. Within a recursive implementation, one must retain the source's fixed-lift convention and use a certified budget before changing any child precision.

For completeness, the weights can be obtained without inverting the entire matrix. Put

$$E_t(T) = \prod_{v \neq t} \left(\frac{T - v}{t - v} \right)^{q_v}, \qquad b_{t,m} = [z^m] \frac{1}{E_t(t + \alpha z)}.$$

The cardinal Hermite construction gives

$$\lambda_{t,j} = E_t(0) \sum_{k=j}^{q_t - 1} b_{t,k-j} (-t/\alpha)^k. \tag{46}$$

Indeed, multiply the truncated quotient $[F(t + \alpha z)/E_t(t + \alpha z)]_{<q_t}$ by $E_t(T)$ and substitute $z = (T - t)/\alpha$. Summing over nodes reproduces each jet, so uniqueness of interpolation proves the formula; collecting each $h_{t,j}$ at $T = 0$ gives (46).

In the tapered construction $b_{t,m}$ are integral at two because $E_t(t + \alpha z)$ is integral with constant term one. Counting valuations of grid differences yields

$$v_2(E_t(0)) = D_t \sum_{j=1}^{a-i} \frac{j}{2^j} (q(i + j) - q(i)) \geq -6 D_t h,$$

where $q(i) = h \max(0, u - i)$ and $\sum_{j \geq 1} j^2/2^j = 6$. Evaluation at $-t/\alpha$ loses at most $4M(a + 1)$ additional powers of two because $q_t \leq 4M$. Therefore

$$\ell_t \leq 6 h D_t + 4M(a + 1) \leq 8 h D_t + 8M(a + 1). \tag{47}$$

Thus the proposed direct certificate is bounded by the source allowance for the same map. It can exploit cancellations in the actual weights, but (47) alone has the same asymptotic scale.

13.2 A finite demonstrated reduction in precision

We computed the exact rational weights of (43) for two small grids. The comparison in Table 3 lists extra bits *above* the desired output precision p. For $a = 1$, $L = 2$, $h = 3$, and $q_{-1} = q_1 = 3$.

a	u	M	Nodes	Source allowance	Certified loss
1	1	1	$-1, 1$	64	7
2	2	2	$-3, -1, 1, 3$	144	33
2	2	2	$-2, 2$	96	7

Table 3: Exact finite Hermite precision calculations.

For $a = 2$, $L = 4$, $h = 3$, the odd nodes have multiplicity six and the valuation-one nodes have multiplicity three. The scaling is $\alpha = 2L$. These configurations satisfy the local interpolation hypotheses but not the large-size packing conditions of the full recursive algorithm. They establish a local certificate improvement, not a measured acceleration of that algorithm.

13.3 Archimedean residuals require a different certificate

For ordinary absolute errors $|e_{t,j}| \leq \delta_{t,j}$,

$$|\widehat{F}(0) - F(0)| \leq \sum_{t,j} |\lambda_{t,j}| \delta_{t,j}. \tag{48}$$

If the target is known to be an integer and the right side is strictly less than $1/2$, nearest-integer rounding is correct. This follows from the triangle inequality and separation of distinct integers. It is a useful Ram-style residual certificate, but the weights can be large. For a normalized expectation over 2^n assignments, a raw expectation error must be less than 2^{-n-1} to ensure count rounding. Ordinary relative accuracy or a small unweighted coefficient residual does not suffice. Exact modular arithmetic is therefore not casually replaceable by floating point.

14 Complex, quaternionic, and nonlinear extensions: relevant limits

The source's factorization and reordering require an associative commutative coefficient algebra. Complex coefficients are compatible with that algebraic condition, but exact bit complexity still needs an explicit finite representation. A complex phase encoding does not reduce the number of assignments or certify cancellation for free.

Quaternion-valued Ram channels in corrected TR60 and RMT extension TR3 require specified left/right multiplication, physical metrics, and ordered operators [18]. They are useful for vector or spinor observables, but substituting quaternions for the scalar coefficient ring here invalidates unrestricted factor reordering: $ij = k$ whereas $ji = -k$. Realification represents a fixed linear quaternion operation by a real matrix and keeps composition ordered. It does not make those matrices commute, reduce the network's width, or prove an exact-counting speedup. Octonions additionally require explicit parentheses; an associative scalar-ring proof cannot be imported unchanged.

Similarly, TR4's nonlinear range-consistency theorems [19] explain how to avoid false roots in transformed systems. They do not guarantee exhaustive isolation of every root of a general Boolean polynomial system. A local Newton certificate, an invertible projected Jacobian, and a small residual each answer a different question from the exact cardinality in (1). For this source, the scalar finite-algebra branch of Ram Calculus is substantially more directly relevant than its hypercomplex or continuous nonlinear PDE branch.

15 Exact tests and reproducible evidence

The accompanying program `eth-support/exact_identity_tests.py` uses Python integers and `fractions.Fraction`, with random seed `20261026`. It writes `eth-support/test-results.json`. No external private data or numerical fitting is used. The tests are small enough to compare against direct enumeration, which is a reference method here, not the proposed asymptotic implementation.

Table 4: Executed exact checks; all passed.

Check	Cases	What the equality establishes
Boolean rational polynomials	132	Direct diagonal sum, original subset-pair formula, aggregated formula, and generating-jet evaluation agree for $1 \le n \le 6$, $0 \le q \le n+1$.

Check	Cases	What the equality establishes
Weighted support filtration	120	The weighted subset aggregation equals the direct sum for weights in $\{1, 2, 3\}$ and varied budgets.
Shared-fiber generating jets	24	Two groups of three bits with cross-group sum dependence give identical global and factored coefficient vectors.
Rational Hermite recovery	36	Exact reconstruction with two unequal multiplicities, degrees one through nine.
Parity lift and global truncation	360	Modulus-amplifying indicators, quadratic remainder expansions, and common-order products agree modulo 2^ℓ, for $1 \le \ell \le 8$.
Cauchy scaled-integrality rows	1,168	All slot pairs and nodes for $L = 2, 4, 8$ have odd-denominator scaled coefficients; origin identity and cross-group divisibility hold in the checked configurations.
Tapered Hermite configurations	2	Exact weight valuations give Table 3; ten further polynomial reconstructions agree with the true origin value.
Negative controls	4	Detect invalid early functional application, rank-only state counting, floating cancellation, and a false derivative rule in a truncated ring.

15.1 A complete small SAT deformation

Consider

$$F = (x_1 \vee x_2) \wedge (\neg x_1 \vee x_3).$$

Its satisfaction polynomial is $(x_1 + x_2 - x_1x_2)(1 - x_1 + x_1x_3)$. Replacing each variable by $(1 - T)x_i$ and summing over all eight assignments gives, exactly,

$$H(T) = 4 - 3T + T^2 - T^3 - T^4. \tag{49}$$

Thus $H(0) = 4$, matching direct counting, and

$$H(1 + z) = -8z - 8z^2 - 5z^3 - z^4.$$

Reconstruction at zero gives $8-8+5-1 = 4$. At $T = 2$, however, $H(2) = -22$: deformed evaluations are not nonnegative counts. This example checks the algebra but does not meet the asymptotically useful $R < Q$ design conditions and is not presented as a fast solver.

15.2 The exact call counts, not elapsed-time claims

The large entries in Table 5 were computed by binomial arithmetic; those many calls were *not executed*. The table quantifies the proven loop reduction, not observed runtime or memory. In particular, the $n = 80$ entry remains enormous and says nothing about practical utility.

n	q	Original C_q	Aggregated B_q
20	2	801	211
40	4	1,544,481	102,091
80	8	7,847,456,478,273	32,490,460,747
6	6	729	64

Table 5: Combinatorial counts evaluated exactly from the formulas.

15.3 Failure cases that must remain visible

Four exact controls illustrate specific invalid substitutions.

1. In $\mathbb{Q}[w]/(w^2)$, multiplying first gives $w^2 = 0$; evaluating each retained factor at one first gives one. A linear final functional must not be treated as a ring homomorphism.
2. An eight-coordinate rank-one binary-weight row has 256 distinct Boolean measurements. Low rank need not mean a small state space.
3. Integer arithmetic gives $(2^{60} + 1) - 2^{60} = 1$, while binary64 floating arithmetic gives zero. Exact cancellation needs a precision certificate or exact arithmetic.
4. Canonical differentiation of the zero product z^2 modulo z^2 is zero, while a purported Leibniz calculation yields $2z$. Truncated coefficient multiplication is not compatible with that derivative.

Another analytic obstruction, used in the corpus, is moment aliasing: uniform even- and odd-parity distributions have identical proper-coordinate marginals but disjoint supports. Low-order assignment moments cannot identify arbitrary constraints. None of these examples disproves the source, which uses more carefully specified objects.

16 Equation comparison and attribution of improvements

Table 6: Equivalent representations and their actual benefit.

Conventional/source form	Ram-compatible form or refinement	Assessment
Sum over Boolean assignments	Boolean quotient plus moment functional $\Lambda(X_S) = 2^{n-\lvert S\rvert}$	Exact rederivation; no automatic compression.
Condition on shared linear measurements	Exact aggregate-state/fiber operator with multiplicity sums	Same source identity; clearer certificate and state-cost accounting.
Subset-pair Boolean jets	One restricted call per U plus a local Hamming generating jet	Proved fewer calls; polynomial arithmetic overhead; no better headline exponent.
Uniform first-order correction budget	Weighted downward-closed support family	Proved conditional extension when higher correction orders exist.

Conventional/source form	Ram-compatible form or refinement	Assessment
Conservative Hermite precision envelope	Actual valuation of the target-functional weights	Proved certificate; strict finite examples; no general asymptotic gain shown.
Arbitrary summary row list	Exact row-basis selection and row-specific integer boxes	Proved instance-dependent reduction without changing fibers.
Tensor basis replacement	Dual inverse transforms on contracted legs; transported product	Exact equivalence; dimensions and hidden contraction costs remain.
Ordinary low-rank or L^2 truncation	Quotient-ideal or valuation-certified truncation; otherwise explicit target error	Prevents unsupported exact-count claims; may require more computation.
Physical quaternionic channels	Ordered real block representation	Methodological relevance only; no demonstrated SAT improvement.

16.1 Advantages of the Ram-based organization

The strongest advantage is a disciplined modular description: state space, coefficient algebra, multiplication, observation functional, and error certificate are all explicit. The new generating-jet aggregation exemplifies how an extra small coefficient state can eliminate a repeated combinatorial index. Weighted order budgets make stronger local vanishing useful without discarding necessary contributions. The precision certificate targets the count itself rather than an unnecessarily uniform coefficient accuracy.

The corpus also contributes useful safeguards: projection leakage is distinguished from quotient reduction; rank is distinguished from attainable state count; finite inverses are distinguished from unrestricted inverses; and nonlinear transformed products retain their range constraints. These are valuable for an implementer deciding where a local optimization remains mathematically exact.

16.2 Disadvantages and comparisons with existing methods

The scalar proof can already be expressed concisely using conventional finite differences, quotient rings, generating functions, and Hermite interpolation. Calling these objects Ram operators does not confer a unique speed advantage. More coefficient dimensions can increase constants and bit arithmetic. Exact row compression may be redundant, sparse-state storage can destroy polynomial-space guarantees, and complex or hypercomplex coordinates can make a purely rational problem harder to implement.

The source's main innovations are precisely where a generic representation is insufficient: simultaneous low-degree incidence designs, arithmetic degree control, and a valuation-sensitive contraction recursion. Those ingredients are retained rather than replaced. A fair implementation comparison must use the source's streamed and structured baseline, not only a naive dense interpolation algorithm or exhaustive assignment sum.

17 Research directions with explicit success criteria

17.1 Implement the aggregated routine inside the actual construction

A next implementation should generate and check source-compatible rows, not just supply easy synthetic factors. It should compare the original C_q routine and the B_q routine on identical instances, recording ring operations, maximum coefficient bits, peak live memory, and elapsed time. A useful result would identify the range of q, J and group sizes in which the saved calls outweigh the extra generating dimension. Correct output must be compared to exact counts on every tractable instance.

17.2 Search for higher-order correction designs

Theorem 9.1 becomes useful if real designs give $\nu_i > 1$ for many coordinates. The optimization problem is to reduce the weighted subset family without increasing R, the number or range of measurements, or construction cost enough to cancel the saving. An asserted improvement to (22) must display all three terms after the redesign. A formal higher-order zero is not free.

17.3 Deploy exact target weights in recursive two-adic recovery

The nodewise certificate can be inserted into a prototype of Appendix D while preserving immutable creation-time lifts. A first goal is a measured reduction in working precision and mode enumeration on nontrivial recursive instances. A stronger goal would be an improved *uniform* upper bound on the valuations of the Hermite weights. Only the latter, combined with the recursion and packing bounds, could justify a better asymptotic exponent. The finite numbers in Table 3 do not establish it.

17.4 Finite-domain and weighted-count extensions

The finite-alphabet algebra (5) and weighted factors permit formal extensions to fixed-domain constraint satisfaction and rational partition functions. The source Section 3 already allows commutative $\mathbb{Q}$-algebras, so that observation alone is not new. A new complexity theorem would require a compatible low-degree design, bounds on domain encoding, factor scopes, coefficient sizes, and a final modulus sufficient to recover the weighted answer. Positivity and an $n + 1$-bit count bound cannot be assumed for arbitrary signed weights.

17.5 Formal verification and negative results

The aggregation and weighted-support theorems are finite-sum identities well suited to Lean formalization. Their implementation should be linked to explicit coefficient arrays and the streamed state machine, rather than proving only an abstract equality. The target-precision theorem similarly needs a verified valuation calculation and fixed-lift interface.

No argument here proves that the source's exponent is optimal. A lower bound for a selected moment representation, an example with many summary values, or an inability to improve an interpolation estimate is not a lower bound for all algorithms. Proving a genuine general lower bound would require a separate computational-model theorem. Conversely, an equivalent Ram formulation does not by itself overcome such a barrier.

18 Conclusion

Ram Calculus is substantively relevant to the source's finite algebra and verification interfaces, not because the paper secretly solves an auxiliary PDE. The most concrete addition is the aggregated Boolean-jet identity, which replaces a subset-pair enumeration by a subset enumeration with a small exact generating state. The weighted version and exact row-basis reduction give conditional instance-sensitive extensions. Target-specific two-adic Hermite weights yield provably valid precision budgets, with strict improvements in the executed finite examples.

These results improve selected calculations and clarify their limitations. They do not supply a stronger unrestricted SAT time bound, certify practical performance, or replace the source's difficult construction and recursive proof. The mathematical contribution is therefore a collection of exact, testable refinements and a precise separation of representation, information, arithmetic precision, and computational complexity. The positive research opportunity is to integrate these refinements into the actual algorithm and determine, with full bit and memory accounting, which local advantages survive at scale.

A Bounded-audit findings and arithmetic safeguards

The separate source-level audit did not find a demonstrated error in the examined Section 3–5 identities, Section 4 construction, Appendix B arithmetic accounting, and Appendix D precision and recursion arguments. This statement is deliberately narrower than global certification. Appendix A's complete combinatorial proof, all external prerequisites, and the circuit-lower-bound consequences were not independently re-proved; the Lean dependency graph was not rebuilt.

Two arithmetic details deserve emphasis. First, parity divisibility in Section 5 is used at the restored integer inputs at $T = 0$, not at the rational deformed inputs at other nodes. Second, the source bounds intermediate numerators, not merely the final answer. A common denominator for a full contribution can be fixed in advance. Adding exponentially many signed contributions increases the numerator bit length by the logarithm of their number, provided each contribution already has a uniform height bound. It is not necessary to multiply every accumulated term into the next one. Polynomial-sized interpolation then admits exact fraction-free elimination with bounded minors. "Fraction-free" includes exact integer division and is not synonymous with division-free inversion.

The contraction audit likewise preserves the distinction between the scalar two-local field and the truncated coefficient algebra containing nilpotents. Only scalar units are inverted. Canonical lifting is not a ring homomorphism: the canonical lift of $1 + 1$ modulo two is zero, while the sum of the two lifts is two. The creation-time convention avoids needing that false homomorphism property. Reducing precision without preserving this convention would not be justified by Theorem 13.1 alone.

These observations explain why the report offers refinements rather than claiming repairs to proven source errors. The negative controls reject tempting but invalid alternative implementations. They are not findings against the original manuscript.

B Source register and reproducibility

Public source TeX files are stored in `eth-support/source-42907c9/`. Extracted PDF text is `eth-support/source-paper-layout.txt`. The small test program and its JSON output are in `eth-support/`. Independent research notes record corpus paths and bounded-audit findings there.

Existing research reports and supplied files were not changed.

The mathematical claims proved in this report do not require the entire private corpus as an axiom system. The specific imported ideas and their limitations are identified in Section 3; the main new identities have self-contained proofs. In particular, the aggregation theorem uses only finite subset inversion and distributivity, and the precision theorem uses only a fixed exact recovery functional and the valuation inequality for sums.

References

[1] OpenAI. *The Exponential Time Hypothesis is False*. October 17, revised October 25, 2026. Supplied PDF and source at commit `42907c9e999cc00d6abe7a50bfc1023250edd1b9`. https://github.com/openai/math/tree/42907c9e999cc00d6abe7a50bfc1023250edd1b9/preprints/The-Exponential-Time-Hypothesis-is-False-October-25-2026.

[2] OpenAI. *Math repository: description and verification status*. Accessed October 26, 2026. https://github.com/openai/math/blob/main/README.md.

[3] OpenAI. *SubexponentialSAT Lean interfaces and comparator challenge*. Repository snapshot `7ef5c0cc5ca4b0e072b7a050fca09ab24bc6fa3a`; `lean/OAI/Algorithms/SubexponentialSAT/Main.lean`, `SqrtLogSpace/Final.lean`, and `lean/ComparatorChallenges/SubexponentialSAT.json`. https://github.com/openai/math/tree/7ef5c0cc5ca4b0e072b7a050fca09ab24bc6fa3a/lean/OAI/Algorithms/SubexponentialSAT.

[4] R. Impagliazzo, R. Paturi, and F. Zane. Which problems have strongly exponential complexity? *Journal of Computer and System Sciences* 63 (2001), 512–530. https://cseweb.ucsd.edu/~paturi/myPapers/pubs/ImpagliazzoPaturiZane_2001_jcss.pdf.

[5] J. Alman and R. Williams. *Probabilistic Rank and Matrix Rigidity*. STOC 2017; arXiv:1611.05558. https://arxiv.org/abs/1611.05558.

[6] R. Beigel and J. Tarui. On ACC. *Computational Complexity* 4 (1994), 350–366. Author-hosted reference: https://www.cis.temple.edu/~beigel/papers/bt-acc-cc.html.

[7] T. M. Chan and R. Williams. Deterministic APSP, Orthogonal Vectors, and More: Quickly Derandomizing Razborov–Smolensky. *ACM Transactions on Algorithms* 17(1), 2021. https://people.csail.mit.edu/rrw/derand-apsp-ov-cr-talg.pdf.

[8] M. Sipser and D. A. Spielman. Expander codes. *IEEE Transactions on Information Theory* 42(6) (1996), 1710–1722. https://www.cs.yale.edu/homes/spielman/Research/expanders.html.

[9] M. Subbarao. *Foundations of Ram Operator Representations and Certified Inversion: Locality, Polynomial Rigidity, Orthogonal Panels, and Stable Recovery*. Local corpus, `RamOperator/RamOperator-Foundations.tex`, especially Sections 2–3, 6–7, and 13.

[10] M. Subbarao. *Local Operators, Orthogonal Bases, and the Ram-Series Question*, revision 2. Local corpus, `RamOperator/RamOperatorSeries-rev2.tex`, finite-jet and polynomial-inverse sections.

[11] M. Subbarao. *P versus NP through Audited Ram Reductions*. Local corpus, revised September 6, 2026, `res-math/TR-item-010-astra.tex`, Boolean quotient, tree closure, and parity-aliasing sections.

[12] M. Subbarao. *Exact Moment Coordinates, Block Mollifiers, and Uniform Rank-Tail Boundaries*. Local corpus, `OpenAI-722-math/M012-Mean-Analytic-Rank/TR-M012-Ram-Mean-Analytic-Rank.tex`.

[13] M. Subbarao. *Smaller Jets and Structured Arithmetic for Uniform Matrix Hitting Points in Positive Characteristic*. Local corpus, `OpenAI-722-math/M231-Positive-Characteristic-PIT/TR-M231-Ram-Positive-Characteristic-PIT.tex`.

[14] M. Subbarao. Corrected discrete shift-variant Ram report. Local corpus, `RamFoundationTRs/TR-rev-1-old-tr166/TR-rev-1-old-tr166.tex`, correction register, exact recovery, and divided-difference sections.

[15] M. Subbarao. Revised *Ram Calculus Foundations*, Volume 1, operator-foundations integration dated October 20, 2026. Local corpus, `RamCalBooks-v2/Operator-Foundations-Integration-20261020/Volume01-Operator-Foundations-rev2/source/volumes/volume1-rev2/chapters/ch08-measurements-C.tex`.

[16] M. Subbarao. RMT extension TR1: frames, atoms, and exact aggregate-state selection. October 2026. Local corpus, `RamRMT-extensions/TR1-rmt-ext-frames-atoms.tex`, Sections 7–9.

[17] M. Subbarao. RMT extension TR2: fractional and complex orders. October 23, 2026. Local corpus, `RamRMT-extensions/TR2-rmt-ext-fractional-complex.tex`, terminal polynomial and jet-channel sections.

[18] M. Subbarao. *Constraint-Preserving Tensor and Hypercomplex RMT*. October 23, 2026. Local corpus, `RamRMT-extensions/TR3-rmt-ext-hypercomplex-constraints.tex`; includes corrected TR60 conventions and references.

[19] M. Subbarao. Nonlinear RMT extension TR4. October 23, 2026. Local corpus, `RamRMT-extensions/TR4-rmt-ext-nonlinear.tex`, transported nonlinearities, range consistency, and residual counterexamples.