

# **Murano Developers Guide**

---

# Murano Developers Guide

v0.1

Publication date 2013-09-04  
Copyright © 2013 Mirantis, Inc.

## Abstract

This document is intended for individuals who wish to use our product or intend to contribute.

---

---

# Table of Contents

|   |    |
|---|----|
| 1. Overview .....                               | 1  |
| Intended Audience .....                         | 1  |
| Document Change History .....                   | 1  |
| 2. Installation Guide .....                     | 2  |
| Pre-Requisites .....                            | 2  |
| Murano API Service .....                        | 2  |
| Install .....                                   | 2  |
| Configure .....                                 | 3  |
| Run .....                                       | 5  |
| Conductor Service .....                         | 5  |
| Install .....                                   | 6  |
| Configure .....                                 | 7  |
| Run .....                                       | 8  |
| Murano Dashboard .....                          | 8  |
| Install .....                                   | 8  |
| SSL configuration .....                         | 9  |
| HTTPS for Murano API .....                      | 9  |
| SSL for RabbitMQ .....                          | 10 |
| 3. Architecture .....                           | 12 |
| Architecture .....                              | 12 |
| REST API .....                                  | 12 |
| Object Model .....                              | 12 |
| Orchestration Engine .....                      | 12 |
| Releases .....                                  | 13 |
| Integration with Heat .....                     | 13 |
| Windows on OpenStack .....                      | 13 |
| 4. API Specification .....                      | 14 |
| Introduction .....                              | 14 |
| Return codes and errors .....                   | 15 |
| Response of POSTs and PUTs .....                | 15 |
| Authentication .....                            | 15 |
| Workflow .....                                  | 15 |
| Hostname assignment .....                       | 15 |
| API .....                                       | 16 |
| Environment API .....                           | 16 |
| Environment Configuration API .....             | 20 |
| Services API .....                              | 23 |
| Example Calls using Web Server as example ..... | 25 |
| Shared Attributes .....                         | 27 |
| Active Directory Specs .....                    | 28 |
| Web Server Specs .....                          | 29 |
| ASP.NET Application Specs .....                 | 30 |
| Web Server Farm Specs .....                     | 30 |
| ASP.NET Application Farm Specs .....            | 31 |
| MS SQL Server Specs .....                       | 32 |
| 5. Workflows XML DSL .....                      | 34 |
| XML DSL .....                                   | 34 |
| DSL functions .....                             | 35 |
| Workflows .....                                 | 36 |
| Accessing Object Model .....                    | 37 |
| Function context .....                          | 38 |

|                             |    |
|-----------------------------|----|
| Workflow rules .....        | 39 |
| Workflow actions .....      | 40 |
| Workflow control .....      | 41 |
| Execution Plans .....       | 41 |
| 6. Known Issues .....       | 43 |
| 7. How To Participate ..... | 44 |

---

## List of Figures

|                            |    |
|----------------------------|----|
| 3.1. Architecture .....    | 12 |
| 4.1. Sample Workflow ..... | 15 |

---

## List of Tables

|  |    |
|--|----|
| 4.1. Environment Object .....  | 16 |
| 4.2. GET /environments Call .....                                    | 16 |
| 4.3. Environment Object .....  | 17 |
| 4.4. POST /environments Call .....                                   | 17 |
| 4.5. Environment Object .....  | 18 |
| 4.6. PUT /environments/<id> Call .....                               | 18 |
| 4.7. Error Response Codes .....                                      | 18 |
| 4.8. GET /environments/<id> Call .....                               | 19 |
| 4.9. Error Response Codes .....                                      | 19 |
| 4.10. DELETE /environments/<id> Call .....                           | 20 |
| 4.11. Error Response Codes .....                                     | 20 |
| 4.12. Configuration Session Object .....                             | 20 |
| 4.13. POST /environments/<id>/configure Call .....                   | 21 |
| 4.14. Error Response Codes .....                                     | 21 |
| 4.15. POST /environments/<id>/sessions/<sessionId>/deploy Call ..... | 21 |
| 4.16. Error Response Codes .....                                     | 21 |
| 4.17. GET /environments/<id>/sessions/<sessionId> Call .....         | 22 |
| 4.18. Error Response Codes .....                                     | 22 |
| 4.19. DELETE /environments/<id>/sessions/<sessionId> Call .....      | 22 |
| 4.20. Error Response Codes .....                                     | 23 |
| 4.21. GET /environments/<id>/services Call .....                     | 23 |
| 4.22. Headers .....  | 23 |
| 4.23. PUT /environments/<id>/services Call .....                     | 24 |
| 4.24. Headers .....  | 24 |
| 4.25. POST /environments/<id>/services Call .....                    | 24 |
| 4.26. Headers .....  | 24 |
| 4.27. DELETE /environments/<id>/services Call .....                  | 24 |
| 4.28. Headers .....  | 25 |
| 4.29. GET /environments/<id>/services Call .....                     | 25 |
| 4.30. Headers .....  | 25 |
| 4.31. POST /environments/<id>/services Call .....                    | 26 |
| 4.32. Headers .....  | 26 |
| 4.33. DELETE /environments/<id>/services/<service_id> Call .....     | 27 |
| 4.34. Headers .....  | 27 |
| 4.35. Service Object Specs .....                                     | 27 |
| 4.36. Service Object Specs .....                                     | 28 |
| 4.37. Active Directory Object .....                                  | 28 |
| 4.38. Active Directory Unit Object .....                             | 28 |
| 4.39. Active Directory Object .....                                  | 28 |
| 4.40. Active Directory Unit Object .....                             | 29 |
| 4.41. Web Server Object .....  | 29 |
| 4.42. Web Server Unit Object .....                                   | 29 |
| 4.43. Web Server Object .....  | 29 |
| 4.44. Web Server Unit Object .....                                   | 29 |
| 4.45. ASP.NET Application Object .....                               | 30 |
| 4.46. ASP.NET Application Unit Object .....                          | 30 |
| 4.47. ASP.NET Application Object .....                               | 30 |
| 4.48. ASP.NET Application Unit Object .....                          | 30 |
| 4.49. Web Server Farm Object .....                                   | 31 |
| 4.50. Web Server Farm Unit Object .....                              | 31 |
| 4.51. Web Server Farm Object .....                                   | 31 |

|  |    |
|--|----|
| 4.52. Web Server Farm Unit Object .....          | 31 |
| 4.53. ASP.NET Application Farm Object .....      | 31 |
| 4.54. ASP.NET Application Farm Unit Object ..... | 32 |
| 4.55. ASP.NET Application Farm Object .....      | 32 |
| 4.56. ASP.NET Application Farm Unit Object ..... | 32 |
| 4.57. MS SQL Server Object .....                 | 32 |
| 4.58. SQL Server Unit object .....               | 33 |
| 4.59. SQL Server Unit object .....               | 33 |
| 4.60. MS SQL Server Unit Object .....            | 33 |

---

# Chapter 1. Overview

Welcome to Murano Project. Full information about Murano in openstack wiki page. [<https://wiki.openstack.org/wiki/Murano>]

Murano is intended to get opportunity for non-experienced users to deploy reliable Windows-based environments with 1-Click. Key goal is to provide UI and API which allows to deploy and operate Windows environments on the "Windows Services" abstraction level. The Service should be able to orchestrate complex circular dependent cases in order to setup complete Windows environments with many dependant services.

## Intended Audience

This guide is intended to individuals who want to contribute to our project.

## Document Change History

This version of the Murano Manual replaces and obsoletes all previous versions. The most recent changes are described in the table below:

| Revision Date      | Summary of Changes           |
|--------------------|------------------------------|
| April. 4, 2013     | • Initial document creation. |
| September. 4, 2013 | • update for Release-0.2     |



---

# Chapter 2. Installation Guide

This chapter describes installation and configuration of Murano services.

Note that all Murano modules can be downloaded from our page [<https://launchpad.net/murano/>] on launchpad.

## Pre-Requisites

Murano supports the following operating systems:

1. Ubuntu 12.04
2. RHEL/CentOS 6.4

These system packages are required for Murano:

### *Ubuntu*

1. python-dev
2. libxml2-dev
3. libxslt-dev
4. libffi-dev

### *CentOS*

1. python-devel
2. libxml2-devel
3. libxslt-devel
4. libffi-devel

## Murano API Service

Murano API provides access to the Murano orchestration engine via API.

This chapter describes the procedure of installation and configuration of Murano API.

## Install

- Superuser privileges is required to install and configure system packages. Let's switch to root account:

```
sudo su -
```

- Clone Murano API git repository:

```
git clone https://github.com/stackforge/murano-api
```

Stable version one of our releases can be checked by tag:

```
git checkout 0.2
```

- Switch to just created directory and then perform installation

*Ubuntu*

```
cd murano-api
sh setup.sh install
```

*CentOS*

```
cd murano-api
yum install -y http://mirror.yandex.ru/epel/6/x86_64/epel-release-6-8.noarch.rpm
sh setup-centos.sh install
```

- Successful installation ends with message like this:

```
Successfully installed muranoapi
Cleaning up...
LOG:> Making sample configuration files at "/etc/murano-api"
LOG:> Reloading initctl
LOG:> Please, make proper configuration, located at "/etc/murano-api", before start
```

## Configure

- First configure rabbitMQ by adding vhost and user with administrator rights:

```
rabbitmqctl add_user muranouser murano
```

```
rabbitmqctl set_user_tags muranouser administrator
rabbitmqctl add_vhost muranovhost
rabbitmqctl set_permissions -p muranovhost muranouser ".*" ".*" ".*"
```

- Copy and edit configuration files:

```
cd /etc/murano-api
cp murano-api.conf.sample murano-api.conf
cp murano-api-paste.ini.sample murano-api-paste.ini

vi murano-api.conf
```

- Configure it according to your environment:
  - *[DEFAULT]* section sets up logging.
  - *[reports]* section allows you to set up names for new rabbitMQ queues.
  - In *[rabbitmq]* section you can set up host configuration where rabbitMQ with just created user and vhost is running.

For more information how to configure SSL take a look at [SSL configuration chapter](#)

- Configure keystone auth\_token in murano-api-paste.ini file. For more information see [Auth-Token Middleware with Username and Password \[http://docs.openstack.org/developer/keystone/configuringservices.html\]](http://docs.openstack.org/developer/keystone/configuringservices.html)

```
vim murano-api-paste.ini
```

```
[pipeline:muranoapi]
pipeline = authtoken context apivlapp
```

```
[app:apivlapp]
paste.app_factory = muranoapi.api.v1.router:API.factory
```

```
[filter:context]
paste.filter_factory = muranoapi.api.middleware.context:ContextMiddleware.factory
```

```
#For more information see Auth-Token Middleware with Username and Password
#http://docs.openstack.org/developer/keystone/configuringservices.html
```

```
[filter:authtoken]
paste.filter_factory = keystoneclient.middleware.auth_token:filter_factory
auth_host = localhost
auth_port = 35357
auth_protocol = http
admin_tenant_name = admin
admin_user = admin
admin_password = password
```

- Register murano-api service in Openstack.

Note: you need to be authorized in Openstack to run this commands. To do this, you can run something like (having changed variables to appropriate values)

```
source $(YOUR_OPENSTACK_DIR)/openrc $(LOGIN) $(PASSWORD)
```

```
keystone service-create --name muranoapi --type murano --description "Murano-API"
```

```
keystone endpoint-create
```

```
    --region RegionOne
```

```
    --service-id The ID field returned by the keystone service-create
```

```
    --publicurl http://x.x.x.x:8082 (where x.x.x.x - host ip where murano-api in
```

```
    --internalurl the same as publicurl
```

```
    --adminurl the same as publicurl
```

## Run

- Run Murano API service:

*Ubuntu*

```
service murano-api start
```

*CentOS*

```
initctl start murano-api
```

## Conductor Service

Conductor is a Murano orchestration engine that transforms object model sent by REST API service into a series of Heat and Murano-Agent commands.

This chapter describes Conductor for contributors of the project.

# Install

- Murano Conductor uses OpenStack Heat for new virtual machines creation, therefore Heat should be installed and configured. Some services require the Internet access for virtual machines to successful deployment.

The detailed information about Heat configuration is described here. [[http://docs.openstack.org/developer/heat/getting\\_started/index.html](http://docs.openstack.org/developer/heat/getting_started/index.html)]

- OpenStack Heat requires Key Pair for Load Balancer instances. Murano Conductor uses LoadBalancer for IIS Farms and ASP.NET Farms. The default name for Key Pair is "murano-lb-key", you can change this parameter in file `/etc/murano-conductor/data/templates/cf/Windows.template`
- Superuser privileges are required to install and configure system packages. Let's switch to root account:

```
sudo su -
```

- Clone Murano Conductor repository from the github.

```
git clone https://github.com/stackforge/murano-conductor
```

Stable version one of our releases can be checked out by tag:

```
git checkout 0.2
```

- Switch to just created directory and then perform installation

*Ubuntu*

```
cd murano-conductor
sh setup.sh install
```

*CentOS*

```
cd murano-conductor
yum install -y
http://mirror.yandex.ru/epel/6/x86_64/epel-release-6-8.noarch.rpm
sh setup-centos.sh install
```

## Configure

- Edit configuration file and take a look at inline comments:

```
cd /etc/murano-conductor
cp conductor.conf.sample conductor.conf
```

- Change configuration file according to your environment.

```
vi conductor.conf
```

- *[DEFAULT]* section is responsible for logging.
- *[heat]* points where heat is running.
- *[rabbitmq]* section points where your rabbitMQ installed and configured.

```
[DEFAULT]

# Path where log will be written
log_file = /var/log/murano-conductor.log
# Log verbosity
debug=True
verbose=True
data_dir = /etc/murano-conductor
# Maximum number of environments that can be processed simultaneously
max_environments = 20

[keystone]
auth_url = http://localhost:5000/v2.0
ca_file =
cert_file =
key_file =
insecure = False

[heat]
# Heat SSL parameters
# Optional CA cert file to use in SSL connections
ca_file =
# Optional PEM-formatted certificate chain file
cert_file =
# Optional PEM-formatted file that contains the private key
key_file =
# If set then the server's certificate will not be verified
insecure = False
```

```
# Valid endpoint types: publicURL (default), internalURL, adminURL
endpoint_type = publicURL

[rabbitmq]
# Connection parameters to RabbitMQ service
# Hostname or IP address where RabbitMQ is located.
# !!! Change localhost to your real IP or hostname as this address must be reachable
host = localhost
# RabbitMQ port (5672 is a default)
port = 5672
# Use SSL for RabbitMQ connections (True or False)
ssl = False
# Path to SSL CA certificate or empty to allow self signed server certificate
ca_certs =
# RabbitMQ credentials. Fresh RabbitMQ installation has "guest" account with "guest" password
# It is recommended to create dedicated user account for Murano using RabbitMQ web console
login = muranouser
password = murano
# RabbitMQ virtual host (vhost). Fresh RabbitMQ installation has "/" vhost preconfigured
# It is recommended to create dedicated vhost for Murano using RabbitMQ web console
virtual_host = muranovhost
```

## Run

- Run Murano Conductor service:

*Ubuntu*

```
service murano-conductor start
```

*CentOS*

```
initctl start murano-conductor
```

## Murano Dashboard

Murano Dashboard provides Web UI for Murano Project.

## Install

- Superuser privileges is required to install and configure system packages. Let's switch to root account:

```
sudo su -
```

- Clone Murano Dashboard repository from the github:

```
git clone https://github.com/stackforge/murano-dashboard
```

- Switch to just created directory and run installation script

*Ubuntu*

```
cd murano-dashboard  
sh setup.sh install
```

*CentOS*

```
cd murano-dashboard  
sh setup-centos.sh install
```

## SSL configuration

Murano components are able to work with SSL. This chapter will help your to make proper settings with SSL configuration.

## HTTPS for Murano API

SSL for Murano API service can be configured in *ssl* section in */etc/murano-api/murano-api.conf*. Just point to a valid SSL certificate. See the example below:

```
[ssl]  
cert_file = PATH  
key_file = PATH  
ca_file = PATH
```

- *cert\_file=PATH*: Path to the certificate file the server should use when binding to an SSL-wrapped socket.



- *key\_file=PATH*: Path to the private key file the server should use when binding to an SSL-wrapped socket.
- *ca\_file=PATH*: Path to the CA certificate file the server should use to validate client certificates provided during an SSL handshake. This is ignored if *cert\_file* and "*key\_file*" are not set.

The use of SSL is automatically started after point to HTTPS protocol instead of HTTP during registration Murano API service in endpoints (Change *publicurl* argument to start with *https://*). See here how to register Murano API in Openstack Keystone.

SSL for Murano API is implemented like in any other Openstack component. This realization is based on *ssl* python module so more information about it can be found here. [<http://docs.python.org/2/library/ssl.html>]

## SSL for RabbitMQ

All Murano components communicate with each other by RabbitMQ. This interaction can be encrypted with SSL. By default all messages in Rabbit MQ are not encrypted. Each RabbitMQ Exchange should be configured separately.

### Murano API -> Rabbit MQ exchange

Edit *rabbitmq* section in */etc/murano-api/murano-api.conf* and set *ssl* option to *True* to enable SSL. Specify the path to the SSL CA certificate in regular format: */path/to/file* without quotes or leave it empty to allow self-signed certificates.

```
[rabbitmq]

# Use SSL for RabbitMQ connections (True or False)
ssl = True

# Path to SSL CA certificate or empty to allow self signed server certificate
ca_certs =
```

### Rabbit MQ -> Murano Conductor exchange

Open */etc/murano-conductor/conductor.conf* and configure *rabbitmq* section in the same way: enable *ssl* option to *True* and set CA certificate path or leave it empty to allow self-signed certificates.

```
[rabbitmq]

# Use SSL for RabbitMQ connections (True or False)
ssl = True

# Path to SSL CA certificate or empty to allow self signed server certificate
ca_certs = /home/user/certificates/example.crt
```

## Murano Agent -> Rabbit MQ exchange

By default all Murano Conductor configuration settings apply to Murano Agent. If you want to configure Murano Agent in a different way change the default template. It can be found here: */etc/murano-conductor/data/templates/agent-config/Default.template*. Take a look at appSettings section:

```
<appSettings>
  <add key="rabbitmq.host" value="%RABBITMQ_HOST%" />
  <add key="rabbitmq.port" value="%RABBITMQ_PORT%" />
  <add key="rabbitmq.user" value="%RABBITMQ_USER%" />
  <add key="rabbitmq.password"
    value="%RABBITMQ_PASSWORD%" />
  <add key="rabbitmq.vhost" value="%RABBITMQ_VHOST%" />
  <add key="rabbitmq.inputQueue"
    value="%RABBITMQ_INPUT_QUEUE%" />
  <add key="rabbitmq.resultExchange" value=" " />
  <add key="rabbitmq.resultRoutingKey"
    value="%RESULT_QUEUE%" />
  <add key="rabbitmq.durableMessages" value="true" />

  <add key="rabbitmq.ssl" value="%RABBITMQ_SSL%" />
  <add key="rabbitmq.allowInvalidCA" value="true" />
  <add key="rabbitmq.sslServerName" value=" " />
</appSettings>
```

Desired parameter should be set directly to the value of the key that you want to change. Quotes are needed to be kept. Thus you can change "rabbitmq.ssl" and "rabbitmq.port" values to make Rabbit MQ work with this exchange in a different from Murano-Conductor way.

---

# Chapter 3. Architecture

## Architecture

The Murano Service communicates with the following OpenStack components:

- Horizon - provides a GUI with ability to use all Murano features;
- Keystone - authenticates users and provides the security token that is used to work with OpenStack, hence limiting the user abilities in Murano based on OpenStack privileges;
- Heat - is used to provision VMs and other OpenStack resources for Windows Environments;
- Glance - stores Windows Server VM images, with each image containing an installed OS and a set of scripts
- Quantum - provides the network configuration API
- Agent - provides agent functionality to communicate with the Orchestration Engine and executes tasks on VMs

**Figure 3.1. Architecture**



## REST API

Murano exposes a service endpoint for communication with a client. It exposes API functions to manipulate objects such as environment and service.

This component is responsible for translating API function parameters to Object Model attributes and propagating the deployment status from the Orchestration Engine.

## Object Model

An internal representation of Windows Services and Environments. All attributes and entities are described in the API specification.

## Orchestration Engine

This is the core component which evaluates Object Model changes and creates a plan for implementing these changes on the instances or in the cloud. This component will support extensions via plug-ins. Plugins can add new services and extend existing services for integration.

## Releases

- *Release-0.1* has 0.1 tag in all Murano repositories. Released 2013-05-30.
- *Release-0.2* has 0.2 tag in all Murano repositories. Released 2013-09-05.

## Integration with Heat

Heat is a cloud resource management engine that allows you to manipulate resources that represent OpenStack entities (Security Groups, Instances, Floating IPs, Volumes, etc.) and some entities such as AutoScaling groups from a single point of control.

OpenStack resource provisioning is one of the steps required for environment deployment and Heat will be used for that purpose. Heat allows you to define all OpenStack resources in a single document that will be easy to maintain and will not require resorting to multiple OpenStack APIs while keeping the software configuration separate.

## Windows on OpenStack

Windows works on KVM pretty smoothly, and with the RedHat-created open-source VirtIO drivers for Windows, it's possible to work efficiently with KVM exposed devices.

In OpenStack's Grizzly release, Microsoft's hypervisor Hyper-V will be supported. The Hyper-V virtual switch will be also supported as a Quantum plug-in. From the performance viewpoint, Hyper-V Server 2012 compares very favorably with bare metal, processing just over 6% fewer transactions per second compared to the same workload running on a similarly configured physical server.

Also, unlike the current OpenStack, Hyper-V also natively supports Windows Clusters.

---

# Chapter 4. API Specification

| Revision Date     | Summary of Changes  |
|-------------------|---|
| February 4, 2013  | • Initial   |
| February 22, 2013 | • Enhance API with latest architecture changes  |
| March 06, 2013    | • Fix specification according to remarks from Dmitry Teselkin   |
| Jun 06, 2013      | • ASP.NET Application, Web Server Farm and ASP.NET Application Farm Services Added, uri/address/endpoint corrections, hostname assignment section added |

## Introduction

Murano Service API is a programmatic interface used for interaction with Murano. Other interaction mechanisms like Murano Dashboard or Murano CLI should use API as underlying protocol for interaction.

## Glossary

For detailed information about entities and terms used in this document, please refer first to architecture.

|                  |  |
|------------------|--|
| Environment      | <p>Environment is a set of logically related Services managed by a single tenant. Environment defines Windows environment boundaries.</p> <p>Services within single Environment may comprise some complex configuration while Services in different Environments are always independent from one another. Each Environment is associated with single OpenStack project (tenant).</p> |
| Service          | <p>Service is building block of Windows environment. Service is a set of one or more Virtual Machines sharing a common purpose and configured together. Each service belongs to a single Environment and single Service Type.</p> <p>Services are comprised from one or more Service Units.</p>  |
| Service Type     | <p>Service type is definition for describing set of features exposed by service.</p>   |
| Service Unit     | <p>Service Units are the actual Windows Server VMs instantiated by OpenStack and then configured according to its Service Type (this may also correspond to one of predefined Windows Server roles).</p>   |
| Service Metadata | <p>Service Metadata is a JSON-encoded definition of Environment, its Services and their Service Units along with all their attributes. Service Metadata may describe both current and the intended state of the Environment.</p>   |
| Session          | <p>All changes to environment done in scope of Session. After all changes to Environment state are accumulated, changes actually are applied only after session is deployed.</p>   |

## Return codes and errors

All REST API calls return the natural HTTP response codes for the operations, e.g. a successful GET returns a HTTP 200, a successful PUT returns a HTTP 201, a GET for a non-existent entity returns HTTP 404, unauthorized operations return HTTP 401 or HTTP 403, internal errors return HTTP 500.

## Response of POSTs and PUTs

All POST and PUT requests by convention should return the created object (in the case of POST, with a generated ID) as if it was requested by GET.

## Authentication

All requests include a Keystone authentication token header (X-Auth-Token). Clients must authenticate with Keystone before interacting with the Murano service.

## Workflow

**Figure 4.1. Sample Workflow**



Let's review a sample workflow (series of API calls) for creating new Environment with Active Directory Service deployment:

1. POST /environments/ - Creating new Environment
2. POST /environments/id/configure – Creating new configuration session for Environment
3. POST /environments/id/services – Creating new ActiveDirectory service
4. POST /environments/id/sessions/session\_id/deploy – Saving and deploying changes

## Hostname assignment

Each Service Object definition may have an attribute "unitNamingPattern" that is used to control hostnames that will be assigned to spawned VM instances of the service.

Hostname pattern has the form of "name#" where "#" character is replaced with sequential number of unit within the service (starting with 1) and all other characters remain intact. For example Service with unitNamingPatter equal to "ad#-loc" will have units with hostnames "ad1-loc", "ad2-loc" etc.

"unitNamingPattern" attribute is optional. If it is omitted then a unique random hostname would be assigned.

# API

## Environment API

This section describes API calls for Environment management.

### Get a List of existing Environments

**Table 4.1. Environment Object**

| Attribute | Type     | Description                                  |
|-----------|----------|--|
| id        | string   | Unique ID                                    |
| name      | string   | User-friendly name                           |
| created   | datetime | Creation date and time in ISO format         |
| updated   | datetime | Modification date and time in ISO format     |
| tenant_id | string   | OpenStack tenant ID                          |
| version   | int      | Current version                              |
| status    | string   | Deployment status: ready, pending, deploying |

### Call

**Table 4.2. GET /environments Call**

| Method | URI           | Description                         |
|--------|---------------|-------------------------------------|
| GET    | /environments | Get a list of existing Environments |

### Payload

None

### Returns

This call returns list of environments. Only the basic properties are returned. For details see "Get Environment Instance Detailed Information":

```
{
  "environments": [
    {
      "id": "0ce373a477f211e187a55404a662f968",
      "name": "dcl",
      "created": "2010-11-30T03:23:42Z",
      "updated": "2010-11-30T03:23:44Z",
      "tenant_id": "0849006f7ce94961b3aab4e46d6f229a",
```

```
        "version": 1,
        "status": "ready"
    },
    {
        "id": "c697bd2429304820a928d145aa42af59",
        "name": "dc2",
        "created": "2010-11-30T03:23:42Z",
        "updated": "2010-11-30T03:23:44Z",
        "tenant_id": "0849006f7ce94961b3aab4e46d6f229a",
        "version": 2,
        "status": "deploying"
    }
]
}
```

## Create Environment instance

**Table 4.3. Environment Object**

| Attribute | Type   | Required | Description        |
|-----------|--------|----------|--------------------|
| name      | string | yes      | User-friendly name |

## Call

**Table 4.4. POST /environments Call**

| Method | URI           | Description            |
|--------|---------------|------------------------|
| POST   | /environments | Create new Environment |

## Payload

```
{
  "name": "env1"
}
```

## Returns

This call returns created environment:

```
{
  "id": "ce373a477f211e187a55404a662f968",
  "name": "env1",
  "created": "2010-11-30T03:23:42Z",
  "updated": "2010-11-30T03:23:44Z",
}
```



```
    "tenant_id": "0849006f7ce94961b3aab4e46d6f229a",  
    "version": 0  
  }
```

## Update Environment Instance

**Table 4.5. Environment Object**

| Attribute | Type   | Required | Description        |
|-----------|--------|----------|--------------------|
| name      | string | yes      | User-friendly name |

### Call

**Table 4.6. PUT /environments/<id> Call**

| Method | URI                | Description                               |
|--------|--------------------|---|
| PUT    | /environments/<id> | Update properties of Environment instance |

**Table 4.7. Error Response Codes**

| Code | Description  |
|------|--|
| 401  | User is not authorized to access this tenant resources |

### Payload

```
{  
  "name": "env1-changed"  
}
```

### Returns

This call returns modified environment object:

```
{  
  "id": "ce373a477f211e187a55404a662f968",  
  "name": "env1-changed",  
  "created": "2010-11-30T03:23:42Z",  
  "updated": "2010-11-30T03:23:44Z",  
  "tenant_id": "0849006f7ce94961b3aab4e46d6f229a",  
  "version": 0  
}
```

## Get Environment Instance Detailed Information

### Call

**Table 4.8. GET /environments/<id> Call**

| Method | URI                | Description   |
|--------|--------------------|---|
| GET    | /environments/<id> | Returns detailed information about Environment including child entities |

**Table 4.9. Error Response Codes**

| Code | Description  |
|------|--|
| 401  | User is not authorized to access this tenant resources |

### Payload

None

### Returns

This call returns environment object with underlying services:

```
{
  "environments": [{
    "id": "0ce373a477f211e187a55404a662f968",
    "name": "dc1",
    "created": "2010-11-30T03:23:42Z",
    "updated": "2010-11-30T03:23:44Z",
    "tenant_id": "0849006f7ce94961b3aab4e46d6f229a",
    "version": 1,
    "status": "deploying",
    "services": [
      "activeDirectories": [{
        "id": "96365940588b479294fe8e6dc073db04",
        "name": "acme.dc",
        "created": "2010-11-30T03:23:42Z",
        "updated": "2010-11-30T03:23:44Z",
        "status": "deploying",
        "units": [{
          "id": "d08887df15b94178b244904b506fe85b",
          "isMaster": true,
          "location": "west-dc"
        }, {
          "id": "dcf0de317e7046bea555539f19b8ea84",
          "isMaster": false,
          "location": "west-dc"
        }
      ]
    ]
  }
]
```

```
}
```

## Remove Environment

### Call

**Table 4.10. DELETE /environments/<id> Call**

| Method | URI                | Description                   |
|--------|--------------------|-------------------------------|
| DELETE | /environments/<id> | Remove specified Environment. |

**Table 4.11. Error Response Codes**

| Code | Description  |
|------|--|
| 401  | User is not authorized to access this tenant resources |

### Payload

None

### Returns

None

## Environment Configuration API

Multiple sessions could be opened for one environment simultaneously, but only one session going to be deployed. First session that starts deploying is going to be deployed; other ones become invalid and could not be deployed at all. User could not open new session for environment that in `deploying` state (that's why we call it "almost lock free" model).

**Table 4.12. Configuration Session Object**

| Attribute      | Type     | Description   |
|----------------|----------|---|
| id             | string   | Session unique ID   |
| environment_id | string   | Environment that going to be modified during this session     |
| created        | datetime | Creation date and time in ISO format                          |
| updated        | datetime | Modification date and time in ISO format                      |
| user_id        | string   | Session owner ID  |
| version        | int      | Environment version for which configuration session is opened |
| state          | string   | Session state. Could be: open, deploying, deployed            |

## Configure Environment / Open session

During this call new working session is created, and session ID should be sent in header (X-Configuration-Session) to all next API calls.

## Call

**Table 4.13. POST /environments/<id>/configure Call**

| Method | URI                          | Description                        |
|--------|------------------------------|------------------------------------|
| POST   | /environments/<id>/configure | Creating new configuration session |

**Table 4.14. Error Response Codes**

| Code | Description  |
|------|--|
| 403  | Could not open session for environment, environment has deploying status |

## Payload

None

## Returns

This call returns created session:

```
{
  "id": "4aecdc2178b9430cbbb8db44fb7ac384",
  "environment_id": "4dc8a2e8986fa8fa5bf24dc8a2e8986fa8",
  "created": "2010-11-30T03:23:42Z",
  "updated": "2010-11-30T03:23:54Z",
  "user_id": "d7b501094caf4daab08469663a9e1a2b",
  "version": 12,
  "state": "open"
}
```

## Deploy changes from Session

### Call

**Table 4.15. POST /environments/<id>/sessions/<sessionId>/deploy Call**

| Method | URI  | Description  |
|--------|--|--|
| POST   | /environments/<id>/sessions/<sessionId>/deploy | Deploying changes made in session with specified <sessionId> |

**Table 4.16. Error Response Codes**

| Code | Description  |
|------|--|
| 403  | Session is invalid                                       |
| 403  | Session is already deployed or deployment is in progress |

## Payload

None

## Returns

None

## Get session information

### Call

**Table 4.17. GET /environments/<id>/sessions/<sessionId> Call**

| Method | URI                                     | Description  |
|--------|---|--|
| GET    | /environments/<id>/sessions/<sessionId> | Getting details about session with specified <sessionId> |

**Table 4.18. Error Response Codes**

| Code | Description                                   |
|------|---|
| 401  | User is not authorized to access this session |
| 403  | Session is invalid                            |

## Payload

None

## Returns

This call returns session information:

```
{
  "id": "4aecdc2178b9430cbbb8db44fb7ac384",
  "environment_id": "4dc8a2e8986fa8fa5bf24dc8a2e8986fa8",
  "created": "2010-11-30T03:23:42Z",
  "updated": "2010-11-30T03:23:54Z",
  "user_id": "d7b501094caf4daab08469663a9e1a2b",
  "version": 0,
  "state": "deploying"
}
```

## Delete Session

### Call

**Table 4.19. DELETE /environments/<id>/sessions/<sessionId> Call**

| Method | URI                                     | Description                               |
|--------|---|---|
| DELETE | /environments/<id>/sessions/<sessionId> | Delete session with specified <sessionId> |

**Table 4.20. Error Response Codes**

| Code | Description  |
|------|--|
| 401  | User is not authorized to access this session          |
| 403  | Session is in deploying state and could not be deleted |

**Payload**

None

**Returns**

None

## Services API

This section describes API calls for managing all types of services.

### Calls and Endpoints

**GET**

Using GET calls to services endpoint user works with list containing all services for specified environment. User can request whole list, specific service, or specific attribute of specific service using tree traversing. To request specific service user should add to endpoint part with service id, e.g.: */environments/<id>/services/<service\_id>*. For selection of specific attribute on service, simply appending part with attribute name will work. For example to request service name, user should use next endpoint: */environments/<id>/services/<service\_id>/name*

**Call****Table 4.21. GET /environments/<id>/services Call**

| Method | URI                         |
|--------|-----------------------------|
| GET    | /environments/<id>/services |

**Table 4.22. Headers**

| Name                    | Type   | Required | Description                       |
|-------------------------|--------|----------|-----------------------------------|
| X-Configuration-Session | string | no       | ID of valid configuration session |

**Payload**

None

**Returns**

Json Object

**PUT**

Using PUT calls user can update or add any attribute on any service.

**Call****Table 4.23. PUT /environments/<id>/services Call**

| Method | URI                         |
|--------|-----------------------------|
| PUT    | /environments/<id>/services |

**Table 4.24. Headers**

| Name                    | Type   | Required | Description                       |
|-------------------------|--------|----------|-----------------------------------|
| X-Configuration-Session | string | yes      | ID of valid configuration session |

**Payload**

Json Object

**Returns**

Json Object

**POST**

POST calls used for adding new elements to lists with objectes.

**Call****Table 4.25. POST /environments/<id>/services Call**

| Method | URI                         |
|--------|-----------------------------|
| POST   | /environments/<id>/services |

**Table 4.26. Headers**

| Name                    | Type   | Required | Description                       |
|-------------------------|--------|----------|-----------------------------------|
| X-Configuration-Session | string | yes      | ID of valid configuration session |

**Payload**

Json Object

**Returns**

Json Object

**DELETE**

User can remove any attribute or list item using DELETE calls.

**Call****Table 4.27. DELETE /environments/<id>/services Call**

| Method | URI                         |
|--------|-----------------------------|
| DELETE | /environments/<id>/services |

**Table 4.28. Headers**

| Name                    | Type   | Required | Description                       |
|-------------------------|--------|----------|-----------------------------------|
| X-Configuration-Session | string | yes      | ID of valid configuration session |

**Payload**

None

**Returns**

None

## Example Calls using Web Server as example

Please use this example for constructing general CRUD calls to services.

### Get a List of existing services

**Call****Table 4.29. GET /environments/<id>/services Call**

| Method | URI                         | Description                       |
|--------|-----------------------------|-----------------------------------|
| GET    | /environments/<id>/services | Get a list of existing WebServers |

**Table 4.30. Headers**

| Name                    | Type   | Required | Description                       |
|-------------------------|--------|----------|-----------------------------------|
| X-Configuration-Session | string | no       | ID of valid configuration session |

**Payload**

None

**Returns**

This call returns list of services:

```
[
  {
    "id": "0ce373a477f211e187a55404a662f968",
    "name": "frontend",
    "type": "webServer",
    "created": "2010-11-30T03:23:42Z",
    "updated": "2010-11-30T03:23:44Z",
    "domain": "ACME",
    "uri": "http://10.0.0.2",
    "units": [{
      "id": "1bf3491c409b4541b6f18ea5988a6437",
      "address": "10.0.0.2",
```



```
        "location": "west-dc"
      }
    ],
  },
  {
    "id": "c697bd2429304820a928d145aa42af59",
    "name": "backend",
    "type": "webServer",
    "created": "2010-11-30T03:23:42Z",
    "updated": "2010-11-30T03:23:44Z",
    "domain": "ACME",
    "uri": "http://10.0.0.3",
    "units": [{
      "id": "eb32f97866d24001baa430cb34e4049f",
      "address": "10.0.0.3",
      "location": "west-dc"
    }]
  }
}
```

## Create Web Server instance

### Call

**Table 4.31. POST /environments/<id>/services Call**

| Method | URI                         | Description           |
|--------|-----------------------------|-----------------------|
| POST   | /environments/<id>/services | Create new Web Server |

**Table 4.32. Headers**

| Name                    | Type   | Required | Description                       |
|-------------------------|--------|----------|-----------------------------------|
| X-Configuration-Session | string | yes      | ID of valid configuration session |

### Payload

```
{
  "name": "frontend",
  "type": "webServer",
  "adminPassword": "password",
  "domain": "acme.dc",
  "units": [{
    "location": "west-dc"
  }]
}
```

### Returns

This call returns created web server:

```
{
  "id": "ce373a477f211e187a55404a662f968",
  "name": "frontend",
  "type": "webServer",
  "created": "2010-11-30T03:23:42Z",
  "updated": "2010-11-30T03:23:44Z",
  "domain": "ACME",
  "units": [{
    "id": "1bf3491c409b4541b6f18ea5988a6437",
    "location": "west-dc"
  }]
}
```

## Remove Web Server

### Call

**Table 4.33. DELETE /environments/<id>/services/<service\_id> Call**

| Method | URI                                      | Description               |
|--------|--|---------------------------|
| DELETE | /environments/<id>/services/<service_id> | Remove specified service. |

**Table 4.34. Headers**

| Name                    | Type   | Required | Description                       |
|-------------------------|--------|----------|-----------------------------------|
| X-Configuration-Session | string | yes      | ID of valid configuration session |

### Payload

None

### Returns

None

## Shared Attributes

This section describes attributes common to all services.

## Request Object Specs

**Table 4.35. Service Object Specs**

| Attribute | Type     | Description                          |
|-----------|----------|--------------------------------------|
| type      | string   | Service Type                         |
| created   | datetime | Creation date and time in ISO format |

| Attribute         | Type     | Description                              |
|-------------------|----------|--|
| updated           | datetime | Modification date and time in ISO format |
| unitNamingPattern | string   | Unit instances naming pattern            |
| availabilityZone  | string   | Availability where service is located    |
| flavor            | string   | Active Directory Unit object             |
| osImage           | string   | Name of image used to power instance     |

## Create Object Specs

**Table 4.36. Service Object Specs**

| Attribute         | Type   | Description                           |
|-------------------|--------|---------------------------------------|
| type              | string | Service Type                          |
| unitNamingPattern | string | Unit instances naming pattern         |
| availabilityZone  | string | Availability where service is located |
| flavor            | string | Active Directory Unit object          |
| osImage           | string | Name of image used to power instance  |

## Active Directory Specs

This section describes objects specs for Active Directory service.

Please, refer to Shared Attributes article for shared/common attributes specification.

## Request Object Specs

**Table 4.37. Active Directory Object**

| Attribute | Type   | Description                  |
|-----------|--------|------------------------------|
| id        | string | Unique ID                    |
| name      | string | Domain name                  |
| domain    | string | Domain name                  |
| units     | object | Active Directory Unit object |

**Table 4.38. Active Directory Unit Object**

| Attribute | Type    | Description   |
|-----------|---------|---|
| id        | string  | Unique ID   |
| isMaster  | boolean | true for primary domain controller, false otherwise |

## Create Object Specs

**Table 4.39. Active Directory Object**

| Attribute | Type   | Required | Description |
|-----------|--------|----------|-------------|
| name      | string | yes      | Domain name |

| Attribute     | Type   | Required | Description                                |
|---------------|--------|----------|--|
| adminPassword | string | yes      | Password from domain administrator account |
| domain        | string | yes      | Domain name                                |
| units         | object | yes      | Active Directory Unit object               |

**Table 4.40. Active Directory Unit Object**

| Attribute        | Type    | Required | Description   |
|------------------|---------|----------|---|
| isMaster         | boolean | yes      | true for primary domain controller, false otherwise |
| recoveryPassword | string  | yes      | Recovery password                                   |

## Web Server Specs

This section describes API calls for managing Windows web-server software – IIS.

Please, refer to Shared Attributes article for shared/common attributes specification.

## Request Object Specs

**Table 4.41. Web Server Object**

| Attribute | Type   | Description   |
|-----------|--------|---|
| id        | string | Unique ID   |
| name      | string | User-friendly name  |
| uri       | string | URI of the Service  |
| domain    | string | Domain name. This attribute may be empty/null/omitted if machine is not a domain member |
| units     | object | Web Server Unit object  |

**Table 4.42. Web Server Unit Object**

| Attribute | Type   | Description |
|-----------|--------|-------------|
| id        | string | Unique ID   |

## Create Object Specs

**Table 4.43. Web Server Object**

| Attribute | Type   | Required | Description            |
|-----------|--------|----------|------------------------|
| name      | string | yes      | User-friendly name     |
| domain    | string | no       | Domain name            |
| units     | object | yes      | Web Server Unit object |

**Table 4.44. Web Server Unit Object**

| Attribute | Type | Required | Description |
|-----------|------|----------|-------------|
| -         | -    | -        | -           |

## ASP.NET Application Specs

This section describes API calls for managing ASP.NET Applications

Please, refer to Shared Attributes article for shared/common attributes specification.

### Request Object Specs

**Table 4.45. ASP.NET Application Object**

| Attribute  | Type   | Description   |
|------------|--------|---|
| id         | string | Unique ID   |
| name       | string | User-friendly name  |
| repository | string | URL of git repository containing the application source files                           |
| uri        | string | URI of the Service  |
| domain     | string | Domain name. This attribute may be empty/null/omitted if machine is not a domain member |
| units      | object | ASP.NET Application Unit object   |

**Table 4.46. ASP.NET Application Unit Object**

| Attribute | Type   | Description |
|-----------|--------|-------------|
| id        | string | Unique ID   |

### Create Object Specs

**Table 4.47. ASP.NET Application Object**

| Attribute  | Type   | Required | Description   |
|------------|--------|----------|---|
| name       | string | yes      | User-friendly name  |
| repository | string | yes      | URL of git repository containing the application source files |
| domain     | string | no       | Domain name   |
| units      | object | yes      | ASP.NET Application Unit object                               |

**Table 4.48. ASP.NET Application Unit Object**

| Attribute | Type | Required | Description |
|-----------|------|----------|-------------|
| -         | -    | -        | -           |

## Web Server Farm Specs

This section describes API calls for managing Web Server (IIS) Web Farm services

Please, refer to Shared Attributes article for shared/common attributes specification.

## Request Object Specs

**Table 4.49. Web Server Farm Object**

| Attribute        | Type    | Description   |
|------------------|---------|---|
| id               | string  | Unique ID   |
| name             | string  | User-friendly name  |
| uri              | string  | URI of the Service  |
| loadBalancerPort | integer | Port number of the Farm   |
| domain           | string  | Domain name. This attribute may be empty/null/omitted if machine is not a domain member |
| units            | object  | Web Server Farm Unit object   |

**Table 4.50. Web Server Farm Unit Object**

| Attribute | Type   | Description |
|-----------|--------|-------------|
| id        | string | Unique ID   |

## Create Object Specs

**Table 4.51. Web Server Farm Object**

| Attribute        | Type    | Required | Description                 |
|------------------|---------|----------|-----------------------------|
| name             | string  | yes      | User-friendly name          |
| loadBalancerPort | integer | yes      | Port number for the Farm    |
| domain           | string  | no       | Domain name                 |
| units            | object  | yes      | Web Server Farm Unit object |

**Table 4.52. Web Server Farm Unit Object**

| Attribute | Type | Required | Description |
|-----------|------|----------|-------------|
| -         | -    | -        | -           |

## ASP.NET Application Farm Specs

This section describes API calls for managing ASP.NET Web Farm Application Services

Please, refer to Shared Attributes article for shared/common attributes specification.

## Request Object Specs

**Table 4.53. ASP.NET Application Farm Object**

| Attribute | Type   | Description        |
|-----------|--------|--------------------|
| id        | string | Unique ID          |
| name      | string | User-friendly name |

| Attribute        | Type    | Description   |
|------------------|---------|---|
| uri              | string  | URI of the Service  |
| repository       | string  | URL of git repository containing the application source files                           |
| loadBalancerPort | integer | Port number of the Farm   |
| domain           | string  | Domain name. This attribute may be empty/null/omitted if machine is not a domain member |
| units            | object  | ASP.NET Application Farm Unit object  |

**Table 4.54. ASP.NET Application Farm Unit Object**

| Attribute | Type   | Description |
|-----------|--------|-------------|
| id        | string | Unique ID   |

## Create Object Specs

**Table 4.55. ASP.NET Application Farm Object**

| Attribute        | Type    | Required | Description   |
|------------------|---------|----------|---|
| name             | string  | yes      | User-friendly name  |
| repository       | string  | yes      | URL of git repository containing the application source files |
| loadBalancerPort | integer | yes      | Port number for the Farm                                      |
| domain           | string  | no       | Domain name   |
| units            | object  | yes      | ASP.NET Application Farm Unit object                          |

**Table 4.56. ASP.NET Application Farm Unit Object**

| Attribute | Type | Required | Description |
|-----------|------|----------|-------------|
| -         | -    | -        | -           |

## MS SQL Server Specs

This section describes API calls for managing MS SQL Server Service.

Please, refer to Shared Attributes article for shared/common attributes specification.

## Request Object Specs

**Table 4.57. MS SQL Server Object**

| Attribute     | Type   | Description                   |
|---------------|--------|-------------------------------|
| id            | string | Unique ID                     |
| name          | string | User-friendly name            |
| mixedModeAuth | bool   | Use LDAP to access SQL Server |
| saPassword    | string | SQL Server admin password     |

| Attribute     | Type   | Description   |
|---------------|--------|---|
| domain        | string | Domain name. This attribute may be empty/null/omitted if machine is not a domain member |
| adminPassword | string | Domain password   |
| units         | object | SQL Server Unit object  |

**Table 4.58. SQL Server Unit object**

| Attribute | Type   | Description |
|-----------|--------|-------------|
| id        | string | Unique ID   |

## Create Object Specs

**Table 4.59. SQL Server Unit object**

| Attribute     | Type   | Required | Description                   |
|---------------|--------|----------|-------------------------------|
| name          | string | yes      | User-friendly name            |
| mixedModeAuth | bool   | yes      | Use LDAP to access SQL Server |
| saPassword    | string | no       | SQL Server admin password     |
| domain        | string | no       | Domain name                   |
| adminPassword | string | no       | Domain admin password         |
| units         | object | yes      | SQL Server Unit object        |

**Table 4.60. MS SQL Server Unit Object**

| Attribute | Type | Required | Description |
|-----------|------|----------|-------------|
| -         | -    | -        | -           |



---

# Chapter 5. Workflows XML DSL

## XML DSL

Workflows are written using XML markup language. This XML has no fixed structure but instead XML tags are translated into Python function calls. Thus such XML can be considered as a simplified programming language.

Consider the following XML fragment:

```
<func arg1="value1" arg2="value2" />
```

This is an equivalent to `func(arg1='value1', arg2='value2')` in Python. Tag name is mapped to a function name, one that Murano Conductor knows. Each attribute corresponds to function argument.

XML functions may also have a body. It is evaluated to "body" argument. Thus

```
<func arg1="value1" arg2="value2">some text</func>
```

is translated to `func(arg1='value1', arg2='value2', body='some text')`

In example above all function arguments were constant values. But they also can be evaluated:

```
<foo arg="value">
  <bar/>
</foo>
```

turns to

```
body_value = bar()
foo(arg='value', body=body_value)
```

Tag body may consist of several function invocations. In such case all values would be concatenated. For example if

```
def foo(**kwargs):
    return "foo"

def bar(**kwargs):
    return "bar"
```

then `<func><foo/> - <bar/></func>` will result in `func(body = 'foo - bar')`

Function parameters can also be function calls using `<parameter>` tag

```
<foo arg="value"/>
```

can be rewritten as

```
<foo>
  <parameter name="arg">value</parameter>
</foo>
```

while that later form is more verbose it allows having dynamically evaluated values as function arguments:

```
<foo>
  <parameter name="arg"><bar/></parameter>
</foo>
```

Functions may also have other custom tags in their body that interpreted in a way different from plain function invocation.

## DSL functions

There are a number of functions in Murano Conductor that can be used in XML DSL:

- `<true/>` - returns True
- `<false/>` - False
- `<null/>` - None
- `<text><foo/></text>` - converts body to string (`str(foo())`)
- list - form list (array) object -

```
<list>
  <item>item1</item>
  <item>item2</item>
  <item><true/></item>
</list>
```

equals to `["item1", "item2", True]`

- map - form dictionary (map) object

```
<map>
  <item name="key1">value1</item>
  <item name="key2">value2</item>
</map>
```

equals to `{ "key1": "value1", "key2": "value2" }` For both list and map functions names of item nodes ("item" in examples above) is irrelevant and can be changed to better match structure usage. For example

```
<map>
  <set name="key"><null/></set>
```

```
</map>
```

Structures can be nested:

```
<list>
  <item>
    <map>
      <item name="name 1">value 1</item>
      <item name="name 2">value 2</item>
    </map>
  </item>
  <item>
    <map>
      <item name="name 1">value 3</item>
      <item name="name 2">value 4</item>
    </map>
  </item>
</list>
```

equals to

```
[
  { 'name 1': 'value 1', 'name 2': 'value 2' },
  { 'name 1': 'value 3', 'name 2': 'value 4' }
]
```

## Workflows

Workflows are XML DSL scripts that describe the steps that conductor need to perform in order to deploy specified environment. All workflow constructs are just ordinary DSL functions similar to those described above.

Usually workflows extract some data from input environment definition (Object Model) and then invoke one of the actions with these data as a input arguments.

Actions are:

- Heat commands that update or delete Heat Stack: <update-cf-stack>, <delete-cf-stack>
- Send command to Murano Agent: <send-command>
- Report state to API: <report>

Workflow logic can be described in 6 steps:

1. Choose a node (set of nodes) to update. If none of the nodes can be updated we are done.
2. According to the current state of node (that is a part of input Object Model) choose appropriate command to execute (update Heat stack or issue PowerShell command)
3. Select appropriate information from Object Model and substitute it into chosen template
4. Execute command

5. Update Object Model according to command execution result

6. Go to step 1

## Accessing Object Model

Object Model is a definition of environment that Murano Conductor was asked to deploy.

Lets take the following Object Model that describes Active Directory service with single controller for our further examples:

```
{
  "name": "MyDataCenter",
  "id": "adc6d143f9584d10808c7ef4d07e4802",
  "services": [ {
    "name": "TestAD",
    "type": "activeDirectory",
    "osImage": { "name": "ws-2012-std", "type": "ws-2012-std" },
    "availabilityZone": "nova",
    "flavor": "ml.medium",
    "id": "9571747991184642B95F430A014616F9",
    "domain": "acme.loc",
    "adminPassword": "SuperP@ssw0rd",
    "units": [ {
      "id": "273c9183b6e74c9c9db7fdd532c5eb25",
      "name": "dc01",
      "isMaster": true,
      "recoveryPassword": "SuperP@ssw0rd!2"
    } ]
  } ]
}
```

There are several functions to select values from Object Model and function to modify it so that the Workflow can persist the changes made during deployment.

All reads and writes to Object Model are relative to some cursor position which is managed by workflow rule. Lets call it current cursor position.

The simplest method of accessing Object Model is a select function. Suppose current cursor position points to a single unit of our single service. Then `<select path="name"/>` is "dc01" and `<select path="isMaster"/>` is True.

Path parameter may start with colon to indicate navigation to one level up or slash to go to Model root:

```
<select path=":"/>
```

is

```
[
  {
    "id": "273c9183b6e74c9c9db7fdd532c5eb25",
    "name": "dc01",
    "isMaster": true,
```

```
        "recoveryPassword": "SuperP@ssw0rd!2"
    }
]
```

`<select path="::domain">` is "acme.loc" and `<select path="/name" />` is "MyDataCenter"

The path also supports drill-down notation: `<select path="::osImage.name">` is "ws-2012-std" `<select path="::units.0.name">` equals to `<select path="/services.0.units.0.name">` that is "dc01"

If the path does not exist then result of a select would be None: `<select path="::noSuchProperty"/>` = None

`<select/>` without path results in object pointed by current cursor position.

It also possible to select multiple values using JSONPath selection language (<http://goessner.net/articles/JsonPath/>):

```
<select-all path="/$.services[?(@.type == 'activeDirectory')].units[*]"/>
```

- returns array of all units of all services of type 'activeDirectory'

JSONPath expressions by default select data relative to current cursor position and has no way for navigating up the Model tree. But Conductor has several improvements to JSONPath language:

- JSONPath expression may start with one or more colon characters to perform query relative to current cursor parent (grandparent etc.)
- JSONPath expression may also start with slash as in example above to query the whole Model from the tree root
- Expressions may reference nonexistent Model attributes in the same way as `<select/>` function does. Such attributes considered to have None values

`<select-single path="JSONPath expression"/>` is similar to `<select-all/>` ,but returns only the first value matched by a JSONPath query or None.

Object Model can also be modified using `<set/>` function. `<set/>` is very similar to `<select/>` with the only difference in that `<select/>` writes values while `<set/>` reads them: `<set path="name">dc02</set>` changes unit name (eg. the object pointed by current cursor position) to "dc02". `<set>` can also introduce new attributes, even nested ones: `<set path="newProperty">value</set>` creates new attribute "newProperty" with given value, `<set path="state.property">value</set>` makes current unit have property "state": `{ "property": "value" }`

In this case "state" is just a convention - a reserved property that would never be used for service our units input properties. There is a also a special property called "temp". The contents of this property (on all services and units and environment itself) if wiped after each deployment.

## Function context

Function context is an equivalent to Python stack frame. This allows functions to have local variables that are visible only to the function XML body.

Function context may be considered as a key-value storage. If a key does not exist in current context then parent context is searched for the key.

Data may be published to function context using ordinary `<set/>` function by using path in a form of "#key": `<set path="#myKey">value</set>` sets "myKey" function context value to "value". This value may be later accessed in inner block using select: `<select path="#myKey"/>`

Values in function context may be not just scalars but a whole objects: `<set path="#myKey"><select/></set>` sets myKey local variable to an object pointed by current cursor position. Because this is a reference to a model part rather than its copy if one edits its content the changes will be also present in original Model. To edit content of local variable (eg. value in function context) "target" argument of `<set/>` function is used: `<set path="property" target="myKey">value</set>`. Because target always denotes a key in function context there is no need for # sign.

Function context values may also be the source for the `<select/>` and other selection functions: `<select path="property" source="myKey"/>`

## Workflow rules

Workflow consists of rules. Rule is a function with the following parameters:

- **match** - JSONPath expression to be executed relative to current cursor position
- **desc** - optional human-readable free-form rule description
- **id** - optional rule ID (auto-generated if not provided)

for example

```
<rule match="$.services[?(@.type == 'msSqlClusterServer' and @.domain)].units[
  <set path="domain">
    <select path="::domain"/>
  </set>
</rule>
```

The logic of rule is simple:

1. Execute given JSONPath expression
2. For each of matched objects make current cursor position point to it and then execute function XML body
3. If JSONPath hasn't matched any object execute `<empty>...</empty>` block if present

Rules can be nested. In this case nested rule's JSONPath expression would be executed relative to parent's rule current cursor position. For outermost rules current cursor position is the Object Model itself.

Rules are grouped into workflows:

```
<workflow>
  <rule id="rule1" match="...">
    ...
  </rule>

  <rule id="rule2" match="...">
```

```
...
  </rule>
</workflow>
```

Workflow which is happen to be a XML DSL function and also a root element of workflow XML files. Workflow function executes rules one by one. If one of the rules has modified some part of Object Model then all rules executed once again. This repeats until there are no more actions that can be performed by workflow. At this point all pending actions (e.g. all the invocations of update-cf-stack, send-command etc.) got executed and the workflow loop is repeated. When there no more actions that can be performed by workflow and also no pending commands then we are done and Object Model with all modifications made by workflows (except for "temp" attributes) returned back to Murano API service.

## Workflow actions

There are several actions (functions) that can be invoked by rules to do the actual deployment. When action is invoked it is not executed immediately but enqueued and executed later when there are no more actions that can be performed by workflow.

The following actions are available for workflow rules:

- **update-cf-stack** - updates Heat stack by substituting values into Heat template and merging it into Heat stack definition. It has the following parameters:
  - **template** - Heat template filename without extension
  - **error** - function context variable to be populated with command error info in case of command failure
  - **mappings** - dictionary to be used for values substitution into template. All values in JSON template file in the form of "\$myKey" are replaced with a value under key "myKey" in this parameter
  - **arguments** - optional dictionary of Heat template arguments ("Parameters" section of Heat templates)

update-cf-stack function also searches for 2 predefined tags in its body:

- **<success>** - a block to be executed after successful stack update
- **<failure>** - block that would be executed in case of function failure

Templates are located in data/cf directory

- **send-command** - sends an execution plan to Murano Agent on specific VM. It has the following parameters:
  - **template** - execution plan template filename without extension
  - **error** - function context variable to be populated with command error info in case of command failure
  - **service** - ID of a service that target units belongs to
  - **unit** - ID of target unit (VM)
  - **mappings** - dictionary to be used for values substitution into template. All values in JSON template file in the form of "\$myKey" are replaced with a value under key "myKey" in this parameter

send-command function also searches for 2 predefined tags in its body:

- **<success>** - a block to be executed after successful stack update

- **<failure>** - block that would be executed in case of function failure

Templates are located in data/agent directory

- **report** - sends status report back to REST API service. It has the following parameters:
  - **entity** - entity type ("unit", "service", "environment")
  - **level** - log level
  - **id** - ID of unit/service/environment
  - **text** - reported status text

## Workflow control

There are several functions that affect workflow execution. `<stop/>` stops execution of workflows causing Conductor returning current result back to REST API service and stop deployment activities.

`<mute/>` excludes current object from being processed by the current rule during next workflow rounds. Mutes table tracks items using pairs of rule id (that is rule function argument, auto-generated if not provided) and object ID ("id" attribute of current object. If object has no such attribute it cannot be muted). It is possible to explicitly specify rule id via "rule" argument and object id via "id" argument. Missing parameters are auto-guessed from current context - current rule ID and current object ID.

Note that objects are automatically muted for every object that matched by the rule but the mutes get reset after each workflow loop round. `<mute/>` places a permanent mute on the object

Mutes can be removed by `<unmute/>` function which has exactly the same arguments as `<mute/>` command but is only usable with explicit specification of rule and id because otherwise if the current object is already muted the rule body would not be executed for the object and thus `<unmute/>` would not be executed either.

When referencing id of a nested rule IDs of all rule chain must be joined by dot. E.g.

```
<rule id="id1">
  <rule id="id2">
    <mute rule="id1.id2"/>
  </rule>
</rule>
```

## Execution Plans

Execution plans are a description of what should be executed on Murano Agent at VM to perform some deployment step.

Execution plans is a JSON document that has 3 keys:

- **Commands** array - list of functions to be executed. Each function has a "Name" property and "Arguments" dictionary which maps function argument names to parameter values.
- **Scripts** - list of PowerShell script file names to be included into execution plans. The scripts contain function implementations that can be referenced in Command array. Script files need to be located in data/templates/agent/scripts directory.



- **RebootOnCompletion** - 0 = do not reboot, 1 = reboot only upon successful plan execution, 2 = reboot always. Murano Agent send execution result after system reboot.

As for other Murano JSON templates keys and values starting with \$ sign will be replaced with a values provided in Workflow.

Example of execution plan:

```
{
  "Scripts":
  [
    "ImportCoreFunctions.ps1",
    "DeployWebApp.ps1"
  ],
  "Commands":
  [
    {
      "Name": "Deploy-WebAppFromGit",
      "Arguments":
      {
        "URL": "$repository"
      }
    }
  ],
  "RebootOnCompletion": 0
}
```

Result of execution plan has the following format:

```
{
  "IsException": false,
  "Result":
  [
    {
      "IsException": false,
      "Result": [ "result value" ]
    }
  ]
}
```

There are result entry for each source command. Each result can have many values - all the outputs of PowerShell function. If IsException is set to true then Result is an array in form of ["Exception type", "Error message"]. IsException at command level means exception during function invocation while root IsException means that execution plan cannot be even started (corrupted data, PowerShell engine failure etc.)

---

# Chapter 6. Known Issues

Actual bug state can be found in Murano launchpad page. [<https://bugs.launchpad.net/murano>]

- Due to current Heat limitation services that involve load-balancer creation (farms) can be deployed only by tenant administrators.
- When Heat creates different clients for Nova, Cinder and others it doesn't pass SSL-related options to clients' constructor. If Nova is configured to have SSL endpoints and self-signed certificates Heat will fail to create instances because there is no way to disable server certificate validation as there is no "insecure" flag passed etc.
- Murano-Conductor doesn't work with python-heatclient>0.2.1.
- Farm services can't be deployed without KeyPair. If KeyPair is not set load balancer won't be created and these messages will show up in logs:

```
2013-08-06 09:10:07 - Unable to deploy instance ipkrmhk0vzq4b6 (asp-farm_instance)
2013-08-06 09:10:07 - Unable to create a Server Farm load balancer on unit ipkrmhk0vzq4b6
```

And deploy will hang up.

---

# Chapter 7. How To Participate

If you would like to ask some questions or make proposals, feel free to reach us on #murano irc channel at FreeNode. Typically somebody from our team will be online at irc from 6:00 to 20:00 UTC. You can also contact Murano community directly by [openstack-dev@lists.openstack.org](mailto:openstack-dev@lists.openstack.org) [<mailto:openstack-dev@lists.openstack.org>]

We're going to hold public weekly meetings on Mondays at 15:00 UTC on #openstack-meeting-alt irc channel.

If you want to contribute either to docs or to code, simply send us change request via [review.openstack.org](http://review.openstack.org) [<http://review.openstack.org>] (gerrit). You can file bugs and register blueprints at Murano launchpad page [<https://launchpad.net/murano>].