

# 1.1 package.json - Server

#nodejs #backend

## Scripts

```
"scripts": {
  "watch": "tsc -w",
  "dev": "nodemon dist/index.js",
  "start": "node dist/index.js",
  "start2": "ts-node src/index.ts",
  "dev2": "nodemon --exec ts-node src/index.ts",
  "create:migration": "mikro-orm migration:create"
},
```

- **tsc -w** - re-compiles .ts to .js on change
- **nodemon** - re-executes the .js code on change
- ts-node is slower than node, so we're using node to run the compiled **dist/index.js** file instead of using ts-node to run the index.ts file

## Dependencies

- ⚠ When installing a package **make sure to come back here and look up the version and install the version listed here** or it might be *"too new"* and thus different

<u>Until the end of MikroORM section</u>	<u>At the end of the project</u>
<pre>"dependencies": {   "@mikro-orm/cli": "4.5",   "@mikro-orm/core": "4.5.10",   "@mikro-orm/migrations": "4.5.10",   "@mikro-orm/postgresql": "4.5",   "apollo-server-express": "2.16.1",   "argon2": "^0.40.3",   "connect-redis": "5.0.0",   "cors": "2.8.5",</pre>	<pre>"dependencies": {   "apollo-server-express": "2.16.1",   "argon2": "^0.40.3",   "connect-redis": "5.0.0",   "cors": "2.8.5",   "dataloader": "2.0.0",   "express": "^4.19.2",   "express-session": "1.17.1",   "graphql": "15.3.0",   "ioredis": "4.17.3",   "nodemailer": "6.4.11",</pre>

```
"express": "^4.19.2",
"express-session": "1.17.1",
"graphql": "15.3.0",
"ioredis": "4.17.3",
"nodemailer": "6.4.11",
"pg": "^8.12.0",
"reflect-metadata": "0.1.13",
"type-graphql": "1.0.0",
"uuid": "8.3.0"
},
```

```
"pg": "^8.12.0",
"reflect-metadata": "0.1.13",
"type-graphql": "1.0.0",
"typeorm": "0.2.25",
"uuid": "8.3.0"
},
```

## DevDependencies

### Until the end of MikroORM section

```
"devDependencies": {
  "@types/connect-redis":
    "0.0.13",
  "@types/cors": "2.8.7",
  "@types/express": "^4",
  "@types/express-session":
    "^1",
  "@types/ioredis": "4.17.3",
  "@types/node": "^20.14.2",
  "@types/nodemailer": "^6",
  "@types/pg": "^8",
  "@types/uuid": "8.3.1",
  "nodemon": "^3.1.3",
  "ts-node": "^10.9.2",
  "typescript": "^5.4.5"
},
```

### At the end of the project

```
"devDependencies": {
  "@types/connect-redis":
    "0.0.13",
  "@types/cors": "2.8.7",
  "@types/express": "^4",
  "@types/express-session":
    "^1",
  "@types/ioredis": "4.17.3",
  "@types/node": "^20.14.2",
  "@types/nodemailer": "^6",
  "@types/pg": "^8",
  "@types/uuid": "8.3.1",
  "nodemon": "^3.1.3",
  "ts-node": "^10.9.2",
  "typescript": "^5.4.5"
},
```

