

81. Page - edit

[#reactjs](#) [#nextjs](#) [#chakraui](#) [#frontend](#) [#page](#) [#error](#) [#server](#) [#backend](#) [#urql](#)

Implement edit Page

- We need a **variable** (postId) in the **URL** of this page, so that the **post** with that **id** is shown to **edit**
i.e. `localhost:3000/edit/123`
- In **NextJS** the convention for such pages is to create a folder with the page name **post** and place the file inside this folder
- The file name should be `[variableName].tsx` - in our case it will be `[id].tsx`
- **Note that** this page is almost 100% the same as the **post** page. We could create a **component** that *could* be used in both pages to reduce **code repetition** (but we won't do it here)

`/pages/post/edit/[id].tsx`

```
import { withUrqlClient } from "next-urql";
import { createUrqlClient } from "../../utils/createUrqlClient";
import { Box, Button } from "@chakra-ui/react";
import { Formik, Form } from "formik";
import { InputField } from "../../components/InputField";
import { Layout } from "../../components/Layout";
import { TextAreaField } from "../../components/TextAreaField";
import { useGetPostFromUrl } from "../../utils/useGetPostFromUrl";
import { useUpdatePostMutation } from "../../generated/graphql";
import { useRouter } from "next/router";

const EditPost = ({}) => {
  const router = useRouter();
  const [{ data, fetching, error, postId }] = useGetPostFromUrl();
  const [, updatePost] = useUpdatePostMutation();

  if (fetching) {
    return (
      <Layout>
        <Box>Loading...</Box>
      </Layout>
    );
  }
}
```

```

if (error) {
  return <div>error</div>;
}

if (!data?.post) {
  return (
    <Layout>
      <Box>Could not find post...</Box>
    </Layout>
  );
}

return (
  <Layout variant="small">
    <Formik
      initialValues={{ title: data.post.title, text: data.post.text }}
      onSubmit={async (values) => {
        await updatePost({ id: postId, ...values });
        router.back(); // takes back to the page that routed here
      }}
    >
      {{{ isSubmitting }} => (
        <Form>
          <InputField
            name="title"
            label="Title"
            placeholder="Title of the post"
          />
          <Box mt={4}>
            <TextAreaField
              name="text"
              label="Body"
              placeholder="Enter your text"
            />
          </Box>
          <Button type="submit" isLoading={isSubmitting} mt={4} color="teal">
            Update Post
          </Button>
        </Form>
      )}
    )}

```

```


    </Formik>
  </Layout>
);
};

export default withUrqlClient(createUrqlClient, { ssr: true })(EditPost);

```

Fix Server Error

- A **server error** occurs if we refresh the **edit** page:



- We can fix this simply by using an optional chain as follows:

/utils/createUrqlClient.ts

```

if (isServer()) {
  // we don't have the ctx object on the browser
  cookie = ctx?.req?.headers?.cookie;
}

```