

Contents

1 GPIO 2

2 USART 3

1 General-purpose I/Os (GPIO)

Each GPIO port has four 32-bit configuration registers. Each GPIO port has four 32-bit configuration registers. Each GPIO port has four 32-bit configuration registers.

1.1 GPIO registers

The GPIO registers can be accessed by byte, half-word or word.

1.1.1 GPIO port mode register (GPIOx_MODER)

Address offset: 0x00

Reset value: 0xA800 0000 for port A

31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16

rw rw rw rw rw rw rw rw rw rw rw rw rw rw rw rw

Bits 2y:2y+1 MODERy[1:0]: Port x configuration bits. 00: Input, 01: General purpose output mode, 10: Alternate function mode, 11: Analog mode.

2 Universal synchronous asynchronous receiver transmitter (USART)

The USART offers a flexible means of full-duplex data exchange with external equipment. The USART offers a flexible means of full-duplex data exchange with external equipment. The USART offers a flexible means of full-duplex data exchange with external equipment.

2.1 Status register (USART_SR)

Address offset: 0x00

Bit 7 TXE: Transmit data register empty. Bit 5 RXNE: Read data register not empty. Bit 7 TXE: Transmit data register empty. Bit 5 RXNE: Read data register not empty.

Revision history

Rev 1: initial release. Changed OSPEEDR bits description. Rev 1: initial release. Changed OSPEEDR bits description. Rev 1: initial release. Changed OSPEEDR bits description.