

Contents

1 Features 2

2 Hardware layout and configuration 2

2.1 Power supply 3

2.2 LEDs 4

2.3 Push-buttons 4

1 Features

The demo kit features an ARM Cortex-M4 microcontroller with 1 Mbyte of Flash memory and 192 Kbytes of RAM in an LQFP100 package. The demo kit features an ARM Cortex-M4 microcontroller with 1 Mbyte of Flash memory and 192 Kbytes of RAM in an LQFP100 package. The demo kit features an ARM Cortex-M4 microcontroller with 1 Mbyte of Flash memory and 192 Kbytes of RAM in an LQFP100 package.

2 Hardware layout and configuration

The kit is designed around the microcontroller. The hardware block diagram illustrates the connection between the MCU and peripherals such as the debugger, LEDs and push-buttons. The kit is designed around the microcontroller. The hardware block diagram illustrates the connection between the MCU and peripherals such as the debugger, LEDs and push-buttons. The kit is designed around the microcontroller. The hardware block diagram illustrates the connection between the MCU and peripherals such as the debugger, LEDs and push-buttons. The kit is designed around the microcontroller. The hardware block diagram illustrates the connection between the MCU and peripherals such as the debugger, LEDs and push-buttons.

2.1 Power supply

The power supply is provided either by the host PC through the USB cable, or by an external 5 V power supply. The on-board regulator generates 3 V for the microcontroller. The power supply is provided either by the host PC through the USB cable, or by an external 5 V power supply. The on-board regulator generates 3 V for the microcontroller. The power supply is provided either by the host PC through the USB cable, or by an external 5 V power supply. The on-board regulator generates 3 V for the microcontroller. The power supply is provided either by the host PC through the USB cable, or by an external 5 V power supply. The on-board regulator generates 3 V for the microcontroller. The power supply is provided either by the host PC through the USB cable, or by an external 5 V power supply. The on-board regulator generates 3 V for the microcontroller.

3 V power supply rail is available on the extension header.

2.2 LEDs

LD3 orange, LD4 green, LD5 red and LD6 blue are user LEDs connected to the I/O pins PD13, PD12, PD14 and PD15 respectively. LD3 orange, LD4 green, LD5 red and LD6 blue are user LEDs connected to the I/O pins PD13, PD12, PD14 and PD15 respectively. LD3 orange, LD4 green, LD5 red and LD6 blue are user LEDs connected to the I/O pins PD13, PD12, PD14 and PD15 respectively. LD3 orange, LD4 green, LD5 red and LD6 blue are user LEDs connected to the I/O pins PD13, PD12, PD14 and PD15 respectively.

2.3 Push-buttons

B1 USER: the user push-button is connected to the I/O PA0. It can also be used as a wake-up button. B2 RESET: the push-button is connected to NRST and is used to reset the microcontroller. B1 USER: the user push-button is connected to the I/O PA0. It can also be used as a wake-up button. B2 RESET: the push-button is connected to NRST and is used to reset the microcontroller. B1 USER: the user push-button is connected to the I/O PA0. It can also be used as a wake-up button. B2 RESET: the push-button is connected to NRST and is used to reset the microcontroller.

2.4 USB OTG supported

The microcontroller supports USB OTG full-speed communication via a micro-AB connector. A green LED indicates when VBUS is present. The microcontroller supports USB OTG full-speed communication via a micro-AB connector. A green LED indicates when VBUS is present. The microcontroller supports USB OTG full-speed communication via a micro-AB connector. A green LED indicates when VBUS is present. The microcontroller supports USB OTG full-speed communication via a micro-AB connector. A green LED indicates when VBUS is present. The microcontroller supports USB OTG full-speed communication via a micro-AB connector. A green LED indicates when VBUS is present. The microcontroller supports USB OTG full-speed communication via a micro-AB connector. A green LED indicates when VBUS is present. The microcontroller supports USB OTG full-speed communication via a micro-AB connector. A green LED indicates when VBUS is present. The microcontroller supports USB OTG full-speed communication via a micro-AB connector. A green LED indicates when VBUS is present.

3 Revision history

Initial release of the document.