RG-ANT13-360 Antenna

5 GHz 13 dBi 360° Omnidirectional Outdoor Base Station Antenna

Product Overview: The Ruijie Reyee RG-ANT13-360 is a high-gain, dual-polarized omnidirectional antenna engineered specifically for 5 GHz Point-to-Multipoint (PTMP) wireless networks. Designed for seamless direct integration with the RG-AirMetro550G-B base station, it delivers reliable 360° broad horizontal coverage up to 2 km across outdoor WISP, CCTV, and campus environments.

13 dBi
ANTENNA GAIN

360° / 7°
HORIZONTAL / VERTICAL BEAMWIDTH


2.0 km
MAX PTMP TRANSMISSION RANGE

IP55
WEATHERPROOF RATING


KEY ARCHITECTURAL FEATURES

- **Full 360° Coverage:** Eliminates blind spots by projecting uniform omnidirectional coverage across regional towns, industrial parks, and outdoor facilities.
- **Dual-Stream 2x2 MIMO:** Integrated horizontal and vertical polarization design with 25 dB minimum cross-polarization isolation for optimized link throughput.
- **AirMetro Integration:** Features an integrated slide-in mounting bracket designed for direct, seamless attachment to the RG-AirMetro550G-B wireless bridge.
- **Extreme Environmental Survival:** Rated IP55 with wind survivability up to 220 km/h (137 mph) and operating temperatures from -40°C to +80°C.

ANTENNA PATTERN VISUAL REPRESENTATION



Azimuth / Horizontal (360°)



Elevation / Vertical (7° Beamwidth)

DETAILED TECHNICAL SPECIFICATIONS

Model Name	RG-ANT13-360
Frequency Range	5.150 GHz to 5.850 GHz
Antenna Gain	13 dBi
Polarization	Dual-Polarized (Horizontal and Vertical)
Horizontal Beamwidth	360°
Vertical Beamwidth	7° (3 dB)
Electrical Downtilt	0°
Max. VSWR	2.0 : 1
Cross-Pol Isolation	25 dB Minimum
Connector Type	2 x RP-SMA Female (Includes two 12 cm RF jumpers)
Dimensions (W x D x H)	769 mm x 120 mm x 81.6 mm (30.3 x 4.7 x 3.2 in)
Weight	2.35 kg (5.18 lbs) excluding bracket
Mounting System	Pole-Mount (Compatible with Ø35 mm to Ø60 mm poles)
Wind Survivability	220.32 km/h (137 mph)
Wind Loading	133 N @ 220.32 km/h (30 lbf @ 137 mph)
Operating Temperature	-40°C to +80°C (-40°F to +176°F)
Operating Humidity	5% to 95% RH (Non-condensing)
IP Rating & Standards	IP55 Weatherproof, CE, GB 2423.41-1994

DEPLOYMENT & TOPOLOGY GUIDELINES

The RG-ANT13-360 is optimized for hub-and-spoke PTMP topologies, serving up to 32 subscriber CPE links per AirMetro base station.



Package Contents: Includes 1× RG-ANT13-360 Antenna Unit, Integrated Mounting Bracket Assembly, Pole-Mounting Hardware, 2× RF Coaxial Jumper Cables (12 cm), Protective Connector Cover, and Installation Guide.