

Commodity Transportation Data Sheet

1 – PRODUCT AND COMPANY IDENTIFICATION

1.1. Product name, trade name and synonyms	Marine Fuels, Marine Fuel Oil, Marine Gas Oil, Marine Diesel Oil Residual Fuel Oil, HFO, MDO, MGO, Bunker oil, Marine bunker oil.
1.2. Relevant identified uses of the substance	Fuel for use in marine diesel engines, boilers, furnaces and other combustion equipment.
1.3. Detail of the supplier & testing company	Please refer to the supplier stated on the safety data sheet. This product is to be tested at an Inspectorate laboratory. Company name: Inspectorate International Limited, 2 Perry Road, Witham, Essex, United Kingdom (Registration Number 638315).
1.4. Emergency telephone number	+1 703-527-3887

2 – HAZARDS IDENTIFICATION

- 2.1. Classification of the substance May be fatal if swallowed and enter airways. Causes skin irritation. May Cause cancer.
May cause damage to organs through prolonged and/or repeated exposure.
DPD Classification: Xn; R20, Xi; R38, Carc. Cat. 1 and 3; R40, N; R45, Xn; R48/21, N; R51/53, Xn; R63, Xn; R65
CLP Classification: Asp. Tox. 1; H304, Skin Irrit. 2; H315, Acute Tox. 4; H332, Carc. 1B; H350, STOT RE 2; H350, Repr. 2; H361d, STOT RE 2.

2.2. Label elements



Hazard Phrases			Precautionary Phrases	
EUH066	Repeated exposure may cause skin dryness or cracking.		P201	Obtain special instructions before use.
H304	May be fatal if swallowed and enter airways.		P260	Do not breathe dust/fume/gas/mist/vapour/spray.
H315	Causes skin irritation.		P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
H332	Harmful if inhaled.		P331	Do not induce vomiting since vomiting may cause additional complications.
H350	May cause cancer.		P501	Dispose of contents/container in accordance with local regulations.
H361d	Suspected of damaging the unborn child.		P280	Wear protective gloves/eye protection.
H373	May cause damage to organs through prolonged or repeated exposure.		P308/313	If exposed or concerned: Get medical advice/attention.
H400	Very toxic to aquatic life.		P332/313	If skin irritation occurs: Get medical advice/attention.
H410	Very toxic to aquatic life with long lasting effects.			

7.1. Precautions for safe handling	Avoid all personal contact with the product. Do not breathe vapour or fumes. Wash hands thoroughly after handling. Ensure that all precautions are taken to ensure minimizing spillage and overflows.
7.2. Conditions for safe storage, including any incompatibilities	Store safely, out of reach of children and away from food, medicine etc. keep in tightly closed original packing.

8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters	No applicable occupational exposure limit exists for this material or its components. Consult local authorities for appropriate values.
8.2. Exposure controls	Wear the personal protective equipment specified below. Respiratory protection – Ensure that sufficient ventilation and mind the wind direction. In the event if excessive amount of H₂S is measured above 10 ppm a respiratory protection is required and must conform to one of the following standards: EN 136/140/145. Hand protection – Gloves of nitrile rubber, approved by EN 374, is recommended. Change gloves often. Eye protection – Wear safety goggles approved by EN 166 if there is a risk of eye splash

9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and Chemical properties	State – Liquid. Odour – Characteristic hydrocarbon. Flash Point – Min. 60.5°C (141°F) (Pensky-Martens Closed Cup). Note - this is a Marine Fuel and it is also a requirement that the Flash Point also meets the SOLAS, Chapter II-1, Reg 4 requirements (which is also min. 60°C). Density @15°C – 820 to 1020 kg/m³. Kinematic Viscosity – 2 to 850 mm²/s. Initial Boiling Point/Range – 150 to 600°C (302 to 1112°F).
--	--

10 – STABILITY AND REACTIVITY

10.1. Reactivity	This material is not expected to react.
10.2. Chemical stability	Stable under normal conditions of storage and use.
10.3. Possibility of hazardous reactions	None known and under normal storage conditions, hazardous reactions will not occur.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Product decomposes in fire conditions or when heated to high temperatures, and inflammable and toxic gases may be released

11 – TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects Likely routes of exposure – Skin and eye contact are the primary routes of exposure. Exposure may also occur through inhalation or following accidental ingestion.

Acute Oral Toxicity – The product does not have to be classified.

Acute Dermal Toxicity – The product does not have to be classified.

Acute Inhalation Toxicity – Harmful by inhalation especially when hydrogen sulphide is present.

Skin corrosion/irritation – Expected to be slightly irritating and may cause reddening. Contact with hot material can cause thermal burns which may result in permanent skin damage.

Serious eye damage/irritation – Expected to be slightly irritating. Contact with hot material may cause eye burns and/or blindness.

Respiratory or skin sensitisation - The product does not have to be classified.

Aspiration Hazard – Note considered an aspiration hazard but may cause chemical pneumonia if ingested or vomited.

Germ cell mutagenicity - The product does not have to be classified.

Carcinogenicity – May cause cancer

Reproductive toxicity – Suspected of damaging the unborn child.

STOT single exposure - The product does not have to be classified, but it is not expected to be a hazard

STOT repeated exposure – May cause damage to organs through prolonged or repeated exposure.

12 – ECOLOGICAL INFORMATION

12.1. Toxicity	Very toxic to aquatic life with long lasting effects.
12.2. Persistence and degradability	Contains substances which is not expected to be readily biodegradable. May cause long-term adverse effects in the aquatic environment.
12.3. Bioaccumulative potential	No data available.
12.4. Mobility in soil	No data available.
12.5. Result of PBT and vPvB assessment	No data available.
12.6. Other adverse effects	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

13 – DISPOSAL CONSIDERATIONS

13.1. Waste Treatment methods	Uncleaned packing and material is to be disposed of via an approved local waste-removal scheme. Empty and clean packing should be disposed of for recycling.
-------------------------------	--

14 – TRANSPORT INFORMATION

14.1. UN Number	Not Applicable. Product not classified as hazardous goods.
14.2. UN Proper Shipping Name	Not Applicable. Product not classified as hazardous goods.
14.3. Transport Hazard Class	Not Applicable. Product not classified as hazardous goods.
14.4. Packing Group	Not Applicable. Product not classified as hazardous goods.
Additional Information	NOT CLASSIFIED AS HAZARDOUS FOR TRANSPORT (ADR, RID, UN, IMO, IATA/ICAO) NOT RESTRICTED AS PER IATA SP A3 AS FLASH POINT IS ABOVE 60.5 DEGREES CELCIUS

15 – REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	Carcinogenic category 2. Special care should be applied to employees. other regulations may apply to this material.
15.2. Chemical safety assessment	Chemical safety assessment has not been performed.

16 – OTHER INFORMATION

Version Number	1.1
Effective date	02 December 2025
Enterprise	SeaHawk Services
Address	1501 Grandview Ave, Paulsboro, NJ 08066, United States
Email	info@Seahawkservices.com
Tel	+1 856-845-41421
Disclaimer	This information is based on our current knowledge and is intended to describe the product/material for the purpose of transporting sample bottles containing this product to one of our SeaHawk Services. It should not therefore be construed as guaranteeing any specific property of the product.