



International Standards 8217

4th Edition - 2010

Distillate Fuels

Characteristic	Limits	DMX	DMA	DMZ	DMB	Units	
Kinematic Viscosity @ 40°C (ISO 3104)	Max	5.500	6.000	6.000	11.00	mm ² /s	
	Min	1.400	2.000	3.000	2.000		
Density @ 15°C (ISO 3675 or 12185)	Max	--	890	890	900	kg/m ³	
Cetane Index (ISO 4264)	Min	45	40	40	35	--	
Sulfur (ISO 8754 or 14596)	Max	1.00	1.50	1.50	2.00	% mass	
Flash Point (ISO 2719)	Min	43.0	60.0	60.0	60.0	°C	
Hydrogen Sulfide (IP 570)	Max	2.00	2.00	2.00	2.00	mg/kg	
Acid Number (ASTM D664)	Max	0.5	0.5	0.5	0.5	mgKOH/g	
Total Sediment by Hot Filtration (ISO 10307-1)	Max	--	--	--	0.10"	% mass	
Oxidation Stability (ISO 12205)	Max	25	25	25	25	g/m ³	
Micro Carbon Residue @ 10% Residue (ISO 10370)	Max	0.30	0.30	0.30	--	% mass	
Micro Carbon Residue (ISO 10370)	Max	--	--	--	0.30	% mass	
Cloud Point (ISO 3015)	Max	-16	--	--	--	°C	
Pour Point (ISO 3016)	Winter	Max	-6	-6	-6	0	°C
	Summer	Max	0	0	0	6	°C
Appearance	--	Clear and Bright			--	--	
Water (ISO 3733)	Max	--	--	--	0.30	% volume	
Ash (ISO 6245)	Max	0.010	0.010	0.010	0.010	% mass	
Lubricity (ISO 12156-1)	Max	520	520	520	520	µm	