

Characteristic	Limits	RMA 10	RMB 30	RMD 80	RME 180	RMG				RMK			Units	
		180	380	500	700	380	500	700						
Kinematic Viscosity @ 40°C	Max	10.00	30.00	80.00	180.0	180.0	380.0	500.0	700.0	380.0	500.0	700.0	mm ² /s	
Density @ 15°C	Max	920.0	960.0	975.0	991.0	991.0				1010.0			kg/m ³	
CCAI	Max	850	860	860	860	870				870			--	
Sulfur	Max	Statutory Requirements											% mass	
Flash Point	Min	60.0											°C	
Hydrogen Sulfide	Max	2.00											mg/kg	
Acid Number	Max	2.5											mgKOH/g	
Total Sediment, Aged	Max	0.10											% mass	
Micro Carbon Residue	Max	2.50	10.00	14.00	15.00	18.00				20.00			% mass	
Pour Point	Winter	Max	0		30								°C	
	Summer	Max	6		30								°C	
Water	Max	0.30	0.50											% volume
Ash	Max	0.040	0.070			0.100				0.150			% mass	
Vanadium	Max	50	150			350				450			mg/kg	
Sodium	Max	50	100		50	100							mg/kg	
Aluminum + Silicon	Max	25	40		50	60							mg/kg	
Used Lubricating Oil (ULO): Calcium and Zinc; or Calcium and Phosphorus	--	The fuel shall be free from ULO. A fuel shall be considered to contain ULO when either one of the following conditions is met: Calcium > 30 and zinc >15; or Calcium> 30 and Phosphorus >15											mg/kg	