



International Standard

ISO 8217:2010

Distillate Fuels

Characteristic		Limits	DMX	DMA	DMZ	DMB	Units
Kinematic Viscosity @ 40°C (ISO 3104)		Max	5.500	6.000	6.000	11.00	mm ² /s
		Min	1.400	2.000	3.000	2.000	
Density @ 15°C (ISO 3675 or 12185)		Max	--	890	890	900	kg/m ³
Cetane Index (ISO 4264)		Min	45	40	40	35	--
Sulfur (ISO 8754 or 14596)		Max	1.00	1.50	1.50	2.00	% mass
Flash Point (ISO 2719)		Min	43.0	60.0	60.0	60.0	°C
Hydrogen Sulfide (IP 570)		Max	2.00	2.00	2.00	2.00	mg/kg
Acid Number (ASTM D664)		Max	0.5	0.5	0.5	0.5	mgKOH/g
Total Sediment by Hot Filtration (ISO 10307-1)		Max	--	--	--	0.10	% mass
Oxidation Stability (ISO 12205)		Max	25	25	25	25	g/m ³
Micro Carbon Residue @ 10% Residue (ISO 10370)		Max	0.30	0.30	0.30	--	% mass
Micro Carbon Residue (ISO 10370)		Max	--	--	--	0.30	% mass
Cloud Point (ISO 3015)		Max	-16	--	--	--	°C
Pour Point (ISO 3016)	Winter	Max	-6	-6	-6	0	°C
	Summer	Max	0	0	0	6	°C
Appearance		--	Clear and Bright			--	--
Water (ISO 3733)		Max	--	--	--	0.30	% volume
Ash (ISO 6245)		Max	0.010	0.010	0.010	0.010	% mass
Lubricity (ISO 12156-1)		Max	520	520	520	520	μm