



International Standard

ISO 8217:2010

Residual Fuels

Characteristic		Limits	RMA 10	RMB 30	RMD 80	RME 180	RMG				RMK			Units
							180	380	500	700	380	500	700	
Kinematic Viscosity @ 40°C		Max	10.00	30.00	80.00	180.0	180.0	380.0	500.0	700.0	380.0	500.0	700.0	mm ² /s
Density @ 15°C		Max	920.0	960.0	975.0	991.0	991.0				1010.0			kg/m ³
CCAI		Max	850	860	860	860	870							--
Sulfur		Max	Statutory Requirements											% mass
Flash Point		Min	60.0											°C
Hydrogen Sulfide		Max	2.00											mg/kg
Acid Number		Max	2.5											mgKOH/g
Total Sediment, Aged		Max	0.10											% mass
Micro Carbon Residue		Max	2.50	10.00	14.00	15.00	18.00				20.00			% mass
Pour Point	Winter	Max	0		30									°C
	Summer	Max	6		30									°C
Water		Max	0.30	0.50										% volume
Ash		Max	0.040	0.070			0.100				0.150			% mass
Vanadium		Max	50	150			350				450			mg/kg
Sodium		Max	50	100		50	100							mg/kg
Aluminum + Silicon		Max	25	40		50	60							mg/kg
Used Lubricating Oil (ULO): Calcium and Zinc; or Calcium and Phosphorus		--	The fuel shall be free from ULO. A fuel shall be considered to contain ULO when either one of the following conditions is met: Calcium > 30 and zinc >15; or Calcium> 30 and Phosphorus >15											mg/kg