



“Classification of digital modulation types using deep Learning”

By: Murtadha N. Abdullaah

Third stage

Al-Nahrain university

College of information engineering

Department of info. & comm. Engineering

1. Introduction

Overview of Digital Modulation

Digital modulation is a core technique in modern communication systems, where digital data is encoded into analog carrier waves by varying amplitude, frequency, or phase. Common schemes include **ASK**, **FSK**, **PSK**, and **QAM**, each offering trade-offs in data rate, power efficiency, and robustness. These techniques are widely used in systems like wireless, satellite, and cellular networks.

The Need for Classification

Accurate modulation classification is critical for effective signal detection, interference handling, and network optimization. It supports functions such as adaptive demodulation and dynamic spectrum management. With the growing number of modulation types, efficient and reliable classification becomes increasingly important, especially in dynamic or noisy environments.

Introduction to Deep Learning

Traditional classification methods rely on manual feature extraction and statistical models, which can be limited in noisy or complex channels. **Deep learning**, particularly **Convolutional Neural Networks (CNNs)**, addresses these challenges by learning features directly from raw I/Q signal data. CNNs are effective at recognizing patterns in high-dimensional data and have shown strong performance in signal classification tasks.

Objective of the Report

This report investigates the use of CNNs for classifying digital modulation schemes under varying noise conditions (simulated using **AWGN** and SNRs from 10 to 30 dB). The goal is to evaluate model performance and highlight the strengths and limitations of deep learning in practical communication environments.

2. Background

Digital Modulation Techniques

Digital modulation is essential for transmitting data over communication channels. Common modulation schemes include:

- **Amplitude Shift Keying (ASK):** Varies the carrier's amplitude to represent binary data. It's simple but highly sensitive to noise.
- **Frequency Shift Keying (FSK):** Changes the carrier frequency to represent data. More robust than ASK and widely used in low-frequency communication.
- **Phase Shift Keying (PSK):** Modifies the phase of the carrier. BPSK and QPSK are common variants, offering higher data rates.
- **Quadrature Amplitude Modulation (QAM):** Combines ASK and PSK by varying both amplitude and phase. Used in high-capacity systems like cable modems (e.g., 64QAM, 256QAM).
- **Amplitude Phase Shift Keying (APSK):** Uses both amplitude and phase changes with improved power efficiency, often in satellite communications.

These techniques are fundamental to systems like Wi-Fi, 5G, and satellite links. Choosing a modulation depends on factors like bandwidth, noise tolerance, and power efficiency.

Challenges in Modulation Classification

Several factors make modulation classification difficult:

- **Noise and Interference:** Distortions from AWGN, interference, or channel impairments can blur signal distinctions, especially at lower SNRs.
- **Complex Modulations:** Higher-order modulations like 256QAM or 128APSK have dense constellations that are harder to separate under noisy conditions.
- **Channel Effects:** Real-world issues such as multipath fading, Doppler shifts, and reflections introduce signal variations that degrade classifier performance.

Traditional Methods of Classification

Conventional approaches rely on manually engineered features (e.g., higher-order moments, spectral and cyclostationary features) fed into statistical classifiers such as **SVM**, **k-NN**, or **GMM**. While these methods can perform well in clean environments, they have limitations:

- **Manual Feature Engineering:** Requires expert knowledge and tuning for each modulation.
- **Poor Scalability:** Performance degrades with more classes or channel complexity.
- **Limited Adaptability:** Struggles with dynamic or unpredictable signal conditions.

Deep Learning in Modulation Classification

Deep learning, especially CNNs, offers a powerful alternative. CNNs automatically learn features from raw I/Q samples, reducing reliance on domain-specific preprocessing. Their advantages include:

- **End-to-End Learning:** Directly learns from raw input, adapting well to various modulation types.
- **Noise Robustness:** Learns hierarchical features that help distinguish signals in noisy or distorted conditions.
- **Scalability:** Handles a large number of modulation classes effectively.
- **Superior Performance:** Demonstrated high accuracy and generalization in both simulated and real-world wireless environments.

CNNs' ability to learn complex, noise-resilient features makes them well-suited for modern modulation classification tasks in dynamic, real-world communication systems.

3. Related Work

Overview of Existing Approaches

Digital modulation classification has evolved from traditional signal processing techniques to deep learning models, particularly Convolutional Neural Networks (CNNs). Early methods involved manual feature extraction from signals followed by statistical classifiers, but these methods were sensitive to noise and channel distortions.

Traditional Methods

Classical techniques extracted features like higher-order moments, spectral, and cyclostationary features, and used classifiers such as Support Vector Machines (SVM), k-Nearest Neighbors (k-NN), and Gaussian Mixture Models (GMMs). While effective in controlled environments, these methods struggled with scalability and handling complex channel impairments.

Deep Learning Approaches

The rise of deep learning, especially CNNs, has significantly advanced modulation classification. CNNs automatically learn features from raw I/Q samples, eliminating the need for manual feature engineering. Studies have demonstrated the effectiveness of CNNs in noisy environments:

- Zhang et al. (2017) showed CNNs outperforming traditional classifiers using raw I/Q samples.
- Liu et al. (2019) found that CNNs surpassed SVMs in multi-class scenarios, achieving high accuracy even in noisy environments.
- Cai et al. (2020) applied CNNs to a wide range of modulations, including higher-order QAM and PSK, showing their robustness and accuracy.

Comparison with Traditional Methods

While traditional methods require significant preprocessing and struggle in real-world conditions, CNNs excel by automatically extracting features and adapting to complex modulation schemes and noisy environments. CNNs have consistently shown higher accuracy, better scalability, and improved generalization across different modulations and SNR conditions compared to traditional classifiers.

Challenges and Limitations in Prior Work

Despite the promising results, several challenges remain in applying deep learning for real-world modulation classification:

- **Data Scarcity:** Many deep learning models require large amounts of labeled data for training. In practical systems, obtaining such data can be expensive and time-consuming.
- **Channel Impairments:** Although CNNs have shown robustness to noise, they still struggle in highly impaired channels where phenomena like severe fading, reflections, and non-linear distortions occur. These factors are difficult to simulate in controlled environments and remain an open area of research.
- **Computational Complexity:** Deep learning models, particularly CNNs, can be computationally expensive. While this is manageable with modern hardware, deploying these models in resource-constrained environments (e.g., embedded systems or mobile devices) requires optimization.

4. Methodology


Dataset and Preprocessing

The dataset used in this study is the RadioML 2018 dataset, which contains I/Q signal samples from 20 different digital modulation schemes. The data includes Signal-to-Noise Ratios (SNR) ranging from 10 to 30, with 4096 frames per modulation type. Each frame consists of I/Q samples, represented as a (1024, 2) array.

The preprocessing steps involve normalizing the I/Q signals to standardize the data, and the dataset is then split into training, validation, and test sets. To ensure consistency across the different modulation schemes, the labels are padded.

Model Architecture

The model is based on a **Convolutional Neural Network (CNN)** designed to classify digital modulation schemes. The architecture includes:



General Model and Specialized Models

1. General Model:

- The **general model** is trained to classify across all modulation schemes (ASK, PSK, APSK, QAM, FSK). It includes all layers and uses a softmax output layer with 24 classes (for 24 modulation types).

2. Specialized Models:

- The general model is used as the foundation to create **five specialized models** that focus on specific modulation groups:
- **ASK Model:** Trained specifically on ASK modulations (e.g., OOK, 4ASK, 8ASK).
- **PSK Model:** Focuses on PSK modulations (e.g., BPSK, QPSK, 8PSK, 16PSK).
- **APSK Model:** Specializes in APSK modulations (e.g., 16APSK, 32APSK, 64APSK).
- **QAM Model:** Focuses on QAM modulations (e.g., 16QAM, 32QAM, 64QAM).
- **FSK Model:** Designed for FSK modulations (e.g., 2FSK, 4FSK, 8FSK).
- For each specialized model, the architecture is similar to the general model, but the output layer is adjusted to the number of classes in that specific modulation group.


Evaluation

The model is evaluated based on **accuracy** and confusion matrices, which show how well the model classifies each modulation scheme. These metrics help assess performance across both the general and specialized models.


5. Results

The performance of the model was evaluated using both individual modulation tests and a final comprehensive test across all modulation types.

- **General Model:**
 - **Test Accuracy: 99.76%**
- **ASK Model:**
 - **Test Accuracy: 99.93%**
- **FSK Model:**
 - **Test Accuracy: 91.65%**
- **PSK Model:**
 - **Test Accuracy: 99.95%**
- **APSK Model:**
 - **Test Accuracy: 98.33%**
- **QAM Model:**
 - **Test Accuracy: 91.35%**



The final test, which evaluates all modulation types at once, yielded a Test Accuracy of 97.215%, demonstrating the model's robust generalization across diverse modulation schemes.



6. Discussion

The model's performance, with a **final test accuracy of 97.215%**, is impressive, particularly given the complexity of classifying various modulation schemes in noisy environments. The **general model** achieves near-perfect accuracy (99.76%) on the broad set of modulations, while specialized models for **ASK**, **PSK**, and **FSK** also show strong performance, especially for simpler modulations like OOK and 4ASK.

In terms of **real-world applicability**, the results are promising but not flawless. While the model performs well in controlled environments with AWGN noise, real-world channels introduce additional challenges such as **multipath fading**, **Doppler shifts**, and **non-linear distortions**. These impairments can degrade signal quality, potentially reducing classification accuracy, particularly for **higher-order modulations** like 256QAM and 128APSK, which are more sensitive to small variations in the signal.

To improve these results further, a few enhancements can be made:

1. **Data Augmentation**: Introducing synthetic data that simulates **multipath fading**, **reflection**, and **Doppler shifts** could help the model generalize better to real-world conditions.
2. **Longer Signal Lengths**: For complex modulations like **QAM** and **APSK**, increasing the signal length (e.g., 2048 or 4096 samples) may provide more detail for accurate classification.
3. **Advanced Architectures**: Exploring **hybrid models** or using techniques like **transfer learning** could help capture more complex patterns, especially for real-world noise and fading effects.

Overall, the model shows great potential for real-world use, but further improvements and testing under diverse channel conditions will be key to achieving even higher robustness.

7. Conclusion

In this report, we demonstrated the effectiveness of deep learning, specifically CNNs, for digital modulation classification. The model achieved high accuracy across various modulation schemes, with the **general model** reaching 99.76% accuracy and the final test accuracy of 97.215%. These results indicate that deep learning can significantly improve the robustness and efficiency of modulation classification in controlled conditions.

However, while the model performs well in ideal settings, challenges remain when applied to real-world conditions with complex channel impairments like fading and multipath. Future work could involve expanding the dataset to include more realistic channel effects, increasing signal lengths, and exploring more advanced architectures to further enhance the model's performance.

Overall, this work highlights the potential of deep learning in communication systems and paves the way for future research and development in digital signal classification.

8. References

1. Zhou, Ruolin & Liu, Fugang & Gravelle, Christopher. (2020). Deep Learning for Modulation Recognition: A Survey With a Demonstration. IEEE Access. PP. 1-1. 10.1109/ACCESS.2020.2986330.
2. Li, Huiqiong & Wei, Ying & Zhu, Changjian. (2022). Convolutional Neural Network Analysis for Modulation Classification of Wireless Communication Signal. 10.3233/ATDE221103.
3. Varasteh, Ehsan & Kashef, Seyed & Valizadeh, Morteza & Zefreh, Mahdi. (2023). Modulation Classification with Convolutional Neural Network Based Deep Learning in Elastic Optical Network. 10.1109/ICEE59167.2023.10334869.
4. Liu, Q., Sun, Y., & Zhang, W. (2018). *Digital modulation classification using deep learning with channel impairments*. International Journal of Communication Systems, 31(12), e3667.
5. Kim, Seung-Hwan & Jaewoo, Kim & Doan, Sang & Kim, Dong-Seong. (2020). Lightweight Deep Learning Model for Automatic Modulation Classification in Cognitive Radio Networks. IEEE Access. 8. 197532-197541. 10.1109/ACCESS.2020.3033989.