

SWR. Linters. Refs. CSS in JS.

Alen Murtić



01

SWR

02

Linters

03

Refs

04

CSS in JS



01

SWR

SWR

Motivation

- Fetch + useEffect + useState is okayish, but we usually require complex features
 - E.g. polling, local caching, fetching on tab focus, request deduplication
 - We could implement this, but let's not reinvent the wheel 😊
- Solution: SWR (stale-while-revalidate)
 - **Hooks based** HTTP client library

SWR

SWR

- yarn add swr
 - Types are added out of the box
- Wrap your app in **SWRConfig** which accepts value of **SWRConfiguration** type
 - Fetcher callback needs to be defined
 - **For all intents and purposes of this Academy just c/p my demo**
- Check out App.tsx in our demo project
- e.g. `const {data: match, error} = useSWR<MatchDetailsResponse>(matchRoute(matchId), {refreshInterval: 10000})`
 - Store result of MatchDetailsResponse type into match variable, error in error variable
 - Poll the server every 10 seconds



SWR example - swr.md



02



Linters

Motivation

- Javascript is dynamically typed and interpreted language with many quirks
- Some of JS quirks are solved by using Typescript, but it is not end-all, be-all
 - TS just describes types, but you can make many other mistakes in JS
- Solution: Linters
 - [Wikipedia](#): “Lint is the computer science term for a static code analysis tool used to flag programming errors, bugs, stylistic errors and suspicious constructs... A program which performs this function is also known as a “linter”
 - Most of linting in e.g. Java or C# is done by the compiler, but JS is interpreted, not compiled

Linters

ESLint

- ~~TSLint - Typescript specific linter - deprecated~~
- THE linter for Javascript and Typescript
- Extendable and customizable
 - You can do practically anything you want if you have enough time and willpower
- Not just for static code analysis, but also for auto code formatting and style
- Many, many, many predefined configurations
 - In a larger project, you will most likely need your own custom config
 - <https://eslint.org/docs/latest/use/configure/>
 - Even at Sofascore, every project has its own configuration because of different structures and technologies



03

Refs

Refs

Refs

- Two distinct usages:
 - Storing data which should not trigger re-renders
 - Manipulating DOM - but, more on that later
- [Official docs](#)
- Returns object with `current` key set to DOM object or `null`
- `useRef` hook - `const ref = useRef(null)`
- `createRef` method - `this.ref = createRef(null)`



Refs example - refs.md



Refs

usePrevious

- Sometimes we need previous prop value in current component
 - In class components `componentDidUpdate` could access it
 - Use case example: animations
- We don't want to re-render on update of previous value
- Solution: `usePrevious` hook



Refs example - usePrevious.md





04

CSS in JS

Motivation

- Classic usage of CSS via classes isn't really for the components era
 - In big projects, those can become mentally unscalable
 - While it supports code reuse, only most basic stuff is re-used
 - E.g. standard project paddings, margins, borders - reminds you of Tailwind CSS
 - CSS is focused on defining document-level stylesheets, not component-level
- Solution: CSS in JS

CSS in JS

CSS in JS

- Idea: Write CSS inside JS files, leverage some JS features
- Advantages:
 - Thinking in components
 - Inject only used styles at render-time, not all styles
 - Handles vendor prefixing (e.g. `-webkit-box-align` or `-moz-box-align`)
 - Dead code elimination
 - Almost flat learning curve because it's very similar to classic CSS, but better
 - No (minimal) inline styling
 - Clean conditional statements

Styled components and Next 13 problems

- Styled components was Sofascore's favorite CSS in JS library - not just ours
 - Excellent development experience, with very minor performance downsides
- Essentially writing CSS inside template strings
 - Allows usage of JS variables in CSS
- The lib would analyze the whole page and create custom classes for best performance
 - Key phrase: whole page - analyzed on client, during runtime
- Next 13 and app router introduces server components
 - Styled components authors basically said "we ain't gonna support it" since it doesn't fit in the lib's philosophy
- Solution: another library with compile-time CSS

Next 13 and RSC compatible libraries

- Other libraries have added full support for RSC
 - vanilla-extract : <https://vanilla-extract.style/>
 - Kuma UI: <https://www.kuma-ui.com/>
 - Panda CSS: <https://panda-css.com/>
 - StyleX - <https://stylexjs.com/>
- We will be using Kuma UI in the next lesson



Styled components example - styled.md



**Thank you for your
attention!**

