

BML Switch — Postman Guide

AppInSnap — Postman Collection Guide

Audience: AppInSnap mobile / QA engineers

Collection file: BML-Switch-Phase0.postman_collection.json

Companion API doc: APPINSNAP-API-GUIDE.md

Test data: APPINSNAP-TEST-DATA.md

Mock OTP = 1234 (never 123456).

1. Prerequisites

1. Switch running locally:

```
docker compose up --build -d
curl -s http://localhost:8080/api/v1/system/health
```

Expect "status": "UP".

2. Postman Desktop or Postman web with ability to import a collection JSON.

2. Import the collection

1. Open Postman → **Import**.

2. Choose **File** → select

docs/handoff/BML-Switch-Phase0.postman_collection.json

(or drag-and-drop the file).

3. Confirm collection name: **BML Switch Phase 0 — AppInSnap**.

4. Open the collection → **Variables** tab. You should see:

Variable	Default	Notes
baseUrl	http://localhost:8080	Change for UAT later
clientId	appinsnap-sandbox	
clientSecret	change_me_sandbox_secret	Sandbox only
accessToken	(empty)	Auto-set by 01 auth/token
refreshToken	(empty)	Auto-set by token
strToken	(empty)	Auto-set by 03 account/login
otpReference	(empty)	Auto-set by OTP send
otpTicket	(empty)	Auto-set by OTP verify
imd	601004	Meezan sample from seed
toIban	PK12MEZN0000001234567890	Sample beneficiary
toAccount	1234567890	Sample beneficiary
fromAccount	0345001234567	Funded seed
toAccountIft	0345001234568	Funded seed
stan	(empty)	Auto-set after IBFT
transactionId	(empty)	Auto-set after IBFT

No separate Postman Environment file is required for local sandbox — collection variables are enough. For a shared team Environment, copy the same keys into an Environment named BML Switch Sandbox and select it in the top-right dropdown.

3. Happy-path run order

Run requests **top to bottom** inside folder **01 — Happy path (in order)**:

#	Request	Saves variables
1	system/health	—
2	auth/token	accessToken, refreshToken
3	lookups/banks	optionally peek imd (already default 601004)
4	account/login	strToken
5	inquiry/balance	—
6	payment/ift	—
7	inquiry/ibft-title	—
8	auth/otp/send	otpReference
9	auth/otp/verify (1234)	otpTicket
10	payment/ibft	stan, transactionId
11	inquiry/ibft-status	—
12	inquiry/limits	—
13	inquiry/receipt	—

Tip: Use Postman's **Collection Runner** on folder 01 – Happy path (in order) with iterations = 1.

Other folders (02 – Lookups, 03 – Negative checks) are optional after the happy path works.

4. How variables are chained

auth/token
■ ■ Tests script → accessToken, refreshToken

account/login
■ ■ Authorization: Bearer {{accessToken}}
■ ■ Tests script → strToken

auth/otp/send
■ ■ body.strToken = {{strToken}}
■ ■ Tests script → otpReference

auth/otp/verify
■ ■ body.otp = "1234"
■ ■ body.otpReference = {{otpReference}}
■ ■ Tests script → otpTicket

payment/ibft
■ ■ body.otpTicket = {{otpTicket}}
■ ■ body.toIMD = {{imd}} (601004)
■ ■ Tests script → stan, transactionId

inquiry/ibft-status / receipt
■ ■ use {{stan}} / {{transactionId}}

If a Tests script did not run (failed request), variables stay empty — fix the failing step and re-run from that point (or from **auth/token** if the channel JWT expired).

5. OTP reminder

Step	Value
Verify body	"otp": "1234"
Wrong OTP / missing ticket on IBFT	Response_Code 78
Sandbox flag	MOCK_OTP=true

6. Idempotency in Postman

IFT and IBFT requests set header:

```
Idempotency-Key: {{$guid}}
```

Each click generates a new UUID (new payment attempt). To test **replay**, freeze a UUID in the header (replace {{\$guid}} with a fixed value) and send the same request twice — second response should match the first success body.

7. Troubleshooting

Symptom	Likely cause	Fix
HTTP 401, CHANNEL_TOKEN_*	Missing/expired Bearer	Re-run auth/token ; check Authorization header
HTTP 401, Response_Code 91	Missing/expired strToken	Re-run account/login ; ensure body includes strToken
HTTP 401, 75	Lockout after 5 bad passwords	Wait 30 min or use reset-password-mock (sandbox)
Response_Code 78 on IBFT	No / invalid otpTicket	Run OTP send → verify with 1234, then IBFT
Response_Code 51	Insufficient funds	Use funded 0345001234567, smaller amount; avoid zero account
Response_Code 76	Bad / inactive IMD	Use 601004 or pick from lookups/banks
Response_Code 14	Bad account / credentials	Check seed accounts & password Sandbox@123
Connection refused	Stack down	docker compose up --build -d
Empty accessToken after token	Tests script not executed	Open request → Tests tab; ensure 200 + JSON access_token

8. Automated alternative

Without Postman:

```
./scripts/smoke.sh
```

Same happy path (OTP 1234) against `http://localhost:8080`.

9. Sharing with the team

1. Share this folder: docs/handoff/ (at least README, API guide, Postman guide, test data, collection JSON).
2. Tell engineers: **import collection** → **run folder 01** – Happy path **in order** → **OTP is 1234**.
3. Point them to APPINSNAP-API-GUIDE.md for request/response contracts.