

BML Switch — Sandbox Test Data

AppInSnap — Sandbox Test Data

Copy/paste sheet for Slack, email, or ticket comments.

Environment: local Docker sandbox · Base URL `http://localhost:8080` · Mock OTP 1234

Channel (AppInSnap client)

Field	Value
client_id	appinsnap-sandbox
client_secret	change_me_sandbox_secret
grant_type	client_credentials
Access token TTL	900 seconds (15 min)
Refresh token TTL	604800 seconds (7 days)

Customer login

Field	Value
Username	ali.khan
Password	Sandbox@123
CNIC (even → auto KYC)	4210112345678
Mobile	03001234567
Full name	ALI KHAN
Odd CNIC (manual review demo)	4210112345679

After login, use body field `strToken` on all customer APIs.

Accounts & balances (seed)

Role	Account	IBAN	Opening balance (PKR)
From (primary)	0345001234567	PK00BMAL0000000345001234567	150000.00
IFT to (same customer)	0345001234568	PK00BMAL0000000345001234568	50000.00
Zero / NSF tests	0345009999999	PK00BMAL0000000345009999999	0.00
Invalid (not found)	0345000000000	—	—

Currency: **PKR**. Fee in mock responses: always 0.00.

Suggested test amounts

Scenario	Amount
----------	--------

Happy IFT	"100.00"
Happy IBFT	"25.00"
NSF (from zero acct)	"10.00" from 0345009999999
Large (still under daily limit)	"1000.00"

Daily debit limit (Asaan display): 200000.00 PKR. Max balance display: 1000000.00.

Mock OTP

Field	Value
Code	1234 (never 123456)
Flag	MOCK_OTP=true
Flow	POST /auth/otp/send → otpReference → POST /auth/otp/verify with otp": "1234" → otpTicket
IBFT without ticket	Response_Code 78

Sample beneficiary banks (IMD) — use Lookups, do not hardcode in app

IMD	Short	Bank	IBAN bank code
601004	Meezan	Meezan Bank Limited	MEZN
601001	HBL	Habib Bank Limited	HABP
601002	UBL	United Bank Limited	UNIL
601003	MCB	MCB Bank Limited	MUCB
627000	BML	Bank Al Murqamah (own)	BMAL

Postman / smoke sample beneficiary

Field	Value
toIMD	601004
toIBAN	PK12MEZN00000001234567890
toAccount	1234567890

Load full list: GET /api/v1/lookups/banks?active=true&supportsIbft=true (≥16 Pakistan banks).

Purpose of payment (examples)

Code	Description
FAM	Family Support
SAL	Salary
GDS	Goods Payment
EDU	Education
MED	Medical

Source of truth: GET /api/v1/lookups/purpose-of-payment.

Idempotency-Key

Rule	Detail
Required on	POST /payment/ift, POST /payment/ibft, POST /account/open
Format	UUID generated by mobile per logical attempt
Header	Idempotency-Key: <uuid>
Replay	Same key + same outcome within ~24h returns cached success body

Auth headers (reminder)

Authorization: Bearer <channel_access_token>
Content-Type: application/json
X-Correlation-Id: <optional-uuid>
Idempotency-Key: <uuid> # money / open only

Customer token goes in JSON body as strToken (not in Authorization).

Quick links

- API guide: APPINSNAP-API-GUIDE.md
- Postman: APPINSNAP-POSTMAN-GUIDE.md
- Collection: BML-Switch-Phase0.postman_collection.json