# RAgent Aftab Currency Exchange API

## RAgent.AftabCurrency.com

**This document is prepared to provide an interface of RAgent.Aftabcurrency.com web service for external services to retrieve transactions from Aftab Currency Exchange system.**

**Version (1.2)**

**Drafted By: JHANZAIB AWAN**

**March 17, 2015**

## REVISION CHART

| Version | Author(s) | Description of Version | Date Completed | Date Modified |
|---|---|---|---|---|
| 1.2 | JhanZaib AwAn | | ---------- | March. 17,2015 |

# Contents


Objective ..... 4

Intended Audience ..... 4

Description ..... 4

End Point ..... 4

WSDL Location ..... 4

General Information ..... 5

Parameters ..... 5

Response ..... 5

aceAuthHeader ..... 6

aceAuthHeader Result Entity ..... 6

Web Service Methods ..... 7

GetPaymentInfo (PaymentNo, Object) ..... 7

GetPaymentStatus (PaymentNo, Object) ..... 9

SetPaymentStatus (Object, Object) ..... 10

Codes ..... 11

Authentication Values ..... 11

## Objective

Receiving Agents can integrate their system with Aftab Currency RAgent Web Services, to “receive” the transactions via Web Service.

## Intended Audience

This document is intended for programmers who are already familiar with the web services. This document does not include general information about web service; it contains the details of integration with Aftab Currency RAgent Web Service API along with I/O parameters.

## Description

Aftab Currency RAgent Web Service API contains following web methods, namely:

1. GetPaymentInfo - Transaction information could be queried, by Payment No.
2. GetPaymentStatus - Transaction status could be queried, by Payment No.
3. SetPaymentStatus - It update the status and info of a transaction.

More methods can be added upon Agents’ request and after reviewing the requirements.

## End Point

Development: <to be Provided>

## WSDL Location

Development: <to be Provided>

# General Information

## Parameters

All methods expect a single Unicode string as parameter. This string is based on Object pattern and will contain the values of different parameters as Object.

## Response

All methods return a **Result** object as response with payment info if required. Various information regarding status and payment can be retrieved from using properties.

## Authentication

Each SOAP request to the API contains two parts, the SOAP Header and the SOAP Body and each response from the API contains two parts, Result and Details. If Authentication fails or error occurs while processing client request, system will generate SOAP exception and error details will be available in Result section.

## aceAuthHeader

| Field Name | Field Length and Characters | Description | Required | Example |
|---|---|---|---|---|
| userID | up to 15 letters or numbers only | A userID for the corresponding use of the branch will be created | Yes | US00100001 |
| userPass | up to 10 letters or numbers only | Unique key supplied by our operation dept. | Yes | xxxxxxxx |
| userKey | up to 10 letters or numbers only | Password supplied by our operation dept. | Yes | |

## aceAuthHeader Result Entity

| Field Name | Field Length and Characters | Description | Required | Example |
|---|---|---|---|---|
| Rflag | up to 1 number only | System will return 1 on success and 0 on failure | Yes | 1 = Successful<br>0 = Failure |
| Code | up to 6 letters | The value of this filed will be 6 chars error code . | No | 100001 |
| Message | up to 50 letters or numbers only | In case the transaction fails, the system will return the reason for failure. This will have a nonblank value in case of failure and will be blank in case of success | No | Invalid parameter length |
| Description | up to 50 letters or numbers only | Detailed error Description | No | Minimum length of Settlement_Currency cannot be less than 3 |

# Web Service Methods

## GetPaymentInfo (PaymentNo as string, aceAuthHeader as object)

Method Name: GetPaymentInfo (ByVal p_Parameter as String, aceAuthHeader(Object)).

Description: It gives Information about transaction in Aftab Currency Exchange system.

Parameter: **PaymentNo** as string, **aceAuthHeader** as Object are required to get payment information from Aftab Currency
Exchange's system.

This method returns transaction information from Aftab Currency Web services system and returns as Transaction object. A Transaction object contains following sub objects/parts.

1) **aceSender:**

This object contains the information of the Sender. Following table contains the details.

| Sr. # | Field Name | Data Type | Length |
|---|---|---|---|
| 1 | Sender Name | String | 150 |
| 2 | SenderAddress | String | 50 |
| 3 | SenderNationality | String | 50 |
| 4 | SenderCity | String | 300 |
| 5 | SenderPostCode | String | 200 |
| 6 | SenderPhone | String | 50 |
| 7 | SenderEmail | String | 50 |
| 8 | SenderIdType | String | 50 |
| 9 | SenderIdNumber | String | 50 |
| 10 | SenderIdIssueDate | Date | |
| 11 | SenderIDExpireDate | Date | |
| 12 | SenderOccupation | String | 250 |

2) **aceReceiver:**

This object contains the information of the Beneficiary. Following table contains the details.

| Sr. # | Field Name | Data Type | Length |
|---|---|---|---|
| 1 | ReceiverName | String | 150 |
| 2 | ReceiverAddress | String | 250 |
| 3 | ReceiverCity | String | 50 |
| 4 | ReceiverPhone | String | 50 |
| 5 | ReceiverAccountNumber | String | 50 |
| 6 | ReceiverBankName | String | 200 |
| 7 | ReceiverBranchName | String | 100 |

3) **aceRemittance:**

This object contains the information of amount to be transferred, service charges, exchange rates and other remittance related information. The details are in following table.

| Sr. # | Field Name | Data Type | Length |
|---|---|---|---|
| 1 | PaymentNumber | String | 50 |
| 2 | PaymentDate | DateTime | |
| 3 | PaymentMethod | String | |
| 4 | ReceiverCurrency | String | 3 |
| 5 | ReceiverAmount | Double | |
| 6 | SendingReason | String | 250 |
| 7 | PaymentStatus | String | 50 |
| 8 | InvoiceNumber | Int | 3 |
| 9 | BranchCode | String | 50 |
| 10 | PaymentReciverIdType | String | 50 |
| 11 | BenIDNumber | String | 50 |
| 12 | BenPhoneNumber | String | 50 |
| 13 | BenTransID | String | 50 |
| 14 | BranchID | String | 50 |
| 15 | UserID | String | 50 |

**4) aceResult (Response Sent to integrator)**

GetPaymentInfo returns an object to integrator in either cases success or failure.

| Sr. # | Field Name | Data Type | Description |
|---|---|---|---|
| 1 | Rflag | INT | |
| 2 | Code | INT | |
| 3 | Message | String | |
| 4 | Detail | String | |

## GetPaymentStatus (PaymentNo as string, aceAuthHeader as object)

Method Name: GetPaymentStatus (ByVal p_Parameter as String, aceAuthHeader as Object).
Description: It gives Information about transaction status in Aftab Currency Exchange system.
Parameter: **PaymentNo** as String, **aceAuthHeader** as Object are required to get payment status information from Aftab Currency Exchange's system.

This method returns transaction status information in Aftab Currency Web services system and returns as **aceTransactionStatus** object. A **aceTransactionStatus** object contains following sub objects/parts.

1) **aceRemittance:**

This object contains the information of amount to be transferred, service charges, exchange rates and other remittance related information. The details are in following table.

| Sr. # | Field Name | Data Type | Length |
|---|---|---|---|
| 1 | PaymentNumber | String | 50 |
| 2 | PaymentDate | DateTime | |
| 3 | PaymentMethod | String | |
| 4 | ReceiverCurrency | String | 3 |
| 5 | ReceiverAmount | Double | |
| 6 | SendingReason | String | 250 |
| 7 | PaymentStatus | String | 50 |
| 8 | InvoiceNumber | Int | 3 |
| 9 | BranchCode | String | 50 |
| 10 | PaymentReciverIdType | String | 50 |
| 11 | BenIDNumber | String | 50 |
| 12 | BenPhoneNumber | String | 50 |
| 13 | BenTransID | String | 50 |
| 14 | BranchID | String | 50 |
| 15 | UserID | String | 50 |

**2) aceResult (Response Sent to integrator)**

GetPaymentStatus returns an aceResult object to integrator in either cases success or failure.

| Sr. # | Field Name | Data Type | Description |
|---|---|---|---|
| 1 | Rflag | INT | |
| 2 | Code | INT | |
| 3 | Message | String | |
| 4 | Detail | String | |

## SetPaymentStatus (aceRemittance as Object, aceAuthHeader as Object)

Method Name: SetPaymentStatus (ByVal p_Parameter as Object, aceAuthHeader(Object).
Description: It Update/Set Information about transaction status in Aftab Currency Exchange system.
Parameter: **aceRemittance** as object, **aceAuthHeader** as object are required to set payment status and other information in Aftab Currency Exchange's system.

This method update/set transaction status and other information in Aftab Currency Web Services system and returns as **aceTransactionStatus** object. A Result object contains following sub objects/parts.

1) **aceRemittance:**

This object contains the information of amount to be transferred, service charges, exchange rates and other remittance related information. The details are in following table.

| Sr. # | Field Name | Data Type | Length |
|---|---|---|---|
| 1 | PaymentNumber | String | 50 |
| 2 | PaymentDate | DateTime | |
| 3 | PaymentMethod | String | |
| 4 | ReceiverCurrency | String | 3 |
| 5 | ReceiverAmount | Double | |
| 6 | SendingReason | String | 250 |
| 7 | PaymentStatus | String | 50 |
| 8 | InvoiceNumber | Int | 3 |
| 9 | BranchCode | String | 50 |
| 10 | PaymentReciverIdType | String | 50 |
| 11 | BenIDNumber | String | 50 |
| 12 | BenPhoneNumber | String | 50 |
| 13 | BenTransID | String | 50 |
| 14 | BranchID | String | 50 |
| 15 | UserID | String | 50 |

**2) aceResult** (**Response Sent to integrator)**

SetPaymentStatus returns an object to integrator in either cases success or failure.

| Sr. # | Field Name | Data Type | Description |
|---|---|---|---|
| 1 | Rflag | INT | |
| 2 | Code | INT | |
| 3 | Message | String | |
| 4 | Detail | String | |

In case of success, the transaction will show the Remittance status else it will show the Error Code.

## Codes

Every Web Method returns a Response containing a number as “Code”. Following are some of these

1000: Success
10004: Branch Information Missing
10005: Invalid Payment information
10006: MTNNum Missing
10007: Authentication Failure
10008: System Updation Error Please Contact To Administrator
10009: DC Rate Not Given
10010: SC Rate Not Given
10011: System error occured. Please contact technical support

## Authentication Values

Every Web Method must be provided following values, the detail of the format is coming further

1. userID - The unique identification of a legitimate user of Integrator System in AftabCurrency.
2. userPass - AftabCurrency Password for the user specified above.
3. userKey - Code Assigned to Sender Location in AftabCurrency System.

All four values shall be provided by RemitAnywhere on registration for API usage. These will be test values.

Once, the integration is approved by our testing staff, Production values will be provided.